NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

06 November 2026

147 verified · 252 raw · 4 sources

147	3	144	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	121	Media
TechCrunch AI	12	Media
The Verge AI	9	Media
HackerNews	8	Community

VERIFIED INTELLIGENCE — 3 stories

VERI

Airbnb is working on an AI travel agent

The Verge AI +1 source 80%

Airbnb plans to roll out an AI agent in the first half of 2027 that will help users plan and book travel, the company said in its Q3 2026 earnings shareholder letter released today. "Today's AI agents are good at simple, routine tasks, like making a restaurant reservation or...

https://www.theverge.com/tech/1028412/airbnb-ai-travel-agent-q3-2026-earnings

VERI

OpenAI says its new cybersecurity model is better at not hacking other companies

The Verge AI +1 source 80%

OpenAI is launching GPT-6 Cyber, the latest version of its cybersecurity AI model, which it says is better at finding vulnerabilities and less likely to go rogue and hack other platforms in the process. OpenAI says that during testing, GPT-6 Cyber went out of bounds less than 1...

https://www.theverge.com/ai-artificial-intelligence/1027599/openai-gpt-6-cyber-launch

VERI

OpenAI is stepping back from NDAs for data center projects

The Verge AI +1 source 80%

Following this week's midterms where voters resoundingly voiced their opposition to data center expansion, OpenAI today announced new commitments to communities where it is working on data center projects, including that it won't use non-disclosure agreements (NDAs) with public...

https://www.theverge.com/ai-artificial-intelligence/1028454/openai-data-center-nda

CONFIRMED SIGNALS — 144 stories

CONF

Show HN: A decent text-to-image model trained for ~$20K (Apache 2.0 Weights)

HackerNews 60% HN 238

My brother and I run a 2-person lab that trains our own generative video models from scratch. The ultimate goal is a set of creative tools that make it easier for anyone to make animation. Video models today are too slow/expensive and lack sufficient controls. Creativity is an...

https://www.linum.ai/field-notes/pjit-21k

CONF

Show HN: 3-minute desk breaks based on Radio Taiso and Wordle

HackerNews 50% HN 4

No summary — see link for full article.

https://www.audioround.com/

CONF

Show HN: Sanctuary – Offline LLM Running on Apple Silicon Metal (iOS)

HackerNews 50% HN 4

No summary — see link for full article.

https://testflight.apple.com/join/Z51G6g5G

CONF

Show HN: Hand Your Markdown Tasks to Claude Code from a Kanban Board

HackerNews 50% HN 3

EtherPK (a markdown / wikilink based notes app) tasks are plain markdown, but the EtherPK client has built powerful functionality on top of markdown tasks, integrating a Kanban board and MCP server to allow you to manage your work in your notes and easily hand off with...

https://blog.etherpk.com/hand-your-markdown-tasks-to-claude-code-from-a-kanban-board

CONF

Show HN: Lo-fi layered over air traffic control (recorded myself)

HackerNews 50% HN 2

Some of you will remember lofiatc.com and I was a huge fan and heavy user until it got shut down. It was streaming LiveATC feeds, and when those got cut off the site went dark and has been ever since. So I decided to bring it back in a way that wouldn't fall to the same fate....

https://finalapproach.fm/

CONF

Show HN: A terminal viewer for plain text data files (JSON,YAML,CSV,XML,)

HackerNews 50% HN 2

When I started working hands-on with OpenAPI specifications, it became clear very quickly that using an editor to read large volumes of deeply nested JSON sucks, a very great deal. So I went looking for something to help, and came across https://jless.io This is an awesome...

https://aless.tabnas.dev/

0 CONF

Show HN: Roblox game idea generator I built with AI as a non-coder

HackerNews 50% HN 2

No summary — see link for full article.

https://robloxideas.com/

1 CONF

Show HN: Trademark Screen – free plain-English trademark check with email watch

HackerNews 50% HN 2

No summary — see link for full article.

https://trademarkscreen.com/

2 CONF

Palo Alto Networks in talks to buy AI agent security startup Clutch for $500M

TechCrunch AI 50%

Clutch, backed by Lightspeed and SignalFire, was last valued at $85 million, according to a source.

https://techcrunch.com/2026/11/05/palo-alto-networks-in-talks-to-buy-ai-agent-security-...

3 CONF

Meta says US users can now video chat with their Muse AI avatar

TechCrunch AI 50%

Meta's AI agent can now take calls as a customizable animated avatar, ahead of the launch of a Tamagotchi-like wearable designed to bring Muse to life.

https://techcrunch.com/2026/11/05/meta-says-us-users-can-now-video-chat-with-their-muse...

4 CONF

OpenAI president Greg Brockman says company could be IPO ready in 2027

TechCrunch AI 50%

Speaking at a Wall Street Journal tech conference on Wednesday, the executive touted how the company had been gaining ground in the enterprise market, where rival Anthropic had already successfully made inroads.

https://techcrunch.com/2026/11/05/openai-president-greg-brockman-says-company-could-be-...

5 CONF

Claude can now analyze your spending with its new Personal Finance tool

TechCrunch AI 50%

With Personal Finance in Claude, users can connect their bank and card accounts through Plaid and ask questions about their finances.

https://techcrunch.com/2026/11/05/claude-can-now-analyze-your-spending-with-its-new-per...

6 CONF

Axiom Math wants to keep AI slop out of mathematics

TechCrunch AI 50%

As AI floods math with unchecked proofs, Axiom Math is betting on verification. The startup’s AI agents just formally verified the Stacks Project, one of the field’s biggest libraries.

https://techcrunch.com/2026/11/05/axiom-math-wants-to-keep-ai-slop-out-of-mathematics/

7 CONF

Dropbox acquires Tigris Data for $350M to bolster its AI infrastructure

TechCrunch AI 50%

The deal is expected to support the development of DBX Agent Cloud, a new storage platform aimed at developers building AI models and agents.

https://techcrunch.com/2026/11/05/dropbox-acquires-tigris-data-for-350m-to-bolster-its-...

8 CONF

Aina’s smart ring has a screen, a joystick, and a mic so you can talk to AI agents

TechCrunch AI 50%

Aina's ring can also take calls and help you dictate notes on your Mac.

https://techcrunch.com/2026/11/05/ainas-smart-ring-has-a-screen-a-joystick-and-a-mic-so...

9 CONF

A YC startup is putting $1M behind 5 unsolved materials science problems for AI

TechCrunch AI 50%

While frontier AI models have solved a remarkable series of outstanding mathematics problems and made progress in the life sciences, they have yet to truly plumb the complex physics in advanced materials.

https://techcrunch.com/2026/11/05/a-yc-startup-is-putting-1m-behind-five-unsolved-mater...

0 CONF

Nothing CEO says company’s mysterious AI-first device is dropping next month

TechCrunch AI 50%

While it's not yet clear what kind of product the smartphone startup is cooking up, Nothing's CEO said the product is designed to leverage AI for productivity gains.

https://techcrunch.com/2026/11/04/nothing-ceo-says-companys-mysterious-ai-first-device-...

1 CONF

Perplexity launches its own take on AI agents for work

The Verge AI 50%

Perplexity is taking on OpenAI and Anthropic with its own work-focused AI agents. The startup's new always-on "Teammates" can take on multiple roles within a workspace, while pulling existing projects, skills, and memory from the Perplexity tools you already use. Teammates...

https://www.theverge.com/ai-artificial-intelligence/1028302/perplexity-teammates-ai-age...

2 CONF

Claude AI can plug directly into your bank account

The Verge AI 50%

Anthropic has a new pitch for managing your personal finances: let Claude do it instead, with a new Personal Finance feature that connects it to your bank and card accounts via the Plaid bank bridging platform. You can ask the chatbot "where did my money go this month," for...

https://www.theverge.com/ai-artificial-intelligence/1027652/anthropic-claude-plaid-pers...

3 CONF

‘Total repudiation’: The blue wave is about to hit AI

The Verge AI 50%

On Tuesday night, Democrats made history as they took control of the House and the Senate, and a blue wave swept through traditionally red and swing states - with the nation's first Black woman governor elected in Georgia, the country's first Native American woman governor...

https://www.theverge.com/ai-artificial-intelligence/1026927/total-repudiation-the-blue-...

4 CONF

Grimes is going to star in an AI movie that’s coming to theaters

The Verge AI 50%

The AI-generated sci-fi film Gods Don't Give Gifts has added a bit of star power: Pop star Grimes is going to appear in the movie. Billed as "the first AI film to come to theatres," Gods Don't Give Gifts is a notable test case for the commercial potential of AI films, and it...

https://www.theverge.com/entertainment/1026282/grimes-ai-movie

5 CONF

The hidden supply chain costs of the AI boom

The Verge AI 50%

Today, I’m talking with Willy Shih, an economist, a professor of management practice at Harvard Business School, and the author of the upcoming book, Where Does My Stuff Come From? The Powerful Economics Behind Global Supply Chains. Willy is one of my all-time favorite Decoder...

https://www.theverge.com/podcast/1024438/willy-shih-supply-chain-ai-chips-ram-where-doe...

6 CONF

You can post AI music straight to SoundCloud from ElevenLabs

The Verge AI 50%

After partnering with Moises earlier this year, SoundCloud is now adding integration with another AI music platform, ElevenLabs. Now, rather than having to export and download your outputs from ElevenLabs and then upload them to SoundCloud, you can publish them directly. As part...

https://www.theverge.com/ai-artificial-intelligence/1027427/ai-music-soundcloud-elevenlabs

7 CONF

Formalizing inverse problems in the age of AI: possibilities, pitfalls, and an invitation

ArXiv CS.AI 50%

arXiv:2611.06962v1 Announce Type: new Abstract: Proof assistants such as Lean check mathematical proofs down to the axioms, and AI agents have recently made writing such proofs cheap. We describe AutoIP, a Lean library in which classical linear regularization theory, together...

https://arxiv.org/abs/2611.06962

8 CONF

BlockLock: Reproducible LLM Inference with Fixed Batch Geometry

ArXiv CS.AI 50%

arXiv:2611.06977v1 Announce Type: new Abstract: Reproducible LLM inference requires that a request produces the same output regardless of the other requests in the batch. Existing solutions pay for this in different ways: batch-invariant kernels constrain every operator, and...

https://arxiv.org/abs/2611.06977

9 CONF

Accelerating Safe Reinforcement Learning with Massive Parallelism

ArXiv CS.AI 50%

arXiv:2611.08273v1 Announce Type: cross Abstract: We investigate the problem of scaling safe reinforcement learning (safe RL) to massively parallel training regimes, where a large number of environments are exe- cuted with short rollout horizons. Although this setting improves...

https://arxiv.org/abs/2611.08273

0 CONF

The Two-Ledger Model: Transaction-Grain Cost Accounting for Multi-Agent AI Systems Across Clouds, Models, and Systems of Record

ArXiv CS.AI 50%

arXiv:2611.06989v1 Announce Type: new Abstract: Enterprises run business transactions through multi-agent AI systems spanning clouds, large language models (LLMs), orchestration harnesses, and systems of record. Finance receives AI cost only at settlement grain, aggregated by...

https://arxiv.org/abs/2611.06989

1 CONF

Autonomous AI Agents Systematically Diverge From Human Preferences in Proof Formalization

ArXiv CS.AI 50%

arXiv:2611.06995v1 Announce Type: new Abstract: Artificial intelligence (AI) systems have ushered in a new age of proof abundance, but helping humans understand these proofs requires new attention to the differences in how AI agents and humans pursue a proof-making task. We...

https://arxiv.org/abs/2611.06995

2 CONF

Trust Responsive Runtime Authorization for Agentic AI with Empirical Characterization of Policy Behavior and Parameter Sensitivity

ArXiv CS.AI 50%

arXiv:2611.06996v1 Announce Type: new Abstract: The policy that converts runtime estimates of an autonomous agent's condition into operational authority is rarely specified or measured. We empirically characterize the Trust Responsive Authorization Policy (TRAP), which maps an...

https://arxiv.org/abs/2611.06996

3 CONF

Adapting the Process of Adaptation: Darwinian, Lamarckian, and Agent-Directed Evolution in AI

ArXiv CS.AI 50%

arXiv:2611.07048v1 Announce Type: new Abstract: Evolution has shaped intelligence for billions of years. Artificial intelligence (AI) now raises a striking possibility: intelligence may begin to direct its own evolution. As AI agents become capable of modifying and evaluating...

https://arxiv.org/abs/2611.07048

4 CONF

When Verification Is Not Agreement: Cross-Agent LLM-to-Dafny Formalization

ArXiv CS.AI 50%

arXiv:2611.07073v1 Announce Type: new Abstract: A verified Dafny postcondition certifies that a formula holds, but it does not guarantee that the result was reached through genuine independent reasoning. We introduce a cross-agent formalization protocol where a Specifier model...

https://arxiv.org/abs/2611.07073

5 CONF

Preference-Guided Adversarial Policy Optimization for Long-Tail Robust Driving

ArXiv CS.AI 50%

arXiv:2603.15221v2 Announce Type: replace-cross Abstract: Deploying autonomous driving systems requires robustness against long-tail scenarios that are rare but safety-critical. While adversarial training offers a promising solution, existing methods typically decouple scenario...

https://arxiv.org/abs/2603.15221

6 CONF

CST-Bench: Benchmarking Counterfactual Spatial Transition Reasoning with Causal Transition On-Policy Self-Distillation

ArXiv CS.AI 50%

arXiv:2611.07541v1 Announce Type: new Abstract: Spatial reasoning is a fundamental capability of multimodal large language models (MLLMs), yet existing benchmarks mainly focus on static scene understanding. When objects are moved or swapped, models must infer not only spatial...

https://arxiv.org/abs/2611.07541

7 CONF

FlashOffloading: Low-Latency KV Cache Offloading for Long-Context LLM Serving

ArXiv CS.AI 50%

arXiv:2611.07542v1 Announce Type: new Abstract: In large language model (LLM) serving systems, the key-value (KV) cache grows linearly with sequence length and concurrency, so long-context inference easily hits the high-bandwidth memory (HBM) capacity wall and results in low...

https://arxiv.org/abs/2611.07542

8 CONF

Embedding-Space Fingerprinting of LoRA Fine-Tunes: Recovering the Training-Data Domain from the Model Artifact Alone

ArXiv CS.AI 50%

arXiv:2611.07610v1 Announce Type: new Abstract: When a base language model is fine-tuned with Low-Rank Adaptation (LoRA), how much of the training data domain leaks into the resulting artifact? This paper studies whether a simple classifier can recover the domain of a fine-tune...

https://arxiv.org/abs/2611.07610

9 CONF

Who Should Know What? Empirical Information Design for Multi-Agent LLM Economies

ArXiv CS.AI 50%

arXiv:2611.07667v1 Announce Type: new Abstract: The performance of multi-agent LLM systems depends not only on the capabilities of the underlying models but also on information-sharing policies, which govern what information each agent observes and at what level of detail. But...

https://arxiv.org/abs/2611.07667

0 CONF

The Price of Safety: Benign-Case Utility and Token Overhead of Memory-Poisoning Defenses in LLM Agents

ArXiv CS.AI 50%

arXiv:2609.22818v3 Announce Type: replace-cross Abstract: Memory-poisoning defenses for LLM agents are usually judged by how well they stop attacks, yet almost all the traffic an agent sees is benign. We measure what these defenses cost when no attack is present. Our harness...

https://arxiv.org/abs/2609.22818

1 CONF

Implicit Regularization via Spectral Neural Networks and Non-linear Matrix Sensing

ArXiv CS.AI 50%

arXiv:2402.17595v2 Announce Type: replace-cross Abstract: The phenomenon of implicit bias has attracted interest in recent years as a fundamental aspect of the remarkable generalizing ability of neural networks. In a nutshell, it entails that gradient descent dynamics in many...

https://arxiv.org/abs/2402.17595

2 CONF

The Intrusion Pathway: How Non-Evidential Context Degrades Language Model Performance

ArXiv CS.AI 50%

arXiv:2611.07778v1 Announce Type: new Abstract: Language models lose accuracy when a prompt contains non-evidential context: irrelevant statements from unrelated domains, or random off-distribution tokens, with no competing answer and no semantic overlap with the query. Such...

https://arxiv.org/abs/2611.07778

3 CONF

Responsible GenAI Use During Active Armed Conflict: Evidence from Sudan's Emergency Response Rooms

ArXiv CS.AI 50%

arXiv:2611.07874v1 Announce Type: new Abstract: Armed conflict can increase the value of Generative AI (GenAI) while undermining the conditions required for its responsible use. Yet the perspectives of community-based humanitarian responders working under these conditions remain...

https://arxiv.org/abs/2611.07874

4 CONF

When Bigger Becomes Brittle: Why Compression Hurts More as Language Models Scale

ArXiv CS.AI 50%

arXiv:2611.07891v1 Announce Type: new Abstract: Quantization and pruning reduce the cost of deploying language models, but their effects are usually reported as benchmark scores. Such scores record only the loss that remains at the output. Inside the model, compression damages...

https://arxiv.org/abs/2611.07891

5 CONF

GuidedWAM: Training-Free Energy Guidance for World Action Models in Autonomous Driving

ArXiv CS.AI 50%

arXiv:2611.07912v1 Announce Type: new Abstract: World action models (WAMs) for autonomous driving couple the driving policy and the visual world model in a single generative network whose objectives are fixed post-training. Conditioning on a new driving objective requires...

https://arxiv.org/abs/2611.07912

6 CONF

How Finite Brains Generalize Without Bound: Spatial Memory as a Universal Computer

ArXiv CS.AI 50%

arXiv:2611.07920v1 Announce Type: new Abstract: A child who learns to add small numbers adds numbers of any length. LSTMs and Transformers trained on short sequences fail on longer ones. We trace the difference to what a learner reads when it decides. A position, a count or a...

https://arxiv.org/abs/2611.07920

7 CONF

ChemE-as-Code: An Open-Source Platform for Agentic AI in Chemical Engineering

ArXiv CS.AI 50%

arXiv:2611.07947v1 Announce Type: new Abstract: ChemE-as-Code provides an open-source environment in which AI agents built on large language models (LLMs) can carry out chemical engineering work and engineers can check it. Its calculation tools range from catalysis through...

https://arxiv.org/abs/2611.07947

8 CONF

Circe: Training-Free LLM Self-Evaluation via Component Interaction Consistency

ArXiv CS.AI 50%

arXiv:2611.07948v1 Announce Type: new Abstract: As large language models (LLMs) are increasingly deployed in real-world applications, evaluating the correctness of their responses is crucial for reliable use. However, such evaluation is challenging because reference answers are...

https://arxiv.org/abs/2611.07948

9 CONF

A Behavioural Framework for Predicting and Understanding Loss of Control in Frontier Artificial Intelligence Systems

ArXiv CS.AI 50%

arXiv:2611.07953v1 Announce Type: new Abstract: Frontier artificial intelligence (AI) systems are increasingly operating over longer horizons with diminishing human oversight, raising the risk of loss of control: systems acting beyond effective human control with potentially...

https://arxiv.org/abs/2611.07953

0 CONF

TCSExam: Evaluating Frontier LLMs on the Full Range of TCS Research

ArXiv CS.AI 50%

arXiv:2611.07962v1 Announce Type: new Abstract: Can large language models (LLMs) advance theoretical computer science and resolve its long-standing open conjectures? To study progress toward this goal, we introduce TCSExam, a unified framework and benchmark covering the full...

https://arxiv.org/abs/2611.07962

1 CONF

Secure Formal Raising: Protecting the Development of AI through Executable Properties

ArXiv CS.AI 50%

arXiv:2611.08042v1 Announce Type: new Abstract: Model raising revisits Turing's developmental view of machine intelligence. Formal Raising (FR) has recently been proposed to complement this view with explicit behavioral properties. This paper extends that proposal to the...

https://arxiv.org/abs/2611.08042

2 CONF

Create Your Own Work Stack: Deploying Self-hosted AI and Tooling in a Tech Startup

ArXiv CS.AI 50%

arXiv:2611.08116v1 Announce Type: new Abstract: Self-hosting AI is often presented as a way to reduce inference costs and increase control, but deployment introduces its own costs. We report our experience deploying a hybrid AI stack at Grayhat Developers, a small software...

https://arxiv.org/abs/2611.08116

3 CONF

Volterra Generative Models via Markovian Lifting

ArXiv CS.AI 50%

arXiv:2606.18071v2 Announce Type: replace-cross Abstract: Diffusion-based generative models usually perturb data through Markov processes driven by Brownian motion. Volterra processes allow more flexible temporal dependence, but their non-Markovian structure complicates score...

https://arxiv.org/abs/2606.18071

4 CONF

PCBRouteAgent: How Close Are LLM Agents to Becoming PCB Routing Engineers?

ArXiv CS.AI 50%

arXiv:2611.08175v1 Announce Type: new Abstract: Automating printed circuit board (PCB) routing requires coordinating board-level connectivity decisions with geometric execution under strict design rules. Although recent agents can interact with native routing tools, reliable...

https://arxiv.org/abs/2611.08175

5 CONF

BabyTheorist: A Benchmark for Learning to Theorize the World from Observation Alone

ArXiv CS.AI 50%

arXiv:2611.08177v1 Announce Type: new Abstract: How would we know whether a machine truly understands the world? We argue that one key capability is \textit{observational theory learning}: acquiring reusable theories from pure observations and applying them to new situations....

https://arxiv.org/abs/2611.08177

6 CONF

Signals, Evidence, and Context: User Scrutiny in Real-World LLM Conversations

ArXiv CS.AI 50%

arXiv:2611.08232v1 Announce Type: new Abstract: Large language models (LLMs) often present synthesized answers without making their supporting evidence easy to inspect. We study how features of these answers relate to users' subsequent accepting, checking, and challenging in...

https://arxiv.org/abs/2611.08232

7 CONF

Concertina: Embodying Manipulation and Cognition in One Diffusion Vision-Language Model

ArXiv CS.AI 50%

arXiv:2611.07513v1 Announce Type: cross Abstract: Most vision-language-action (VLA) policies decouple manipulation from cognition by bolting an external action mechanism onto a vision-language model (VLM)--either quantizing actions into discrete tokens whose errors bear no...

https://arxiv.org/abs/2611.07513

8 CONF

A Generative Model of Contextual Integrity: Appropriate vs. Inappropriate Information Sharing

ArXiv CS.AI 50%

arXiv:2611.08284v1 Announce Type: new Abstract: Contextual integrity (CI) holds that appropriate information flow depends on context-specific norms. The same disclosure may be appropriate in one context and inappropriate in another. We build a generative model of contextual...

https://arxiv.org/abs/2611.08284

9 CONF

Benchmarking Large Language Models on Heterogeneous Cognitive and Biomedical Knowledge Graphs: The Role of Graph Grounding in Multi-Hop Reasoning and Hallucination Mitigation

ArXiv CS.AI 50%

arXiv:2611.08315v1 Announce Type: new Abstract: Large language models (LLMs) are increasingly used in biomedical and cognitive neuroscience, but their ability to reason reliably over heterogeneous knowledge graphs (KGs) remains unclear. We benchmark five LLMs (GPT-5.1, Gemini...

https://arxiv.org/abs/2611.08315

0 CONF

Enhancing Local and Global Structure in Compressed AI Agent Memory

ArXiv CS.AI 50%

arXiv:2611.08341v1 Announce Type: new Abstract: AI agents store text as embedding vectors and compress them at scale. A compression is accepted when each item's nearest neighbors survive, but agents also consolidate, delete, and compare memories, tasks that depend on which items...

https://arxiv.org/abs/2611.08341

1 CONF

LinAlg-Bench: A Forensic Benchmark Revealing Structural Failure Modes in LLM Mathematical Reasoning

ArXiv CS.AI 50%

arXiv:2605.16675v2 Announce Type: replace Abstract: We introduce LinAlg-Bench, a diagnostic benchmark evaluating 10 frontier large language models on structured linear algebra computation across a strict dimensional gradient of 3x3, 4x4, and 5x5 matrices. Spanning 9 task types...

https://arxiv.org/abs/2605.16675

2 CONF

The Gold Rush in AI4Math, II: What are signatures of AI-assisted Proofs?

ArXiv CS.AI 50%

arXiv:2611.08412v1 Announce Type: new Abstract: The growing use of AI in mathematics raises a question: can we detect AI involvement in proofs, separately from AI assistance with writing? Historical arXiv papers, recent papers disclosing substantive AI use, and manuscripts...

https://arxiv.org/abs/2611.08412

3 CONF

Benchmarks as Software: Terminal-Bench and the Case for Continuous Benchmarks

ArXiv CS.AI 50%

arXiv:2611.08417v1 Announce Type: new Abstract: Coding agents are among the most economically consequential deployments of LLMs to date, making reliable evaluation increasingly important. Yet even benchmarks that are carefully validated at release can become stale. As models...

https://arxiv.org/abs/2611.08417

4 CONF

The Power of Meta Access in the Software of the Future --- Demonstrated on LLM Chat UIs and Chat AI

ArXiv CS.AI 50%

arXiv:2611.08428v1 Announce Type: new Abstract: Chat remains the default surface for many large language model (LLM) tasks, even as agentic tools such as OpenCode excel at coding and automation. Yet the model sees the current dialogue but not the workspace around it. We explore...

https://arxiv.org/abs/2611.08428

5 CONF

Scientist World: Grow a Research World for AI-Scientists

ArXiv CS.AI 50%

arXiv:2611.08478v1 Announce Type: new Abstract: AI-Scientists arrived, but a world for them to grow in did not. Human scientists take theirs for granted $-$ centuries of open problems and shared ideas, waiting in the scientific literature. To AI-Scientists, that world is...

https://arxiv.org/abs/2611.08478

6 CONF

Manifold-Constrained Initial Noise Optimization for Efficient Generative Model Alignment

ArXiv CS.AI 50%

arXiv:2610.00365v2 Announce Type: replace-cross Abstract: Recent advances in distillation and flow-map models have enabled deterministic one- or few-step generation for high-quality data, facilitating a new branch of reward alignment approaches that directly optimize the initial...

https://arxiv.org/abs/2610.00365

7 CONF

A minimal dynamical model of human-AI cognitive coevolution

ArXiv CS.AI 50%

arXiv:2611.06928v1 Announce Type: cross Abstract: The rapid deployment of generative AI raises the question of whether pervasive cognitive offloading drives a measurable, potentially irreversible decline in unassisted human reasoning. We examine this question with a...

https://arxiv.org/abs/2611.06928

8 CONF

ApproxBrain: Certified Sufficiency Frontiers in Connectome-Constrained Neural Systems

ArXiv CS.AI 50%

arXiv:2611.06929v1 Announce Type: cross Abstract: Background. A connectome specifies the substrate available to a nervous system, not how much of it a given computation requires. Reported compact sufficient circuits are point estimates: one subset, one task, one fidelity...

https://arxiv.org/abs/2611.06929

9 CONF

BrainPFN: Amortized Brain-Behaviour Prediction via Prior-Data Fitted Networks

ArXiv CS.AI 50%

arXiv:2611.06934v1 Announce Type: cross Abstract: The standard approach to predicting behavioral phenotypes from functional MRI is represented by Kernel Ridge Regression (KRR) applied on functional connectivity (FC) matrices. However, this approach is limited: separate models...

https://arxiv.org/abs/2611.06934

0 CONF

KG-AST for Cheaper CI/CD: Budgeted Test Selection and AI Bug Review

ArXiv CS.AI 50%

arXiv:2611.06950v1 Announce Type: cross Abstract: Continuous integration and AI-assisted review spend the same budget on every commit, although few commits introduce bugs. We study KG-AST, which scores each commit risk from git history and code-graph features before heavy tests...

https://arxiv.org/abs/2611.06950

1 CONF

Big Models, Small Gains: Frozen Forecasters as Classifiers on MONSTER

ArXiv CS.AI 50%

arXiv:2611.06988v1 Announce Type: cross Abstract: Forecasting foundation models are increasingly used as frozen feature extractors for time series classification, but it remains unclear whether their pretrained representations offer an advantage over strong classifiers that do...

https://arxiv.org/abs/2611.06988

2 CONF

Compositional Unalignment: Auditing Safety in Large Vision-Language Models

ArXiv CS.AI 50%

arXiv:2611.07216v1 Announce Type: cross Abstract: Large vision-language models (LVLMs) are vulnerable to compositional harm: an image and a prompt that are benign in isolation become harmful through the model's cross-modal reasoning. Recent alignment methods report strong scores...

https://arxiv.org/abs/2611.07216

3 CONF

SD-LoRA: Training-Time Structural Distillation into LoRA for Few-Shot Vision-Language Adaptation

ArXiv CS.AI 50%

arXiv:2611.07063v1 Announce Type: cross Abstract: Few-shot adaptation of vision-language models must balance two competing goals: learning fine-grained visual distinctions from very limited supervision and preserving the efficiency that makes frozen CLIP-like models attractive...

https://arxiv.org/abs/2611.07063

4 CONF

Finite-Time Convergence and Regret Guarantees for Neural Reinforcement Learning in POMDPs

ArXiv CS.AI 50%

arXiv:2611.07069v1 Announce Type: cross Abstract: Reinforcement learning (RL) in Partially Observable Markov Decision Processes (POMDPs) is computationally challenging due to the curse of long-range dependence on history. Fortunately, recent studies have shown that a range of...

https://arxiv.org/abs/2611.07069

5 CONF

A Night at the LLM Zoo: Data Conditioned Flow Matching for Generating Pretrained LLM Weights

ArXiv CS.AI 50%

arXiv:2611.07103v1 Announce Type: cross Abstract: A challenge to Weight Space Learning as it expands from task specific and vision models to Large Language Models (LLMs) is the absence of a well curated and analyzed LLM population. To address this, we train such a model zoo for...

https://arxiv.org/abs/2611.07103

6 CONF

Adapting LLM Judges to Observed Human Annotation Policy through Soft Prompt Tuning

ArXiv CS.AI 50%

arXiv:2611.07126v1 Announce Type: cross Abstract: Large Language Models (LLMs) are increasingly employed as automated judges for evaluating chatbot responses. While proprietary models can achieve high agreement with human annotators, they remain costly and difficult to deploy in...

https://arxiv.org/abs/2611.07126

7 CONF

More Agents, More Reliable? System-Level Reliability of Multi-Agent LLMs under Operational-Profile Uncertainty

ArXiv CS.AI 50%

arXiv:2611.07140v1 Announce Type: cross Abstract: Teams increasingly build software from cooperating large language model (LLM) agents, often assuming more agents mean more reliability. Yet the usual evidence, average benchmark accuracy, ignores the input mix a deployed system...

https://arxiv.org/abs/2611.07140

8 CONF

SeVerus: Context-Aware, Gamified Benchmarking for Rust Verification

ArXiv CS.AI 50%

arXiv:2611.07194v1 Announce Type: cross Abstract: Coding agents achieve high success rates on existing benchmarks for Verus, a verifier for Rust programs. These benchmarks typically provide the auxiliary lemmas needed to complete a proof. In practice, however, such lemmas must...

https://arxiv.org/abs/2611.07194

9 CONF

TileQuant: Tile as the Precision-Allocation Unit for LLM Mixed-Precision Post-Training Quantization

ArXiv CS.AI 50%

arXiv:2611.07217v1 Announce Type: cross Abstract: Post-training quantization (PTQ) reduces large language model (LLM) deployment costs, but preserving quality requires accounting for uneven weight sensitivity. Uniform PTQ uses one weight bit-width, importance-aware PTQ adjusts...

https://arxiv.org/abs/2611.07217

0 CONF

SPILLWAY: Separating Target Admission from Sanitization to Defend Tool-Using Agents against Prompt Injection

ArXiv CS.AI 50%

arXiv:2611.07222v1 Announce Type: cross Abstract: Tool-using agents act on email, files, and payments, so an instruction hidden in a web page or a shared document can make an agent send data or money to an attacker. Many runtime defenses put a language model on the decision that...

https://arxiv.org/abs/2611.07222

1 CONF

When LLM Routers Overpay: The Cost of Strong-Model Preference

ArXiv CS.AI 50%

arXiv:2602.03478v2 Announce Type: replace Abstract: LLM routing aims to reduce inference costs by assigning easy queries to less expensive models and reserving stronger models for cases in which they are needed. However, we find that existing routers often violate this principle...

https://arxiv.org/abs/2602.03478

2 CONF

KG-Neighbor: Knowledge-Guided Neighborhood Construction for Embedding Visualization

ArXiv CS.AI 50%

arXiv:2611.07246v1 Announce Type: cross Abstract: In embedding visualizations, nearby instances are interpreted as semantically related, although neighborhoods derived from input embeddings may not reflect content relationships. Neighborhood-based dimensionality reduction (DR)...

https://arxiv.org/abs/2611.07246

3 CONF

TriAttention: Unified Sparse Mixed-Precision Attention for Long-Context LLM Inference

ArXiv CS.AI 50%

arXiv:2611.07256v1 Announce Type: cross Abstract: Sparsity and quantization reduce the cost of attention by skipping interactions and lowering the precision of those retained. However, useful interactions differ in their precision requirements: some tolerate low-precision scores...

https://arxiv.org/abs/2611.07256

4 CONF

Satisficing as competitive Bayesian weighting: a minimal model of goal-directed choice under an unattained target

ArXiv CS.AI 50%

arXiv:2611.07270v1 Announce Type: cross Abstract: Animals and humans often do not maximize; they act relative to goals (aspiration levels) that are frequently not yet met. How can a goal that is not (yet) realized organize choice? Deacon (2012) calls such absence-referenced...

https://arxiv.org/abs/2611.07270

5 CONF

Selective Retrieval Routing for Multi-Violation Knowledge Graph Repair

ArXiv CS.AI 50%

arXiv:2611.07342v1 Announce Type: cross Abstract: Knowledge graphs often contain missing or inconsistent facts that undermine the applications built on them. Schema validation detects such violations but does not identify which of several valid repairs recovers the intended...

https://arxiv.org/abs/2611.07342

6 CONF

VTAM: Efficient Visuo-Tactile World-Action Models for Contact-Rich Manipulation without Tactile Pretraining

ArXiv CS.AI 50%

arXiv:2603.23481v2 Announce Type: replace-cross Abstract: Tactile vision-language-action models (VLAs) and tactile world-action models (WAMs) are a promising new paradigm for contact-rich manipulation, but existing models either underutilize touch, rely on large-scale tactile...

https://arxiv.org/abs/2603.23481

7 CONF

Localization Does Not Imply Steerability: A Mechanistic Study of Sign Errors in LLM Mathematics

ArXiv CS.AI 50%

arXiv:2611.07478v1 Announce Type: cross Abstract: When large language models do multi-step mathematics, a characteristic failure recurs: the model writes one wrong sign token mid-computation -- a cofactor sign, the minus of a recursive integration-by-parts step -- then executes...

https://arxiv.org/abs/2611.07478

8 CONF

Signed but Not Safe: Requirement Integrity in Multi-Agent LLM Handoffs

ArXiv CS.AI 50%

arXiv:2611.07483v1 Announce Type: cross Abstract: Enterprise AI agents increasingly split a user's request across subagents and merge their results, and each handoff can summarize away, alter or ignore a requirement. We report a preregistered study with synthetic, exactly...

https://arxiv.org/abs/2611.07483

9 CONF

Failure Prediction and Classification in Vision-Language-Action Models Via Calibrated Latent Probing

ArXiv CS.AI 50%

arXiv:2611.08425v1 Announce Type: cross Abstract: Vision-Language-Action models (VLAs) enable general-purpose embodied intelligence, but their performance is brittle under distribution shift, where unanticipated failures can damage equipment or endanger people. Deploying VLAs in...

https://arxiv.org/abs/2611.08425

0 CONF

Stress Testing Chain-of-Thought Monitoring Against Covert Misalignment

ArXiv CS.AI 50%

arXiv:2611.07586v1 Announce Type: cross Abstract: As LLM agents advance rapidly in autonomy, the risk of hidden objectives that bypass safety constraints becomes increasingly plausible. Chain-of-thought (CoT) monitoring offers a key control mechanism by reading the agent's...

https://arxiv.org/abs/2611.07586

1 CONF

FisherDistill: Diffusion Distribution Distillation via Closed-Form Fisher Critics

ArXiv CS.AI 50%

arXiv:2611.07604v1 Announce Type: cross Abstract: Recent advances in diffusion distillation have enabled high-quality image generation in only one or a few network function evaluations (NFEs). Despite their efficiency, aggressively distilled generators often retain a residual...

https://arxiv.org/abs/2611.07604

2 CONF

The Popular Get More Popular: Auditing Brand Bias in Generative Search

ArXiv CS.AI 50%

arXiv:2611.07614v1 Announce Type: cross Abstract: The shift from traditional to generative search has fundamentally transformed online product discovery. Because conversational recommendations synthesize choices into a few direct answers, subtle systemic preferences toward...

https://arxiv.org/abs/2611.07614

3 CONF

Measuring the Marginal Value of Verifier-Based RL Beyond Supervised Fine-Tuning

ArXiv CS.AI 50%

arXiv:2611.07639v1 Announce Type: cross Abstract: Reinforcement learning from verifiable rewards (RLVR) is usually evaluated as an alternative to supervised fine-tuning (SFT), or as a stage that follows it, with the implicit assumption that the RL stage contributes gains of its...

https://arxiv.org/abs/2611.07639

4 CONF

Beyond Instruction Override: Benchmarking Indirect Prompt Injection with Task-Tampering Attacks

ArXiv CS.AI 50%

arXiv:2611.07640v1 Announce Type: cross Abstract: Indirect prompt-injection (IPI) benchmarks predominantly test planted instructions that redirect a tool-using agent toward an attacker-chosen task. Yet attacker-controlled content can instead tamper with the outcome of the task...

https://arxiv.org/abs/2611.07640

5 CONF

What the Middleman Delivers: Answer Behavior, Tool Permissions, and Billed Usage in LLM API Relays

ArXiv CS.AI 50%

arXiv:2611.07650v1 Announce Type: cross Abstract: Third-party application programming interface (API) relays offer access to large language models (LLMs), often at lower prices. Users depend on these services for model quality, instruction compliance, and accurate billing....

https://arxiv.org/abs/2611.07650

6 CONF

Equivariant Deep Learning in Direct-Product Space for Electronic-Structure Hamiltonian Prediction

ArXiv CS.AI 50%

arXiv:2611.07695v1 Announce Type: cross Abstract: Most existing equivariant architectures for Hamiltonian prediction propagate features in direct-sum spaces of irreducible spherical tensors, whereas the target Hamiltonian is naturally an operator block in a direct-product...

https://arxiv.org/abs/2611.07695

7 CONF

FinMultiHopQA: A KG-Grounded Multi-Hop Financial QA Benchmark for Evidence-Driven Reasoning

ArXiv CS.AI 50%

arXiv:2510.02906v2 Announce Type: replace-cross Abstract: Multi-hop financial question answering often requires composing evidence distributed across filing sections, fiscal years, and peer companies. Prior financial QA benchmarks address parts of this problem individually, but...

https://arxiv.org/abs/2510.02906

8 CONF

tok: a textual concrete syntax of BPMN and DMN for humans and AI agents

ArXiv CS.AI 50%

arXiv:2611.07945v1 Announce Type: cross Abstract: tok is a plain-text notation for Business Process Model and Notation (BPMN) 2.0.2 process models and Decision Model and Notation (DMN) 1.5 decisions. One engine checks a tok document against both standards, compiles the document...

https://arxiv.org/abs/2611.07945

9 CONF

Continued Training of Continuous Language Flows with Token Identity Squared Supervision

ArXiv CS.AI 50%

arXiv:2611.07721v1 Announce Type: cross Abstract: Diffusion and flow models have recently been extended to language modeling, generating text through continuous denoising in token embedding spaces. Pretrained models provide token representations and contextual prediction...

https://arxiv.org/abs/2611.07721

00 CONF

Scaling Neural Motor Decoding via Decoupled Behavioral Pretraining

ArXiv CS.AI 50%

arXiv:2611.08263v1 Announce Type: cross Abstract: Recent neural decoding approaches achieve strong performance by training on large collections of paired neural-behavioral recordings, but such datasets are expensive, invasive, and difficult to scale. In contrast, behavioral data...

https://arxiv.org/abs/2611.08263

01 CONF

Bridging Structure and Semantics: Knowledge Graph Verification via Triple-to-Text Alignment

ArXiv CS.AI 50%

arXiv:2611.07780v1 Announce Type: cross Abstract: Semantic accuracy is an important dimension of knowledge graph quality. Graph-based scoring methods exploit relational structure, while textual representations allow classifiers to draw on knowledge encoded by pre-trained...

https://arxiv.org/abs/2611.07780

02 CONF

Axis-LoRA: Probing and Adapting Embedding Models for Personal-Memory Retrieval

ArXiv CS.AI 50%

arXiv:2611.07820v1 Announce Type: cross Abstract: As LLMs are increasingly asked questions about a user's personal experiences, retrieval must distinguish memories by time, place, person, and event. Current personal-memory pipelines rely on frozen dense embedding models to embed...

https://arxiv.org/abs/2611.07820

03 CONF

Masked diffusion as random sequential adsorption: an exactly solvable model for parallel decoding

ArXiv CS.AI 50%

arXiv:2611.07845v1 Announce Type: cross Abstract: Masked diffusion models generate text by reversing a stochastic masking process. Unlike autoregressive LLMs, which generate text one token at a time, they can reveal many tokens in parallel, at the price of an error, since tokens...

https://arxiv.org/abs/2611.07845

04 CONF

When, Where, How: Active In-Context Learning for Tabular Foundation Models

ArXiv CS.AI 50%

arXiv:2611.07886v1 Announce Type: cross Abstract: Tabular Foundation Models (TFMs) adapt to a new task only through the labeled rows in their context. However, labels are expensive to acquire in real-world scenarios due to the need for highly specific domain knowledge to ensure...

https://arxiv.org/abs/2611.07886

05 CONF

CardioLM: A multilingual suite of small language models for the cardiology domain

ArXiv CS.AI 50%

arXiv:2611.07940v1 Announce Type: cross Abstract: Background: Cardiovascular care generates large volumes of clinical free-text documentation in local languages. However, clinical natural language processing (NLP) resources remain concentrated in English, and no existing...

https://arxiv.org/abs/2611.07940

06 CONF

Technohybridism: Recursive Semantic Normalization in AI-Mediated Societies

ArXiv CS.AI 50%

arXiv:2611.07984v1 Announce Type: cross Abstract: Language-generating AI systems are no longer only objects of linguistic interaction: their outputs increasingly re-enter the communicative and institutional practices from which their training material was drawn. Drawing on...

https://arxiv.org/abs/2611.07984

07 CONF

Can an LLM Actually Reason and Program about Neural Network's Weights or is it just memorization on steroids? Exploring "Weight-Space Programming"

ArXiv CS.AI 50%

arXiv:2611.08070v1 Announce Type: cross Abstract: Large language models (LLMs) have recently been reported to read and write the raw weights of neural networks directly, a capability termed weight-space programming. We ask whether the reading side of this capability reflects...

https://arxiv.org/abs/2611.08070

08 CONF

Who Can Evaluate AI Independently? A Framework for Analysing Evaluation Infrastructure

ArXiv CS.AI 50%

arXiv:2611.08134v1 Announce Type: cross Abstract: AI evaluation is increasingly central to AI safety and governance, yet taking part in an evaluation does not by itself confer authority over its design, its execution or the resources it depends on. This paper examines how...

https://arxiv.org/abs/2611.08134

09 CONF

Interpretable Multimodal MRI-Clinical Fusion for Functional Outcome Prediction After Acute Ischemic Stroke

ArXiv CS.AI 50%

arXiv:2611.08154v1 Announce Type: cross Abstract: This study evaluates the added prognostic value of day-1 multimodal MRI for predicting three-month functional outcome after acute ischemic stroke (AIS). Sixty-six AIS patients with ADC, DWI, FLAIR, and clinical data were...

https://arxiv.org/abs/2611.08154

10 CONF

Accepted but Wrong: Silent Failures of LLM Code Repairs after API Migrations

ArXiv CS.AI 50%

arXiv:2611.08269v1 Announce Type: cross Abstract: After a runtime or API migration, an LLM-repaired procedure can run cleanly yet return wrong results, and a release check on typical test inputs ships it. We report a preregistered study of 73 tasks covering 60 documented changes...

https://arxiv.org/abs/2611.08269

11 CONF

DART: Domain-Agnostic Residual Transfer for Generalist Anomaly Detection

ArXiv CS.AI 50%

arXiv:2611.08271v1 Announce Type: cross Abstract: Generalist Anomaly Detection (GAD) aims to detect anomalies in unseen domains using only a few reference samples. Recent normal-abnormal guided methods improve this setting by exploiting abnormal references, but their residuals...

https://arxiv.org/abs/2611.08271

12 CONF

Hybrid Machine Learning for Imbalanced Landing-Phase Safety Event Prediction from Flight Data

ArXiv CS.AI 50%

arXiv:2611.08386v1 Announce Type: cross Abstract: Landing-phase safety-event prediction requires the detection of rare abnormal approaches within strongly imbalanced multivariate flight data. Capturing coupled temporal behavior while distinguishing event-specific signatures...

https://arxiv.org/abs/2611.08386

13 CONF

MedGraph: Maintaining Patient State with Graph Memory for Long-Term Medical Dialogue

ArXiv CS.AI 50%

arXiv:2611.08433v1 Announce Type: cross Abstract: LLM-based medical assistants that follow a patient across visits need a memory that keeps the patient's clinical state correct as it changes. We examine the errors of five memory systems on longitudinal medical dialogue and find...

https://arxiv.org/abs/2611.08433

14 CONF

Understanding AI from the Inside: The State of Mechanistic Interpretability for AI Safety

ArXiv CS.AI 50%

arXiv:2611.08438v1 Announce Type: cross Abstract: Neural networks are likely to be among the most consequential artefacts in human history. As these systems become more capable and autonomous, their potential to cause societal harm also grows, making AI safety one of the...

https://arxiv.org/abs/2611.08438

15 CONF

Label-Wording Augmentation in a Typed-Decision Encoder: Gains on Unfamiliar Words, Not on Abbreviations or Codes

ArXiv CS.AI 50%

arXiv:2611.08439v1 Announce Type: cross Abstract: Typed-decision models score options that the caller supplies at request time, so their accuracy depends on label wording that the model's developer does not control. We compare two releases of a 307M-parameter multilingual...

https://arxiv.org/abs/2611.08439

16 CONF

ARMs: Adaptive Red-Teaming Agent against Multimodal Models with Plug-and-Play Attacks

ArXiv CS.AI 50%

arXiv:2510.02677v2 Announce Type: replace Abstract: As vision-language models (VLMs) gain prominence, their multimodal interfaces also introduce new safety vulnerabilities, making the safety evaluation challenging and critical. Existing red-teaming efforts are either restricted...

https://arxiv.org/abs/2510.02677

17 CONF

Cognitive Foundations for Reasoning and Their Manifestation in LLMs

ArXiv CS.AI 50%

arXiv:2511.16660v3 Announce Type: replace Abstract: Large language models (LLMs) solve complex problems yet fail on simpler variants, suggesting they achieve correct outputs through mechanisms fundamentally different from human reasoning. To understand this gap, we synthesize...

https://arxiv.org/abs/2511.16660

18 CONF

Harness Updating Is Not Harness Benefit: Disentangling Evolution Capabilities in Self-Evolving LLM Agents

ArXiv CS.AI 50%

arXiv:2605.30621v2 Announce Type: replace Abstract: LLM agents are increasingly deployed as systems built around editable external harnesses, including prompts, skills, memories and tools, that shape task execution without changing model parameters. Harness self-evolution adapts...

https://arxiv.org/abs/2605.30621

19 CONF

Are LLM Safety Judges Policy-Invariant? A Three-Principle Stress-Test

ArXiv CS.AI 50%

arXiv:2605.06161v2 Announce Type: replace Abstract: LLM-as-a-Judge pipelines have become the de facto evaluator for agent safety, yet existing benchmarks treat their verdicts as ground-truth proxies without checking whether the verdicts depend on the agent's behavior or merely...

https://arxiv.org/abs/2605.06161

20 CONF

Coding with the Enemy: Can Human Developers Detect AI Agent Sabotage?

ArXiv CS.AI 50%

arXiv:2606.05647v3 Announce Type: replace Abstract: AI coding agents are increasingly embedded in real-world software development, collaborating with human developers while gaining broader access to codebases and tools. This creates a new attack surface: an agent can exploit...

https://arxiv.org/abs/2606.05647

21 CONF

ThermoLLM: LLM-Based Multi-Zone HVAC Control with a Spatiotemporal Context

ArXiv CS.AI 50%

arXiv:2606.22911v2 Announce Type: replace Abstract: Multi-zone HVAC control is a spatial decision problem in which indoor thermal evolution and control decisions depend not only on outdoor conditions and internal heat gains but also on zone layout, physical adjacency, and...

https://arxiv.org/abs/2606.22911

22 CONF

Value Over Language Model: Detecting Original Contribution in Writing

ArXiv CS.AI 50%

arXiv:2609.00700v2 Announce Type: replace Abstract: LLMs have been rapidly adopted across writing tasks, prompting the development of tools for detecting LLM-generated text. Yet, these tools largely measure how much of a document's surface text was written by an LLM and aren't...

https://arxiv.org/abs/2609.00700

23 CONF

Backdoor Containment via Expert Quarantine and Shutdown in LLMs

ArXiv CS.AI 50%

arXiv:2610.00663v2 Announce Type: replace Abstract: Backdoored large language models (LLMs) can behave normally on benign inputs while producing attacker-specified outputs under hidden triggers. Existing defenses span four stages---prior-training, in-training, post-training, and...

https://arxiv.org/abs/2610.00663

24 CONF

VIGOR: Zero-Shot Visual Generalization via Latent-Space Consistency in Model-Based Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.02801v2 Announce Type: replace Abstract: Model-based reinforcement learning (MBRL) achieves strong sample efficiency by planning in learned latent dynamics but degrades substantially under unseen visual distractions such as background, lighting, or camera changes....

https://arxiv.org/abs/2610.02801

25 CONF

GAAC: Lossless KV Compression for Bandwidth-Efficient LLM Inference on Personal Devices

ArXiv CS.AI 50%

arXiv:2610.38210v2 Announce Type: replace Abstract: Weight-only, lossy quantization substantially reduces the storage and memory requirements for serving large language models (LLMs), but the growing key-value (KV) cache remains a bottleneck for long-context inference on...

https://arxiv.org/abs/2610.38210

26 CONF

Taurus: LLM-in-the-Loop CT Annotation Matches Coding Agents at Half the Cost

ArXiv CS.AI 50%

arXiv:2611.00247v2 Announce Type: replace Abstract: Dense labels of the aorta in CT are slow to draw, and the public aortic CT datasets that could stand in for them each label different structures under their own conventions. Large language model (LLM) agents can now write code...

https://arxiv.org/abs/2611.00247

27 CONF

Q-Learning under Finite Model Uncertainty

ArXiv CS.AI 50%

arXiv:2407.04259v4 Announce Type: replace-cross Abstract: We propose a robust Q-learning algorithm for Markov decision processes under model uncertainty when each state--action pair is associated with a finite ambiguity set of candidate transition kernels. This finite-measure...

https://arxiv.org/abs/2407.04259

28 CONF

Instruction-Tuning Large Language Models with Medical Classification Data Improves ICD Coding of German Tumor Diagnoses

ArXiv CS.AI 50%

arXiv:2510.13624v2 Announce Type: replace-cross Abstract: Accurate coding of tumor diagnoses with ICD-10-GM and ICD-O-3 is essential for structured cancer documentation in Germany. Smaller open-weight LLMs are appealing for privacy-preserving automation but often struggle with...

https://arxiv.org/abs/2510.13624

29 CONF

Analysis of LLM Vulnerability to GPU Soft Errors: An Instruction-Level Fault Injection Study

ArXiv CS.AI 50%

arXiv:2601.19912v2 Announce Type: replace-cross Abstract: Large language models (LLMs) are highly compute- and memory-intensive, posing significant demands on high-performance GPUs. At the same time, advances in GPU technology driven by shrinking transistor sizes and lower...

https://arxiv.org/abs/2601.19912

30 CONF

AI-Generated Image Detectors Exploit Global Artifacts: Evidence from Inpainting Exchange

ArXiv CS.AI 50%

arXiv:2602.00192v2 Announce Type: replace-cross Abstract: Modern diffusion-based inpainting enables realistic, localized image manipulation, raising critical challenges for reliable detection. We show that state-of-the-art AI-generated image detectors largely fail to identify...

https://arxiv.org/abs/2602.00192

31 CONF

How Far Can a Trainable Frequency Move? Resolution, Grids and Coupling in Trainable-FrequencyQuantum Models

ArXiv CS.AI 50%

arXiv:2602.23409v4 Announce Type: replace-cross Abstract: Trainable-frequency quantum models train the prefactors of their encoding gates so that the circuit's frequencies can move onto the target's. From the unit start of prior work, training rarely reaches a target more than...

https://arxiv.org/abs/2602.23409

32 CONF

Stability and Generalization in Looped Transformers

ArXiv CS.AI 50%

arXiv:2604.15259v3 Announce Type: replace-cross Abstract: Looped transformers promise test-time compute scaling by spending more iterations on harder problems, but it remains unclear which architectural choices let them extrapolate to harder problems at test time rather than...

https://arxiv.org/abs/2604.15259

33 CONF

Learning to Think from Multiple Thinkers: How Chain-of-Thought Heterogeneity Affects Efficient Learnability

ArXiv CS.AI 50%

arXiv:2604.24737v2 Announce Type: replace-cross Abstract: Chain-of-thought (CoT) supervision makes computationally hard learning problems tractable by exposing intermediate steps that are easy to learn via next-token prediction. However, in practice, CoT datasets draw on...

https://arxiv.org/abs/2604.24737

34 CONF

Vector Policy Optimization: Training for Diversity Improves Test-Time Search

ArXiv CS.AI 50%

arXiv:2605.22817v2 Announce Type: replace-cross Abstract: Language models must now generalize out of the box to novel environments and work inside inference-scaling search procedures, such as AlphaEvolve, that select rollouts with a variety of task-specific reward functions....

https://arxiv.org/abs/2605.22817

35 CONF

Everything at Every Scale: Scale-Invariant Diffusion with Continuous Super-Resolution

ArXiv CS.AI 50%

arXiv:2605.26032v2 Announce Type: replace-cross Abstract: Creating images from noise is image generation; reconstructing fine details from coarse inputs is super-resolution. Despite their practical differences, both can be understood as reversing information loss across scales....

https://arxiv.org/abs/2605.26032

36 CONF

Teach the Way It Thinks: Guiding LLM Post-training Data Engineering with Sparse Autoencoders

ArXiv CS.AI 50%

arXiv:2605.27354v2 Announce Type: replace-cross Abstract: Data engineering for large language model (LLM) reinforcement learning (RL) decides which samples to train on, when to present them, and which to batch together. Existing methods mostly rely on external feedback, such as...

https://arxiv.org/abs/2605.27354

37 CONF

The Standard Interpretable Model: Design interpretable machine learning methods from elementary symmetries

ArXiv CS.AI 50%

arXiv:2606.12289v3 Announce Type: replace-cross Abstract: As Artificial Intelligence models grow in complexity, interpretability has become an indispensable tool for understanding, debugging, and controlling their computations. However, interpretability lacks general theories to...

https://arxiv.org/abs/2606.12289

38 CONF

Keeping Jerk in Check: Jointly Trained Perception-Gated Experts for Smooth Terrain Transitions

ArXiv CS.AI 50%

arXiv:2606.19633v2 Announce Type: replace-cross Abstract: Perceptive legged locomotion across discontinuous terrain requires shared locomotion knowledge, task-specific maneuvers, and smooth transitions between them. Existing approaches train specialized policies independently...

https://arxiv.org/abs/2606.19633

39 CONF

Variable-aware representation, not relation typing, explains the performance of an event-graph model for ICU mortality prediction: temporal and external validation

ArXiv CS.AI 50%

arXiv:2608.02663v2 Announce Type: replace-cross Abstract: Event-graph neural networks represent intensive care unit (ICU) records as typed entities linked by timestamped observations, and their gains are often attributed to relation-specific message passing. We tested which...

https://arxiv.org/abs/2608.02663

40 CONF

AI Slop and Hallucinations in Vulnerability Assessment: A Survey on Reasoning Failures and Trustworthy Mitigation

ArXiv CS.AI 50%

arXiv:2608.25667v2 Announce Type: replace-cross Abstract: The integration of Large Language Models (LLMs) into cybersecurity has transformed vulnerability assessment, but it has also produced a trustworthiness crisis driven by the unchecked proliferation of "AI slop." These...

https://arxiv.org/abs/2608.25667

41 CONF

DynSHAP: Towards Explainable Dynamic Survival Analysis

ArXiv CS.AI 50%

arXiv:2609.13042v2 Announce Type: replace-cross Abstract: Deep learning models for dynamic survival analysis (DSA) achieve strong predictive performance by incorporating longitudinal patient data, but their black box nature limits clinical trust and adoption. Existing...

https://arxiv.org/abs/2609.13042

42 CONF

AnchorRep: Defending LLMs Against Cross-Model Adversarial Transfer via Representation Repulsion

ArXiv CS.AI 50%

arXiv:2609.32602v2 Announce Type: replace-cross Abstract: Adversarial attacks optimized on a single open-weight LLM can transfer to and jailbreak architecturally different models, allowing an attacker with white-box access to one model to compromise independently deployed...

https://arxiv.org/abs/2609.32602

43 CONF

What Does the Effective Dimension of a Hybrid Quantum Neural Network Actually Measure?

ArXiv CS.AI 50%

arXiv:2610.14070v2 Announce Type: replace-cross Abstract: Hybrid quantum neural networks (QNNs) pass features from a classical backbone into a variational quantum circuit, and many studies log a scalar called the effective dimension as a sign of capacity or model quality. The...

https://arxiv.org/abs/2610.14070

44 CONF

Revisiting Generative vs. Dense Retrieval: A Static Value Prior Reverses the Gap

ArXiv CS.AI 50%

arXiv:2610.19065v2 Announce Type: replace-cross Abstract: Generative retrieval (GR) has emerged as a strong candidate generator for sequential recommendation as language models and semantic-item identifiers have improved. However, GR is not a uniformly stronger replacement of...

https://arxiv.org/abs/2610.19065

45 CONF

The Physical Cost of Context: Quality-Constrained Resource Accounting for Coding Agents

ArXiv CS.AI 50%

arXiv:2610.34763v2 Announce Type: replace-cross Abstract: Coding agents resend a growing context on every model call, and context policies are usually judged by the prompt tokens they save. Executed work also depends on call count and prefix reuse: a caching runtime prefills...

https://arxiv.org/abs/2610.34763

46 CONF

Human-Centred, Risk-Constrained Evaluation of Financial Document Recognition: Evidence, Critical Errors, and Selective Automation

ArXiv CS.AI 50%

arXiv:2611.02775v2 Announce Type: replace-cross Abstract: Financial document recognition is often assessed using character and word error rates, although these metrics do not express whether a system preserves the financial facts on which people and organisations act. This paper...

https://arxiv.org/abs/2611.02775

47 CONF

Sonar-MoE: In-Backward Expert Updates for Memory-Efficient Mixture-of-Experts Training

ArXiv CS.AI 50%

arXiv:2611.03577v2 Announce Type: replace-cross Abstract: Most parameters of a Mixture-of-Experts (MoE) model belong to its experts, and standard training keeps every expert gradient in GPU memory until the optimizer step. This memory grows with the number and size of the...

https://arxiv.org/abs/2611.03577