NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

11 November 2026

172 verified · 275 raw · 5 sources

172	7	165	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	143	Media
TechCrunch AI	16	Media
HackerNews	10	Community
The Verge AI	9	Media
MIT Tech Review	1	Media

VERIFIED INTELLIGENCE — 7 stories

VERI

Show HN: We wanted to build an AI application, not maintain RAG pipelines

HackerNews +1 source 90% HN 3

arXiv:2611.09792v2 Announce Type: replace Abstract: Current evaluations of agentic AI systems primarily rely on benchmarks. However, the static nature of benchmarks makes them uninformative about the value of auditing interventions at deployment time. For reliable deployment, we...

https://akropolys.cloud/docs/

VERI

Anthropic targets $1.4 trillion IPO

The Verge AI +1 source 80%

Anthropic confirmed on Tuesday that its IPO could be one of the biggest ever, even while falling short of previous expectations. Its IPO price is expected to be between $70.00 and $78.00 per share, which would put its valuation as high as $1.4 trillion, according to the The New...

https://www.theverge.com/ai-artificial-intelligence/1030703/anthropic-ipo-1-4-trillion

VERI

ChatGPT is getting verified AI ‘Business Agents’

The Verge AI +1 source 80%

ChatGPT is going to let you chat with verified "Business Agents" that represent a brand to help you with things like comparison shopping. The feature, available first to "eligible" e-commerce and online service businesses in the US, is launching as part of a suite of...

https://www.theverge.com/ai-artificial-intelligence/1030552/openai-chatgpt-business-age...

VERI

An Augmented Lagrangian Approach to Lifted Bellman Linear Programming

ArXiv CS.AI +1 source 80%

arXiv:2611.14183v1 Announce Type: new Abstract: Temporal-difference critics regress onto a bootstrapped target and usually need a target network. Lifted Bellman Linear Programming (LBLP) instead expresses the in-sample optimal values of offline RL as the solution to a linear...

https://arxiv.org/abs/2611.14183

VERI

Data augmentation using generative networks to identify dementia

ArXiv CS.AI +1 source 80%

arXiv:2004.05989v1 Announce Type: cross Abstract: Data limitation is one of the most common issues in training machine learning classifiers for medical applications. Due to ethical concerns and data privacy, the number of people that can be recruited to such experiments is...

https://arxiv.org/abs/2004.05989

VERI

Do AI Agents need Preventive Care? An Epidemiologic Cohort Design for Agentic AI

ArXiv CS.AI +1 source 80%

arXiv:2611.13333v1 Announce Type: new Abstract: As AI agents increasingly perform tasks autonomously across sectors, including healthcare and biomedical research, understanding how their behaviors develop and influence outcomes over time becomes increasingly important. Existing...

https://arxiv.org/abs/2611.13333

VERI

Tracing Moral Foundations in Large Language Models

ArXiv CS.AI +1 source 80%

arXiv:2601.05437v4 Announce Type: replace-cross Abstract: Large language models often produce human-like moral judgments, but it is unclear whether this reflects an internal conceptual structure or superficial ``moral mimicry.'' Using Moral Foundations Theory (MFT) as an...

https://arxiv.org/abs/2601.05437

CONFIRMED SIGNALS — 165 stories

CONF

Show HN: Valencia, Spain in Sim City/Isometric View

HackerNews 60% HN 231

No summary — see link for full article.

https://tinyvalencia.com/

CONF

Show HN: I have trained 15 blood glucose forecasting models on my own data

HackerNews 50% HN 18

No summary — see link for full article.

https://github.com/0xdeadf1sh/T1DMAI

0 CONF

Show HN: WolveKafka – Consume Kafka with a plain HTTP endpoint

HackerNews 50% HN 11

No summary — see link for full article.

https://github.com/wolveflake/wolvekafka

1 CONF

Show HN: Daily GPU Rental Prices Across AWS, Azure, RunPod and Vast.ai

HackerNews 50% HN 10

No summary — see link for full article.

https://taipeiledger.com/gpu/

2 CONF

Show HN: TheoremSmith: Mass-Producing Hard Proof Problems to Train LLMs

HackerNews 50% HN 10

Making models better at formal verification will help push the boundaries of math research and significantly reduce the number of bugs in our code. Recently, training models on RL environments (tasks paired with verifiers that reward correct solutions) has driven big gains in...

https://charleshuang.me/2026/09/27/theoremsmith/

3 CONF

Show HN: Cosh – An open-source AI agent orchestrator

HackerNews 50% HN 8

I had been staring at some of the empty walls in my home and wanted to put up some frames but was always worried about the right measurements on where to put the holes, you can enter the size of the wall and the frames that you already have or planning to buy, or pick from your...

https://github.com/DiegoZaluski/co-sh

4 CONF

Show HN: Mimzie, an agent-neutral alternative to the Claude Suite/Claude Cowork

HackerNews 50% HN 6

hi HN! I built Mimzie, an agent neutral AI workspace inspired by the Claude Suite (Docs, Sheets, Slides) and Cowork. It's a free desktop app that runs ChatGPT, Claude, Gemini, and Grok in their native CLI harnesses. Think T3 Code or Conductor but for knowledge work. It's...

https://mimzie.com/

5 CONF

Show HN: Caramel: a speech-to-speech conversation model trained only on audio

HackerNews 50% HN 4

I trained a speech-to-speech model last night, inspired by Dessa. I'm calling the model caramel-1. The model learned from recordings of people talking and nothing else, and has never seen a single word of text. The code, the training recipe and the weights are open source....

https://naklecha.com/research/caramel-1

6 CONF

Show HN: I checked 66 AI tools' privacy policies for AI training

HackerNews 50% HN 3

No summary — see link for full article.

https://getpolicypeek.com/

7 CONF

OpenAI acquires Odessia, travel startup created by Sonder founder

TechCrunch AI 50%

OpenAI has not yet said what its plans are for the future of travel. But Sonder founder Francis Davidson is a well-known figure in the travel industry.

https://techcrunch.com/2026/11/10/openai-acquires-odessia-travel-startup-created-by-son...

8 CONF

OpenAI, Anthropic face new oversight as New York’s AI safety law takes effect

TechCrunch AI 50%

New York is preparing to enforce its sweeping AI safety law, requiring major developers like OpenAI and Anthropic to register, disclose safety practices, and report critical incidents or face fines.

https://techcrunch.com/2026/11/10/openai-anthropic-face-new-oversight-as-new-yorks-ai-s...

9 CONF

Oura to acquire AI-native primary care startup Counsel Health for $625M

TechCrunch AI 50%

The deal comes a few weeks after Oura postponed its up to $2.2 billion IPO indefinitely, citing “uncertainty in the IPO market.”

https://techcrunch.com/2026/11/10/oura-to-acquire-ai-native-primary-care-startup-counse...

0 CONF

OpenAI rolls out new business profiles, making ChatGPT just a little bit more like Google

TechCrunch AI 50%

OpenAI is looking to make ChatGPT a more robust consumer discovery engine, and a host of new features seek to empower businesses to help it do that.

https://techcrunch.com/2026/11/10/openai-rolls-out-new-business-profiles-making-chatgpt...

1 CONF

Anthropic launches Claude Meetings to turn workplace discussions into plans and tasks

TechCrunch AI 50%

As participants talk, Claude can draft the plan being discussed, map out a timeline on a whiteboard, answer questions in the meeting chat, and access connected work apps to retrieve information, such as last year's figures.

https://techcrunch.com/2026/11/10/anthropic-launches-claude-meetings-to-turn-workplace-...

2 CONF

Nvidia CEO Jensen Huang’s affair with alleged Chinese spy: a timeline

TechCrunch AI 50%

The affair could have ramifications for national security as the U.S. and China race to develop the most advanced AI infrastructure.

https://techcrunch.com/2026/11/10/nvidia-ceo-jensen-huangs-affair-with-alleged-chinese-...

3 CONF

Google broadens its AI hardware portfolio with two new specialized chips

TechCrunch AI 50%

Google's new tensor processing units (TPUs) broaden its chip portfolio to more use cases: confidential model training and more memory capacity.

https://techcrunch.com/2026/11/10/google-broadens-its-ai-hardware-portfolio-with-two-ne...

4 CONF

Anthropic sets IPO price range of $70 to $78 per share to reach an implied valuation of $1.404 trillion

TechCrunch AI 50%

The company could end up being worth a hefty $1.404 trillion if its shares list at the top of the price range, on a fully diluted basis.

https://techcrunch.com/2026/11/10/anthropic-sets-ipo-price-range-of-70-to-78-per-share-...

5 CONF

After challenging Google’s Android with Cyanogen, its co-founder takes aim at Windows for AI era

TechCrunch AI 50%

Kora is set to launch as a free-to-use alternative to Windows, targeting users who rely heavily on AI models and agents.

https://techcrunch.com/2026/11/10/after-challenging-googles-android-with-cyanogen-its-c...

6 CONF

Cyberattacks threaten to make open source AI a little less open, Hugging Face exec warns

TechCrunch AI 50%

Hugging Face executive Irene Solaiman warns that growing cyberattacks on open AI platforms could force tighter security restrictions, threatening the accessibility that makes open source communities valuable to developers worldwide.

https://techcrunch.com/2026/11/10/cyberattacks-threaten-to-make-open-source-ai-a-little...

7 CONF

The Download: Pelosi’s successor targets AI and data centers face power woes

MIT Tech Review 50%

This is today’s edition of The Download, our weekday newsletter that provides a daily dose of what’s going on in the world of technology. Nancy Pelosi’s replacement is ready to regulate AI —Grace Huckins As a California state senator, Scott Wiener authored legislation aimed at...

https://www.technologyreview.com/2026/11/10/1148150/the-download-pelosi-successor-ai-re...

8 CONF

The US is winning the AI race. Jensen Huang could have blown it

The Verge AI 50%

As espionage targets go, Jensen Huang is perhaps one of the least surprising on Earth. The Nvidia CEO runs one of the world's most valuable companies, controls the in-demand technology fueling the AI boom, and is cozy with presidents, CEOs, and all manner of important people. He...

https://www.theverge.com/ai-artificial-intelligence/1031063/jensen-huang-ai-race-us-chi...

9 CONF

The indie game community is in disarray over AI and Big Walk

The Verge AI 50%

Some Independent Games Festival (IGF) jurors published a statement yesterday saying they would not vote for games that use generative AI in "any capacity." Soon after, the developer of indie hit Big Walk has published a statement saying it "sparingly" used AI in the "final...

https://www.theverge.com/games/1030994/big-walk-independent-games-festival-igf-ai

0 CONF

Anthropic has its own AI-powered office suite now

The Verge AI 50%

For years, Anthropic has been known for its focus on enterprise and coding tools that attract high-flying corporate clients, inspiring competing frontier labs - like OpenAI, SpaceXSI, and Meta - to copy its strategies. Earlier this year, Claude Code went through its own...

https://www.theverge.com/ai-artificial-intelligence/1030709/anthropic-has-its-own-ai-po...

1 CONF

eBay appears to have shut the door on third-party AI agents

The Verge AI 50%

eBay appears to have blocked AI agents, including Meta's Muse, from browsing on the platform - the latest speed bump in the AI agent race. A reader tells The Verge that for several weeks he's had his Muse agent browse and curate a daily digest of watches for sale on platforms...

https://www.theverge.com/tech/1030838/ebay-ai-agents-meta-muse-agentic-shopping

2 CONF

Google releases Gemini 4 Carbon with agent ‘swarm’ feature

The Verge AI 50%

Google is rolling out its latest AI model, Gemini 4 Carbon, to the general public after releasing it to a select group of "cybersecurity defenders" two weeks ago. Google claims Carbon is its "strongest model" yet, and capable of competing with the very best systems from...

https://www.theverge.com/ai-artificial-intelligence/1030787/google-gemini-4-carbon-publ...

3 CONF

Adobe is going all in on agentic AI

The Verge AI 50%

Adobe is committing itself to the notion that chatbots and AI agents could be your next design assistant, or even automate creative workflows and repetitive tasks on your behalf. Some of the tools and features announced today at Adobe's Max conference in Miami, Florida, include...

https://www.theverge.com/tech/1030593/adobe-max-ai-agents-mcp-firefly-assistant-updates

4 CONF

Hands-on with Ring’s new AI drone camera for your home

The Verge AI 50%

Ring is finally shipping a flying indoor drone camera. For real this time. The Ring Drone Cam will arrive on January 27th, 2027, for $249.99, Ring founder Jamie Siminoff said at a launch event in New York City this week. If it does actually ship, it will arrive almost six years...

https://www.theverge.com/tech/1030601/ring-drone-cam-hands-on-price-release-date-ai-pilot

5 CONF

Hx2Dx: From Anamnesis to Diagnosis - A Multimodal Arena for Conversational Clinical Reasoning in LLMs

ArXiv CS.AI 50%

arXiv:2611.14122v1 Announce Type: new Abstract: Large language models (LLMs) achieve expert-level diagnostic accuracy in static evaluations, where the model receives a curated vignette or case report that already condenses the diagnostically relevant findings. Such evaluations...

https://arxiv.org/abs/2611.14122

6 CONF

Train on prefill, monitor at decode: Using sparse autoencoders for topic monitoring

ArXiv CS.AI 50%

arXiv:2611.12935v1 Announce Type: new Abstract: Topic monitoring is the task of labelling the topic of each token in a model's response during generation. Activation-based monitors that run at generation time have so far been trained to detect harmful content and are limited to...

https://arxiv.org/abs/2611.12935

7 CONF

LandslideFM: A Foundation Model Towards Unified Landslide Perception and Understanding

ArXiv CS.AI 50%

arXiv:2611.12936v1 Announce Type: new Abstract: Intelligent landslide detection is essential for disaster prevention. However, existing models primarily focus on isolated visual tasks, require extensive labeled data, and lack deep analytical and scene-understanding capabilities....

https://arxiv.org/abs/2611.12936

8 CONF

Disentangling Multimodal Rotary Positional Embedding in Vision-Language Models

ArXiv CS.AI 50%

arXiv:2611.13334v1 Announce Type: new Abstract: Vision-language models widely adopt Multimodal Rotary Position Embedding (MRoPE), an extension of Rotary Position Embedding (RoPE) that incorporates temporal, height, and width axes to encode the spatial structure of visual tokens....

https://arxiv.org/abs/2611.13334

9 CONF

Reinforcement Learning based control of Cancer Chemotherapy treatments

ArXiv CS.AI 50%

arXiv:2611.12940v1 Announce Type: new Abstract: Reinforcement Learning has achieved tremendous success in recent years. Extending its scope from the traditional complex games such as Atari, Go, Pokeman, and Chess, reinforcement learning has caught researchers' attention on...

https://arxiv.org/abs/2611.12940

10 CONF

Just AI Governance and the Forbidden-Boundary Principle

ArXiv CS.AI 50%

arXiv:2611.13007v1 Announce Type: cross Abstract: Artificial intelligence (AI) increasingly shapes consequential decisions, yet predictive accuracy is not a sufficient justification for delegated authority. This conceptual study develops an integrated framework for assessing...

https://arxiv.org/abs/2611.13007

1 CONF

Tabular Foundation Models vs Tuned Gradient Boosting for Telecom Churn: A Profit- and Calibration-Aware Evaluation

ArXiv CS.AI 50%

arXiv:2611.12942v1 Announce Type: new Abstract: Tabular foundation models (TFMs) predict from a labelled context in a single forward pass. A recent benchmark reported that they decisively outperform tree ensembles for customer churn, but it compared them with untuned...

https://arxiv.org/abs/2611.12942

2 CONF

SetPrint: Black-Box LLM Fingerprinting via Setwise Correspondence of Response Changes

ArXiv CS.AI 50%

arXiv:2611.12950v1 Announce Type: new Abstract: Black-box LLM fingerprinting aims to determine whether a target model was derived from a source model when only the output responses to input queries are observable. One way to reveal this relationship is to perturb each query and...

https://arxiv.org/abs/2611.12950

3 CONF

FAIDER: Fairness-Aware Item-Level Decoding for Large Language Model Recommenders

ArXiv CS.AI 50%

arXiv:2611.10285v2 Announce Type: replace Abstract: Large language model (LLM) recommenders can produce semantically different recommendations when a user's protected attribute changes, even if the interaction history remains fixed. Controlling this disparity is challenging when...

https://arxiv.org/abs/2611.10285

4 CONF

RBLA+: Efficient Rank-Specific LoRA Adapter Extraction for Federated Fine-Tuning with Heterogeneous Clients

ArXiv CS.AI 50%

arXiv:2611.12961v1 Announce Type: new Abstract: Federated fine-tuning with low-rank adaptation (LoRA) reduces communication and computational overhead by training and exchanging compact trainable LoRA factors. Clients may use different LoRA ranks to meet adapter communication...

https://arxiv.org/abs/2611.12961

5 CONF

AgentScript-Eval: Benchmarking LLMs and Agents for Code Generation in an Enterprise DSL

ArXiv CS.AI 50%

arXiv:2611.13183v1 Announce Type: cross Abstract: Domain-specific languages (DSLs) are widely used in enterprise software, giving a compact interface to complex tasks, from data access to infrastructure automation. Platforms increasingly extend them to agents, where a developer...

https://arxiv.org/abs/2611.13183

6 CONF

MoveBench: A Rubric-Based Benchmark for Evaluating Large Language Models in Sports and Health Coaching

ArXiv CS.AI 50%

arXiv:2610.26185v3 Announce Type: replace Abstract: Despite rapid advances in large language models (LLMs), their deployment in the sports and health domain remains high-risk due to the absence of domain-specific evaluation benchmarks. Existing general-purpose benchmarks (e.g.,...

https://arxiv.org/abs/2610.26185

7 CONF

From Questions to Decisions: Benchmarking How LLM Agents Acquire Decision-Relevant Information from Human Beings

ArXiv CS.AI 50%

arXiv:2611.13015v1 Announce Type: new Abstract: LLM agents are increasingly asked to make plans for people, such as scheduling drivers or assigning nurses. However, people's requests are often incomplete, and the supporting information for decision-making may be outdated,...

https://arxiv.org/abs/2611.13015

8 CONF

ChipOmni: A General-Purpose AI Agent for Electronic Design Automation

ArXiv CS.AI 50%

arXiv:2611.13020v1 Announce Type: new Abstract: Electronic design automation (EDA) workflows remain highly fragmented, requiring engineers to coordinate heterogeneous representations, specialised software tools, and iterative verification across multiple design stages. Although...

https://arxiv.org/abs/2611.13020

9 CONF

GRAP: Gender Rubric-Aware Probing for Analyzing Gender Bias in LLMs

ArXiv CS.AI 50%

arXiv:2611.13024v1 Announce Type: new Abstract: As LLMs increasingly mediate everyday interactions, subtle gender biases in open-ended responses pose growing societal risks. Existing probing methods have two key limitations: they rely on fixed-format tasks, such as pronoun...

https://arxiv.org/abs/2611.13024

0 CONF

Trust, but verify, audit and attribute: a human-in-the-loop framework for checking AI-produced research results

ArXiv CS.AI 50%

arXiv:2611.13042v1 Announce Type: new Abstract: Artificial intelligence (AI) systems now produce research results in bulk: in October 2026 a single laboratory released more than 700 AI-generated mathematics manuscripts, only part of them with machine-checked proofs. Such volumes...

https://arxiv.org/abs/2611.13042

1 CONF

Textual Response-Aware Guidance for Zero-Shot Adversarial Robustness of Vision-Language Models

ArXiv CS.AI 50%

arXiv:2610.40309v2 Announce Type: cross Abstract: Vision-language models (VLMs) exhibit strong zero-shot generalization but remain vulnerable to adversarial attacks. Existing adversarial fine-tuning methods often use pre-trained model guidance to preserve image--text alignment...

https://arxiv.org/abs/2610.40309

2 CONF

Agreeing on the Answer but Not the Reason: Measurement Limits of LLM Reasoning Failure Taxonomies

ArXiv CS.AI 50%

arXiv:2611.13140v1 Announce Type: new Abstract: Failure taxonomies for LLM reasoning are increasingly reported as measurements: papers state what fraction of a model's errors fall into named categories, then compare those fractions across models. We show that for one such...

https://arxiv.org/abs/2611.13140

3 CONF

Teaching the Harness: Student-Aware Skill Transfer for LLM Agents

ArXiv CS.AI 50%

arXiv:2611.13144v1 Announce Type: new Abstract: Effective teaching requires reasoning about the learner as well as the task, a capacity that Theory of Mind describes as inferring another agent's latent state from its behavior. We ask whether a stronger LLM teaches a fixed...

https://arxiv.org/abs/2611.13144

4 CONF

Broad-Persistent Advising in Interactive Reinforcement Learning via Latent State Encoding

ArXiv CS.AI 50%

arXiv:2611.13712v1 Announce Type: new Abstract: Deep Interactive Reinforcement Learning (Deep IntRL) accelerates reinforcement learning training by incorporating external advice. However, conventional Deep IntRL uses each piece of advice only in the current step and discards it...

https://arxiv.org/abs/2611.13712

5 CONF

AI Alignment Is Neither Solvable nor Sufficient

ArXiv CS.AI 50%

arXiv:2611.13167v1 Announce Type: new Abstract: Humans and AI systems increasingly act within the same social and economic environments. Alignment, the goal of ensuring that AI systems act in accordance with human values, is widely regarded as a central challenge for ensuring...

https://arxiv.org/abs/2611.13167

6 CONF

Counting Under Disagreement: Dollar-Weighted Measurement, Selective Machine Labelling and Budgeted Human Review from Disagreeing AI Readers of Administrative Text

ArXiv CS.AI 50%

arXiv:2611.13215v1 Announce Type: new Abstract: We study AI-assisted measurement when one text label applies to many administrative records, the target is a monetary total, and the human readings that anchor the machines disagree. The testbed is 121,070 grant-purpose texts from...

https://arxiv.org/abs/2611.13215

7 CONF

Reliability of Claude Code as an Agentic AI Grading System for Handwritten University Exams

ArXiv CS.AI 50%

arXiv:2611.13217v1 Announce Type: new Abstract: This study examines the reliability of Claude Code, an agentic deployment of the Claude Opus 4.6 large language model, as a grading system for handwritten university exams. Four research questions addressed agreement with expert...

https://arxiv.org/abs/2611.13217

8 CONF

Dependable Long-Horizon LLM Agents: A Trajectory-Centered Empirical Study of Where Errors Enter and Which Controls Reach Them

ArXiv CS.AI 50%

arXiv:2611.13254v1 Announce Type: new Abstract: When an LLM agent fails part-way through a long task, the usual analysis records a symptom: a failure-mode label, or the agent and step judged responsible. It does not say where the error entered, which state carried it to the...

https://arxiv.org/abs/2611.13254

9 CONF

F3-AGI v4.0: Bioenergetically-Gated Active Inference, Metaplastic Preconditioning, and Residual Program Synthesis for Sample-Efficient Abstract Reasoning

ArXiv CS.AI 50%

arXiv:2611.13325v1 Announce Type: new Abstract: Few-shot abstract reasoning on ARC-AGI requires inducing algorithmic transformations from 2 to 5 demonstration pairs without task-specific pretraining. Because few-shot demonstrations under-constrain the hypothesis space, program...

https://arxiv.org/abs/2611.13325

0 CONF

No finite rulebook can certify every safe program: an impossibility theorem for gatekeeping AI agents

ArXiv CS.AI 50%

arXiv:2611.13367v1 Announce Type: new Abstract: An AI assistant writes small programs, and a gatekeeper must decide, from the code alone, whether each one may run. Suppose the rules are fixed: never perform a forbidden action, never let the output depend on a secret, always...

https://arxiv.org/abs/2611.13367

1 CONF

SteerDistill: Quantizing LLM Agents via Closed-Loop Teacher Steering

ArXiv CS.AI 50%

arXiv:2611.13410v1 Announce Type: new Abstract: Low-bit quantization reduces the inference cost of LLM agents but can compromise task success. Examining failed rollouts, we find that quantized agents overlook task requirements or environmental conditions, producing environment...

https://arxiv.org/abs/2611.13410

2 CONF

SafeRoute-MAS: Coverage-Aware and Risk-Calibrated Message Routing for Multi-Agent Scientific Reasoning

ArXiv CS.AI 50%

arXiv:2611.13454v1 Announce Type: new Abstract: We introduce SafeRoute-MAS, a coverage-aware, risk-calibrated procedure that keeps all specialist messages or removes one using only pre-integration information. On a sealed cache of 5,328 committees, its source-compatible...

https://arxiv.org/abs/2611.13454

3 CONF

When Reasoning looks like Hidden Understanding: How Chain-of-Thought Fosters Anthropomorphism, Perceptions of Epistemic Superiority, and Cognitive Deference

ArXiv CS.AI 50%

arXiv:2611.13456v1 Announce Type: new Abstract: As AI-based products permeate society, specifically systems using generative models, a belief system is emerging about what these products are and what they can and cannot do. One common belief concerns the perception of the form...

https://arxiv.org/abs/2611.13456

4 CONF

The WoW: A Large-Scale World Knowledge Corpus for Full-Lifecycle LLM Training

ArXiv CS.AI 50%

arXiv:2611.13487v1 Announce Type: new Abstract: Existing Chinese educational corpora often suffer from fragmented coverage and a lack of systematic organization. In this paper, we propose WoW (\textbf{Wo}rld Kno\textbf{w}ledge), a large-scale dataset designed for the full-cycle...

https://arxiv.org/abs/2611.13487

5 CONF

Agent Benchmarks Stop Ranking Before They Run Out of Tasks

ArXiv CS.AI 50%

arXiv:2611.13541v1 Announce Type: new Abstract: Data-science and ML-engineering agents are evaluated on benchmarks such as MLE-bench, ALE-Bench, SWE-fficiency and AlgoTune, whose tasks yield a quantity (a Kaggle metric, contest score or speedup). When one stops separating the...

https://arxiv.org/abs/2611.13541

6 CONF

CulturalCrosswords: A Multilingual Benchmark of Answer Constraints and Grid Completion

ArXiv CS.AI 50%

arXiv:2611.10044v2 Announce Type: replace-cross Abstract: When several answers fit a riddle, exact-match scoring can penalise a valid response. CulturalCrosswords tests how answer constraints affect large language models (LLMs) solving cultural riddles, whose solutions draw on...

https://arxiv.org/abs/2611.10044

7 CONF

Benchmarking Vendor-Guided Optimizations on Edge NPUs: From NPU Only to End-to-End Performance. Extended technical report

ArXiv CS.AI 50%

arXiv:2611.13563v1 Announce Type: new Abstract: Edge NPU performance depends not only on hardware capabilities, but also on model transformation and the overall deployment pipeline. We propose a benchmarking methodology that separates these effects by comparing three...

https://arxiv.org/abs/2611.13563

8 CONF

Transformers Provably Learn Graph Search: Training Dynamics and the Exponential Power of Depth

ArXiv CS.AI 50%

arXiv:2611.13594v1 Announce Type: new Abstract: Large Language Models (LLMs) have achieved remarkable progress on complex reasoning tasks, yet the mechanisms by which they acquire reasoning capabilities and the efficiency of their reasoning remain poorly understood. In this...

https://arxiv.org/abs/2611.13594

9 CONF

Relaxing Cross-Modal Correspondence for Multimodal Remote Sensing Pretraining

ArXiv CS.AI 50%

arXiv:2611.13807v1 Announce Type: cross Abstract: Multimodal remote sensing pretraining commonly relies on exact instance-level correspondence across modalities, implicitly treating strictly paired observations as a prerequisite for learning transferable representations. In this...

https://arxiv.org/abs/2611.13807

0 CONF

Benchmarking LLM Next-Step Recommendations with Knowledge Space Theory

ArXiv CS.AI 50%

arXiv:2611.13667v1 Announce Type: new Abstract: Selecting an LLM for next-step recommendation requires benchmarks that reflect the intended educational task and domain. We present a benchmarking method that uses Knowledge Space Theory (KST) as a formal evaluation reference....

https://arxiv.org/abs/2611.13667

1 CONF

Topological Dynamics Under Non-Stationary Supervision: Persistent Homology of Neural Network Weight Evolution

ArXiv CS.AI 50%

arXiv:2611.13701v1 Announce Type: new Abstract: We investigate how the persistent topology of neuron- weight point clouds evolves under stable and non-stationary supervision. An identical multilayer perceptron is trained on Fashion-MNIST with correct labels, a fixed random...

https://arxiv.org/abs/2611.13701

2 CONF

Agentic AI Meets Formal Verification in the Era of Agentic Hardware Development

ArXiv CS.AI 50%

arXiv:2611.13705v1 Announce Type: new Abstract: As AI agents become increasingly capable of generating and optimizing hardware circuits, ensuring the correctness of AI-generated designs becomes more important. Meanwhile, advances in AI lower the barriers to developing and...

https://arxiv.org/abs/2611.13705

3 CONF

Explainable Iterative Data Visualization Refinement via an LLM Agent

ArXiv CS.AI 50%

arXiv:2604.15319v3 Announce Type: replace-cross Abstract: Exploratory analysis of high-dimensional data relies on embedding the data into a low-dimensional space, based on which a visualization plot is produced to uncover meaningful structures and to communicate geometric and...

https://arxiv.org/abs/2604.15319

4 CONF

Toward Autonomous RTL and Synthesis Optimization: Benchmarking and Self-Improving Agents

ArXiv CS.AI 50%

arXiv:2611.13713v1 Announce Type: new Abstract: Recent advances in large language models (LLMs) and autonomous agents are creating new opportunities for hardware design optimization. This paper examines three connected directions toward autonomous RTL and synthesis optimization:...

https://arxiv.org/abs/2611.13713

5 CONF

Structured Kernel Surrogate Models for Multimodal Attribution

ArXiv CS.AI 50%

arXiv:2611.13198v1 Announce Type: cross Abstract: We study the problem of cross-sample modality attribution, which involves measuring how one modality in one sample affects the learning outcome in other multimodal samples. This problem is crucial in a multimodal system because a...

https://arxiv.org/abs/2611.13198

6 CONF

From Counterfactual Edits to Human Narratives: LLM-Driven Interpretations for Recommender System Explanations

ArXiv CS.AI 50%

arXiv:2611.13914v1 Announce Type: new Abstract: Recommender systems increasingly influence what users discover and consume online, yet the decision logic behind their outputs often remains opaque. Counterfactual explanation (CFX) methods provide an effective way to show which...

https://arxiv.org/abs/2611.13914

7 CONF

Beyond Proxy Metrics: MLLMs as Human Surrogates for Explainable AI Evaluation

ArXiv CS.AI 50%

arXiv:2611.13926v1 Announce Type: new Abstract: Explainable AI (XAI) has expanded into a broad and impactful research area, but the fundamental question of how best to evaluate explanation techniques has proven frustratingly elusive. Methodologies typically revolve around either...

https://arxiv.org/abs/2611.13926

8 CONF

BadMoE: Backdooring Mixture-of-Experts LLMs via Routing-Aware Triggers and Task-Underutilized Experts

ArXiv CS.AI 50%

arXiv:2504.18598v3 Announce Type: replace-cross Abstract: Mixture-of-Experts (MoE) architectures are rapidly becoming the standard for building scalable and efficient large language models (LLMs), thanks to their routing mechanism that activates only a subset of experts for each...

https://arxiv.org/abs/2504.18598

9 CONF

Cross-Border Fulfillment Center Selection via Doubly Robust Estimation and Linear Programming

ArXiv CS.AI 50%

arXiv:2611.14174v1 Announce Type: new Abstract: We introduce the cross-border (XB) fulfillment center (FC) Selection Model: a multi-stage optimization framework combining forecasting, doubly robust estimation, and linear programming to select optimal source FCs. For each...

https://arxiv.org/abs/2611.14174

0 CONF

Prune-and-Merge: Training-Free Scaling of Vision Transformers

ArXiv CS.AI 50%

arXiv:2610.18039v3 Announce Type: replace-cross Abstract: Vision Transformers achieve strong performance but incur high computational costs from quadratic token interactions. Training-free token reduction methods improve efficiency, but their robustness remains underexplored. We...

https://arxiv.org/abs/2610.18039

1 CONF

When Should Agents Remember? Falsification-Gated Self-Evolution for LLM Agents

ArXiv CS.AI 50%

arXiv:2611.14326v1 Announce Type: new Abstract: LLM agents increasingly operate in long-horizon, verifier-rich environments, but current self-improvement mechanisms often write episode-derived lessons directly into memory, making local success an unreliable signal for reusable...

https://arxiv.org/abs/2611.14326

2 CONF

Recurrent Modular Structure in Spiking Neural Network Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2611.14262v1 Announce Type: new Abstract: Biological neural circuits are both modular and recurrent, with dense communities sparsely linked to one another. Spiking neural networks (SNNs) for reinforcement learning are usually feed-forward, and it is unclear how to obtain...

https://arxiv.org/abs/2611.14262

3 CONF

Multimodal Abstention That Preserves Acquired Correct Answers

ArXiv CS.AI 50%

arXiv:2611.14311v1 Announce Type: new Abstract: Adding abstention to a task-adapted multimodal model can discard correct answers, including capabilities acquired during adaptation. We formulate abstention repair as maximizing correct abstention on unanswerable questions under a...

https://arxiv.org/abs/2611.14311

4 CONF

Don't Just Trust Your Memory: Evidence-Linked Memory Reduces Memory-Induced Degradation in LLM Agents

ArXiv CS.AI 50%

arXiv:2611.14320v1 Announce Type: new Abstract: External memory enables LLM agents to improve from experience by distilling trajectories of past tasks into concise lessons for new tasks. However, memory can also lead to memory-induced degradation, where an agent fails on tasks...

https://arxiv.org/abs/2611.14320

5 CONF

An Energy-Based Perspective on Machine Learning

ArXiv CS.AI 50%

arXiv:2611.14383v1 Announce Type: new Abstract: Energy-based models (EBMs) define a distribution through a scalar energy, $p_\theta(x)\propto\exp(-E_\theta(x))$, and are usually presented as one model family among many. This tutorial has a broader goal: beyond introducing EBMs,...

https://arxiv.org/abs/2611.14383

6 CONF

Bits or permutations? Spending a fixed inference budget on weight precision or on option-order averaging in small local language models

ArXiv CS.AI 50%

arXiv:2611.14413v1 Announce Type: new Abstract: Local language models can save memory by storing weights in fewer bits, and they can reduce sensitivity to the order of answer options by averaging a few reorderings. We ask whether the first makes the second worse, and which is...

https://arxiv.org/abs/2611.14413

7 CONF

Precision on Demand: Escalating Weight Bits at Uncertain Decoding Steps in a Small Local Model

ArXiv CS.AI 50%

arXiv:2611.14418v1 Announce Type: new Abstract: Local decoding usually fixes one weight precision for the whole generation. We study a different allocation: store 8-bit weights, decode with their top 4 bits, and redo a step at 8 bits only when the low-precision output...

https://arxiv.org/abs/2611.14418

8 CONF

Evaluating LLM-Generated World Models for Neuro-Symbolic Reasoning

ArXiv CS.AI 50%

arXiv:2611.14419v1 Announce Type: new Abstract: Formal world models can support planning, verification, and safety reasoning, but constructing them from open-ended natural-language situations is difficult, particularly in multi-agent settings where several formalizations may be...

https://arxiv.org/abs/2611.14419

9 CONF

Re-Search: Dissecting LLM Ideation Through a Two-Player Questioning Game

ArXiv CS.AI 50%

arXiv:2611.14487v1 Announce Type: new Abstract: Research ideation is iterative: researchers refine their ideas step by step based on feedback. Yet existing evaluations obscure this search process, making it difficult to understand how LLMs explore the space of research ideas and...

https://arxiv.org/abs/2611.14487

0 CONF

Causal Time Series Modeling of Supraglacial Lake Evolution in Greenland under Distribution Shift

ArXiv CS.AI 50%

arXiv:2510.15265v1 Announce Type: cross Abstract: Causal modeling offers a principled foundation for uncovering stable, invariant relationships in time-series data, thereby improving robustness and generalization under distribution shifts. Yet its potential is underutilized in...

https://arxiv.org/abs/2510.15265

1 CONF

AFNO: Universal Certifiably-Arbitrage-Free Operator Learning Framework for European Call-Price Surfaces

ArXiv CS.AI 50%

arXiv:2611.12899v1 Announce Type: cross Abstract: Neural operators (NOs) have been introduced as deep learning-powered solutions to the computational bottleneck of solving families of problems. Once trained, an NO can rapidly output approximate solutions, avoiding the need to...

https://arxiv.org/abs/2611.12899

2 CONF

M\"obius Interaction Filtering: Order-Selective Spectral Regularization for Multimodal Humor Detection

ArXiv CS.AI 50%

arXiv:2611.12913v1 Announce Type: cross Abstract: Multimodal humor detection requires interpreting language, vocal delivery, and visual behavior jointly. Expressive fusion must also regulate how interactions of different orders enter the final judgment. We propose M\"obius...

https://arxiv.org/abs/2611.12913

3 CONF

Third Eye: Beyond Immediate Gains in Recursive Self-Improvement

ArXiv CS.AI 50%

arXiv:2611.12988v1 Announce Type: cross Abstract: Does a useful self-update remain useful after the model updates again? Third Eye separates immediate performance from the outcome of a further native update. We evaluate five 3-8B backbones on math and code: 64 fresh runs, three...

https://arxiv.org/abs/2611.12988

4 CONF

TIB: Sample-wise Tempered Information Bottleneck for Multimodal Attribution beyond Alignment Assumption

ArXiv CS.AI 50%

arXiv:2611.12997v1 Announce Type: cross Abstract: Multimodal (e.g. vision-language, in this work) attribution aims to interpret the models without access to ground-truth explanatory supervision. Existing multimodal attribution methods typically rely on paired modalities as proxy...

https://arxiv.org/abs/2611.12997

5 CONF

An Open Implementation Flow for the Xilinx Spartan-3E and Spartan-6 that Runs in the Browser, Checked Byte for Byte Against ISE

ArXiv CS.AI 50%

arXiv:2611.13008v1 Announce Type: cross Abstract: The author describes an open implementation flow, from HDL to a programmable bitstream, for the Xilinx Spartan-3E (XC3S100E to XC3S1200E) and Spartan-6 (XC6SLX16, XC6SLX45), devices that only the discontinued ISE 14.7 supports....

https://arxiv.org/abs/2611.13008

6 CONF

GTAGym: Real AAA Game Tasks Environment for Evaluation and Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2611.13028v1 Announce Type: cross Abstract: AAA games offer a rich testbed for evaluating agent perception, reasoning, and control. However, evaluating whether agents can complete tasks in AAA games is challenging and often human-annotated because task outcomes are often...

https://arxiv.org/abs/2611.13028

7 CONF

Continuous-Time Set-Transformers for Asynchronous WiFi-IMU Indoor Localization

ArXiv CS.AI 50%

arXiv:2611.13057v1 Announce Type: cross Abstract: Indoor localization commonly combines WiFi received signal strength indicator (RSSI) fingerprints with inertial measurements. However, these sensor streams are sampled asynchronously at different rates; therefore, observations...

https://arxiv.org/abs/2611.13057

8 CONF

A Multi-Word Tokenizer for 204 Languages That Needs Fewer Tokens Than GPT-4o's, Including on English

ArXiv CS.AI 50%

arXiv:2611.13059v1 Announce Type: cross Abstract: Languages of India need 1.6 to 14 times as many tokens as English on GPT-4o's tokenizer for the same content, which makes them more expensive and slower to serve. We train tokenizers from scratch on human-written text in about...

https://arxiv.org/abs/2611.13059

9 CONF

Just Image Transformers with Late-Stage Pixel Refinement

ArXiv CS.AI 50%

arXiv:2611.13120v1 Announce Type: cross Abstract: Recent work on latent-free diffusion transformers has demonstrated the feasibility of training image generators without a latent VAE. This avoids compression artifacts from the VAE and simplifies the training pipeline. In...

https://arxiv.org/abs/2611.13120

00 CONF

Which Successes Make Good References? Action-Sequence Alignment for Multi-Turn On-Policy Distillation

ArXiv CS.AI 50%

arXiv:2611.13135v1 Announce Type: cross Abstract: On-policy distillation (OPD) reduces train-inference distribution mismatch by supervising a student on its own trajectories. For multi-turn tool-use agents, conditioning the teacher on a validated same-task successful trajectory...

https://arxiv.org/abs/2611.13135

01 CONF

DOBB: Dynamic Oriented Bounding Boxes for Multi-Agent Collision Avoidance under State Uncertainty and Heterogeneous Dynamics

ArXiv CS.AI 50%

arXiv:2611.13142v1 Announce Type: cross Abstract: Learning-based decentralized collision avoidance must remain reliable under state-estimation uncertainty and heterogeneous agent dynamics. Existing methods typically address these factors through training-domain variation or by...

https://arxiv.org/abs/2611.13142

02 CONF

Autonomous Optimization of Numerical Algorithms by an AI Agent: Application to Atomistic Simulation

ArXiv CS.AI 50%

arXiv:2611.13143v1 Announce Type: cross Abstract: Coding agents built on large language models, run in automated improvement loops, can discover more efficient algorithms. We present AIOA, a framework that brings this approach to the numerical algorithms of atomistic simulation:...

https://arxiv.org/abs/2611.13143

03 CONF

Multimodal Road Closure Mapping via Cross-Modal Graph Attention

ArXiv CS.AI 50%

arXiv:2611.13192v1 Announce Type: cross Abstract: Accurate and timely identification of road closures is critical for large-scale navigation and logistics systems, yet remains challenging due to the need to jointly reason over visual evidence, spatial context, and road network...

https://arxiv.org/abs/2611.13192

04 CONF

Variance Reduction for Gradients from Diffusion Teachers

ArXiv CS.AI 50%

arXiv:2605.21489v3 Announce Type: replace-cross Abstract: Pretrained diffusion models serve as frozen teachers for pipelines such as text-to-3D, single-step distillation, and data attribution. The teacher gradients these pipelines consume are expectations over noise levels and...

https://arxiv.org/abs/2605.21489

05 CONF

Train High, Ship Low: Efficient LoRA Synchronization for Distributed On-Policy Post-Training

ArXiv CS.AI 50%

arXiv:2611.13306v1 Announce Type: cross Abstract: Transmitting LoRA adapters to rollout workers can bottleneck distributed on-policy post-training over bandwidth-constrained networks. Lowering the training rank may limit the capacity a workload needs, while adaptive optimizer...

https://arxiv.org/abs/2611.13306

06 CONF

PegasusAI Studio: Legible Cyberinfrastructure and Accountable AI Agents for Scientific Workflows

ArXiv CS.AI 50%

arXiv:2611.13309v1 Announce Type: cross Abstract: AI coding agents can now construct scientific workflows, but operating them on shared cyberinfrastructure (CI) raises problems that code generation does not solve. Agents need current knowledge of the workflow system and its...

https://arxiv.org/abs/2611.13309

07 CONF

The AI Era's Lines of Code? A Case Study on What an Engineer's Token Spend Measures

ArXiv CS.AI 50%

arXiv:2611.13396v1 Announce Type: cross Abstract: Organizations use engineers' token spend to monitor AI adoption, set budgets, and measure productivity, but the metric's relationship with engineering output is unclear. We link five weeks of token usage in coding agents to the...

https://arxiv.org/abs/2611.13396

08 CONF

The Dose Makes the Poison: Exposure-Aware Evaluation of Generative Drug Design

ArXiv CS.AI 50%

arXiv:2611.13398v1 Announce Type: cross Abstract: Generative models are increasingly used to propose molecules for drug discovery. They can produce far more candidates than can be experimentally tested, making computational selection essential. Most selection methods rely on...

https://arxiv.org/abs/2611.13398

09 CONF

Placing LLM Lookup Tables by Per-Layer Prefetch Deadlines

ArXiv CS.AI 50%

arXiv:2611.13413v1 Announce Type: cross Abstract: DeepSeek-V4.1's 203 GB of Engram n-gram tables sit in host DRAM today, taking 190 of the 223 GiB a 4-GPU serving process uses. Row indices depend only on input tokens, so reads can start with each step and overlap earlier layers....

https://arxiv.org/abs/2611.13413

10 CONF

Free Lunch Uncertainty: Sequence-Level R\'enyi Entropy from Particle Decoding for Adaptive LLM Reasoning

ArXiv CS.AI 50%

arXiv:2611.13414v1 Announce Type: cross Abstract: Quantifying uncertainty over an entire LLM completion is critical for selective prediction and adaptive compute. Zero-cost signals such as mean token entropy and log-probability are local to tokens or to one completion, and...

https://arxiv.org/abs/2611.13414

11 CONF

Leveraging Psychophysical Attentional Distribution for Gaze-Augmented Reward Modeling

ArXiv CS.AI 50%

arXiv:2611.13477v1 Announce Type: cross Abstract: Integrating human feedback into language models has gained increasing attention as a means to align model outputs with human preferences, with Reinforcement Learning from Human Feedback (RLHF) serving as a prominent framework for...

https://arxiv.org/abs/2611.13477

12 CONF

MOAI: Module-Optimizing Architecture for non-interactive secure transformer Inference

ArXiv CS.AI 50%

arXiv:2611.13641v1 Announce Type: cross Abstract: Privacy concerns have been raised in Large Language Models (LLM) inference when models are deployed in Cloud Service Providers (CSP). Homomorphic encryption (HE) offers a promising solution by enabling secure inference directly...

https://arxiv.org/abs/2611.13641

13 CONF

AURA: Auditory Spatial Intelligence via a Unified Representation from a General-Audio Encoder through Complete Alignment

ArXiv CS.AI 50%

arXiv:2611.13687v1 Announce Type: cross Abstract: Answering spatial questions about multi-source scenes requires a model both to identify each sound and to locate it. Existing spatial audio-language models obtain spatial information from a dedicated encoder, which separates...

https://arxiv.org/abs/2611.13687

14 CONF

A Hardware-Trained Generative Quantum Eigensolver for Sample-Based Quantum Diagonalization of Organotin Hydroxides up to 70 Qubits

ArXiv CS.AI 50%

arXiv:2611.13755v1 Announce Type: cross Abstract: Quantum hardware can provide feedback for training circuit generators beyond the reach of exact classical simulation. We train generative quantum eigensolver (GQE) policies, transformers conditioned on molecular descriptors, to...

https://arxiv.org/abs/2611.13755

15 CONF

Bridging Graph and Pairwise Learning for Gene Regulatory Network Inference from scRNA-seq Data

ArXiv CS.AI 50%

arXiv:2611.13801v1 Announce Type: cross Abstract: Motivation: Gene regulatory networks (GRNs) capture the underlying interactions through which transcription factors (TFs) regulate genes. Based on gene expression data, existing GRN inference approaches generally fall into two...

https://arxiv.org/abs/2611.13801

16 CONF

CASCADE: Constraint-Aware SCAffolded DEcomposition for Logical Anomaly Detection

ArXiv CS.AI 50%

arXiv:2611.13820v1 Announce Type: cross Abstract: Logical Anomaly Detection (LAD) requires verifying whether all category-specific constraints, such as object counts, pairing relations, and measurement ranges, are satisfied by a query image given only a few normal references....

https://arxiv.org/abs/2611.13820

17 CONF

PolyRoute: A Twelve-Language and Code-Mixed Benchmark for Typed-Decision Routing, with Baselines and a Leaderboard

ArXiv CS.AI 50%

arXiv:2611.13843v1 Announce Type: cross Abstract: Typed-decision encoders answer a question about a text in one forward pass, but their behaviour outside English is rarely measured on a fixed yardstick. We release PolyRoute: 322 native-language support messages in 12 languages...

https://arxiv.org/abs/2611.13843

18 CONF

Satellite Pretraining Is Not One Thing: A Matched-Pair Study of Generic and Earth-Observation Foundation Models for Scene Classification

ArXiv CS.AI 50%

arXiv:2611.13849v1 Announce Type: cross Abstract: Geospatial foundation models are pretrained on satellite and aerial imagery, but whether such an encoder beats a strong generic one for few-label land-use/land-cover mapping remains unclear, as prior comparisons rarely isolate...

https://arxiv.org/abs/2611.13849

19 CONF

Mechanistic Interpretability of Deep Neural Networks: Methods, Frameworks, and Perspectives

ArXiv CS.AI 50%

arXiv:2611.13868v1 Announce Type: cross Abstract: Deep neural networks underpin fundamental tasks in a wide range of signal domains, such as image, audio, and language processing. However, their internal mechanisms are notably difficult to interpret. Internal activations are...

https://arxiv.org/abs/2611.13868

20 CONF

Transparency Disclosures for Chain-of-Thought Monitorability

ArXiv CS.AI 50%

arXiv:2611.13873v1 Announce Type: cross Abstract: Chain-of-thought (CoT) monitoring is one of the most valuable tools for monitoring advanced AI systems, but it is under threat. We argue that frontier AI developers should report specific indicators to make these threats...

https://arxiv.org/abs/2611.13873

21 CONF

Region-Wise Logit Fusion and Utility-Gated Refinement for Brain Metastasis Segmentation

ArXiv CS.AI 50%

arXiv:2611.13884v1 Announce Type: cross Abstract: BraTS-METS 2026 Task 1 evaluates segmentation of brain metastases and postoperative resection cavities on heterogeneous multiparametric MRI, requiring detection of small enhancing foci while preserving the geometry and hierarchy...

https://arxiv.org/abs/2611.13884

22 CONF

MicroBT: Centroid-Guided Synergistic Learning for Multi-Modal Micro Brain Tumor Segmentation and Counting

ArXiv CS.AI 50%

arXiv:2611.13912v1 Announce Type: cross Abstract: Multi-modal brain tumor segmentation is essential for clinical diagnosis, radiotherapy planning, and longitudinal monitoring. While recent studies have achieved remarkable overall segmentation performance, they rely on...

https://arxiv.org/abs/2611.13912

23 CONF

Domain-Invariant and Language-Model-Assisted Acoustic Side-Channel Attacks on Keyboards

ArXiv CS.AI 50%

arXiv:2611.13922v1 Announce Type: cross Abstract: Acoustic side-channel attacks (ASCA) recover typed text from the sound of keystrokes, using only a commodity microphone and no access to the victim's device. Prior work establishes that such attacks succeed under idealized...

https://arxiv.org/abs/2611.13922

24 CONF

TAPCO-G: LLM-Guided Design-Adaptive Timing and Power Co-Optimization with Graph-Based Physical Priors

ArXiv CS.AI 50%

arXiv:2611.13931v1 Announce Type: cross Abstract: Post-placement timing and power co-optimization is critical to meeting setup timing targets and reducing power within placement constraints. A cell replacement can improve timing along one path while increasing power or reducing...

https://arxiv.org/abs/2611.13931

25 CONF

The Case for AI-Enabled Gate Monitoring as Farm Security in the UK: A PRISMA-Guided Review of the Evidence on Rural Crime, Livestock Predation and Farm Access

ArXiv CS.AI 50%

arXiv:2611.13933v1 Announce Type: cross Abstract: Farm security in the UK rests on thinner evidence than its cost suggests. We ran a PRISMA guided review: twelve searches of Web of Science and Scopus on 2nd -4th November 2026 returned 1,183 records (761 unique), and...

https://arxiv.org/abs/2611.13933

26 CONF

Tailoring Optimization Approaches with Domain Knowledge in Industry Process for Meta-heuristic Development

ArXiv CS.AI 50%

arXiv:2611.13940v1 Announce Type: cross Abstract: The paper presents an Industry Process for Meta-heuristic Development (IPMD) schema, a systematic methodology for applying meta- and hyper-heuristic applications to optimization problems. In this context, we present a case study...

https://arxiv.org/abs/2611.13940

27 CONF

Chem World: A Large-Scale Benchmark and Physics-Aware Framework for Trustworthy Molecular Property Prediction

ArXiv CS.AI 50%

arXiv:2611.13945v1 Announce Type: cross Abstract: Molecular property prediction is fundamental to computational chemistry and drug formulation research, yet existing benchmarks remain fragmented across datasets, properties, and evaluation protocols, limiting systematic...

https://arxiv.org/abs/2611.13945

28 CONF

Controlled Knowledge Engineering for Taxonomy Induction with Tool-Grounded LLM Agents and Runtime-Adaptive Policies

ArXiv CS.AI 50%

arXiv:2611.13966v1 Announce Type: cross Abstract: Taxonomies are structured knowledge representations that support semantic search, recommendation, product catalog organization, and retrieval-augmented generation. Their automated construction from a fixed set of candidate...

https://arxiv.org/abs/2611.13966

29 CONF

Specify Privacy Yourself: Assessing Inference-Time Personalized Privacy Preservation Ability of Large Vision-Language Models

ArXiv CS.AI 50%

arXiv:2611.13997v1 Announce Type: cross Abstract: Large Vision-Language Models (LVLMs) have demonstrated remarkable capabilities but raise significant privacy concerns due to their abilities to infer sensitive personal information from images with high precision. While current...

https://arxiv.org/abs/2611.13997

30 CONF

Coding Agent Memory Post-Training II: Unlocking the Memory Potential of Pre-trained File Operations for Long-Horizon Tasks via On-Policy Distillation

ArXiv CS.AI 50%

arXiv:2611.14009v1 Announce Type: cross Abstract: Language-model agents increasingly tackle long-horizon tasks whose interaction histories exceed the model's active context. They must therefore decide what to write down and what to read back, and when to do either. Recent work...

https://arxiv.org/abs/2611.14009

31 CONF

A Stage-Wise Explainable Pipeline for Arteriolar-to-Venular Ratio Estimation and Retinopathy Screening

ArXiv CS.AI 50%

arXiv:2611.14013v1 Announce Type: cross Abstract: The arteriolar-to-venular diameter ratio (AVR) is a clinically motivated marker of retinal vascular health. We present a five-stage pipeline for AVR estimation and exploratory retinopathy screening from fundus images, with...

https://arxiv.org/abs/2611.14013

32 CONF

Program-Aided Patchable Skill Evolution

ArXiv CS.AI 50%

arXiv:2611.14019v1 Announce Type: cross Abstract: Agent skills have emerged as an effective means of enabling LLM agents to solve complex, interactive tasks by encoding reusable knowledge without modifying model parameters. Recent approaches further improve skill adaptation by...

https://arxiv.org/abs/2611.14019

33 CONF

HandsOnAid: Building and Evaluating an Offline First-Aid Assistant for Emergency Response Scenarios

ArXiv CS.AI 50%

arXiv:2611.14059v1 Announce Type: cross Abstract: Emergencies can occur where there is no phone signal and no ambulance nearby. A small language model on a phone can be helpful in such situations, but its advice needs to be safe and accurate. We built HandsOnAid, a 4-bit Gemma...

https://arxiv.org/abs/2611.14059

34 CONF

Obscured Wildfire Flame Detection by Spatio-temporal Analysis of Smoke Patterns Using Frame-wise Transformers

ArXiv CS.AI 50%

arXiv:2611.14074v1 Announce Type: cross Abstract: In this paper, we propose a new paradigm in wildfire management for detecting both visible and obscured fire using Deep Learning (DL). The essence of our method is the joint spatial and temporal analysis of RGB videos, embracing...

https://arxiv.org/abs/2611.14074

35 CONF

ZoomGain: Mining Global-to-Zoom Perception Gaps for Fine-Grained Visual Supervision

ArXiv CS.AI 50%

arXiv:2611.14076v1 Announce Type: cross Abstract: Fine-grained visual perception requires Vision-Language Models (VLMs) to locate and interpret subtle evidence within complex scenes. Constructing supervision for this ability is challenging: questions must have correct,...

https://arxiv.org/abs/2611.14076

36 CONF

Verifiable Agentic Traffic Class: A Policed Quality-of-Service Mechanism for Agentic AI Traffic, Evaluated from Simulation to Real-Kernel Adversarial Testing

ArXiv CS.AI 50%

arXiv:2611.14211v1 Announce Type: cross Abstract: Software agents built on large language models generate traffic unlike human web traffic, yet routers have no class for it and cannot verify a sender's claim to be an agent. This paper proposes the Verifiable Agentic Traffic...

https://arxiv.org/abs/2611.14211

37 CONF

Spectral-Convolutional Factorized Transformer for Joint Multipath Parameter Estimation: Applications to mmWave Positioning and Radio SLAM

ArXiv CS.AI 50%

arXiv:2611.01491v2 Announce Type: replace-cross Abstract: Future 6G wireless networks are expected to evolve toward AI-native systems that support intelligent, environment-aware services, including positioning and mapping. Current research has already integrated AI into several...

https://arxiv.org/abs/2611.01491

38 CONF

An AI Assistant for Automating Anti-Corruption Expertise of Draft Legislation Based on the TRACE Framework

ArXiv CS.AI 50%

arXiv:2611.14244v1 Announce Type: cross Abstract: We present an AI assistant for automating anti-corruption expertise of draft legislation based on the TRACE architecture, designed to screen bills for corruption risks: pinpoint provisions an expert would criticise and name the...

https://arxiv.org/abs/2611.14244

39 CONF

Achieving Robust Channel Estimation Neural Networks on Doppler effects by Designed Training Data

ArXiv CS.AI 50%

arXiv:2611.14267v1 Announce Type: cross Abstract: Channel estimation is crucial in wireless communication systems. Many existing works train and test their models using the same or similar channel. However, practical channels are infinitely diverse and time-variant while...

https://arxiv.org/abs/2611.14267

40 CONF

Forward-Value Discretization: Faster Stochastic Diffusion Sampling Without High-Order Approximation

ArXiv CS.AI 50%

arXiv:2611.14328v1 Announce Type: cross Abstract: Stochastic diffusion samplers often require substantially more neural function evaluations (NFEs) than deterministic samplers to achieve comparable sample quality. Although higher-order discretization accelerates deterministic...

https://arxiv.org/abs/2611.14328

41 CONF

AI Isn't Getting Dumber, We're Getting Pickier: Rising Standards in Human Evaluation of Large Language Models

ArXiv CS.AI 50%

arXiv:2611.14333v1 Announce Type: cross Abstract: Users often complain that AI assistants such as ChatGPT are getting worse. Some versions do change, but human evaluation leaves a second possibility untested: the people judging may change. We separate the two on Chatbot Arena, a...

https://arxiv.org/abs/2611.14333

42 CONF

EngineAgent: Agentizing On-Device LLM Inference Engines with Inference Stack Hierarchy Awareness and Hardware Abilities

ArXiv CS.AI 50%

arXiv:2611.14356v1 Announce Type: cross Abstract: Rapidly evolving LLM architectures and heterogeneous mobile hardware make supporting new models in on-device inference engines a recurring and costly system challenge. Each model may require coordinated changes across conversion,...

https://arxiv.org/abs/2611.14356

43 CONF

Blurring the Block Boundaries: Overlapping Block Denoising for Efficient Diffusion Language Models

ArXiv CS.AI 50%

arXiv:2611.14387v1 Announce Type: cross Abstract: Diffusion Language Models (DLMs) have emerged as effective alternatives to autoregressive models for latency-critical tasks, enabling faster token generation. Recent advances employ block diffusion with self-editing capabilities,...

https://arxiv.org/abs/2611.14387

44 CONF

Two Communities, One Problem: Branch-and-Bound vs. A* for Resource-Constrained Project Scheduling

ArXiv CS.AI 50%

arXiv:2611.14426v1 Announce Type: cross Abstract: Branch-and-Bound (B&B) and A^* are popular exact search methods originating from Operations Research and Artificial Intelligence, respectively. Although the two methods share fundamental search principles, their different ways...

https://arxiv.org/abs/2611.14426

45 CONF

Medical Image Segmentation: Foundation Model Adaptation versus Task-Specific Training

ArXiv CS.AI 50%

arXiv:2611.14519v1 Announce Type: cross Abstract: Foundation models pretrained on large natural-image collections are increasingly adapted for medical image segmentation, in the expectation that they will replace models trained for each task. Most comparisons, however, use data...

https://arxiv.org/abs/2611.14519

46 CONF

Robustness Verification in Neural Networks

ArXiv CS.AI 50%

arXiv:2403.13441v2 Announce Type: replace Abstract: In this paper we investigate formal verification problems for Neural Network computations. Of central importance will be various robustness and minimization problems such as: Given symbolic specifications of allowed inputs and...

https://arxiv.org/abs/2403.13441

47 CONF

Accurate Predictions in Education with Discrete Variational Inference

ArXiv CS.AI 50%

arXiv:2509.23484v3 Announce Type: replace Abstract: One of the largest drivers of social inequality is unequal access to personal tutoring, with wealthier individuals able to afford it, while the majority cannot. Affordable, effective AI tutors offer a scalable solution. We...

https://arxiv.org/abs/2509.23484

48 CONF

Dynamic Mixed-Precision Routing for Efficient Multi-step LLM Interaction

ArXiv CS.AI 50%

arXiv:2602.02711v4 Announce Type: replace Abstract: Large language models (LLMs) achieve strong performance in long-horizon agentic tasks through multi-step interaction and reasoning at test time. However, repeatedly invoking these models incurs substantial inference cost over...

https://arxiv.org/abs/2602.02711

49 CONF

Can AI Agents Synthesize Scientific Conclusions in Health?

ArXiv CS.AI 50%

arXiv:2606.11337v2 Announce Type: replace Abstract: Scientific AI agents increasingly retrieve evidence, reason across sources, and synthesize conclusions used in consequential decisions. Yet, their ability to do so in high-stakes domains such as health remains unclear. We...

https://arxiv.org/abs/2606.11337

50 CONF

Decide, Ask, or Defer: Clinical LLMs under Incomplete Evidence

ArXiv CS.AI 50%

arXiv:2610.04542v3 Announce Type: replace Abstract: Clinical LLMs must decide not only what diagnosis to produce, but also whether the available evidence is sufficient for autonomous decision making. Binary DECIDE/ABSTAIN formulations merge distinct non decision states and do...

https://arxiv.org/abs/2610.04542

51 CONF

Scoped Semantic Invariance as a Foundation for LLM Reliability

ArXiv CS.AI 50%

arXiv:2610.33267v2 Announce Type: replace Abstract: LLMs often answer semantically equivalent queries inconsistently, even when the underlying facts are known. We formalize consistency as semantic invariance over equivalence classes of queries and show that invariance under...

https://arxiv.org/abs/2610.33267

52 CONF

Are Spiking Neural Networks Harder to Steal? The Role of Stochastic Encoding in Model Extraction

ArXiv CS.AI 50%

arXiv:2610.36298v2 Announce Type: replace Abstract: Machine learning models deployed on edge devices are vulnerable to model stealing attacks, in which an adversary replicates a model using only its predictions. Existing defenses add mechanisms that are costly on...

https://arxiv.org/abs/2610.36298

53 CONF

Low-Margin Branch Points in Deterministic LLM Deliberation

ArXiv CS.AI 50%

arXiv:2611.00546v2 Announce Type: replace Abstract: Deterministic multi-agent LLM deliberation can exactly re- play a fixed transcript, yet exact replay alone does not test local resistance to controlled internal interventions. Because each response becomes context for later...

https://arxiv.org/abs/2611.00546

54 CONF

MAGAR: Multimodal Agents for GUI-Based 3D Mechanical Assembly and Minimal Rework

ArXiv CS.AI 50%

arXiv:2611.02472v2 Announce Type: replace Abstract: A GUI command can be correct at the interface level yet still produce an incorrect assembly. An agent must identify the relevant components, respect their structural relationships, and determine which parts should move during...

https://arxiv.org/abs/2611.02472

55 CONF

Kierston & KierstonBench: Simulation of Allentown, PA and Evaluation of Language Models in Crime Investigation and Surveillance Tasks

ArXiv CS.AI 50%

arXiv:2611.04785v2 Announce Type: replace Abstract: Large language models are candidates for collecting and analyzing records in criminal investigations and mass surveillance. Their capability and accuracy in this work cannot currently be measured. Real deployments lack the...

https://arxiv.org/abs/2611.04785

56 CONF

Veterans' Mental Health Crisis Severity Annotation: Do LLMs Agree More Than Human Experts?

ArXiv CS.AI 50%

arXiv:2611.10048v2 Announce Type: replace Abstract: Large language models (LLMs) offer a scalable approach for annotating mental health and crisis-related social media content, but their reliability in safety-critical tasks remains unclear. This study evaluates LLM-based...

https://arxiv.org/abs/2611.10048

57 CONF

Agentic discrete-event simulation for manufacturing system design: an open 3D simulator, a benchmark and an industrial case

ArXiv CS.AI 50%

arXiv:2611.10602v2 Announce Type: replace Abstract: The design of manufacturing systems relies on discrete-event simulation (DES) models that experts still build in tool-specific interfaces. AI agents can now write simulation code, but every model they write from scratch is new,...

https://arxiv.org/abs/2611.10602

58 CONF

Towards using Large Language Models for Risk Negotiation and Consensus-building in One Health contexts

ArXiv CS.AI 50%

arXiv:2509.09906v2 Announce Type: replace-cross Abstract: Risk negotiation under the One Health framework requires balancing competing stakeholder interests across human, animal, and environmental health domains - a process constrained by information complexity and time...

https://arxiv.org/abs/2509.09906

59 CONF

Self-Improving Training & Thinking

ArXiv CS.AI 50%

arXiv:2601.21343v5 Announce Type: replace-cross Abstract: Large language models are classically trained in stages: pretraining on raw text followed by post-training for instruction following and reasoning. However, this separation creates a fundamental limitation: many desirable...

https://arxiv.org/abs/2601.21343

60 CONF

BrainVista: Modeling Naturalistic Brain Dynamics as Multimodal Next-Token Prediction

ArXiv CS.AI 50%

arXiv:2602.04512v2 Announce Type: replace-cross Abstract: Naturalistic fMRI offers a time-resolved window into cortical dynamics during continuous multimodal experience, where future brain states are jointly governed by endogenous neural context and exogenous sensory drive....

https://arxiv.org/abs/2602.04512

61 CONF

KAIROS: Stateful, Context-Aware Power-Efficient Agentic Inference Serving

ArXiv CS.AI 50%

arXiv:2604.16682v2 Announce Type: replace-cross Abstract: Power has become a central bottleneck for AI inference. This problem is becoming more urgent as agentic AI emerges as a major workload class, yet prior power-management techniques focus almost entirely on single-turn LLM...

https://arxiv.org/abs/2604.16682

62 CONF

COMO: Closed-Loop Optical Molecule Recognition with Minimum Risk Training

ArXiv CS.AI 50%

arXiv:2604.23546v2 Announce Type: replace-cross Abstract: Optical chemical structure recognition (OCSR) translates molecular images into machine-readable representations such as SMILES strings or molecular graphs, but remains challenging in real-world documents due to wide...

https://arxiv.org/abs/2604.23546

63 CONF

Epistemic Infrastructures of Science in AI Era Should Rebalance Costs of Generation and Verification

ArXiv CS.AI 50%

arXiv:2605.10425v2 Announce Type: replace-cross Abstract: AI systems can now cheaply generate plausible scientific artifacts such as papers, reviews, and surveys. This creates a risk of \emph{epistemic pollution} in our scientific systems, where unreliable but plausible-looking...

https://arxiv.org/abs/2605.10425

64 CONF

Examining the Impact of Data and Training Methods on Emergent and Subliminal Misalignment

ArXiv CS.AI 50%

arXiv:2605.12798v2 Announce Type: replace-cross Abstract: Post-training a language model can induce surprising behavioral changes far beyond the intended training target. We study two particularly striking examples: emergent misalignment (EM), where fine-tuning on a narrow...

https://arxiv.org/abs/2605.12798

65 CONF

DOTRAG: Retrieval-Time Reasoning Along Paths

ArXiv CS.AI 50%

arXiv:2605.18760v2 Announce Type: replace-cross Abstract: Graph Retrieval-Augmented Generation (GraphRAG) faces significant challenges in complex relational retrieval tasks, particularly in densely connected knowledge graphs where the number of possible paths grows rapidly with...

https://arxiv.org/abs/2605.18760

66 CONF

With Tools or Because of Tools? Tracing Capability Gains in Multimodal Agents

ArXiv CS.AI 50%

arXiv:2606.02357v3 Announce Type: replace-cross Abstract: Tool-augmented multimodal agents show strong benchmark gains, often taken as evidence that agents have learned to use tools. We argue that this interpretation can be premature: a tool-call trace alone does not show...

https://arxiv.org/abs/2606.02357

67 CONF

Self-Modeling Interventions can Modulate Emergent Misalignment

ArXiv CS.AI 50%

arXiv:2606.23700v2 Announce Type: replace-cross Abstract: Emergent misalignment (EM) has been linked to the activation of misaligned persona vectors and evil character traits, suggesting that EM operates through disruption of the model's aligned character rather than direct...

https://arxiv.org/abs/2606.23700

68 CONF

Reinforcement Learning over Patient Trajectories for Clinical Reasoning in EHR Foundation Models

ArXiv CS.AI 50%

arXiv:2609.12277v2 Announce Type: replace-cross Abstract: Electronic health record (EHR) foundation models trained on longitudinal patient trajectories have demonstrated strong performance across diverse clinical prediction tasks. However, their clinical reasoning capabilities...

https://arxiv.org/abs/2609.12277

69 CONF

Learning Perturbation Robust Policies for LLM Agents with Stable Optimization

ArXiv CS.AI 50%

arXiv:2609.34064v2 Announce Type: replace-cross Abstract: Reinforcement learning (RL) has become an effective post-training paradigm for long-horizon large language model (LLM) agents. However, we find that the resulting policies can be sensitive to various policy perturbations,...

https://arxiv.org/abs/2609.34064

70 CONF

Split and Bridge: Multimodal Generation via Diffusion Bridging

ArXiv CS.AI 50%

arXiv:2611.10441v2 Announce Type: replace-cross Abstract: Visual data are often expressed through multiple complementary modalities (e.g., images and segmentation masks), each capturing different aspects of the same underlying structure. Most existing multimodal methods adopt a...

https://arxiv.org/abs/2611.10441

71 CONF

Beyond the Mean Gap: What Transferred-Angle QAOA Retains on a Superconducting Processor

ArXiv CS.AI 50%

arXiv:2611.10529v2 Announce Type: replace-cross Abstract: Hardware executions of the quantum approximate optimization algorithm (QAOA) are often validated by comparing the device's mean cost with a simulation, a check that can miss what matters for optimization. Under global...

https://arxiv.org/abs/2611.10529

72 CONF

Direct Trajectory Optimization for Inference-Time Alignment of Text-to-Image Diffusion Models

ArXiv CS.AI 50%

arXiv:2611.11821v2 Announce Type: replace-cross Abstract: Alignment of text-to-image diffusion models with reward functions is a key challenge in controllable generation. Existing approaches typically rely on optimizing model inputs or fine-tuning denoising networks, which...

https://arxiv.org/abs/2611.11821