NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

16 October 2026

150 verified · 300 raw · 4 sources

150	2	148	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	135	Media
The Verge AI	6	Media
TechCrunch AI	6	Media
HackerNews	6	Community

VERIFIED INTELLIGENCE — 2 stories

VERI

Wolof-Adapted Industry-Ready Open-Weight Language Models

ArXiv CS.AI +2 sources 100%

arXiv:2610.20824v1 Announce Type: cross Abstract: Wolof is spoken by 23M people, mostly in Senegal, but remains weakly supported by open-weight language models, while API models raise cost, governance, and sovereignty constraints for local deployments. In this paper, we present...

https://arxiv.org/abs/2610.20824

VERI

Bluesky’s AI tool now lets you make games and apps to share on social

The Verge AI +1 source 80%

Bluesky's Attie AI tool, which initially launched earlier this year as a way to use AI to build your own feeds, now lets you make "small" social apps like games, polls, and dashboards that you can then share with others as their own websites. In an interview at TechCrunch...

https://www.theverge.com/tech/1012374/bluesky-ai-attie-small-social-games-apps

CONFIRMED SIGNALS — 148 stories

CONF

Show HN: Textfold – a native Mac text expander with plain text snippets

HackerNews 50% HN 4

No summary — see link for full article.

https://textfold.app

CONF

Show HN: Rails-preflight, a static check of what blocks your next Rails upgrade

HackerNews 50% HN 3

No summary — see link for full article.

https://github.com/aslam/rails-preflight

CONF

Show HN: Lobby Domains: Find Domains with Chrome's On-Device AI

HackerNews 50% HN 2

No summary — see link for full article.

https://lobby.domains/

CONF

Show HN: Guess the LLM – read an answer and guess which model wrote it

HackerNews 50% HN 2

Hi HN, I made a game to test if people can really tell AI models apart. Models from all the frontier labs answer the same question. You read one answer and guess who wrote it. You can also pick just the models you want to compare. I made it and still only get 5/10 lol. Curious...

https://guessthellm.com/

CONF

Show HN: BitRun v0.2 – Run 8B ternary LLMs on CPU with live wattage telemetry

HackerNews 50% HN 2

No summary — see link for full article.

https://github.com/IshekKhal/bitrun

CONF

Show HN: Mordiem – OpenAI-compatible API with multi-network failover

HackerNews 50% HN 2

No summary — see link for full article.

https://mordiem.com

CONF

When it came to Cal AI’s viral success, a small army of influencers paid off

TechCrunch AI 50%

The company generated over $30 million in revenue in two years and was acquired by MyFitnessPal for an undisclosed amount of money in March.

https://techcrunch.com/2026/10/15/when-it-came-to-cal-ais-viral-success-a-small-army-of...

0 CONF

Amazon devices chief Panos Panay sees a future where AI devices replace the need to use apps

TechCrunch AI 50%

Speaking at TechCrunch Disrupt, Amazon devices chief Panos Panay described a future where ambient AI devices work in the background, anticipating users' needs instead of waiting for commands.

https://techcrunch.com/2026/10/15/amazon-devices-chief-panos-panay-sees-a-future-where-...

1 CONF

Anthropic is letting METR researchers look under the hood with employee-level access

TechCrunch AI 50%

METR will publish its own assessments of Anthropic’s risks, incidents, and practices, and the frontier AI model maker has given up the right to block them.

https://techcrunch.com/2026/10/15/anthropic-is-letting-metr-researchers-look-under-the-...

2 CONF

Amazon’s Bee launches two new personal AI devices, starting at $75

TechCrunch AI 50%

Amazon-owned Bee has launched its first new AI devices since its acquisition, including an updated wearable and a credit-card-sized recorder that attaches to smartphones. The devices can summarize conversations, create to-do lists, and integrate with Alexa and Amazon shopping,...

https://techcrunch.com/2026/10/15/amazons-bee-launches-two-new-personal-ai-devices-star...

3 CONF

ChatGPT can peek at your Chrome tabs now

The Verge AI 50%

OpenAI's ChatGPT Atlas browser is gone, but now ChatGPT's Google Chrome extension is getting some upgrades that allow it to use the browser tabs you already have open. With the extension installed, OpenAI says ChatGPT can now view your browser tabs when you tag Chrome in...

https://www.theverge.com/ai-artificial-intelligence/1012510/openai-chatgpt-google-chrom...

4 CONF

Trump posts AI-edited photo to brag about White House restoration work

The Verge AI 50%

President Donald Trump posted a series of photos on Truth Social showing off renovations to the White House - but one of them appears to be modified with AI. The picture, which compares an old White House column to a "restored" one, has several discrepancies and was flagged by...

https://www.theverge.com/policy/1012445/donald-trump-ai-photo-white-house-rennovation-c...

5 CONF

Friends don’t let friends feed their data to AI agents

The Verge AI 50%

There's a growing trend in the consumer tech world: gadgets designed to spy on everything and everyone around you, regardless of whether or not anyone else actually consented to it. Now, with the advent of "AI personal assistants" like Meta's Muse, you're being cheerfully asked...

https://www.theverge.com/tech/1011938/muse-ai-data-friends-consent

6 CONF

Nobody is safe from celebrity AI deepfakes

The Verge AI 50%

In hindsight, the post on Instagram should have raised more red flags. The image purported to show actress Mia Goth, just days after filing for divorce from actor and filmmaker Shia LaBeouf, posing in a T-shirt with a pointed message: MY EX IS MY BIGGEST FAN. To really drive...

https://www.theverge.com/report/1011927/instagram-celebrity-ai-slop-likeness-taylor-swi...

7 CONF

The World Won't Wait: Evaluating and Teaching Agents Under a Live Clock

ArXiv CS.AI 50%

arXiv:2610.20665v1 Announce Type: new Abstract: Large language model (LLM) agents can solve complex interactive tasks, yet reasoning and tool calls take time. In continuously changing environments, an otherwise correct action may arrive too late. We introduce RealtimeBench, with...

https://arxiv.org/abs/2610.20665

8 CONF

Evaluating Model Capabilities After Benchmark Saturation

ArXiv CS.AI 50%

arXiv:2610.20667v1 Announce Type: new Abstract: Rapid advances in AI capabilities are causing benchmarks to saturate. Once several models approach perfect scores, a benchmark loses its power to differentiate between them, and with it its utility for informing AI safety cases and...

https://arxiv.org/abs/2610.20667

9 CONF

Amortizing Sequential Experimental Design in Reasoning LLMs

ArXiv CS.AI 50%

arXiv:2610.20832v1 Announce Type: cross Abstract: Despite their extensive pretraining knowledge and strong reasoning capabilities, large language models (LLMs) struggle to adaptively gather information in experimental design tasks. We study how to amortize sequential Bayesian...

https://arxiv.org/abs/2610.20832

0 CONF

Counterfactual Neighborhood Risk Fields: Evidence-Grounded Selective Safety for Vision-Language Models

ArXiv CS.AI 50%

arXiv:2610.20679v1 Announce Type: new Abstract: Representation-based safety defenses for vision-language models (VLMs) often learn to separate harmful from benign inputs, but separation alone does not establish what a risk score means or when it should be trusted. We introduce...

https://arxiv.org/abs/2610.20679

1 CONF

Learning to Steer LLM Agents and Multi-Agent Systems

ArXiv CS.AI 50%

arXiv:2610.22316v1 Announce Type: cross Abstract: Large language model (LLM)-based agents and multi-agent systems increasingly tackle complex tasks through long-horizon tool use and inter-agent collaboration. However, these systems are prone to deviating from the overall goal as...

https://arxiv.org/abs/2610.22316

2 CONF

Open-world AI: a Tale of Three Requirements

ArXiv CS.AI 50%

arXiv:2610.20782v1 Announce Type: new Abstract: The closed world asks AI for specialized competence and lets it manufacture the iid data its theory assumes: a fixed criterion licenses collecting examples until the task is covered. The open world asks for versatility --- taking...

https://arxiv.org/abs/2610.20782

3 CONF

Evolving Together, Failing Apart: The Skill-Policy Co-evolution Trap in Self-Improving Agents

ArXiv CS.AI 50%

arXiv:2610.20845v1 Announce Type: new Abstract: Skill-policy co-evolution, in which an agent's policy model and its skill bank improve each other during training, is a promising paradigm for self-improving agents. Current evaluations score the co-evolved policy on the final bank...

https://arxiv.org/abs/2610.20845

4 CONF

Confidence-Calibrated Inference Expansion for Evaluator-Guided Test-Time Reasoning

ArXiv CS.AI 50%

arXiv:2610.20836v1 Announce Type: new Abstract: Evaluator-guided reasoning presents a local control problem at every step: trust the current answer, return a fallback, or spend more inference. We formulate this choice as a compute-aware three-action controller, scoring terminal...

https://arxiv.org/abs/2610.20836

5 CONF

A Multi-Tiered AI Accessibility Model (MAIAM): Proportionate Access and Capability Limits for Comprehensive Frontier AI Safety

ArXiv CS.AI 50%

arXiv:2610.20921v1 Announce Type: new Abstract: Most debate about releasing capable AI systems treats the choice as binary: keep the model behind an API, or publish the weights. That framing runs together two separate decisions. One is how capable a system may become. The other...

https://arxiv.org/abs/2610.20921

6 CONF

Mosaic: Multi-Session Agentic Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.22174v1 Announce Type: cross Abstract: Most existing agentic reinforcement learning methods assume single-session trajectories, where interaction proceeds within one continuously accumulated context. However, agentic techniques such as context compaction and subagent...

https://arxiv.org/abs/2610.22174

7 CONF

Towards Better Aligned LLM Judges for Radiology Report Evaluation across Modalities and Anatomies

ArXiv CS.AI 50%

arXiv:2604.03376v2 Announce Type: replace Abstract: Current work on radiology report evaluation has focused primarily on LLM-based metrics for chest X-rays (CXR), leaving open whether such approaches remain robust across other modalities and anatomies, and which model and prompt...

https://arxiv.org/abs/2604.03376

8 CONF

MSP: Modality Self-Play for Training Multimodal LLMs Without Paired Cross-Modal Data

ArXiv CS.AI 50%

arXiv:2610.20965v1 Announce Type: new Abstract: Large multimodal models have achieved remarkable progress by scaling model capacity and training on massive paired multimodal data. However, this paradigm introduces a fundamental bottleneck: aligned multimodal datasets are...

https://arxiv.org/abs/2610.20965

9 CONF

Deep Reinforcement Learning for HPC Job Scheduling: A Statistical Evaluation

ArXiv CS.AI 50%

arXiv:2610.21008v1 Announce Type: new Abstract: Deep Reinforcement Learning (DRL) offers learned job selection for High-Performance Computing (HPC), but performance against heuristics alone does not establish value beyond action masking. Six DRL treatments are compared: Proximal...

https://arxiv.org/abs/2610.21008

0 CONF

Failure Is the Mother of Success: Recovering Supervision with Grounding Hindsight

ArXiv CS.AI 50%

arXiv:2610.21018v1 Announce Type: new Abstract: When every rollout for a problem fails, GRPO receives neither a successful exemplar nor a nonzero group-relative advantage, so it learns nothing from exactly the problems it most needs to learn. The failed reasoning can...

https://arxiv.org/abs/2610.21018

1 CONF

Learning When to Withdraw: Curriculum Coverage and Rule-Specific Failures in Fine-Tuned Language Agents

ArXiv CS.AI 50%

arXiv:2610.21045v1 Announce Type: new Abstract: Tool-using language agents must revise prepared actions when evidence changes or authority is revoked. Selective withdrawal means suspending affected actions, preserving supported work, and resuming only after sufficient repair. We...

https://arxiv.org/abs/2610.21045

2 CONF

OmicsBench: a long-horizon multi-turn benchmark of AI agents on research-study-scale bioinformatics

ArXiv CS.AI 50%

arXiv:2610.21074v1 Announce Type: new Abstract: Computational biologists increasingly delegate substantial analyses to AI agents in long-horizon, multi-turn sessions, yet most benchmarks of agents' bioinformatics capabilities pose a single short task with a single-shot prompt....

https://arxiv.org/abs/2610.21074

3 CONF

SciΠvot: Benchmarking Principal-Investigator Judgment at Pivotal Moments of Scientific AutoResearch Agents

ArXiv CS.AI 50%

arXiv:2610.21082v1 Announce Type: new Abstract: Large language model (LLM) agents can keep scientific experiments running for months with little human supervision, but reliable autonomous research also requires scientific judgment. Evaluating scientific judgment is difficult...

https://arxiv.org/abs/2610.21082

4 CONF

Design the Feedback, Not Just the Reward: Environments for Open-Ended Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2608.27906v3 Announce Type: replace Abstract: Reinforcement learning has advanced large language models on tasks with reliable verifiers, where checking an outcome provides a clear basis for reward. Extending this approach to open-ended tasks requires environments that can...

https://arxiv.org/abs/2608.27906

5 CONF

Planning Commitment of LLM under Partial Observability

ArXiv CS.AI 50%

arXiv:2610.21108v1 Announce Type: new Abstract: LLM-based planning agents commit to plans of different lengths before interacting with a partially observable environment. Some aggressively commit to a long plan based on assumptions about unobserved states, while others...

https://arxiv.org/abs/2610.21108

6 CONF

Kolab: Benchmarking Human-Agent Collaboration in Long-Horizon Workflows

ArXiv CS.AI 50%

arXiv:2610.21109v1 Announce Type: new Abstract: When humans collaborate with AI agents on long-horizon tasks, what happens to the agents' contributions? For solving long-horizon tasks, humans place greater importance on ongoing interaction with AI agents (e.g., revising plans)...

https://arxiv.org/abs/2610.21109

7 CONF

MemScope: Evolving Agent Memory Architectures through Localized Code Repair

ArXiv CS.AI 50%

arXiv:2610.21170v1 Announce Type: new Abstract: Agent memory architectures define how LLM agents store and reuse experience across tasks, but they are typically fixed after deployment, limiting their adaptability across task types. Recent self-evolving approaches instead adapt...

https://arxiv.org/abs/2610.21170

8 CONF

Bellman-Consistent Trajectory RL for LLM Arithmetic Reasoning

ArXiv CS.AI 50%

arXiv:2610.21060v1 Announce Type: cross Abstract: To address sparse terminal rewards in LLM arithmetic reasoning, we propose a Bellman-consistent trajectory RL method. Our framework introduces Trajectory Bellman Residual Minimization (TBRM) to transform sparse rewards into dense...

https://arxiv.org/abs/2610.21060

9 CONF

Mine, Sample, Render: Test-Time Diversity Alignment Of Generative Models

ArXiv CS.AI 50%

arXiv:2610.21185v1 Announce Type: new Abstract: Modern generative models produce high-quality individual outputs but struggle to sample diversely, even when explicitly instructed to do so. We introduce MINE-SAMPLE-RENDER (MSR), a test-time approach that externalizes the...

https://arxiv.org/abs/2610.21185

0 CONF

Functional Subnetwork Localization for Efficient Continual Learning in Large Language Models

ArXiv CS.AI 50%

arXiv:2610.21537v1 Announce Type: new Abstract: Biological intelligence continually adapts to new information while retaining prior skills through localized plasticity. In contrast, continual learning in large language models (LLMs) remains vulnerable to catastrophic forgetting....

https://arxiv.org/abs/2610.21537

1 CONF

Entertain, then Cancel: How Thinking Makes Reasoning Models Read Some and Or Literally

ArXiv CS.AI 50%

arXiv:2610.21204v1 Announce Type: new Abstract: When a speaker says ``some students passed'', listeners infer that not all of them did. Reasoning models now let users decide how long a model thinks before it answers, but we do not know what extra thinking does to such everyday...

https://arxiv.org/abs/2610.21204

2 CONF

TRACER: Trajectory-Aware Tool Retrieval for LLM Agents

ArXiv CS.AI 50%

arXiv:2610.21267v1 Announce Type: cross Abstract: Modern agents select tools from registries, but exposing entire registries incurs high token costs and can impair selection as they grow. We present TRACER, a retrieval front-end that indexes observed tool-call sequences in a...

https://arxiv.org/abs/2610.21267

3 CONF

Auditing Escalation Reliability in Healthcare LLM Agents: A Perturbation-Controlled Benchmark of Workflow-State Failures

ArXiv CS.AI 50%

arXiv:2610.21270v1 Announce Type: new Abstract: Trustworthy biomedical AI requires reliable action selection when evidence is missing, stale, conflicting, or late, not only accurate answers on static inputs. We instantiate an episode-level evaluation protocol as 400 synthetic...

https://arxiv.org/abs/2610.21270

4 CONF

Discovering state-of-the-art quantum circuits with large language models

ArXiv CS.AI 50%

arXiv:2610.22367v1 Announce Type: cross Abstract: Significant efforts are currently being directed toward the implementation of large-scale quantum information processors, but realizing useful quantum advantage also requires the development of efficient quantum algorithms. While...

https://arxiv.org/abs/2610.22367

5 CONF

Quantum Versus Classical Machine Learning for Neuropsychiatric Disorders: A Feature-Matched Multi-Cohort Evaluation

ArXiv CS.AI 50%

arXiv:2610.21344v1 Announce Type: new Abstract: Resting-state functional connectivity is widely used in machine learning-based classification of neuropsychiatric disorders. Quantum machine learning models have been proposed for functional connectivity data, but few studies have...

https://arxiv.org/abs/2610.21344

6 CONF

Self-Guided LLM Reasoning for Error Diagnosis in Vehicle Routing Problems

ArXiv CS.AI 50%

arXiv:2610.21393v1 Announce Type: new Abstract: Vehicle Routing Problems (VRPs) are fundamental to many real-world applications. Recent advances in large language models (LLMs) have spurred progress in solving these NP-hard problems. However, most existing approaches assume that...

https://arxiv.org/abs/2610.21393

7 CONF

Watts If? A Benchmark for Counterfactual Reasoning About the AI Data Center Buildout

ArXiv CS.AI 50%

arXiv:2610.21397v1 Announce Type: new Abstract: An AI data center is committed years before it draws a watt: a few discrete choices (grid or on-site gas, evaporative or dry cooling, which county to file in) fix its capital, water draw, and carbon path, and LLMs are now asked to...

https://arxiv.org/abs/2610.21397

8 CONF

SecureClaw: Clawing Back Control of LLM Agents

ArXiv CS.AI 50%

arXiv:2606.09549v3 Announce Type: replace-cross Abstract: Tool-using large language model (LLM) agents face two distinct security failures: unauthorized external actions and exposure of sensitive plaintext inside the runtime before any final output check can intervene. Existing...

https://arxiv.org/abs/2606.09549

9 CONF

JevAgentHarness: Benchmarking, Deploying and Training Decision Models That Share Control with LLMs

ArXiv CS.AI 50%

arXiv:2610.21412v1 Announce Type: new Abstract: Large language model (LLM) agents now fix software, operate computers and serve customers, but their harnesses, the programs that run them, call a large LLM at every step, which makes long tasks slow and costly. Most of these calls...

https://arxiv.org/abs/2610.21412

0 CONF

RICE-Alpha: Reliability-Informed Correction with Event Graphs for LLM-Agent Stock Forecasting

ArXiv CS.AI 50%

arXiv:2609.34004v2 Announce Type: cross Abstract: Equity-relevant news evolves through temporally dependent corporate events, making historical information useful only when event continuity, information availability, and transition reliability are modeled. Existing LLM-based...

https://arxiv.org/abs/2609.34004

1 CONF

Agentic-Priors: Using Large Language Models to Address the Cold Start Problem in Preference Elicitation

ArXiv CS.AI 50%

arXiv:2610.21938v1 Announce Type: cross Abstract: An agent that learns a user's preferences from their choices faces a cold start problem: before any choices are observed, it must rely solely on a prior. Informative priors are usually fitted to historical choice data, which new...

https://arxiv.org/abs/2610.21938

2 CONF

AI-Driven Disaster Response and Displacement Monitoring

ArXiv CS.AI 50%

arXiv:2610.21482v1 Announce Type: new Abstract: ARTIFICIAL INTELLIGENCE (AI) has demonstrated its potential across a wide range of humanitarian tasks, offering scalable and data-driven solutions to some of the world's most pressing challenges. For instance, in addressing climate...

https://arxiv.org/abs/2610.21482

3 CONF

ISW-Agent: Integrating LLM-Driven Dialogue with n8n Workflow for Internal Solitary Wave Remote Sensing Image Processing

ArXiv CS.AI 50%

arXiv:2610.21502v1 Announce Type: new Abstract: Internal solitary wave (ISW) remote sensing requires task parameters and spatial information to be transferred across image acquisition, detection, stripe extraction, and propagation prediction. Here, we present ISW-Agent, which...

https://arxiv.org/abs/2610.21502

4 CONF

Decomposing Brain-LLM Alignment with Interpretable Semantic Representations

ArXiv CS.AI 50%

arXiv:2610.21508v1 Announce Type: new Abstract: Large language models (LLMs) predict neural responses during naturalistic language comprehension, but the linguistic information underlying this brain alignment remains difficult to interpret. We use SCRIBE, an interpretable...

https://arxiv.org/abs/2610.21508

5 CONF

Distributionally Robust Regularization of Sparse Integer Programming Trained Learning Models

ArXiv CS.AI 50%

arXiv:2311.01994v2 Announce Type: replace-cross Abstract: Building explainable machine learning models is crucial for human users to be able to interpret the proposed statistical relationship obtained from the training data. Mixed-integer optimization formulations are often used...

https://arxiv.org/abs/2311.01994

6 CONF

CriticaLLM: Using LLMs as Autonomous Game Master for Tabletop Role-Playing Games

ArXiv CS.AI 50%

arXiv:2610.21525v1 Announce Type: new Abstract: Large Language Models (LLMs) have shown impressive capabilities across many tasks, including processing large amounts of text, following instructions, and generating ideas. This allows the use of such models in various contexts,...

https://arxiv.org/abs/2610.21525

7 CONF

Reinforcement Learning-driven Diffusion Models: Language, Vision, and Beyond

ArXiv CS.AI 50%

arXiv:2610.21539v1 Announce Type: new Abstract: Diffusion models (DMs) have steadily demonstrated outstanding performance in high-fidelity, controllable generation across diverse scenarios, following the "pretraining-finetuning" paradigm established in LLMs. Despite these...

https://arxiv.org/abs/2610.21539

8 CONF

AgentPerturb: Evaluating LLM Agent Robustness under Controlled Interaction Perturbations

ArXiv CS.AI 50%

arXiv:2610.21624v1 Announce Type: new Abstract: Real-world tasks are often complex and noisy, posing substantial challenges for LLM agents. Yet existing evaluations lack a systematic framework for jointly characterizing potential perturbation targets and types. We use this...

https://arxiv.org/abs/2610.21624

9 CONF

Learning to Read Out: Unembedding Dynamics in Language Model Pretraining

ArXiv CS.AI 50%

arXiv:2610.21025v1 Announce Type: cross Abstract: When does a language model acquire a capability? Developmental studies usually answer this by tracking when models start producing the correct token. But that prediction passes through the unembedding matrix, or readout, which is...

https://arxiv.org/abs/2610.21025

0 CONF

Interpreting Language Model Parameters

ArXiv CS.AI 50%

arXiv:2610.20748v1 Announce Type: cross Abstract: Mechanistic interpretability aims to uncover how neural networks use their parameters to implement their impressive neural algorithms. Although previous work has uncovered substantial structure in the intermediate representations...

https://arxiv.org/abs/2610.20748

1 CONF

CoWorld Reasoner: Agentic Multimodal Reasoning with the Evolving Video World Model-Driven Harness

ArXiv CS.AI 50%

arXiv:2610.21910v1 Announce Type: new Abstract: As Vision-Language Models (VLMs) advance, they are increasingly expected to perform spatiotemporal reasoning over motion, actions, and view changes beyond what the input images show. Video World Models (VWMs) provide a natural...

https://arxiv.org/abs/2610.21910

2 CONF

GraphACM: Graph-based Action Consistency Measurement for Uncertainty Quantification in LLM Agents

ArXiv CS.AI 50%

arXiv:2610.22031v1 Announce Type: new Abstract: Behavioral consistency across repeated executions provides an informative signal for assessing the reliability of large language model (LLM) agents. However, existing approaches typically summarize consistency with a single...

https://arxiv.org/abs/2610.22031

3 CONF

FAOPs: Normal Forms and an Algebra for AI Agent Workflows

ArXiv CS.AI 50%

arXiv:2610.22061v1 Announce Type: new Abstract: Organizations increasingly encode operational procedures as multi-step agent skills, here called Agent Operating Procedures (AOPs), that must be traceable, auditable, reproducible, access-controlled, and bounded in time and cost,...

https://arxiv.org/abs/2610.22061

4 CONF

One Is Not Enough: How People Use Multiple AI Models in Everyday Life

ArXiv CS.AI 50%

arXiv:2603.26107v1 Announce Type: cross Abstract: People increasingly use multiple Multimodal Large Language Models (MLLMs) concurrently, selecting each based on its perceived strengths. This cross-platform practice creates coordination challenges: adapting prompts to different...

https://arxiv.org/abs/2603.26107

5 CONF

CART: Compatible Routing for Multimodal Continual Instruction Tuning

ArXiv CS.AI 50%

arXiv:2610.22137v1 Announce Type: new Abstract: Multimodal Large Language Models (MLLMs) achieve strong performance through instruction tuning, yet real-world applications often require them to continually acquire new capabilities from sequential tasks, i.e., Multimodal...

https://arxiv.org/abs/2610.22137

6 CONF

Retrieved but Not Read: Understanding Why Search-Augmented LLMs Fail to Use Available Evidence

ArXiv CS.AI 50%

arXiv:2610.21731v1 Announce Type: cross Abstract: Web search allows LLMs to access up-to-date information, but it remains unclear why they sometimes produce outdated answers even when relevant evidence is available. To study this problem, we construct temporal facts whose values...

https://arxiv.org/abs/2610.21731

7 CONF

Are You Sure Your LLM Is Sure? Repairing and Auditing Confidence

ArXiv CS.AI 50%

arXiv:2610.22139v1 Announce Type: new Abstract: Confidence scores determine whether an LLM answer is accepted, reviewed, or regenerated, yet scalar recalibration can only correct errors visible through the score itself. We introduce RADAR (Repair, Adopt, and Diagnose After...

https://arxiv.org/abs/2610.22139

8 CONF

RAG-RST: Retrieved Exemplars as In-Context Discourse Schema for RST Parsing

ArXiv CS.AI 50%

arXiv:2610.22150v1 Announce Type: new Abstract: In Rhetorical Structure Theory (RST), each edge of a discourse tree carries a nuclearity label, marking which span holds the central content, and a relation drawn from a closed inventory of functional categories. Neither label is a...

https://arxiv.org/abs/2610.22150

9 CONF

Multi-sourced AI Tutor for Non-Native English Speaker Students

ArXiv CS.AI 50%

arXiv:2610.22163v1 Announce Type: new Abstract: Large language models (LLMs) are increasingly being adopted as teaching tools in computing education, particularly for developing AI tutors capable of answering student questions. With the rise in enrollment of international...

https://arxiv.org/abs/2610.22163

0 CONF

AutoSFT: An Agentic System for Automated Data Research in Supervised Fine-Tuning

ArXiv CS.AI 50%

arXiv:2610.22194v1 Announce Type: new Abstract: Language model agents increasingly automate post-training, but when given the full training stack they converge on supervised fine-tuning and spend most effort revising training data. Existing systems give the agent one kind of...

https://arxiv.org/abs/2610.22194

1 CONF

X-RIC: An Agentic RAN-Intelligent Controller Benchmark for Enhancing Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.22269v1 Announce Type: new Abstract: The O-RAN ALLIANCE introduces architectural flexibility through disaggregation and AI-driven control. While the RAN Intelligent Controller (RIC) enables centralized optimization, current AI approaches lack reasoning capabilities...

https://arxiv.org/abs/2610.22269

2 CONF

LEASH: Uncertainty-Aware Weak-to-Strong Escalation and Oversight for Computer-Use Agents

ArXiv CS.AI 50%

arXiv:2610.22280v1 Announce Type: new Abstract: Computer-use agents increasingly tackle long-horizon tasks, where running a frontier model at every step is expensive and a small open-weight model alone often fails. Weak-to-strong escalation offers a middle ground where a weak...

https://arxiv.org/abs/2610.22280

3 CONF

EliteReplay: Preserving Diverse Solutions in RL Post-Training via Quality-Diversity Search

ArXiv CS.AI 50%

arXiv:2610.22290v1 Announce Type: new Abstract: Reinforcement learning has become a common post-training technique to improve the accuracy of LLMs on verifiable tasks. However, such training can narrow the set of solutions the model can produce. Several approaches have attempted...

https://arxiv.org/abs/2610.22290

4 CONF

Evaluation Awareness Beyond English: Do LLMs Act Differently When Tested in Indic Languages?

ArXiv CS.AI 50%

arXiv:2610.22333v1 Announce Type: new Abstract: Large language models (LLMs) can often tell when they are being tested. This ability, known as evaluation awareness, can lead models to act more cautiously during safety evaluations than in real use. Existing work has studied...

https://arxiv.org/abs/2610.22333

5 CONF

FDE-Gym: The Last Mile of AI Delivery

ArXiv CS.AI 50%

arXiv:2610.22350v1 Announce Type: new Abstract: Existing agent benchmarks typically evaluate agents on well-specified tasks defined by issue reports, specifications, or task tickets. Real-world customer delivery is different: forward-deployed engineers (FDEs) must clarify...

https://arxiv.org/abs/2610.22350

6 CONF

Truth for Believable AI: Expressed Doubt, Provenance, and Belief Revision as an Engineerable Stance

ArXiv CS.AI 50%

arXiv:2609.26035v1 Announce Type: cross Abstract: Conversational agents often express answers in a uniformly confident register. We test whether expressed uncertainty, provenance-aware assertion, and explicit belief revision can be implemented as a behavior layer over a fixed...

https://arxiv.org/abs/2609.26035

7 CONF

Self-improving data synthesis enables scalable adaptation of embedding models

ArXiv CS.AI 50%

arXiv:2610.14730v2 Announce Type: replace-cross Abstract: AI agents require specialised retrieval across domains and tasks, but adapting embedding models is constrained by costly manual training-data design. Here we introduce SYNTRA, a self-improving agentic framework that turns...

https://arxiv.org/abs/2610.14730

8 CONF

Open Benchmark of AI Impact on Humans (ImpactBench): an expert-guided, open platform for the holistic evaluation of AI impact on humans

ArXiv CS.AI 50%

arXiv:2610.20690v1 Announce Type: cross Abstract: The present work is concerned with how to measure, at scale, the multi-dimensional impact of generative AI models on the individuals who use them. In service of this goal, we introduce the Open Benchmark of AI Impact on Humans,...

https://arxiv.org/abs/2610.20690

9 CONF

INFUSE: A Unified Surface Benchmark for Indirect Prompt Injection in Agentic Systems

ArXiv CS.AI 50%

arXiv:2610.20776v1 Announce Type: cross Abstract: LLM-based agents increasingly execute long-horizon, end-to-end workflows involving shell commands, code modification, dependency installation, and interaction with remote services. This growing autonomy expands their exposure to...

https://arxiv.org/abs/2610.20776

0 CONF

Following Delegation Traces to Study Human Oversight in Interaction with Multimodal AI

ArXiv CS.AI 50%

arXiv:2610.21948v1 Announce Type: cross Abstract: As multimodal AI systems are becoming our everyday thought partners, the shift towards studying how users transfer control to these systems becomes especially urgent. In this paper, we report an overview of findings from an...

https://arxiv.org/abs/2610.21948

1 CONF

Forecast lead time and the timing of crew deployment for weather-driven power outages using AI weather models

ArXiv CS.AI 50%

arXiv:2610.20918v1 Announce Type: cross Abstract: Utilities request mutual aid crews to restore power after severe storms, and requesting early secures more crews but relies on less accurate forecasts. We examined how forecast lead time affects the value of outage predictions...

https://arxiv.org/abs/2610.20918

2 CONF

How to Train Your Little Dragon: Teaching a Small Language Model to Construct and Refine GPU Optimization Scripts

ArXiv CS.AI 50%

arXiv:2610.20980v1 Announce Type: cross Abstract: Compiler transformations interact, making GPU kernel optimization a search for combinations that preserve the computation while improving performance. We introduce HOW TO TRAIN YOUR LITTLE DRAGON, a training method that teaches a...

https://arxiv.org/abs/2610.20980

3 CONF

EigDiff: Eigensample Diffusion - or how to significantly reduce training dataset size with marginal performance variation?

ArXiv CS.AI 50%

arXiv:2610.20999v1 Announce Type: cross Abstract: Diffusion models are notoriously expensive to train, requiring large-scale datasets to learn how to gradually reverse the noise from images over multiple small denoising steps. Current approaches focus on distilling the number of...

https://arxiv.org/abs/2610.20999

4 CONF

PremiseCheck: Efficient Fact-Checking of Human and AI Peer Reviews

ArXiv CS.AI 50%

arXiv:2610.21046v1 Announce Type: cross Abstract: Peer review is under strain from the growth of submissions, and review comments written by humans or AI can misstate what a paper says. We introduce ReviewFact, a benchmark that labels such factual errors in review comments under...

https://arxiv.org/abs/2610.21046

5 CONF

SSR: Structural Signal Retriever for Scalable Agent Discovery in LLM-Orchestrated Multi-Agent Systems

ArXiv CS.AI 50%

arXiv:2610.21113v1 Announce Type: cross Abstract: Large-scale multi-agent ecosystems require mechanisms for discovering suitable agents without exposing entire registries to a large language model (LLM) orchestrator. The challenge is not only to retrieve relevant Agent Cards...

https://arxiv.org/abs/2610.21113

6 CONF

Stronger Judges Do Not See More: Deployment-Integrity Blindness in LLM Evaluation

ArXiv CS.AI 50%

arXiv:2610.21135v1 Announce Type: cross Abstract: LLM-agent evaluation reports behavioral scores but leaves the identity of the deployed runtime stack unreported. A tampered deployment that preserves evaluated outputs passes every output-only evaluator. We introduce DIB-Bench, a...

https://arxiv.org/abs/2610.21135

7 CONF

OnBodyAI - Why the Next AI Needs a Body

ArXiv CS.AI 50%

arXiv:2610.21137v1 Announce Type: cross Abstract: The next AI will not win by knowing more about the world. It will win because it knows you: because it lives on your body, works for you and answers to you. That is what the term OnBodyAI stands for. It describes what happens...

https://arxiv.org/abs/2610.21137

8 CONF

When is a better LLM worth paying for? Stochastic Optimization with Switching Mixed-Fidelity Oracles

ArXiv CS.AI 50%

arXiv:2610.21139v1 Announce Type: cross Abstract: Large language models (LLMs) are increasingly used upstream of decision-making to clean data, detect label errors, and reconstruct missing values. Yet LLM-assisted data curation creates a new operational tradeoff: higher-fidelity...

https://arxiv.org/abs/2610.21139

9 CONF

CARE-SD: Explainable Reasoning Architecture for Local SLM Self-Disclosure Analysis in Textual Data

ArXiv CS.AI 50%

arXiv:2610.21151v1 Announce Type: cross Abstract: Cybersecurity interviews uncover critical security experiences, behaviors, and privacy concerns often not fully captured by conventional technical assessments. Consequently, identifying genuine self-disclosures is challenging...

https://arxiv.org/abs/2610.21151

0 CONF

Language Models Share a Readout Bottleneck in Working Memory

ArXiv CS.AI 50%

arXiv:2610.21176v1 Announce Type: cross Abstract: Large language models (LLMs) reproduce a human working-memory signature on the N-back task: performance declines as memory load N increases, and errors concentrate on lures, items that repeat the current stimulus at a neighboring...

https://arxiv.org/abs/2610.21176

1 CONF

FedSumUp: User-Auditable Privacy-Aware Representation Sharing for Resource-Constrained Federated Intelligence

ArXiv CS.AI 50%

arXiv:2610.21194v1 Announce Type: cross Abstract: Existing federated data condensation methods face privacy risks, as uploaded synthetic data may preserve sensitive information and remain vulnerable to reconstruction attacks. Moreover, their generation often incurs considerable...

https://arxiv.org/abs/2610.21194

2 CONF

What do AI chatbots do after users decline therapeutic redirection for suicide thoughts?

ArXiv CS.AI 50%

arXiv:2610.21253v1 Announce Type: cross Abstract: Safety evaluations of artificial intelligence (AI) chatbots focus on therapeutic redirection, statements urging users who disclose suicide thoughts to seek help from crisis lines or other human sources. How chatbots respond when...

https://arxiv.org/abs/2610.21253

3 CONF

Fractional Power-of-Two Quantization for Efficient and Effective Multiplier-Free LLM Inference

ArXiv CS.AI 50%

arXiv:2610.21257v1 Announce Type: cross Abstract: Large Language Models (LLMs) demand efficient inference, where the multiply-accumulate (MAC) operations in linear projections dominate compute and energy cost. Post-training quantization (PTQ) reduces this cost by mapping weights...

https://arxiv.org/abs/2610.21257

4 CONF

TRACER: A Multimodal Harness for Patient Care in Hospitals

ArXiv CS.AI 50%

arXiv:2610.21266v1 Announce Type: cross Abstract: Continuous video and clinical records provide complementary information for understanding how patient behavior evolves over a hospital stay. A central challenge is how to represent behavior across the entire stay while preserving...

https://arxiv.org/abs/2610.21266

5 CONF

Memorilla: Latent Semantic Memory for LLMs

ArXiv CS.AI 50%

arXiv:2610.21375v1 Announce Type: cross Abstract: Memory enables large language models (LLMs) to use information beyond their parameters, such as past user conversations, long documents, or an agent's earlier actions. For a frozen LLM, access to this accumulated knowledge is...

https://arxiv.org/abs/2610.21375

6 CONF

Can LLMs Tell Stories Out of Order? A Corpus and Benchmark for Nonlinear Narrative Generation

ArXiv CS.AI 50%

arXiv:2610.21468v1 Announce Type: cross Abstract: Every story has two orders: the order in which its events happen and the order in which they are told. A story is nonlinear when the two differ. We introduce a benchmark of 83 published works that measures whether language models...

https://arxiv.org/abs/2610.21468

7 CONF

When Is Muon Optimal? Radial Fragility and Minimax Geometry

ArXiv CS.AI 50%

arXiv:2610.21549v1 Announce Type: cross Abstract: Muon replaces a matrix gradient by an approximate polar factor and has shown strong empirical performance in neural-network training. The Isotropic Curvature Model (ICM) provides a curvature-based explanation for this update by...

https://arxiv.org/abs/2610.21549

8 CONF

Product Interaction: An Algebraic Formalism for Deep Learning Architectures

ArXiv CS.AI 50%

arXiv:2602.02573v2 Announce Type: replace-cross Abstract: Modern neural architectures are largely developed as distinct empirical constructions, despite recurring principles across convolutional, attention, state-space, and equivariant models. We introduce Product Interactions,...

https://arxiv.org/abs/2602.02573

9 CONF

When Does Muon Actually Win? A Paired Data-, Time-, and Tuning-Budget Benchmark

ArXiv CS.AI 50%

arXiv:2610.21555v1 Announce Type: cross Abstract: Muon's gains in data efficiency motivate evaluating its performance under explicit data, time, and tuning budgets. On a single A100 GPU, we compare a reference single-device Muon implementation with AdamW across 17.7M- and...

https://arxiv.org/abs/2610.21555

00 CONF

BiShield-TEE: On the (In-)Security of Unilateral Weight Obfuscation in On-Device TEE-Shielded LLM Partition

ArXiv CS.AI 50%

arXiv:2610.21565v1 Announce Type: cross Abstract: On-device deployment of large language models (LLMs) is increasingly adopted due to latency and privacy requirements, but exposes proprietary models to reverse engineering and intellectual property theft. Trusted Execution...

https://arxiv.org/abs/2610.21565

01 CONF

Independent Data-Integrity Verification for LLM-Driven Functional Coverage Closure in Hardware Design

ArXiv CS.AI 50%

arXiv:2610.21570v1 Announce Type: cross Abstract: LLM agents can write directed tests that close functional coverage, but coverage only shows that a state was reached, not that the data on the way there was correct. This is a long-known point in verification and we do not claim...

https://arxiv.org/abs/2610.21570

02 CONF

Decoding What iOS Location Services Send to Apple: An LLM Is an Unreliable Analyst but a Useful Toolmaker

ArXiv CS.AI 50%

arXiv:2610.21597v1 Announce Type: cross Abstract: Reverse engineering the data formats used by mobile software is skilled and slow, and using AI to assist with it is attractive. We evaluate this for the protobuf messages that an iPhone sends to Apple's location services. Working...

https://arxiv.org/abs/2610.21597

03 CONF

Human Interventions as Labels: Localizing, Steering, and (Sometimes) Editing the Computations Behind LLM Agent Failures

ArXiv CS.AI 50%

arXiv:2610.21708v1 Announce Type: cross Abstract: When an LLM agent misbehaves, a human steps in, and that intervention is usually discarded or replayed as training data. We treat it instead as a measurement: a label pointing at the internal computation that failed. We study it...

https://arxiv.org/abs/2610.21708

04 CONF

Encoded but Exposed: Language Embeddings can Reveal More Than They Should in Recommender Systems

ArXiv CS.AI 50%

arXiv:2610.21713v1 Announce Type: cross Abstract: Language embeddings are increasingly used in recommenders to represent item content, but their privacy risks remain poorly understood. We study whether item embeddings can reveal item identities when an adversary has access to...

https://arxiv.org/abs/2610.21713

05 CONF

DINO-FIL: Multi-Layer Transformer Fusion for Generative Inpainting Forgery Localization

ArXiv CS.AI 50%

arXiv:2610.21780v1 Announce Type: cross Abstract: We propose DINO-FIL, a transformer-based framework for pixel-level localization of generative image forgeries. The method leverages multi-layer representations from a pretrained DINOv3 ViT-H+/16 encoder combined with a...

https://arxiv.org/abs/2610.21780

06 CONF

In the Guise of Correction: How Framing and Cultural Adaptation Erode LLM Safety on Real-World Criminal Cases

ArXiv CS.AI 50%

arXiv:2610.21789v1 Announce Type: cross Abstract: Existing safety benchmarks rely largely on synthetic prompts with loosely grounded taxonomies and offer little focused analysis of severe crime categories. We introduce GUISE, a benchmark of criminal-assistance scenarios sourced...

https://arxiv.org/abs/2610.21789

07 CONF

Provably Efficient Risk-Sensitive Offline Reinforcement Learning via Optimized Certainty Equivalents

ArXiv CS.AI 50%

arXiv:2610.21870v1 Announce Type: cross Abstract: Risk-sensitive reinforcement learning (RL) addresses decision-making under uncertainty and adverse outcomes. Learning risk-sensitive policies from fixed datasets is important when additional interaction with the environment is...

https://arxiv.org/abs/2610.21870

08 CONF

Why Shallow Neural Networks Learn Sinusoidal Components First: An Orthogonal Polynomial Dynamics Framework

ArXiv CS.AI 50%

arXiv:2610.21964v1 Announce Type: cross Abstract: Neural networks often learn low-frequency components before high-frequency ones --- a phenomenon called spectral bias or termed F-principle. Many numerical studies have demonstrated this phenomenon, and theoretical studies have...

https://arxiv.org/abs/2610.21964

09 CONF

Time to Fake It: Continual Machine Learning Intensifies Unfairness in Deepfake Detection

ArXiv CS.AI 50%

arXiv:2610.21974v1 Announce Type: cross Abstract: Deepfake detectors safeguard against misinformation, rendering their failures as much a societal as a technical concern. As generators constantly evolve, detectors trained on static datasets miss newly arising threats, while...

https://arxiv.org/abs/2610.21974

10 CONF

Priming Base Models for Agentic Post-Training: An Open Midtraining Recipe

ArXiv CS.AI 50%

arXiv:2610.22019v1 Announce Type: cross Abstract: Frontier models, general-purpose and domain-specific alike, now include a midtraining stage between pretraining and post-training, but little has been published about how this stage is built. We present an open midtraining recipe...

https://arxiv.org/abs/2610.22019

11 CONF

Momentum, Commentary Tone, and Earnings Surprise in LLM Financial Forecasts

ArXiv CS.AI 50%

arXiv:2610.22043v1 Announce Type: cross Abstract: Which inputs drive a language model's financial forecast? We construct synthetic earnings announcements that independently reverse 20-day momentum, non-informational commentary tone, and whether fixed actual EPS beats a...

https://arxiv.org/abs/2610.22043

12 CONF

Decoding Naturalistic Speech from fMRI with Temporal Modeling and Multimodal Alignment

ArXiv CS.AI 50%

arXiv:2610.22049v1 Announce Type: cross Abstract: Reconstructing what a person perceives from their brain activity is a stringent test of whether neural recordings carry meaningful information. Naturalistic speech offers a rich testbed for this challenge: it unfolds over...

https://arxiv.org/abs/2610.22049

13 CONF

Change the Number, Change the Answer: Assessing Rating Scale Sensitivity in LLM-Based Text Scoring

ArXiv CS.AI 50%

arXiv:2610.22187v1 Announce Type: cross Abstract: Large language models (LLMs) are increasingly used in computational social science to assign scalar scores to social and psychological constructs. However, studies use different rating scales, and whether their scores remain...

https://arxiv.org/abs/2610.22187

14 CONF

Decentralized LLM Workflows via Sequential Auctions

ArXiv CS.AI 50%

arXiv:2610.22201v1 Announce Type: cross Abstract: We present a scalable framework for solving multi-step tasks through a decentralized market of self-interested agents. Prior theoretical work demonstrated that agents organized through sequential auctions can converge to a...

https://arxiv.org/abs/2610.22201

15 CONF

Librarian Agents: Training LLMs to Curate Long-Context Workspaces that Anticipate Future Queries

ArXiv CS.AI 50%

arXiv:2610.22273v1 Announce Type: cross Abstract: Reasoning over long document contexts remains a challenge for large language models (LLMs). Standard retrieval methods are inherently reactive, bottlenecking agents with complex, cross-document reasoning at inference time, while...

https://arxiv.org/abs/2610.22273

16 CONF

AI Consilium: a Benchmark of LLM Clinical Multidisciplinary Second Opinions

ArXiv CS.AI 50%

arXiv:2610.22298v1 Announce Type: cross Abstract: Large language models (LLMs) can generate differential diagnoses for complex cases, but a useful second opinion must also be factually grounded, clinically coherent, actionable, and safe. We developed a multidimensional benchmark...

https://arxiv.org/abs/2610.22298

17 CONF

Knowledge That Is Linear Before Fine-Tuning Generalizes After It

ArXiv CS.AI 50%

arXiv:2610.22300v1 Announce Type: cross Abstract: Not all facts a language model can recall support further learning equally well. We distinguish active facts, which support generalization beyond their own recall, from inert facts, which can be recalled but do not support such...

https://arxiv.org/abs/2610.22300

18 CONF

LIBERO-Industry: Benchmarking Robotic Manipulation under Industrial Process Constraints

ArXiv CS.AI 50%

arXiv:2610.16782v2 Announce Type: replace Abstract: Industrial manipulation in flexible manufacturing, e.g., high-mix, low-volume (HMLV) electronics assembly, requires robot policies to adapt to changing products and production conditions. Such settings impose industrial process...

https://arxiv.org/abs/2610.16782

19 CONF

Agent Skill Framework: Perspectives on the Potential of Small to Medium Language Models in Industrial Environments

ArXiv CS.AI 50%

arXiv:2602.16653v4 Announce Type: replace Abstract: Skills are getting increasingly used in recent agentic frameworks, performing robustly with proprietary LLMs. Yet, their effectiveness for small and medium-sized open-source models (270M--80B) remains underexplored, especially...

https://arxiv.org/abs/2602.16653

20 CONF

LLM-as-an-Investigator: Evidence-First Agentic Reasoning for Robust Interactive Problem Diagnosis

ArXiv CS.AI 50%

arXiv:2606.13220v2 Announce Type: replace Abstract: Large language models (LLMs) are used for technical troubleshooting, where problem descriptions are often incomplete and multiple causes can explain the same symptoms. Effective diagnosis requires acquiring discriminative...

https://arxiv.org/abs/2606.13220

21 CONF

Mind the Delay: Latency-aware Query Routing for Heterogeneous LLM pools

ArXiv CS.AI 50%

arXiv:2607.18253v2 Announce Type: replace Abstract: Large language model (LLM) query routers typically assign each query to a suitable model that balances response accuracy and monetary cost. Subsequently, separate system-level load balancers based on policies such as...

https://arxiv.org/abs/2607.18253

22 CONF

T-GADE: Thermodynamical Generative-AI-Driven Evolution of LLM Artifacts

ArXiv CS.AI 50%

arXiv:2609.12286v2 Announce Type: replace Abstract: Introducing large language models (LLMs) into evolutionary computation enables semantic generation of candidates, but the classical problem of maintaining population diversity remains. Inspired by the thermodynamical genetic...

https://arxiv.org/abs/2609.12286

23 CONF

Asynchrony Is Nearly Free for Evolution Strategies on Long-Horizon LLM Agentic Tasks

ArXiv CS.AI 50%

arXiv:2610.04196v2 Announce Type: replace Abstract: Synchronous policy updates can limit the efficiency of post-training for long-horizon LLM agents. When trajectories span multiple interaction turns, completion times can vary substantially, and synchronous update barriers leave...

https://arxiv.org/abs/2610.04196

24 CONF

SCOPE: Certified Theorem Proving with a Language Model as the Policy Planner

ArXiv CS.AI 50%

arXiv:2610.08319v2 Announce Type: replace Abstract: In proof assistants such as Lean, a generated proof must pass machine compilation checks, so evaluation needs no human scoring. Direct generation fails on multi-step numeric propositions: a proof is valid only if every content...

https://arxiv.org/abs/2610.08319

25 CONF

What Coding Agents Leave Unsaid: Measuring Task-State Gaps Between Execution and Reports

ArXiv CS.AI 50%

arXiv:2610.20003v2 Announce Type: replace Abstract: Human supervisors rely on coding agents' reports to assess progress, verify repairs, and decide when to intervene. But a supervisor cannot investigate a failure they were never told occurred. Failed attempts, workarounds, and...

https://arxiv.org/abs/2610.20003

26 CONF

STAMP: Symmetric Temporal Averaging Message Passing for Domain Adaptation in Chronologically Split Graphs

ArXiv CS.AI 50%

arXiv:2411.10957v2 Announce Type: replace-cross Abstract: This paper addresses domain adaptation in graph-structured data under chronological splits. We consider transductive semi-supervised node classification (SSNC), in which labels of historical nodes are used to predict...

https://arxiv.org/abs/2411.10957

27 CONF

PanoDiff-SR: Synthesizing Dental Panoramic Radiographs using Diffusion and Super-resolution

ArXiv CS.AI 50%

arXiv:2507.09227v2 Announce Type: replace-cross Abstract: Interest in generating realistic synthetic medical images has grown in recent years. Such datasets can mitigate the scarcity of public data for artificial intelligence research and support education. Work on synthesizing...

https://arxiv.org/abs/2507.09227

28 CONF

Adaptive Duration Model for Text Speech Alignment

ArXiv CS.AI 50%

arXiv:2507.22612v3 Announce Type: replace-cross Abstract: Speech-to-text alignment is a critical component of neural text to speech (TTS) models. Autoregressive TTS models typically use an attention mechanism to learn these alignments on-line, while non-autoregressive end to end...

https://arxiv.org/abs/2507.22612

29 CONF

UniFGVC: Universal Training-Free Few-Shot Fine-Grained Vision Classification via Attribute-Aware Multimodal Retrieval

ArXiv CS.AI 50%

arXiv:2508.04136v4 Announce Type: replace-cross Abstract: Few-shot fine-grained visual classification (FGVC) aims to discriminate between subtly different categories with very limited data. While Multimodal Large Language Models (MLLM) exhibit strong capabilities in both...

https://arxiv.org/abs/2508.04136

30 CONF

Multi-task Neural Diffusion Processes

ArXiv CS.AI 50%

arXiv:2510.03419v3 Announce Type: replace-cross Abstract: Neural diffusion processes provide a scalable, non-Gaussian approach to modelling distributions over functions, but existing formulations are limited to single-task inference and do not capture dependencies across related...

https://arxiv.org/abs/2510.03419

31 CONF

RAG4Tickets: AI-Powered Ticket Resolution via Retrieval-Augmented Generation on JIRA and GitHub Data

ArXiv CS.AI 50%

arXiv:2510.08667v3 Announce Type: replace-cross Abstract: Modern software teams frequently encounter delays in resolving recurring or related issues due to fragmented knowledge scattered across JIRA tickets, developer discussions, and GitHub pull requests (PRs). To address this...

https://arxiv.org/abs/2510.08667

32 CONF

Scientific feedback reveals productive regimes beyond training conventions

ArXiv CS.AI 50%

arXiv:2512.15756v2 Announce Type: replace-cross Abstract: Human-imposed design conventions can restrict the alternatives represented in scientific training data and shape the search preferences learned by generative models. We show that scientific performance feedback can...

https://arxiv.org/abs/2512.15756

33 CONF

Benchmarking Code LLM-as-a-Judge via Constrained Perturbation and Calibration

ArXiv CS.AI 50%

arXiv:2512.20159v2 Announce Type: replace-cross Abstract: Code from LLM-assisted development may contain defects like API hallucinations, motivating the development of code evaluation metrics to assess such code before deployment. As conventional rule-based metrics merely score...

https://arxiv.org/abs/2512.20159

34 CONF

Orchestrating LLM Agents for Scientific Research: A Pilot Study of Multiple Choice Question (MCQ) Generation and Evaluation

ArXiv CS.AI 50%

arXiv:2602.18891v2 Announce Type: replace-cross Abstract: Advances in large language models (LLMs) are rapidly transforming scientific work, yet empirical evidence on how these systems reshape research activities remains limited. We report a mixed-methods pilot evaluation of an...

https://arxiv.org/abs/2602.18891

35 CONF

TensorDex: A Compact, Tensor-Centric Storage System for Modern AI Models

ArXiv CS.AI 50%

arXiv:2604.17104v3 Announce Type: replace-cross Abstract: Modern model hubs store hundreds of petabytes of large language models (LLMs), with fine-tuned variants dominating the storage footprint. These variants contain substantial cross-model redundancy that delta compression...

https://arxiv.org/abs/2604.17104

36 CONF

ChaosBench-Logic v2: Evaluating LLM Logical Reasoning over Dynamical Systems at Scale

ArXiv CS.AI 50%

arXiv:2605.24305v2 Announce Type: replace-cross Abstract: Standard accuracy on binary reasoning benchmarks hides critical failure modes: prior collapse, inconsistency under paraphrase, and inability to reason about parameter-dependent dynamics. We present ChaosBench-Logic v2, a...

https://arxiv.org/abs/2605.24305

37 CONF

Moment-Video: Diagnosing Temporal Fidelity of Video MLLMs on Momentary Visual Events

ArXiv CS.AI 50%

arXiv:2606.02522v2 Announce Type: replace-cross Abstract: Video multimodal large language models (MLLMs) have made rapid progress in general and long-form video understanding, yet their ability to capture and use brief, answer-critical visual evidence remains underexplored....

https://arxiv.org/abs/2606.02522

38 CONF

Rethinking Calibration for High-Sparsity LLM Pruning: From Single Sources to Capability Coverage

ArXiv CS.AI 50%

arXiv:2606.03328v4 Announce Type: replace-cross Abstract: Post-training LLM pruning relies on a small calibration set, usually chosen heuristically and judged by WikiText perplexity or by mean accuracy on general-domain commonsense benchmarks. This single-axis view hides...

https://arxiv.org/abs/2606.03328

39 CONF

Hitting a Moving Target: Test-Time Adaptation for AI Text Detection under Continual Distribution Shift

ArXiv CS.AI 50%

arXiv:2606.25152v2 Announce Type: replace-cross Abstract: Deployed AI text detection approaches are supervised, relying on training-time access to labeled datasets of both human-written and AI-generated text. This approach is vulnerable to three types of distribution shifts that...

https://arxiv.org/abs/2606.25152

40 CONF

From Signals to Transfer: A Factorised Study of Probe-Based Uncertainty Estimation in Large Language Models

ArXiv CS.AI 50%

arXiv:2606.27679v2 Announce Type: replace-cross Abstract: Probe-based uncertainty estimation (UE) has emerged as a prominent approach to detect hallucinations in Large Language Models (LLMs) by learning uncertainty from internal model signals. Yet, recent methods vary...

https://arxiv.org/abs/2606.27679

41 CONF

Retrieval Over Training: Similarity search-based Model Selection for Time Series Anomaly Detection

ArXiv CS.AI 50%

arXiv:2610.20243v2 Announce Type: replace-cross Abstract: Anomaly detection is a fundamental task for time-series analytics, with important implications for the downstream performance of many applications. Despite the large number of anomaly detection methods proposed in the...

https://arxiv.org/abs/2610.20243

42 CONF

Right Answer, Wrong Tokens: Tail-Aware Credit Calibration for RLVR

ArXiv CS.AI 50%

arXiv:2607.07976v2 Announce Type: replace-cross Abstract: Although reinforcement learning (RL) improves the reasoning capabilities of large language models (LLMs), GRPO-style methods can suffer from a positive-credit contamination failure mode. Specifically, uniform credit...

https://arxiv.org/abs/2607.07976

43 CONF

Amplitude-Only FFN Intervention for Tool-Structured LLM Inference: Method, Gated Evaluation Protocol, and Cross-Model Empirical Results

ArXiv CS.AI 50%

arXiv:2607.11183v4 Announce Type: replace-cross Abstract: We study Amplitude Gating (AG), an inference-time intervention that masks feed-forward network (FFN) activation coordinates while keeping pretrained weights fixed. Six SwiGLU sites separate shared and gate-only inputs,...

https://arxiv.org/abs/2607.11183

44 CONF

Don't Regenerate, Debug: A Domain-Specific Agent for Repairing Near-Miss Accelerator Kernels

ArXiv CS.AI 50%

arXiv:2608.02712v2 Announce Type: replace-cross Abstract: Kernel generation for hardware accelerators such as GPUs and NPUs has become a proving ground for large language models (LLMs), and state-of-the-art systems raise correctness through pipelines that couple LLMs with...

https://arxiv.org/abs/2608.02712

45 CONF

ValueFormer: Stage-Aware Value Labels for Online Failure Detection and VLA Post-Training

ArXiv CS.AI 50%

arXiv:2608.02958v2 Announce Type: replace-cross Abstract: Generalist vision-language-action (VLA) policies now transfer to new scenes with little task-specific training, but they still fail silently: from the action stream alone, a collapsing rollout looks much like one making...

https://arxiv.org/abs/2608.02958

46 CONF

ICON decomposition: Multivariate concept auditing reveals shortcuts that neural networks rely on

ArXiv CS.AI 50%

arXiv:2608.26083v4 Announce Type: replace-cross Abstract: Deep neural networks often exploit spurious associations, a failure known as shortcut learning. Before deployment, models should therefore be audited for reliance on concepts such as acquisition artifacts and patient...

https://arxiv.org/abs/2608.26083

47 CONF

D-DOIT: Training-free Adaptation of Discrete Diffusion via Doob's h-Transform

ArXiv CS.AI 50%

arXiv:2610.04938v2 Announce Type: replace-cross Abstract: We propose D-DOIT (Discrete Doob-Oriented Inference-time Transformation), a training-free and efficient adaptation method for discrete diffusion models with generic rewards. D-DOIT formulates adaptation as sampling from a...

https://arxiv.org/abs/2610.04938

48 CONF

LASER: Latent Space Adjoint Matching for Support-Constrained Entropy-Regularized Offline RL

ArXiv CS.AI 50%

arXiv:2610.08989v2 Announce Type: replace-cross Abstract: While offline reinforcement learning (RL) enables policy optimization from static datasets without costly online interaction, it remains bottlenecked by the risk of executing out-of-distribution (OOD) actions. Recent...

https://arxiv.org/abs/2610.08989

49 CONF

EV-JEPA: Elastic V-JEPA for Any Device and Cross-Device Inference

ArXiv CS.AI 50%

arXiv:2610.14324v2 Announce Type: replace-cross Abstract: Foundation models like V-JEPA are increasingly deployed across a heterogeneous edge-cloud continuum spanning smart glasses, phones, robots, and servers. Yet, they are typically trained as rigid, fixed-capacity networks...

https://arxiv.org/abs/2610.14324

50 CONF

Why Do Agent Teams Fail Across Boundaries? A Failure Taxonomy for Agent-to-Agent Systems with Private States

ArXiv CS.AI 50%

arXiv:2610.19342v2 Announce Type: replace-cross Abstract: Agents are increasingly interacting with other agents that act for different principals (people or organizations on whose behalf they work), such as a buyer's personal agent negotiating with an enterprise's seller agent....

https://arxiv.org/abs/2610.19342