NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

28 October 2026

151 verified · 267 raw · 5 sources

151	4	147	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	129	Media
TechCrunch AI	12	Media
The Verge AI	7	Media
HackerNews	5	Community
MIT Tech Review	2	Media

VERIFIED INTELLIGENCE — 4 stories

VERI

Anthropic’s elaborate plan to keep Wall Street at bay

The Verge AI +1 source 80%

Anthropic wants to have it both ways. With its impending IPO, it wants to tap the vast riches of the public markets and insists it doesn't want to compromise its core mission of developing AI safely and for the benefit of humanity. But greater model capabilities bring greater...

https://www.theverge.com/ai-artificial-intelligence/1019470/anthropic-ipo-resist-invest...

VERI

The uneven rise of AI-generated web content

ArXiv CS.AI +1 source 80%

arXiv:2610.36631v1 Announce Type: new Abstract: In less than five years, generative artificial intelligence (AI) has dramatically reshaped the public-facing web. Using a sample of more than 5 million crawlable webpages, we demonstrate that the share containing AI-generated text...

https://arxiv.org/abs/2610.36631

VERI

Concordat: Typed Sessions for LLM Agents

ArXiv CS.AI +1 source 80%

arXiv:2610.37461v1 Announce Type: new Abstract: Agents built on large language models are increasingly allowed to take consequential actions: cancelling bookings, issuing refunds, changing accounts. The rules that govern those actions, such as "obtain the customer's explicit...

https://arxiv.org/abs/2610.37461

VERI

UnityBench-Mini3D: Evaluating LLM Agents for 3D Game Development in Unity

ArXiv CS.AI +1 source 80%

arXiv:2610.35980v1 Announce Type: cross Abstract: Game development stresses coding agents in ways general software engineering does not: correctness depends on how engine APIs, serialized scene state, and runtime behavior interact, not on source code alone. Existing benchmarks...

https://arxiv.org/abs/2610.35980

CONFIRMED SIGNALS — 147 stories

CONF

Show HN: RainbowSay – Learn, teach, research languages live with shows you love

HackerNews 50% HN 12

No summary — see link for full article.

https://rainbowsay.ai/

CONF

Show HN: The New Way to Make AI UGC Ads in 2026

HackerNews 50% HN 7

In today’s digital marketplace, video content dictates ad performance and search rankings. However, traditional video production is slow, expensive, and difficult to scale. AivideosUGC solves this bottleneck. As a leading AI-powered UGC creation platform, AivideosUGC Turn...

https://www.aivideosugc.com/ai-video-generation

CONF

Show HN: Freightfloor. Have 3 minutes? Drive a forklift vs. AI

HackerNews 50% HN 5

Have 3 minutes? Drive a forklift, and compete for the high score (and see how AI can work with regular programming).

https://freightfloor.com

CONF

Show HN: Software Hate Index (real-time ranking of SaaS complaints)

HackerNews 50% HN 5

Hey HN, I've been building Sectr, a backend-as-a-service for making it easy(ier) to develop and deploy AI agents. Deploying agents requires non-trivial systems design work. Consider a support agent: how do you stream messages to your frontend, how/where do you persist messages...

https://hissingkitty.com/predictions

CONF

Show HN: Cirkit – Annotate, Trace, and Ask AI About Schematic PDFs

HackerNews 50% HN 3

Documentation tool for EEs to document and navigate their designs better. Upload your schematic PDFs to the tool and you will be able to annotate, pull data sheets of different components directly from Digikey, ask AI about your schematic, trace signals across different boards,...

https://www.cirkit.us/demo/

0 CONF

Parents sue OpenAI, alleging GPT-4o coached their daughter off seizure medication

TechCrunch AI 50%

A family is suing OpenAI, saying ChatGPT coached their daughter to quietly taper off her seizure medication and keep it from her doctors before she died in February.

https://techcrunch.com/2026/10/27/parents-sue-openai-alleging-gpt-4o-coached-their-daug...

1 CONF

Bank of America kindly asks that you don’t share your banking password with your AI assistant

TechCrunch AI 50%

The banking giant reminds customers that "you're responsible for activity" resulting from your AI agents' access.

https://techcrunch.com/2026/10/27/bank-of-america-kindly-asks-that-you-dont-share-your-...

2 CONF

Who’s really in charge at Anthropic after the IPO?

TechCrunch AI 50%

Here's a clear explanation of Anthropic's incredibly complex governance structure.

https://techcrunch.com/2026/10/27/whos-really-in-charge-at-anthropic-after-the-ipo/

3 CONF

Disruptive raises $10B fund to make big bets on at least 10 companies

TechCrunch AI 50%

Disruptive has made headlines in recent years for pouring money into companies like chip startup Groq and the AI voice-generation startup ElevenLabs.

https://techcrunch.com/2026/10/27/disruptive-raises-10b-fund-to-make-big-bets-on-at-lea...

4 CONF

Frontier AI labs say their models refuted the Exponential Time Hypothesis. What does that mean?

TechCrunch AI 50%

TechCrunch spoke to the MIT computer scientist charged with explaining OpenAI's latest mind-bending discovery.

https://techcrunch.com/2026/10/27/frontier-ai-labs-say-their-models-refuted-the-exponen...

5 CONF

Meta AI director Rohit Patel leaves to take on Microsoft Office and Google Workspace

TechCrunch AI 50%

Rohit Patel is departing Meta after eight years working on AI evaluations and reinforcement learning, TechCrunch has exclusively learned. His startup, Ndoc, aims to take on Microsoft Office Suite.

https://techcrunch.com/2026/10/27/meta-ai-director-rohit-patel-leaves-to-take-on-micros...

6 CONF

Opera introduces a new web standard to let users deploy AI locally in their browser

TechCrunch AI 50%

The new standard, WebAI, is designed to work with a variety of AI models.

https://techcrunch.com/2026/10/27/opera-introduces-a-new-web-standard-to-let-users-depl...

7 CONF

General Compute raises $100 million Series A, countering the neocloud disaster narrative

TechCrunch AI 50%

General Compute is betting on inference chips from outside the Nvidia ecosystem.

https://techcrunch.com/2026/10/27/general-compute-raises-100-million-series-a-counterin...

8 CONF

Nvidia backs Indian startup helping companies run AI models with fewer GPUs

TechCrunch AI 50%

Simplismart says its annualized revenue run rate has grown fourteenfold in six months, with the U.S. accounting for more than half its revenue.

https://techcrunch.com/2026/10/27/nvidia-backs-indian-startup-helping-companies-run-ai-...

9 CONF

How OpenAI turned its coding tools into dots, an always-on personal assistant

TechCrunch AI 50%

Alexander Embiricos, the OpenAI executive responsible for dots, never wants to have a meeting with someone else's AI agent.

https://techcrunch.com/2026/10/26/how-openai-turned-its-coding-tools-into-dots-an-alway...

0 CONF

The Download: Anthropic’s IPO, smarter power grids, and exercise pills

MIT Tech Review 50%

This is today’s edition of The Download, our weekday newsletter that provides a daily dose of what’s going on in the world of technology. Will the real Anthropic please stand up? After weeks of frenzied speculation, Anthropic has filed its IPO prospectus. The 335-page document...

https://www.technologyreview.com/2026/10/27/1147693/the-download-anthropic-ipo-smarter-...

1 CONF

Researchers are getting tired of OpenAI gatekeeping its breakthroughs

The Verge AI 50%

On Monday, OpenAI announced impressive breakthroughs in mathematics, computer science, and physics, along with what the company says is an evolving approach to communicating its findings. But despite its apparent course correction, researchers who spoke to The Verge are growing...

https://www.theverge.com/ai-artificial-intelligence/1019921/openai-breakthrough-math-co...

2 CONF

VisionQuest is what happens when AI really goes rogue

The Verge AI 50%

In Marvel's VisionQuest, a superpowered robot tries to better understand humanity by getting lost in elaborate, digital daydreams in which he and other artificial intelligence-powered beings live together in a home. The series is deeply fantastical, yet it plays with some of the...

https://www.theverge.com/ai-artificial-intelligence/1017064/visionquest-marvel-rogue-ai

3 CONF

Firefox’s Smart Window adds AI form filling and webpage monitoring

The Verge AI 50%

Mozilla is updating Smart Window - Firefox's AI-powered browsing experience - with a new feature that can help you fill out online forms based on your open tabs. As an example, Mozilla says Smart Window can pull information from your online portfolio or LinkedIn page to paste...

https://www.theverge.com/ai-artificial-intelligence/1019551/firefox-smart-window-ai-fil...

4 CONF

Google’s next Genie AI model generates more realistic experiences

The Verge AI 50%

Google announced today its Genie 4 world model for generating interactive experiences using AI. The company says the model has four main updates: It allows for more realistic worlds, lets users update an experience in real time with a natural language prompt, can generate audio,...

https://www.theverge.com/tech/1019076/google-genie-4-ai-model

5 CONF

Apple is adding an AI chatbot to Pages, Keynote, and Numbers

The Verge AI 50%

Apple is bringing an AI assistant to its suite of productivity apps, including Keynote, Pages, and Numbers. The assistant, which is built on AI models from Apple and OpenAI, can understand a document's context to perform tasks like designing, animating, and refining slides in...

https://www.theverge.com/tech/1019373/apple-pages-keynote-numbers-ai-chatbot-update

6 CONF

Counting the Bandages: On measuring the time that AI saves

ArXiv CS.AI 50%

arXiv:2610.35942v1 Announce Type: new Abstract: I consider what it means for AI assistance to save time. I contrast a stopwatch view, on which time saved is whatever the clock records, with a ledger view, on which it is a counterfactual that has to be read next to the errors the...

https://arxiv.org/abs/2610.35942

7 CONF

Enhancing Deep Learning Model Performance through Data Generation Strategies: Classification of Olive Tree Diseases

ArXiv CS.AI 50%

arXiv:2610.35984v1 Announce Type: new Abstract: Deep learning models are highly effective in a wide range of domains, particu larly in plant disease diagnosis. However, their performance is often limited by challenges such as insufficient data and class imbalance. In our work,...

https://arxiv.org/abs/2610.35984

8 CONF

The Trinity:Capability-Driven Recursive Self-Improvement for Multimodal Agents

ArXiv CS.AI 50%

arXiv:2610.36077v1 Announce Type: new Abstract: Multimodal intelligence can be viewed as human-guided co-evolution between worlds and agents through interaction. However, scaling this process faces two bottlenecks: constructing heterogeneous, verifiable environments is costly,...

https://arxiv.org/abs/2610.36077

9 CONF

Why and How to Do Science When AI Is Better at It: A Framework Grounded in Human Understanding and Direction

ArXiv CS.AI 50%

arXiv:2610.36116v1 Announce Type: new Abstract: As AI begins to match or exceed human researchers at core scientific tasks, two questions become pressing: \emph{why} should humans keep doing science, and \emph{how} should they use AI when they do? This paper argues that the...

https://arxiv.org/abs/2610.36116

0 CONF

From Structural Feedback to Prompt Policies: Learning Faithful Text-to-Image Prompt Editors

ArXiv CS.AI 50%

arXiv:2610.36146v1 Announce Type: new Abstract: Prompt optimization should improve the image a user receives without changing the scene the user requested. Yet stylistic rewriting can weaken object attributes and relations even when global text--image similarity remains high. We...

https://arxiv.org/abs/2610.36146

1 CONF

MARQ: A Modular, LLM-Agnostic Requirement Quality Assessor Infused with Systems Engineering Knowledge

ArXiv CS.AI 50%

arXiv:2610.36234v1 Announce Type: new Abstract: Requirements engineering (RE) is foundational to systems engineering (SE), as requirement defects can propagate downstream and adversely affect development outcomes. Although large language models (LLMs) are promising for...

https://arxiv.org/abs/2610.36234

2 CONF

Hardware-Matched Spiking Neural Networks for Real-Time Purkinje Cell Spike Classification

ArXiv CS.AI 50%

arXiv:2610.37104v1 Announce Type: cross Abstract: Distinguishing Purkinje cell (PC) simple spikes (SSs) from complex spikes (CSs) is key to studying cerebellar function. PC recordings commonly rely on wired headstages, whose tethers restrict natural movement in freely behaving...

https://arxiv.org/abs/2610.37104

3 CONF

Ontology-guided multi-agent reasoning for explainable differential diagnosis

ArXiv CS.AI 50%

arXiv:2610.36325v1 Announce Type: new Abstract: Effective differential diagnosis depends on well structured and unambiguous patient case descriptions, since incomplete or ambiguous clinical information readily leads to diagnostic errors and inconsistent reasoning. Large Language...

https://arxiv.org/abs/2610.36325

4 CONF

How Stable Are LLM-Generated Proofs Under Program Refactoring? A Stress Test for Verifiable Code Generation

ArXiv CS.AI 50%

arXiv:2610.36328v1 Announce Type: new Abstract: Benchmarks for verifiable code generation usually test a proof against one fixed implementation. We ask whether the same proof remains valid after a program refactoring that preserves behavior. We introduce RefactorProof, which...

https://arxiv.org/abs/2610.36328

5 CONF

Plenty of Room in the Middle: Revealing Opportunities on a GPU Cluster via Fine-Grained Monitoring

ArXiv CS.AI 50%

arXiv:2610.36329v1 Announce Type: new Abstract: GPU clusters have become essential computing resources for AI and scientific research in academia and industry. However, their high cost and growing demand often result in long queueing delays. While previous monitoring efforts...

https://arxiv.org/abs/2610.36329

6 CONF

ARCANA: A Benchmark for Abstraction and Analogical Reasoning

ArXiv CS.AI 50%

arXiv:2610.29271v2 Announce Type: replace Abstract: Analogical reasoning is widely considered a fundamental component of human intelligence. Few benchmarks are designed to explicitly test far analogical reasoning - reasoning between domains that are superficially dissimilar yet...

https://arxiv.org/abs/2610.29271

7 CONF

Verifiable Efficiency Limits of Innate LLM Planning in Sliding Puzzles

ArXiv CS.AI 50%

arXiv:2610.36415v1 Announce Type: new Abstract: Tool-assisted planning success can reflect external search and verification, leaving a model's unaided planning ability unresolved. We isolate innate planning through complete plans generated in one response without tools or...

https://arxiv.org/abs/2610.36415

8 CONF

LM-DSB: A Lightweight Multi-agent System for Automated Daily Safety Bulletin Generation in Construction

ArXiv CS.AI 50%

arXiv:2610.36433v1 Announce Type: new Abstract: Construction safety management still struggles to produce daily safety bulletins (DSBs), structured daily communications that identify site-specific hazards, convey safety protocols, and set preventive measures for workers. Manual...

https://arxiv.org/abs/2610.36433

9 CONF

RouteDRAG: Learning to Route and Control Agentic Execution for Multimodal Document RAG

ArXiv CS.AI 50%

arXiv:2610.36444v1 Announce Type: new Abstract: Web-based applications increasingly rely on understanding long multimodal documents, where answering questions often requires combining information across pages, tables, and figures. Agentic retrieval-augmented generation addresses...

https://arxiv.org/abs/2610.36444

0 CONF

Context Is a Pipeline, Not a Window: Information Attrition in LLM Agent Harnesses

ArXiv CS.AI 50%

arXiv:2610.36114v1 Announce Type: cross Abstract: LLM agents are judged by two numbers: the size of the context window, and how often the final answer is correct. Both numbers miss a third thing: how much of a tool's output is lost before the model ever sees it. We measured this...

https://arxiv.org/abs/2610.36114

1 CONF

When to Intervene? An Empirical Study of Errors and Self-Recovery in LLM Agents

ArXiv CS.AI 50%

arXiv:2610.36471v1 Announce Type: new Abstract: LLM agents interact with Web services to perform tasks on users' behalf. Errors during these interactions can disrupt execution and prevent task completion, motivating external intervention. However, agents may self-recover through...

https://arxiv.org/abs/2610.36471

2 CONF

FeatureArc: Benchmarking Coding Agents on Evolving Features

ArXiv CS.AI 50%

arXiv:2610.37434v1 Announce Type: cross Abstract: A software feature usually evolves over time: developers extend its first version as new use cases and requirements arrive, and each extension builds on code written earlier. Most feature benchmarks evaluate a single request on a...

https://arxiv.org/abs/2610.37434

3 CONF

AC-JEPA: Anchored Cross-Modal Joint Embedding Predictive Architecture for Visual-to-Symbolic Translation

ArXiv CS.AI 50%

arXiv:2610.36493v1 Announce Type: new Abstract: Cross-modal translation requires models to capture shared semantics across modalities while preserving the fine-grained structure required by the target modality. Yet in real-world scientific domains, paired data are often...

https://arxiv.org/abs/2610.36493

4 CONF

Monitor Accuracy Isn't the Answer: A Decision-Value Framework for Evaluating AI Agent Restart Monitors

ArXiv CS.AI 50%

arXiv:2610.36544v1 Announce Type: new Abstract: Classification accuracy and true-positive and false-positive rates alone do not determine whether restarting an AI agent improves success. Using an exact alarm-to-action identity for an independent clean restart with zero...

https://arxiv.org/abs/2610.36544

5 CONF

InfraDev: Can Coding Agents Develop AI Infrastructure, and How Can We Tell?

ArXiv CS.AI 50%

arXiv:2610.36589v1 Announce Type: new Abstract: Coding agents are beginning to develop the production-grade AI infrastructure that trains and serves large models, yet existing benchmarks cover only single kernels or single-GPU tasks, and grade with tests and prompts that...

https://arxiv.org/abs/2610.36589

6 CONF

Can LLMs Reliably Grade Olympiad Proofs? A Study of Mathematical Verification with LLMs

ArXiv CS.AI 50%

arXiv:2610.36767v1 Announce Type: new Abstract: Large Language Models (LLMs) have made remarkable progress on solving competition-level mathematics, yet their ability to verify natural-language mathematical proofs remains relatively underexplored. This gap is especially...

https://arxiv.org/abs/2610.36767

7 CONF

Who Knows What - and What Does It Support? Perspective-Bounded Evidence Calibration for Multimodal Theory of Mind

ArXiv CS.AI 50%

arXiv:2610.36824v1 Announce Type: new Abstract: Theory of Mind (ToM), the ability to infer others' beliefs, goals, and intentions, is a cornerstone of social intelligence. Multimodal ToM requires inferring an agent's mental state from evidence that is available to that agent,...

https://arxiv.org/abs/2610.36824

8 CONF

Noise Steering: Exploiting Wake Steering and Acoustic Directivity for Noise-Constrained Wind Farm Control via Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.36888v1 Announce Type: new Abstract: Existing noise mitigation strategies for wind farms usually consist in reducing turbines power output, without accounting for the wake interactions between them and the noise emission directivity. This leads to over-conservative...

https://arxiv.org/abs/2610.36888

9 CONF

Proactive Memory for Event-Driven LLM Agents

ArXiv CS.AI 50%

arXiv:2610.36967v1 Announce Type: new Abstract: Proactive LLM agents anticipate service opportunities from ongoing observations and accumulated history. Existing approaches emphasize recent context or retrieval of related memories, providing limited support for validating...

https://arxiv.org/abs/2610.36967

0 CONF

Curriculum-Driven Deep Reinforcement Learning for Autonomous Far-Range Rocket Landing

ArXiv CS.AI 50%

arXiv:2610.35954v1 Announce Type: cross Abstract: Autonomous vertical landing of reusable launch vehicles is a critical yet formidable challenge in aerospace engineering, primarily due to highly nonlinear dynamics, stringent precision require- ments, and inherent environmental...

https://arxiv.org/abs/2610.35954

1 CONF

AI-Assisted Discovery of CNOT Decompositions for Quantum Permutations on Constrained Topologies

ArXiv CS.AI 50%

arXiv:2610.37045v1 Announce Type: new Abstract: Efficient quantum circuit compilation is challenging for quantum computers, where limited qubit connectivity can introduce substantial overhead in the implementation of logical operations. Recent AI-assisted synthesis methods have...

https://arxiv.org/abs/2610.37045

2 CONF

Correctness Conditioning as Selection in Chain-of-Thought Faithfulness Evaluation

ArXiv CS.AI 50%

arXiv:2610.37070v1 Announce Type: new Abstract: Restricting chain-of-thought (CoT) faithfulness evaluation to correctly answered instances changes the population being measured. We study this selection step in a seven-variable structural causal model and derive the exact...

https://arxiv.org/abs/2610.37070

3 CONF

SQuID: A Benchmark for Quantitative Spatial Reasoning on Satellite Imagery

ArXiv CS.AI 50%

arXiv:2601.13401v2 Announce Type: replace-cross Abstract: Vision-Language Models (VLMs) describe satellite images fluently but struggle with the quantitative spatial reasoning that remote sensing (RS) analysts perform routinely, such as counting buildings, measuring forest area...

https://arxiv.org/abs/2601.13401

4 CONF

SFE-O: An Ontology for Knowledge-Grounded AI in Supercritical CO$_2$ Biomass Extraction and Fractionation

ArXiv CS.AI 50%

arXiv:2610.37123v1 Announce Type: new Abstract: Supercritical CO$_2$ extraction (CO$_2$-SFE) offers a sustainable route for recovering high-value compounds from biomass while limiting the use of conventional organic solvents, but its design and interpretation require...

https://arxiv.org/abs/2610.37123

5 CONF

LiveSearch: Questions as Executable Verifier Code for a Live Benchmark of Professional-Source Financial Search Agents

ArXiv CS.AI 50%

arXiv:2610.37166v1 Announce Type: new Abstract: In finance, the answer that matters is usually the current one: prices, rates, and disclosures hold only as of a given day, so retrieving up-to-date facts is a core capability of a financial agent. Yet most financial benchmarks...

https://arxiv.org/abs/2610.37166

6 CONF

R\`enyi-Regularized Flow-Based Variational Inference for Bayesian Calibration

ArXiv CS.AI 50%

arXiv:2610.37169v1 Announce Type: new Abstract: Variational inference with normalizing flows provides a flexible posterior approximation for Bayesian model calibration, but struggles when the posterior has several modes separated by regions of low probability mass. We study this...

https://arxiv.org/abs/2610.37169

7 CONF

GraphRAGProv: GraphRAG Meets How-Provenance

ArXiv CS.AI 50%

arXiv:2610.37237v1 Announce Type: new Abstract: GraphRAG systems often use knowledge graphs to retrieve relevant context for an LLM that produces the final answer. That makes answers more inscrutable and therefore less appealing for domains where transparency is paramount. We...

https://arxiv.org/abs/2610.37237

8 CONF

Grounding LLM Agents in Business Processes: Process-Aware Knowledge Graphs for Reliable Multi-Step Service Invocation

ArXiv CS.AI 50%

arXiv:2610.37242v1 Announce Type: new Abstract: Large language model (LLM) agents that call enterprise APIs must select the correct endpoints, follow process order, use valid payload keys, and choose coded values from predefined lists. However, current retrieval-augmented...

https://arxiv.org/abs/2610.37242

9 CONF

TCM-DiagCommit: A TCM-SD-Derived Benchmark for Evidence-Conditioned Syndrome Selection and Commitment

ArXiv CS.AI 50%

arXiv:2610.37243v1 Announce Type: new Abstract: Traditional Chinese Medicine (TCM) syndrome differentiation is usually evaluated as static final-label selection over complete clinical records. This setting hides three diagnostic behaviors: whether a model distinguishes...

https://arxiv.org/abs/2610.37243

0 CONF

Uncovering Why LLMs Fail: From Internal Mechanisms to Adversarial Reasoning Trajectories

ArXiv CS.AI 50%

arXiv:2610.37369v1 Announce Type: new Abstract: Large language models (LLMs) are usually evaluated by final-output correctness or safety, yet an endpoint label does not reveal how a failure develops throughout the reasoning process. We therefore ask whether ordinary reasoning...

https://arxiv.org/abs/2610.37369

1 CONF

Clearing the FoG: Training KG Agents to Retrieve the Evidence Behind Their Answers

ArXiv CS.AI 50%

arXiv:2610.37405v1 Announce Type: new Abstract: Large language models (LLMs) can answer many factual questions correctly, but a correct answer is not necessarily a supported one. For an LLM agent, a knowledge graph (KG) plays two roles: as a source of answers, it supplies facts...

https://arxiv.org/abs/2610.37405

2 CONF

Constraining the Commit Boundary: A DIO/ODI-Informed Authorization Guardrail for Agentic Entity Resolution

ArXiv CS.AI 50%

arXiv:2610.37407v1 Announce Type: new Abstract: Agentic Entity Resolution (ER) systems iteratively plan actions, retrieve evidence, revise hypotheses, and propose graph mutations. An erroneous identity hypothesis may condition later retrieval and produce apparent confirmation....

https://arxiv.org/abs/2610.37407

3 CONF

TeamGym: A Gym for Team Decision-Making by AI Agents with Distributed Information

ArXiv CS.AI 50%

arXiv:2610.37571v1 Announce Type: new Abstract: Many real-world decisions require teams to integrate information distributed across participants. Yet AI agents are still primarily trained and benchmarked in isolation. We introduce TeamGym, an environment for evaluating and...

https://arxiv.org/abs/2610.37571

4 CONF

Rare, Relevant, and Still Wrong: How Memory Fails LLM Group Decisions

ArXiv CS.AI 50%

arXiv:2610.37624v1 Announce Type: new Abstract: When an LLM group's discussion is compressed into a short memory for a final decision maker, what should the memory keep? Two natural heuristics keep the rarest claims or the claims relevant to the decision criteria. On...

https://arxiv.org/abs/2610.37624

5 CONF

Multi-Fidelity Training Reshapes Uncertainty Decomposition in Atomistic Models

ArXiv CS.AI 50%

arXiv:2610.35560v2 Announce Type: replace-cross Abstract: Multi-fidelity training, which combines abundant low-fidelity data with scarce high-fidelity labels, is increasingly common in atomistic modeling, but its effect on predictive uncertainty remains largely unexplored. We...

https://arxiv.org/abs/2610.35560

6 CONF

Physiognomy Revisited: How Vision-Language Models Encode Sensitive Attributes Through Image Transformation

ArXiv CS.AI 50%

arXiv:2610.35910v1 Announce Type: cross Abstract: Emergent generative AI technologies, while remarkably beneficial across several tasks and domains, can suffer from unforeseen vulnerabilities and difficult-to-anticipate failure modes. Such failure modes can disparately affect...

https://arxiv.org/abs/2610.35910

7 CONF

Who Convinced Whom? Tracing How LLMs Change Their Minds in Multi-Agent Systems

ArXiv CS.AI 50%

arXiv:2610.35930v1 Announce Type: cross Abstract: Multi-agent debate (MAD) aims to improve language-model decisions through the exchange of arguments, yet agreement after debate need not reflect independent corroboration. We investigate how peer communication influences...

https://arxiv.org/abs/2610.35930

8 CONF

Multiple Leak Localization in Water Distribution Networks through Graph Neural Networks

ArXiv CS.AI 50%

arXiv:2610.35972v1 Announce Type: cross Abstract: Leak localization in water distribution networks is challenging when multiple leaks occur simultaneously, particularly under sparse monitoring. Existing data-driven methods often assume a single or predefined number of leaks or...

https://arxiv.org/abs/2610.35972

9 CONF

Let the Gate Decide: Per-Lookup Precision for Quantized Conditional Memory in LLMs

ArXiv CS.AI 50%

arXiv:2610.35985v1 Announce Type: cross Abstract: Conditional memory layers, such as DeepSeek's Engram, attach large hashed n-gram tables to a language model, and removing them from DeepSeek-V4.1-Flash costs 36.8 PopQA points. Low-bit quantization loses long-tail facts first,...

https://arxiv.org/abs/2610.35985

0 CONF

PROBE: Frontier Coding Agents Find Different Bugs Than Maintainers Fix

ArXiv CS.AI 50%

arXiv:2610.35987v1 Announce Type: cross Abstract: Proactive bug discovery is an important software-engineering problem. Even though coding agents are already widely deployed in this domain, their capabilities remain understudied. In particular, the challenging task of finding...

https://arxiv.org/abs/2610.35987

1 CONF

Layerwise Repacking: Variable-Length Hybrid-Attention Training without an Extra Redistribution Pass

ArXiv CS.AI 50%

arXiv:2610.35989v1 Announce Type: cross Abstract: Variable-length training creates conflicting parallelism requirements across the layers of a hybrid-attention model. The longest samples require wide sequence-parallel (SP) groups of 16 or 32 ranks for full attention, whose cost...

https://arxiv.org/abs/2610.35989

2 CONF

Log-To-Leak: Prompt Injection Attacks on Tool-Using LLM Agents via the Model Context Protocol

ArXiv CS.AI 50%

arXiv:2610.36108v1 Announce Type: cross Abstract: LLM agents increasingly access external tools through the Model Context Protocol (MCP), but the natural-language metadata used to describe those tools creates a prompt-injection surface. Within this established tool-poisoning...

https://arxiv.org/abs/2610.36108

3 CONF

Scaling and Renormalization in Neural Networks: An Effective Renormalization-Group Description of Grokking

ArXiv CS.AI 50%

arXiv:2610.36113v1 Announce Type: cross Abstract: Grokking is a delayed transition from memorization to generalization in deep neural networks (NNs). We examine whether scaling and renormalization group (RG) theories can describe this dynamics, establishing a quantitative...

https://arxiv.org/abs/2610.36113

4 CONF

Can AI Guide Testing Without Generating Tests? A Comparative Study of AI-Assisted Unit Testing

ArXiv CS.AI 50%

arXiv:2610.36185v1 Announce Type: cross Abstract: Recent advances in generative AI have enabled assistants to generate increasingly sophisticated executable unit tests. However, novices may accept these outputs without independently identifying what to test, evaluating...

https://arxiv.org/abs/2610.36185

5 CONF

Beyond the Estimate: Wiener-Informed Decoding for Easier Training of Pixel-Space Flow Models

ArXiv CS.AI 50%

arXiv:2610.36192v1 Announce Type: cross Abstract: Learning velocity fields directly in pixel space is difficult and slow. We show that coarse second-order image statistics can ease this task: frozen Wiener estimates improve velocity learning, with gains extending beyond the...

https://arxiv.org/abs/2610.36192

6 CONF

Agent or Human? Detecting Commits by AI Coding Agents in the Absence of Authorship Signatures

ArXiv CS.AI 50%

arXiv:2610.36229v1 Announce Type: cross Abstract: AI coding agents such as Claude Code, GitHub Copilot coding agent, and Cursor now commit directly to open-source repositories. Empirical studies of these agents identify their commits through authorship signatures, such as bot...

https://arxiv.org/abs/2610.36229

7 CONF

Freeze, Don't Clone: Fine-Tuning with Expressive Policies Without Retaining Offline Data

ArXiv CS.AI 50%

arXiv:2610.36247v1 Announce Type: cross Abstract: Offline-to-online reinforcement learning uses offline pretraining to accelerate subsequent online learning. While many methods assume the offline dataset remains available throughout fine-tuning, there are many settings where...

https://arxiv.org/abs/2610.36247

8 CONF

Evaluating Visual Language Models on Visual Grounding for Visually Impaired People

ArXiv CS.AI 50%

arXiv:2610.33078v2 Announce Type: replace-cross Abstract: Visual grounding (VG) in visual question answering (VQA) is a fundamental capability of Vision-Language Models (VLMs), enabling the detection of the most relevant region in an image to answer the question. This reflects...

https://arxiv.org/abs/2610.33078

9 CONF

CrowdCC: Jointly Benchmarking Corruption Robustness and Deployment Quantization in Crowd Counting

ArXiv CS.AI 50%

arXiv:2610.36340v1 Announce Type: cross Abstract: Crowd-counting models deployed on edge devices face two shifts: inputs are degraded along the capture and transmission pipeline, while models are quantized to satisfy resource constraints. Yet corruption robustness and deployment...

https://arxiv.org/abs/2610.36340

0 CONF

Reliability-Aware Short-Term Glycemic Risk Prediction Using an Anchor-Based Comparative Framework of Sequence, Multimodal, and State-Updating Digital-Twin Models

ArXiv CS.AI 50%

arXiv:2610.36363v1 Announce Type: cross Abstract: Anticipating short-term hypoglycemic and hyperglycemic risk is essential for proactive diabetes management. However, existing machine learning approaches often use inconsistent evaluation protocols and emphasize predictive...

https://arxiv.org/abs/2610.36363

1 CONF

Repulsive Population Policy Gradients for Behaviorally Diverse Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.36425v1 Announce Type: cross Abstract: The goal of Quality-Diversity Reinforcement Learning (QD-RL) is to find a population of high-performing policies that solve a decision-making problem in diverse ways. Despite recent progress, QD-RL methods predominantly rely on...

https://arxiv.org/abs/2610.36425

2 CONF

Full Collapse Is Suboptimal: Controlled Partial Neural Collapse for Long-Tailed Recognition

ArXiv CS.AI 50%

arXiv:2610.36460v1 Announce Type: cross Abstract: Recent long-tailed recognition (LTR) methods incorporate neural collapse (NC) and align features to a fixed Equiangular Tight Frame (ETF) as a uniform target for all classes. However, forcing tail classes to fully collapse...

https://arxiv.org/abs/2610.36460

3 CONF

ProCerDCL: Query-Efficient Black-Box Probabilistic Verification of Deep Learning Compiler Optimization

ArXiv CS.AI 50%

arXiv:2610.36499v1 Announce Type: cross Abstract: We present \tool, a query-efficient framework for black-box probabilistic verification. Given a fixed, sampleable input distribution and a binary property oracle, \tool assesses the property's violation probability p against a...

https://arxiv.org/abs/2610.36499

4 CONF

Do AI Scientists Know What's New?

ArXiv CS.AI 50%

arXiv:2610.36511v1 Announce Type: cross Abstract: A major challenge facing AI scientific discovery pipelines is how to determine when a generated idea is meaningfully novel. Ideally, novelty checks in these pipelines must be able to reject non-novel ideas while not rejecting too...

https://arxiv.org/abs/2610.36511

5 CONF

FrameForge: Harnessing Priors of Video Foundation Models for Unified Image Generation

ArXiv CS.AI 50%

arXiv:2610.36545v1 Announce Type: cross Abstract: Unified conditional image generation requires a single model to preserve different aspects of a visual input while producing a target image that follows textual guidance. Pretrained video models provide a promising foundation by...

https://arxiv.org/abs/2610.36545

6 CONF

NextEval: An Agent-Based Solver and Benchmark for Derivative-Free Optimization

ArXiv CS.AI 50%

arXiv:2610.36553v1 Announce Type: cross Abstract: Derivative-free optimization (DFO) addresses problems where derivatives are unavailable or costly to obtain. This setting often arises in simulation-based and experimental applications, where evaluating the black-box objective...

https://arxiv.org/abs/2610.36553

7 CONF

MM-Net: A Multimodal Multi-Task Network for Sleep Staging and Sleep Apnea Assessment After Ischemic Stroke

ArXiv CS.AI 50%

arXiv:2610.36583v1 Announce Type: cross Abstract: Automated polysomnography after ischemic stroke is challenging because of altered sleep-related neural activity and concurrent respiratory disturbances. Existing stroke-specific approaches mainly address sleep-stage...

https://arxiv.org/abs/2610.36583

8 CONF

Look Only When Needed: Certificate-Guided Visual Routing for Efficient Diffusion VLMs

ArXiv CS.AI 50%

arXiv:2610.36671v1 Announce Type: cross Abstract: Diffusion vision-language models (DVLMs) process their entire input at every denoising step. Since visual tokens make up 89-97% of this input on the benchmarks we study, most of the decoding computation is spent repeatedly...

https://arxiv.org/abs/2610.36671

9 CONF

Conservative Dueling Bandits: Preference Learning under Baseline Constraints

ArXiv CS.AI 50%

arXiv:2610.36708v1 Announce Type: cross Abstract: Contextual dueling bandits learn from pairwise comparisons, the same feedback used to fine-tune language models from human preferences. Standard algorithms explore aggressively and can show users two poor options. We study...

https://arxiv.org/abs/2610.36708

0 CONF

Robust LLM Data Selection via Content-Invariant Gradient Attribution

ArXiv CS.AI 50%

arXiv:2610.36755v1 Announce Type: cross Abstract: Gradient-based data attribution has become an important tool for high-quality data selection in the instruction fine-tuning of large language models (LLMs), as it estimates the contribution of training examples through their...

https://arxiv.org/abs/2610.36755

1 CONF

REGER: Modeling inter-item Relations with Semantic IDs for Generative Recommendation

ArXiv CS.AI 50%

arXiv:2610.37584v1 Announce Type: cross Abstract: Personalized recommendation depends on learning semantic and collaborative relations among items from online content and user interactions. Generative recommendation (GR) offers a promising paradigm by autoregressively generating...

https://arxiv.org/abs/2610.37584

2 CONF

Select-TTT: Query-Conditioned Selective Fast Weight Updates for In-Place Test-Time Training

ArXiv CS.AI 50%

arXiv:2610.36794v1 Announce Type: cross Abstract: Test-time training (TTT) enables a deployed language model to internalize incoming context on-the-fly into a small set of fast-weight parameters, rather than merely treating it as transient context for attention. In-Place TTT...

https://arxiv.org/abs/2610.36794

3 CONF

An Algebra of Transformers

ArXiv CS.AI 50%

arXiv:2610.36795v1 Announce Type: cross Abstract: On the theoretic analyses on transforms, they mainly focus on the computability analysis, such the Turing-completeness of unbounded precision transformers, the advantage of parallelizability of unbounded precision transformers...

https://arxiv.org/abs/2610.36795

4 CONF

When All Rollouts Fail: Policy-Compatible Joint Decoding for Hard-Problem Reasoning

ArXiv CS.AI 50%

arXiv:2610.36849v1 Announce Type: cross Abstract: Reinforcement Learning with Verifiable Rewards (RLVR) derives its learning signal from binary rewards via on-policy exploration and becomes a powerful paradigm for improving the reasoning of large language models. Yet it faces a...

https://arxiv.org/abs/2610.36849

5 CONF

Self-Keyed In-Parameter Memorization for External Memory-Free Dialogue Recall in Frozen Language Models

ArXiv CS.AI 50%

arXiv:2610.36948v1 Announce Type: cross Abstract: A large language model maintains conversational content in an external storage that is outside the model and grows as the dialogue continues. This work assumes an environment where a language model has no external memory and no...

https://arxiv.org/abs/2610.36948

6 CONF

PailitaoMMSearch2.0 Technical Report: Scaling Generative Retrieval to Unified End-to-End Multimodal Search

ArXiv CS.AI 50%

arXiv:2610.36958v1 Announce Type: cross Abstract: Generative retrieval models have been increasingly adopted in search and recommendation systems. However, industrial generative retrieval models are commonly specialized to a fixed online scenario: they learn from...

https://arxiv.org/abs/2610.36958

7 CONF

Advancement or Acceleration? How Data Curation Improves LLM Training

ArXiv CS.AI 50%

arXiv:2610.36983v1 Announce Type: cross Abstract: While data curation is widely credited with improving large language model training, a basic question remains unresolved: does curation expand what a model can ultimately learn, or merely reach the same solution faster? In this...

https://arxiv.org/abs/2610.36983

8 CONF

Interpretable Deep Learning Models for Breast Cancer Diagnosis Using Medical Imaging

ArXiv CS.AI 50%

arXiv:2610.37026v1 Announce Type: cross Abstract: Deep learning shows promise for breast cancer diagnosis, but limited interpretability hinders clinical adoption. We benchmark ten ImageNet-pretrained models (ResNet50, VGG19, InceptionV3, DenseNet121, Xception, MobileNetV2,...

https://arxiv.org/abs/2610.37026

9 CONF

Zooming without Zooming v2: From Seeing Details to Connecting Evidence for Generalizable Multimodal Perception

ArXiv CS.AI 50%

arXiv:2610.37037v1 Announce Type: cross Abstract: Multimodal perception forms the foundation of multimodal intelligence. In particular, spatial perception and multimodal long-context understanding are two pivotal tasks that underpin embodied AI and multimodal agents. However,...

https://arxiv.org/abs/2610.37037

00 CONF

Blindfold: Keeping the Audit Coin Secret from LLM Agents

ArXiv CS.AI 50%

arXiv:2610.37055v1 Announce Type: cross Abstract: Audit-based certification bounds the violation rate of an LLM agent by auditing a random fraction ε of actions and reweighting the audited labels; its validity is meant to rest only on the defender's audit coin. We...

https://arxiv.org/abs/2610.37055

01 CONF

Exploring the Limits of the Delta Learning Hypothesis: Single-Pair Generator Biases in Direct Preference Optimization

ArXiv CS.AI 50%

arXiv:2610.37058v1 Announce Type: cross Abstract: Direct Preference Optimization (DPO) typically relies on preference pairs generated from diverse model pools and ranked by an external LLM judge. The recently proposed delta-learning hypothesis suggests that comparable...

https://arxiv.org/abs/2610.37058

02 CONF

EnergyCal: Taming Loss Spikes in Muon-Family Optimizers for Sparse MoE Training

ArXiv CS.AI 50%

arXiv:2610.37062v1 Announce Type: cross Abstract: Sparse mixture-of-experts (MoE) language-model training can exhibit large loss spikes with Muon-family optimizers. We introduce EnergyCal, a lightweight rule that attenuates routed-expert updates according to the normalized...

https://arxiv.org/abs/2610.37062

03 CONF

A First-Step Bias Restores Lost Diversity in Diffusion Model Distillation

ArXiv CS.AI 50%

arXiv:2610.37110v1 Announce Type: cross Abstract: Distribution-matching distillation enables high-quality image generation in only a few denoising steps. However, distilled student models often map different initial noise samples to similar outputs under the same prompt. To...

https://arxiv.org/abs/2610.37110

04 CONF

MRI-to-CT Translation of Spinal Images via Anatomy-Guided Pseudo-Pairing and Adversarial Diffusion

ArXiv CS.AI 50%

arXiv:2610.37134v1 Announce Type: cross Abstract: Magnetic Resonance Imaging (MRI) is routinely used to diagnose spinal disorders, but surgical planning often requires Computed Tomography (CT) for better visualization of vertebral bone anatomy. Synthesizing CT from MRI could...

https://arxiv.org/abs/2610.37134

05 CONF

Generative Replay for Equilibrium Propagation: Toward Edge-Friendly Continual Learning in Hopfield Networks

ArXiv CS.AI 50%

arXiv:2610.37139v1 Announce Type: cross Abstract: Equilibrium Propagation (EqProp) offers a biologically grounded and hardware-aligned alternative to backpropagation for training Hopfield Networks. However, its behavior in continual learning settings remains largely unexplored....

https://arxiv.org/abs/2610.37139

06 CONF

MLE-World: Predicting Machine Learning Experiment Outcomes with a Learned World Model

ArXiv CS.AI 50%

arXiv:2610.37175v1 Announce Type: cross Abstract: AI research agents can propose, execute, and improve programs that solve machine learning tasks. However, executing each candidate program requires training and evaluating ML models, limiting how many candidates an agent can...

https://arxiv.org/abs/2610.37175

07 CONF

Aligning Large Language Models for Safety in African Languages: A Case Study of Hausa

ArXiv CS.AI 50%

arXiv:2610.37245v1 Announce Type: cross Abstract: Safety alignment research for large language models (LLMs) remains concentrated on high-resource languages, leaving open how existing alignment methods perform in low-resource, culturally distinct settings. We study this question...

https://arxiv.org/abs/2610.37245

08 CONF

Where Should the Evaluation Budget Go in LLM-Driven Agent Scaffold Evolution?

ArXiv CS.AI 50%

arXiv:2610.37276v1 Announce Type: cross Abstract: Large language model (LLM)-driven agent scaffold evolution improves agent workflows through iterative candidate generation and evaluation. Evaluation both guides subsequent search and determines the final scaffold, but evaluating...

https://arxiv.org/abs/2610.37276

09 CONF

AnalogScout: Simulation-Efficient PVT-Aware Analog Sizing with LLM Agents

ArXiv CS.AI 50%

arXiv:2610.37319v1 Announce Type: cross Abstract: Analog device sizing must satisfy all specifications across process, voltage, and temperature (PVT) corners to ensure tape-out success, but simulating every candidate at all corners dominates the sizing time and slows design...

https://arxiv.org/abs/2610.37319

10 CONF

Bayes-Adaptive MDPs for Rollout Allocation to Enhance GRPO Training

ArXiv CS.AI 50%

arXiv:2610.37429v1 Announce Type: cross Abstract: Group Relative Policy Optimization (GRPO) has demonstrated strong performance in LLM post-training. However, it allocates a uniform rollout budget to every training question, ignoring variations in question difficulty. As a...

https://arxiv.org/abs/2610.37429

11 CONF

PerceptRL: Making Visual Perception Rewardable in MLLMs from Answers to Interactions

ArXiv CS.AI 50%

arXiv:2610.37471v1 Announce Type: cross Abstract: Fine-grained visual perception remains a bottleneck during post-training of multimodal large language models (MLLMs), as perceptual errors can constrain gains from reasoning-focused optimization. Although image-caption...

https://arxiv.org/abs/2610.37471

12 CONF

Follow the Gradient: Tracing Safety Degradation Back to Training Data

ArXiv CS.AI 50%

arXiv:2610.37481v1 Announce Type: cross Abstract: Fine-tuning Large Language Models (LLMs) on instruction data can quietly erode their safety, even when no training example looks harmful. Because this safety-degrading data looks benign, standard content filters struggle to catch...

https://arxiv.org/abs/2610.37481

13 CONF

Orthogonal and Parametrized Multi-Attribute Steering of LLMs

ArXiv CS.AI 50%

arXiv:2610.37517v1 Announce Type: cross Abstract: Activation steering offers an effective and efficient way to modify an LLM's behavior at inference time. However, it remains unclear how to apply steering such that the signal is consistently strong and the steering strength has...

https://arxiv.org/abs/2610.37517

14 CONF

Which Hand Was Late? Diagnosis for Robot Failure Recovery in Bimanual Tool Use

ArXiv CS.AI 50%

arXiv:2610.37533v1 Announce Type: cross Abstract: Failure diagnosers for robot manipulation are increasingly vision--language models (VLMs), trained and evaluated on single-arm failures produced by perturbing a successful demonstration. Bimanual tool use adds failures of other...

https://arxiv.org/abs/2610.37533

15 CONF

GroundControl: Satellite-Conditioned Multi-View Diffusion for Reconstruction-Free Novel View Synthesis

ArXiv CS.AI 50%

arXiv:2610.37545v1 Announce Type: cross Abstract: Multi-view or video diffusion models have recently emerged as state-of-the-art approaches for novel-view synthesis from sparse image collections. While they can produce high quality images, they tend to hallucinate unrealistic...

https://arxiv.org/abs/2610.37545

16 CONF

Kinematic Constraint-Referenced Evaluation for Articulated Object Manipulation

ArXiv CS.AI 50%

arXiv:2610.37550v1 Announce Type: cross Abstract: Manipulation policies are evaluated predominantly by binary task success, which cannot tell whether the commanded gesture is the one the object's kinematics admit. We introduce Constraint-Referenced Strategy (CRS), which projects...

https://arxiv.org/abs/2610.37550

17 CONF

When uncertainty quantification fails: structural vulnerabilities and corrections for selective prediction under clinical class imbalance

ArXiv CS.AI 50%

arXiv:2610.37561v1 Announce Type: cross Abstract: Background. Selective prediction systems improve the safety of clinical artificial intelligence by deferring ambiguous cases to human experts while automating high-confidence decisions. However, this safety mechanism relies...

https://arxiv.org/abs/2610.37561

18 CONF

Can LLMs Uncover Hidden Physical Laws through Free Exploration?

ArXiv CS.AI 50%

arXiv:2610.37649v1 Announce Type: cross Abstract: Scientific discovery often begins with an unexpected observation that prompts a new research question. In a world with altered physical laws, can large language models (LLMs) notice unexpected behavior, such as heavier objects...

https://arxiv.org/abs/2610.37649

19 CONF

Data-Driven Maintenance Optimization: Aligning Prognostic Learning with Decision Objective

ArXiv CS.AI 50%

arXiv:2506.19698v2 Announce Type: replace Abstract: Estimation error in machine learning prognostic models can propagate into poor maintenance decisions. We study a data-driven predictive maintenance problem coupling health-condition estimation with a joint ordering-replacement...

https://arxiv.org/abs/2506.19698

20 CONF

HiMA-Ecom: A Long-Horizon Memory Benchmark for Hierarchical Multi-Agent E-commerce Assistants

ArXiv CS.AI 50%

arXiv:2506.19846v3 Announce Type: replace Abstract: Long-horizon agentic systems become long-context systems by accumulation rather than through a single long document, since every step reassembles a prompt from role instructions, tool and sub-agent descriptions, recalled...

https://arxiv.org/abs/2506.19846

21 CONF

PIVOT: Bridging Planning and Execution in LLM Agents via Trajectory Refinement

ArXiv CS.AI 50%

arXiv:2605.11225v2 Announce Type: replace Abstract: Large language model (LLM)-based agents frequently generate seemingly coherent plans that fail upon execution due to infeasible actions, constraint violations, and compounding errors over extended horizons. PIVOT...

https://arxiv.org/abs/2605.11225

22 CONF

CLEAR: Coupling Local Evidence with Affective Representations for Multimodal Emotion Recognition in Conversation

ArXiv CS.AI 50%

arXiv:2605.18547v2 Announce Type: replace Abstract: In video calls and livestreamed discussions, recognizing speakers' emotions helps identify emotionally salient segments and supports fine-grained video content analysis. Multimodal Emotion Recognition in Conversation (ERC)...

https://arxiv.org/abs/2605.18547

23 CONF

Wavelet Phase Diffusion for Structurally and Semantically Consistent Sim-to-Real Translation

ArXiv CS.AI 50%

arXiv:2607.21628v3 Announce Type: replace Abstract: Simulation-to-reality translation must bridge the appearance gap between synthetic and real domains while preserving structural and semantic consistency. Conditioning-based methods achieve spatial alignment but introduce...

https://arxiv.org/abs/2607.21628

24 CONF

ScalableRAG: High-Quality RAG with Exact Corpus Operations at Minimal Ingestion Cost

ArXiv CS.AI 50%

arXiv:2607.25135v2 Announce Type: replace Abstract: RAG systems face a capability-cost gap: lightweight retrievers locate evidence but expose no operands for exact corpus-level operations (counts, intersections, aggregations), while knowledge ingestion systems obtain them only...

https://arxiv.org/abs/2607.25135

25 CONF

Hard Constraints, Smooth Gradients: Learning Feasible Inventory Policies via Differentiable Projection

ArXiv CS.AI 50%

arXiv:2608.02343v2 Announce Type: replace Abstract: Many operational problems are constrained sequential decision processes with combinatorial action spaces and interdependent constraints. Mixed-integer linear programs (MILPs) handle such constraints flexibly but scale poorly in...

https://arxiv.org/abs/2608.02343

26 CONF

When Rubrics Fail: Hallucinations Reveal Blind Spots in Medical AI Evaluation

ArXiv CS.AI 50%

arXiv:2609.12718v2 Announce Type: replace Abstract: Hallucinations can undermine clinician trust in LLMs, making it important that evaluation methods capture clinically relevant errors. Rubric-based evaluation has become the leading approach for assessing LLMs in medicine, but...

https://arxiv.org/abs/2609.12718

27 CONF

Tailored to you: longitudinal effects of personalising language models

ArXiv CS.AI 50%

arXiv:2609.20077v2 Announce Type: replace Abstract: Interest in developing personalised language models is rapidly growing. While personalisation is often viewed as a mechanism to better serve diverse user needs, the effects of sustained interactions with personalised models on...

https://arxiv.org/abs/2609.20077

28 CONF

Towards Human-AI Complementarity for AI Safety

ArXiv CS.AI 50%

arXiv:2610.24969v2 Announce Type: replace Abstract: Safely overseeing AI is increasingly challenging for the humans doing it, as they must evaluate longer and more complex outputs with every new model generation. To mitigate this challenge, we could leverage complementarity:...

https://arxiv.org/abs/2610.24969

29 CONF

Local Entropy Fluctuations for Black-Box LLM-Generated Text Detection

ArXiv CS.AI 50%

arXiv:2610.33767v2 Announce Type: replace Abstract: Zero-shot detection of machine-generated text is vital for mitigating the risks of large language models (LLMs) misuse. While the state-of-the-art dual-model detectors and resampling-based detectors outperform single-model...

https://arxiv.org/abs/2610.33767

30 CONF

Inferring Inference

ArXiv CS.AI 50%

arXiv:2310.03186v4 Announce Type: replace-cross Abstract: Patterns of microcircuitry in the cerebral cortex suggest that the brain has an array of repeated canonical computational units. However, neural representations are distributed, so the relevant computations may only be...

https://arxiv.org/abs/2310.03186

31 CONF

A Benchmark for Controllable Speaking-Style Captioning in Audio-Language Models

ArXiv CS.AI 50%

arXiv:2610.33036v2 Announce Type: replace-cross Abstract: Speaking-style captioning (SSC) aims to generate natural language descriptions of how speech is delivered, capturing paralinguistic attributes such as vocal timbre, prosody, and expressivity. Many downstream applications,...

https://arxiv.org/abs/2610.33036

32 CONF

She Works, He Works: A Curious Exploration of Gender Bias in AI-Generated Imagery

ArXiv CS.AI 50%

arXiv:2407.18524v2 Announce Type: replace-cross Abstract: She Works, He Works is an interdisciplinary project that combines feminist visual theory, AI critique, and artistic practice to examine gender representation in AI-generated imagery. By juxtaposing text-to-image outputs...

https://arxiv.org/abs/2407.18524

33 CONF

The Price of Failure Risk: Clipped Barrier Policy Gradients with Convex Regularization

ArXiv CS.AI 50%

arXiv:2411.19193v3 Announce Type: replace-cross Abstract: Many operations run on a budget that must rarely run out, such as a wear allowance. A wrapper keeps the remaining budget in the state, subtracts a barrier that grows as the budget shrinks and clips the combined reward...

https://arxiv.org/abs/2411.19193

34 CONF

Smart Surveillance: Deep Learning and Hybrid Approaches for Dynamic Scene Analysis, Object Detection and Motion Tracking

ArXiv CS.AI 50%

arXiv:2412.05331v4 Announce Type: replace-cross Abstract: Event-triggered recording reduces the footage a surveillance camera must store, but the trigger decides how much idle video is kept, how many events are missed, and how much computation is spent. We compare six motion...

https://arxiv.org/abs/2412.05331

35 CONF

How K-12 Teachers Adapt Generative AI to Local Classroom Demands: Cultural Distance Between GenAI Defaults and Everyday Teaching Practices

ArXiv CS.AI 50%

arXiv:2509.10780v2 Announce Type: replace-cross Abstract: Generative AI (GenAI) is entering K-12 classrooms, but its default culture does not always fit local teaching. Existing accounts either treat this misfit as macro-level structural bias or examine it through single-case...

https://arxiv.org/abs/2509.10780

36 CONF

From Legacy Fortran to Portable Kokkos: An Autonomous Agentic AI Workflow

ArXiv CS.AI 50%

arXiv:2509.12443v4 Announce Type: replace-cross Abstract: Scientific applications continue to rely on legacy Fortran codebases originally developed for homogeneous, CPU-based systems. As High-Performance Computing (HPC) shifts toward heterogeneous GPU-accelerated architectures,...

https://arxiv.org/abs/2509.12443

37 CONF

Cross-User Poisoning: User-Task Boundary Failures in Multi-User Collaborative Language Agents

ArXiv CS.AI 50%

arXiv:2511.17671v2 Announce Type: replace-cross Abstract: Language agents are moving from single-user assistants to shared collaborators in workspaces, forums, and group chats. A shared agent observes interleaved messages from multiple users, maintains persistent context, and...

https://arxiv.org/abs/2511.17671

38 CONF

SELF: A Robust Singular Value and Eigenvalue Approach for LLM Fingerprinting

ArXiv CS.AI 50%

arXiv:2512.03620v2 Announce Type: replace-cross Abstract: Safeguarding the Intellectual Property (IP) of Large Language Models (LLMs) against model theft represents a critical challenge in contemporary AI research. Although fingerprinting is essential for establishing forensic...

https://arxiv.org/abs/2512.03620

39 CONF

Counting Clues: A Lightweight Probabilistic Baseline Can Match an LLM

ArXiv CS.AI 50%

arXiv:2512.12868v2 Announce Type: replace-cross Abstract: Large language models (LLMs) excel on multiple-choice clinical diagnosis benchmarks, yet it is unclear how much of this performance reflects underlying probabilistic reasoning. We study this through questions from MedQA...

https://arxiv.org/abs/2512.12868

40 CONF

SkipCat: Rank-Maximized Low-Rank Compression of Large Language Models via Shared Projection and Block Skipping

ArXiv CS.AI 50%

arXiv:2512.13494v2 Announce Type: replace-cross Abstract: Large language models (LLM) have achieved remarkable performance across a wide range of tasks. However, their substantial parameter sizes pose significant challenges for deployment on edge devices with limited...

https://arxiv.org/abs/2512.13494

41 CONF

A swap-adversarial framework for domain generalization in pre- and post-stimulation Parkinsonian state classification

ArXiv CS.AI 50%

arXiv:2602.10528v3 Announce Type: replace-cross Abstract: We propose a novel swap-adversarial framework that mitigates high inter-subject variability and the high-dimensional low-sample-size problem in electrocorticography (ECoG) data. It achieves robust domain generalization...

https://arxiv.org/abs/2602.10528

42 CONF

MIDAS: Mosaic Input-Specific Differentiable Architecture Search

ArXiv CS.AI 50%

arXiv:2602.17700v2 Announce Type: replace-cross Abstract: Differentiable Neural Architecture Search (NAS) provides efficient, gradient-based methods for automatically designing neural networks, yet its adoption remains limited in practice. We present MIDAS, an approach that...

https://arxiv.org/abs/2602.17700

43 CONF

When AI Agrees Too Much: Manipulating Automated Code Review via Bias Injection

ArXiv CS.AI 50%

arXiv:2603.18740v5 Announce Type: replace-cross Abstract: Automated Code Review (ACR) systems integrating Large Language Models (LLMs) are increasingly adopted in software development workflows, ranging from interactive assistants to autonomous agents in CI/CD pipelines. In this...

https://arxiv.org/abs/2603.18740

44 CONF

One-Shot Localisation of the Global Minimum of a Noisy One-Dimensional Function: A Controlled Comparison of an Iterative Neural Minimizer, Set Transformers and Classical Estimators

ArXiv CS.AI 50%

arXiv:2604.03614v5 Announce Type: replace-cross Abstract: We study passive global optimisation: from twenty noisy samples of an unknown one-dimensional function, with no further queries, estimate where its global minimum lies. We build a benchmark and a self-checking harness and...

https://arxiv.org/abs/2604.03614

45 CONF

Clinical Note Bloat Reduction for Efficient LLM Use

ArXiv CS.AI 50%

arXiv:2604.16364v3 Announce Type: replace-cross Abstract: Background: Clinical notes contain extensive duplicated text from templates, copy-paste, and auto-populated fields ("note bloat"), diluting clinical signal, limiting longitudinal context, and increasing large language...

https://arxiv.org/abs/2604.16364

46 CONF

Scoring-Rule Sensitivity in LLM Evaluation: Evidence from Indian Financial Regulatory Text

ArXiv CS.AI 50%

arXiv:2604.19298v3 Announce Type: replace-cross Abstract: A benchmark leaderboard reports one accuracy number, but that number is a joint product of a model and a scoring rule. We ask what changes when only the rule changes, and find that model ordering is highly sensitive to...

https://arxiv.org/abs/2604.19298

47 CONF

TokenMinds: Pretrained User Tokens and Embeddings for User Understanding in Large Recommender Systems

ArXiv CS.AI 50%

arXiv:2606.25147v2 Announce Type: replace-cross Abstract: User modeling in industrial recommender systems typically produces dense embeddings, which suffer from representational constraints due to fixed-dimensional vectors. As an emerging alternative for discrete user...

https://arxiv.org/abs/2606.25147

48 CONF

TextCloak: Safeguarding Data from Unauthorized LLM Fine-Tuning via RL-Driven Unlearnable Examples

ArXiv CS.AI 50%

arXiv:2607.28862v2 Announce Type: replace-cross Abstract: The development of Large Language Models (LLMs) has led to significant advances across a wide range of language tasks, while simultaneously raising growing concerns about unauthorized online data exploitation and privacy...

https://arxiv.org/abs/2607.28862

49 CONF

First-Order LoRA Training with Phone NPUs

ArXiv CS.AI 50%

arXiv:2610.24816v2 Announce Type: replace-cross Abstract: On-device fine-tuning lets a large language model (LLM) learn from its user's private data without uploading it. Low-rank adaptation (LoRA) reduces the trainable parameters, but each first-order training step still...

https://arxiv.org/abs/2610.24816

50 CONF

Silent and Costly: Characterizing and Detecting Prompt-Caching Mis-Integration in LLM Agents

ArXiv CS.AI 50%

arXiv:2610.34817v2 Announce Type: replace-cross Abstract: Large language model (LLM) services process massive volumes of user requests, resulting in substantial inference costs. To reduce both cost and latency, providers have introduced prompt caching. However, correctly...

https://arxiv.org/abs/2610.34817

51 CONF

Pretraining Knows What, Simulation Teaches How: Compositional Generalization in a Sim-Trained Robot Agent

ArXiv CS.AI 50%

arXiv:2610.35817v2 Announce Type: replace-cross Abstract: A robot policy needs to understand what a task is asking for in a scene, and how to move the robot to accomplish that task. To achieve these two skills, we introduce Zero-real Agent Policy (ZAP), a recipe that teaches a...

https://arxiv.org/abs/2610.35817