

## Problem Set 3 Exercise #17: Sort Three Digits

**Reference:** Lecture 7 notes

**Learning objective:** Sorting

**Estimated completion time:** 30 minutes

### Problem statement:

We have illustrated Bubble Sort algorithm using integer arrays in lecture. Determining whether one element, say `arr[i]`, is greater than its neighbour `arr[i+1]`, is simply done by comparing them (i.e. `if (arr[i] > arr[i+1])`).

What if the array elements are more complex (for example, each element is a string, or is an object – we will cover string and object later), or the comparison criterion is more complex?

Suppose you want to sort an integer array in increasing order of the first 3 digits of each element, how would you modify the Bubble Sort algorithm given in the lecture notes?

For example, in the sample run #1 below, the first 3 digits of the 6 values are 123, 987, 32, 555, 801 and 729. These 6 values are thus sorted and printed out in ascending order of their first 3 digits.

Complete the skeleton program **PS3\_Ex17\_SortThreeDigits.java** for the above task.

### Sample run #1:

```
Enter the number of elements: 6
Enter 6 elements: 12345 9870 32 5555555 801784 729
Sorted array: [32, 12345, 5555555, 729, 801784, 9870]
```

### Sample run #2:

```
Enter the number of elements: 5
Enter 5 elements: 23456 3456 456 56 6
Sorted array: [6, 56, 23456, 3456, 456]
```