Neologik Onboarding - Quick Reference

Overview

This script creates resources and assigns permissions for Neologik deployment in a customer's Azure tenant.

Run: `.\Install-NeologikEnvironment.ps1` in PowerShell 7 as Administrator

Prerequisites

Required Permissions to Run Script

User must have:

- ✅ **Owner** role at subscription level
- ✅ **Global Administrator** role in Entra ID

Reason: Script assigns Azure RBAC roles (requires Owner) and Entra ID directory roles (requires Global Administrator)

---

vCPU Quota

Neologik requires sufficient vCPU quota in the target subscription and region before deployment can proceed. Check and request increases **before** running the onboarding script.

Checking current quota

1. Azure Portal → **Subscriptions** → select your subscription → **Usage + quotas**
2. Filter by your target region and search for `Standard D2ds v6` or `Standard DC2ds v6` to see current usage vs. limit

Requesting an increase

Azure Portal → **Usage + quotas** → select the quota line → **New Quota Request**

Azure OpenAI Quota

Neologik requires sufficient Azure OpenAI token quota in the target region before deployment can proceed. Check and request increases **before** running the onboarding script.

Checking current quota

1. Sign in to Azure AI Foundry
2. Navigate to **Operate** → **Quota** in the left pane

3. Find **gpt-5.4-mini** in the list and confirm you have sufficient tokens-per-minute (TPM) available in your target region

Requesting an increase

Use the Azure OpenAI quota request form. Requests typically take up to 10 business days to approve.

Variables Used

- `{org}` = Organization code (3 characters, lowercase)
- `{env}` = Environment type (`dev` or `prd` , lowercase)
- `{region}` = Azure region abbreviation (e.g., `uks` , `eus` , lowercase)
- `{index}` = Environment index (e.g., `01` , `02`)
- `{agent-name}` = Bot agent name (lowercase, max 7 characters)

Example: Organization "ABC", dev environment, UK South, index 01, bot agent name "support"

- Resource Group: `rg-neo-abc-dev-uks-01`
- Key Vault: `kvneoabcdev01`
- Storage Account: `stneodeployabcdevuks01`
- User Group: `Neologik User Group support - abc-dev`

Changes Applied by Script

1. Guest User Invitations (Entra ID)

Action: Invite Neologik users as B2B guests (if not already invited)

Source: Email addresses loaded from `NeologikGuestUsers.txt` file

Note: Guest users will only be invited if they don't already exist in the tenant

---

2. Security Groups (Entra ID)

Action: Create security groups (3+ groups depending on bot count)

Bot User Groups (one per bot):

Group Name	Members
`Neologik User Group {agent-name} - {org}-{env}`	Current user + Neologik guests

Note: If you configure 2 bots with agent names "bot" and "support", you'll get:

- `Neologik User Group bot - {org}-{env}`
- `Neologik User Group support - {org}-{env}`

Standard Groups (always created):

Group Name	Members
`Neologik NCE User Group - {org}-{env}`	Current user + Neologik guests
`Neologik Admin User Group - {org}-{env}`	Current user + Neologik guests

Scope: Entra ID tenant level

---

3. Resource Group

Action: Create resource group

Name	Location
`rg-neo-{org}-{env}-{region}-{index}`	Customer specified (e.g., uksouth)

Scope: Subscription

---

4. Role Assignments - Security Groups

Action: Assign roles to Neologik Admin User Group

Role	Scope	Principal
Contributor	Resource Group	Neologik Admin User Group

---

5. App Registration & Service Principal (Entra ID)

Action: Create app registration for GitHub deployments

Property	Value
Name	`Neologik GitHub Service Connection - {org}-{env}`
Type	Multi-tenant (AzureADMultipleOrgs)
Client Secret	Created (365-day expiration)
Secret Storage	Stored in Key Vault

Group Membership

- Added to: `Neologik Admin User Group - {org}-{env}`

---

6. Role Assignments - Service Principal

Action: Assign roles to service principal

Role	Scope	Principal
Contributor	Subscription	Service Principal
User Access Administrator	Subscription	Service Principal
Application Administrator	Entra ID (Directory Role)	Service Principal

---

7. Key Vault

Action: Create Key Vault with RBAC authorization

Property	Value
Name	`kvneo{org}{env}{index}`
Authorization	Microsoft Entra ID RBAC (no access policies)
Public Access	Enabled
Soft Delete	Enabled (Azure default)

Secrets Stored

Secret Name	Content
`neologik-deployment-service-principle-secret`	Service Principal client secret

Role Assignments

Role	Scope	Principal
Key Vault Secrets Officer	Resource Group	Neologik Admin User Group

Note: Allows group members to read/write secrets in Key Vault

---

8. Storage Account

Action: Create storage account for certificate storage

Property	Value
Name	`stneodeploy{org}{env}{region}{index}`
Authentication	Microsoft Entra ID only
Shared Key Access	Disabled
Public Access	Enabled
Blob Container	`certificate`

Role Assignments

Role	Scope	Principal
Storage Blob Data Contributor	Resource Group	Neologik Admin User Group

Note: Allows group members to upload/manage certificates

---

9. Managed Identities (User-Assigned)

Action: Create 2 managed identities

Identity 1: Script Runner Service Connection

Property	Value
Name	`neologik-script-runner-service-connection-{org}-{env}`
Display Name	`Neologik Script Runner Service Connection - {org}-{env}`

Role Assignments:

Role	Scope
Contributor	Subscription
Application Administrator	Entra ID (Directory Role)

Identity 2: SQL Managed Identity

Property	Value
Name	`neologik-sql-managed-identity-{org}-{env}`
Display Name	`Neologik SQL Managed Identity - {org}-{env}`

Role Assignments:

Role	Scope
Directory Readers	Entra ID (Directory Role)

Summary of Permissions by Scope

Subscription Level

Principal	Role
Service Principal (GitHub)	Contributor
Service Principal (GitHub)	User Access Administrator
Managed Identity (Script Runner)	Contributor

Resource Group Level

Principal	Role
Neologik Admin User Group	Contributor
Neologik Admin User Group	Key Vault Secrets Officer
Neologik Admin User Group	Storage Blob Data Contributor

Entra ID (Directory Roles)

Principal	Role
Service Principal (GitHub)	Application Administrator
Managed Identity (Script Runner)	Application Administrator
Managed Identity (SQL)	Directory Readers