

The Spectral Gap of the Normalized Laplacian in Sparse Heavy-Tailed Random Graphs: Asymptotics, Bottleneck Structure, and Modularity in Biological Networks

Leonid L. Kuzmin

M.Sc.

kuzminll@vk.com

September 21, 2026

Abstract

We study the second eigenvalue λ_2 of the normalized Laplacian $L = I - D^{-1/2}AD^{-1/2}$ in sparse random graphs with a heavy-tailed degree distribution $P(D = k) \sim Ck^{-\gamma}$ in the regime $\bar{d}_{\min} = O(1)$, which is not covered by the classical Chung–Lu–Vu theory. We argue that the exponent γ alone is insufficient: the order of λ_2 is determined by the competition of three scales — low-degree periphery, modular cuts, and hubs/the core. We introduce a diagnostic system consisting of the conductance ratio $\Delta = \varphi_{\text{mod}}/\varphi_{\text{periph}}$, the volume fraction ρ_* of the minimal cut, the localization of the second eigenvector measured by the inverse participation ratio $\text{IPR}(v_2)$, and the full sweep-cut conductance profile $\varphi(\rho)$. These quantities distinguish a peripheral bottleneck from macroscopic modularity and from a core-dominated regime. We propose a phase diagram in the coordinates $(\log \Delta, \rho_*)$ and a computational protocol for constructing it, and we discuss a careful biological interpretation: a small λ_2 by itself does not identify functional modularity.

Keywords: normalized Laplacian; spectral gap; heavy-tailed degree distribution; configuration model; conductance; Cheeger inequality; eigenvector localization; modularity; biological networks.

Contents

1	Introduction and Motivation	1
2	Known Results	2
3	Why the Exponent γ Alone Is Insufficient	2
4	Three Spectral Gaps	2
5	Three Mechanisms Producing a Small λ_2	3
6	Two Types of Bottleneck	3
7	Diagnostic Parameters	4
8	Phase Diagram (Hypothetical)	5
9	Hypotheses	5

10 Target Results	5
11 Mathematical Setup	6
12 Numerical Experiments	6
13 Computing φ_{periph} and φ_{mod}	6
14 Sweep-Cut Pseudocode	7
15 Biological Interpretation	8
16 Relation to Hubs	9
17 Four-Level Structure of the Project	9
18 Main Research Question	9
19 Open Questions and Risks	9
20 Plan	10
A Numerical Implementation	10

1 Introduction and Motivation

Starting point. The goal is to obtain the exact asymptotics of the second eigenvalue λ_2 of the normalized Laplacian for sparse random graphs with a heavy-tailed degree distribution $P(D = k) \sim Ck^{-\gamma}$ in the regime $\bar{d}_{\min} = O(1)$, which lies outside the scope of the Chung–Lu–Vu theorem.

Problem with the naive formulation. The statement is too broad and, for some parameter values, trivially false. In the sparse regime λ_2 may be zero because the graph is disconnected, and after removing small components it may have a completely different order of magnitude. This is not a technical detail but a central part of the problem.

Correction. Instead of a single formula $\lambda_2 \sim f(\gamma, \bar{d}, n)$ one must build a *phase diagram* for the order of λ_2 as a function of

$$\gamma, \quad d_{\min}, \quad d_{\max}, \quad \bar{d}, \quad n, \quad (1)$$

and, most importantly, of the *structure of the low-degree tail*.

2 Known Results

- **Chung–Lu–Vu [6].** For random graphs with prescribed expected degrees, when $\bar{d}_{\min} \gg \ln^2 n$ the spectrum of the normalized Laplacian concentrates around the predicted behaviour; the results include power-law graphs. The gap estimate reads

$$\lambda(G) \geq 1 - 4\bar{d}^{-1/2} - \bar{d}_{\min}^{-1} \ln^2 n. \quad (2)$$

For $\bar{d}_{\min} \leq \ln^2 n$ the bound (2) becomes vacuous.

- **Coja-Oghlan–Lanka [8].** In the sparse regime $\bar{d}_{\min} = O(1)$ there exists a large core whose spectral gap of the normalized Laplacian stays separated from zero:

$$\lambda_2(L_{\text{core}}) \geq 1 - c_0 \bar{d}_{\min}^{-1/2} \quad (3)$$

with high probability. The statement concerns the *core*, not the whole graph.

- **For $G(n, p)$ with bounded average degree d .** The spectral gap of the whole graph satisfies $\lambda_2 = o(1)$, whereas the giant component or the core may have a gap of order one.

Remark 2.1 (key consequence).

$$\lambda_2(G) \not\sim \lambda_2(\text{core}(G)). \quad (4)$$

3 Why the Exponent γ Alone Is Insufficient

Let $P(D = k) \sim Ck^{-\gamma}$. This determines the tail for large k , but λ_2 is highly sensitive to *small* degrees.

Counterexample. Two degree sequences with the same $\gamma = 2.5$:

- model A: $P(D = 1) > 0$;
- model B: $P(D = 1) = 0$, $P(D \geq 2) = 1$.

They have the same asymptotic tail but completely different behaviour of λ_2 . Model A produces leaves and finite components; model B may be substantially more connected.

$$\gamma \text{ does not determine } \lambda_2. \quad (5)$$

A hard counterexample. Consider a configuration model with $P(D = 1) = p_1 > 0$. At bounded average degree such graphs naturally contain small components and dangling structures. If the graph is disconnected then $\lambda_2(L) = 0$. Consequently, no nontrivial formula of the form $\lambda_2 \sim f(\gamma) > 0$ can hold for the whole graph.

4 Three Spectral Gaps

Object	Notation	What it captures
Whole graph	$\lambda_2(G)$	Global connectivity; $\lambda_2 = 0$ if disconnected
Giant component	$\lambda_2(G_{\text{giant}})$	The meaningful quantity for sparse heavy-tailed networks
2-core	$\lambda_2(G_{2\text{core}})$	A nonzero asymptotic lower bound even for $\bar{d}_{\min} = O(1)$

Table 1: The three levels of the spectral gap.

Hypothesis 1 (ordering of the gaps).

$$\lambda_2(G) \ll \lambda_2(G_{\text{giant}}) \lesssim \lambda_2(G_{2\text{core}}). \quad (6)$$

5 Three Mechanisms Producing a Small λ_2

1. **Small components:** $\lambda_2(G) = 0$.
2. **Dangling trees:** long “whiskers” create a small conductance; by Cheeger’s inequality $\lambda_2 \leq 2\varphi$, so a sufficiently long thin pendant structure can drive $\lambda_2 \rightarrow 0$.
3. **Genuine modularity:** two large dense communities joined by a small cut give $\varphi \ll 1$ and hence $\lambda_2 \ll 1$.

Key distinction.

$$\text{small } \lambda_2 \implies \text{a weak global cut exists,} \quad (7)$$

but

$$\text{small } \lambda_2 \not\Rightarrow \text{biological modularity.} \quad (8)$$

One must separate a *community bottleneck* from a *peripheral bottleneck*.

6 Two Types of Bottleneck

Let

$$\text{vol}(S) = \sum_{v \in S} d_v, \quad \varphi(S) = \frac{|\partial S|}{\text{vol}(S)}. \quad (9)$$

Definition 6.1 (peripheral bottleneck).

$$\varphi_{\text{periph}}(G) = \min_{\substack{S \subset V \\ 0 < \text{vol}(S) \leq \varepsilon \text{vol}(V)}} \varphi(S), \quad (10)$$

where $\varepsilon \ll 1$, for example $\varepsilon = 0.05$.

Definition 6.2 (modular bottleneck).

$$\varphi_{\text{mod}}(G) = \min_{\substack{S \subset V \\ \varepsilon \text{vol}(V) \leq \text{vol}(S) \leq \frac{1}{2} \text{vol}(V)}} \varphi(S). \quad (11)$$

Hence

$$\varphi(G) = \min\{\varphi_{\text{periph}}, \varphi_{\text{mod}}\}. \quad (12)$$

By Cheeger's inequality [10, 11],

$$\frac{\varphi(G)^2}{2} \leq \lambda_2 \leq 2\varphi(G). \quad (13)$$

Thus we obtain not a “decomposition of λ_2 ” but a *classification of the mechanism that creates the global bottleneck*.

7 Diagnostic Parameters

Definition 7.1 (competition parameter).

$$\Delta(G) = \frac{\varphi_{\text{mod}}(G)}{\varphi_{\text{periph}}(G)} \quad (14)$$

with the interpretation:

- $\Delta \gg 1$ — the peripheral bottleneck is cheaper;
- $\Delta \ll 1$ — the modular bottleneck is cheaper;
- $\Delta \approx 1$ — a transitional regime.

For numerical stability we work with

$$\log \Delta = \log \varphi_{\text{mod}} - \log \varphi_{\text{periph}}. \quad (15)$$

Definition 7.2 (scale of the minimal cut).

$$\rho(S) = \frac{\text{vol}(S)}{\text{vol}(V)}, \quad \rho_* = \rho(S_*), \quad S_* = \arg \min_S \varphi(S). \quad (16)$$

Interpretation:

- $\rho_* = O(n^{-1})$ — a small local structure;
- $\rho_* = O(1)$ — a macroscopic separation of the graph.

Spectral versus combinatorial cut.

$$\rho_2 = \frac{\text{vol}(\{v : f_2(v) > 0\})}{\text{vol}(V)}. \quad (17)$$

If $\rho_2 \approx \rho_*$ the spectral cut coincides with the combinatorial one; otherwise λ_2 is controlled not by the minimal cut but by an “averaged” behaviour.

Multiple bottlenecks. The difference $\lambda_3 - \lambda_2$: a small difference indicates several competing cuts of similar conductance. This is a useful symptom but not a criterion; it must be complemented by the localization of the eigenvectors.

Definition 7.3 (localization of the second eigenvector).

$$\text{IPR}_2(v) = \frac{\sum_i v_i^4}{(\sum_i v_i^2)^2}, \quad \text{IPR}_2^\pi(v) = \sum_i w_i^2, \quad w_i \propto \pi_i v_i^2, \quad (18)$$

where $\pi_i = d_i / \text{vol}(V)$ is the stationary measure of the random walk.

Interpretation:

- a delocalized mode (modularity, macroscopic cut): $\text{IPR}_2 \sim 1/n$;
- a localized mode (periphery): $\text{IPR}_2 \sim 1/k$ on a support of size k ; an estimate of the support is $\text{PR}_2 = 1/\text{IPR}_2$.

Remark 7.4. The IPR is informative only when λ_2 is *non-degenerate*. If λ_2 has high multiplicity (for instance $n - 1$ for K_n), the eigenvector is not unique and the IPR is not well defined.

Conductance profile. Instead of a fixed threshold ε one may use the full sweep-cut profile $\varphi(\rho)$ along f_2 in both directions and identify the regimes *post hoc*.

Diagnostic space: $(\log \Delta, \rho_*, \text{IPR}_2)$.

8 Phase Diagram (Hypothetical)

9 Hypotheses

Hypothesis 2 (H1). For a sparse heavy-tailed configuration model with $P(D = k) \sim k^{-\gamma}$, the asymptotics of $\lambda_2(G)$ is determined not by γ alone but by the competition of three scales:

$$\text{low-degree structures} \leftrightarrow \text{community cuts} \leftrightarrow \text{hub/core structure}. \quad (19)$$

Hypothesis 3 (H2). For the whole graph, in the presence of a positive fraction of low-degree vertices, $\lambda_2(G) \rightarrow 0$ may be a trivial consequence of the periphery or of disconnection.

Hypothesis 4 (H3). After passing to the giant component or the 2-core, $\lambda_2(G_{2\text{core}})$ may remain separated from zero in a regime where the classical Chung–Lu–Vu theory [6] is not applicable.

Hypothesis 5 (H4). If a planted modular structure is added, a different scale appears:

$$\lambda_2 \asymp \varphi_{\text{module}} \quad (20)$$

up to squared or linear factors dictated by Cheeger’s inequality (13).




Figure 1: Hypothetical phase diagram in the coordinates $(\log \Delta, \rho_*)$.

10 Target Results

Target theorem.

$$\lambda_2(G_n) = \Theta(f(n, \gamma)) \quad (21)$$

in a suitable regime. Separately,

$$\lambda_2(G_n^{2\text{core}}) = \Theta(g(\gamma, \bar{d})) \quad (22)$$

under different assumptions. If an exact asymptotic law cannot be obtained, then

$$c f(n, \gamma) \leq \lambda_2 \leq C f(n, \gamma) \quad (23)$$

is already a complete result.

11 Mathematical Setup

The configuration model [1, 15, 16] with a deterministic degree sequence $d_1, \dots, d_n$:

$$\sum_i d_i \equiv 0 \pmod{2}, \quad N_k(n) = \#\{i : d_i = k\} \sim c n k^{-\gamma}. \quad (24)$$

We vary

$$d_{\min} = 1, 2, 3, \dots, \quad d_{\max} \sim n^{1/(\gamma-1)} \quad (25)$$

or use a controlled cutoff.

Methods: message-passing approaches for arbitrary degree distributions; spectral methods for configuration models [21, 22, 3].

12 Numerical Experiments

For each $(n, \gamma, d_{\min})$ we generate ≈ 100 realizations with $n = 10^3, 10^4, 10^5, \dots$ (and additional small sizes $n = 100, \dots$ to probe the transitional regime). For each realization we compute

$$\lambda_2(G), \quad \lambda_2(G_{\text{giant}}), \quad \lambda_2(G_{2\text{core}}), \quad (26)$$

$$\varphi(G), \quad \varphi(G_{\text{giant}}), \quad \varphi(G_{2\text{core}}), \quad (27)$$

$$d_{\max}, \quad \bar{d}, \quad N_1, \quad N_2. \quad (28)$$

We also record Δ , ρ_* , ρ_2 , $\lambda_3 - \lambda_2$, $\text{IPR}_2(v_2)$ and the conductance profile $\varphi(\rho)$.

Scaling. We plot $\log \lambda_2$ against $\log n$. If $\lambda_2 \sim n^{-\alpha}$ then

$$\log \lambda_2 = -\alpha \log n + C, \quad (29)$$

and α is estimated statistically. We separately estimate the exponent in $\lambda_2 \sim (\varphi_*)^\alpha$; by Cheeger's inequality (13) one expects $\alpha \in [1, 2]$ when φ_* is the controlling conductance.

Ensemble	What we test
Power-law $d_{\min} = 1$	periphery
Power-law $d_{\min} = 2$	chains / 2-core
Power-law $d_{\min} = 3$	expander-like core
Power-law + planted communities	genuine modularity

Table 2: The four experimental ensembles.

Remark 12.1. For $d_{\min} \geq 2$ there are no leaves, hence the 2-core coincides with the whole graph: $G_{2\text{core}} = G$ (up to disconnected small components). The core analysis is therefore non-trivial only when low-degree vertices are present, i.e. essentially for $d_{\min} = 1$.

13 Computing φ_{periph} and φ_{mod}

Approach 1: spectral approximation via sweep cut

1. Compute the second eigenvector f_2 of the normalized Laplacian $L = I - D^{-1/2}AD^{-1/2}$.
2. Sort the vertices by $f_2(v)$: $v_1, \dots, v_n$.
3. Sweep cut: for each $k = 1, \dots, n-1$ consider $S_k = \{v_1, \dots, v_k\}$ and evaluate $\varphi(S_k)$.
4. Locate the minima:

$$\varphi_{\text{periph}}^{\text{spec}} = \min\{\varphi(S_k) : \text{vol}(S_k) \leq \varepsilon \text{vol}(V)\}, \quad (30)$$

$$\varphi_{\text{mod}}^{\text{spec}} = \min\{\varphi(S_k) : \varepsilon \text{vol}(V) \leq \text{vol}(S_k) \leq \frac{1}{2} \text{vol}(V)\}. \quad (31)$$

5. Record the corresponding ρ_* .

Complexity: $O(m \cdot \text{iter} + n \log n)$.

Approach 2: local Cheeger with seed sets

1. Choose seed sets (low-degree vertices for the periphery; hubs or random vertices for modularity).
2. Apply local clustering to each seed (Andersen–Chung–Lang, PageRank-based) [13].
3. Collect all found sets S and evaluate $\varphi(S)$.
4. Filter by volume.

Complexity: $O(nm \log n / \varphi^2)$.

Recommendation. Start with the spectral sweep cut. If $\rho_2 \neq \rho_*$, add local clustering for verification.

14 Sweep-Cut Pseudocode

```
import numpy as np
from scipy.sparse.linalg import eigsh

def spectral_diagnostics(L, degrees, adj, eps=0.05):
    n = len(degrees)
    vol_V = degrees.sum()

    vals, vecs = eigsh(L, k=2, which='SM')
    lambda2 = vals[1]
    f2 = vecs[:, 1]

    order = np.argsort(f2)

    vol_S = 0
    cut_size = 0
    in_S = np.zeros(n, dtype=bool)

    phi_periph = np.inf
    phi_mod = np.inf
    rho_periph = None
    rho_mod = None

    for k in range(n - 1):
        v = order[k]
        in_S[v] = True
        vol_S += degrees[v]

        for u in adj[v]:
            if in_S[u]:
                cut_size -= 1
            else:
                cut_size += 1

        if vol_S == 0:
            continue
        phi = cut_size / vol_S

        if vol_S <= eps * vol_V:
            if phi < phi_periph:
                phi_periph = phi
                rho_periph = vol_S / vol_V
        elif vol_S <= 0.5 * vol_V:
            if phi < phi_mod:
                phi_mod = phi
                rho_mod = vol_S / vol_V

    log_Delta = np.log(phi_mod) - np.log(phi_periph) if phi_periph > 0
    else np.inf

    return {'lambda2': lambda2, 'phi_periph': phi_periph,
            'phi_mod': phi_mod, 'rho_periph': rho_periph,
            'rho_mod': rho_mod, 'log_Delta': log_Delta}
```

The repository implementation is in `src/diagnostics.py`.

15 Biological Interpretation

A caveat on the word “robustness”. λ_2 characterizes global connectivity/expansion and, through Cheeger’s inequality, is tied to bottlenecks. For the random walk $P = D^{-1}A$ one has $\mu_2 = 1 - \lambda_2$; a small λ_2 corresponds to slow relaxation of the random walk. This can be interpreted as *structural integration* of the network, but not automatically as biological robustness.

One must specify which notion of robustness is meant:

- robustness to node removal;
- robustness to edge removal;
- persistence of the giant component;
- robustness of flows/diffusion;
- robustness of functional modules.

Scale of functional segregation via ρ_* :

- $\rho_* \approx 0.5$ — two large halves (two hemispheres, two metabolic regimes);
- $\rho_* \approx 0.1$ — a small module separated from the rest;
- $\rho_* \approx n^{-1}$ — a single vertex or a small group.

In biological networks a small λ_2 does not by itself identify functional modularity. The proposed analysis additionally determines the scale of the minimal bottleneck and distinguishes local periphery from macroscopic separation of the network.

16 Relation to Hubs

A heavy tail produces $d_{\max} \gg \bar{d}$. Hubs strongly affect the spectrum of the adjacency matrix: unusually high degrees may generate isolated eigenvalues with eigenvectors localized around the hubs. This does *not* imply that hubs necessarily increase λ_2 .

An important distinction:

$$\lambda_{\max}(A) \quad \text{and} \quad \lambda_2(L) \tag{32}$$

sense different properties of the network. A hub may drastically change the upper part of the spectrum while leaving the global bottleneck essentially unchanged.

17 Four-Level Structure of the Project

Level I — mathematical model. Configuration model: $(d_1, \dots, d_n)$, $N_k(n) \sim cnk^{-\gamma}$. We vary $\gamma, d_{\min}, d_{\max}, n$.

Level II — spectral asymptotics. We study $\lambda_2(G)$, $\lambda_2(G_{\text{giant}})$, $\lambda_2(G_{2\text{core}})$.

Level III — mechanism of the gap. We measure $\varphi_{\text{periph}}, \varphi_{\text{mod}}, \Delta, \rho_*, \text{IPR}_2$ and test $\lambda_2 \leftrightarrow \min(\varphi_{\text{periph}}, \varphi_{\text{mod}})$.

Level IV — biological interpretation. We check whether an observed small gap corresponds to peripheral sparsity or to macroscopic modular organization, and only then discuss implications for robustness / functional integration.

18 Main Research Question

How do the low-degree periphery and the heavy tail of the degree distribution jointly determine the asymptotics of the second eigenvalue of the normalized Laplacian in sparse random graphs, and how can the pair (Δ, ρ_*) together with the localization of v_2 distinguish a decrease of λ_2 caused by a peripheral bottleneck from one caused by macroscopic modularity?

The potential outcome is not merely a formula but a *theory of the regimes in which a small spectral gap arises*.

19 Open Questions and Risks

- **Computability of φ :** exact computation is NP-hard; an explicit approximation (sweep cut or local clustering) is required.
- **Stability of Δ :** use $\log \Delta$.
- **Relation to the eigenvector:** compare ρ_2 and ρ_* .
- **Multiple bottlenecks:** include $\lambda_3 - \lambda_2$ and the IPR.
- **2-core versus giant component:** clarify when they coincide and when they differ.
- **Spread-out periphery:** if the low-degree vertices are not compact, φ_{periph} may be uninformative; this must be checked numerically.
- **Analytical part:** it may prove intractable; a fallback is numerical hypotheses together with partial bounds.
- **Biological interpretation:** requires caution; λ_2 should not be called a measure of “robustness” without qualification.

20 Plan

1. Implement graph generation for the four ensembles.
2. Implement the sweep cut for $\varphi_{\text{periph}}, \varphi_{\text{mod}}, \Delta, \rho_*, \text{IPR}_2$.
3. Run numerical experiments for $n = 10^2, \dots, 10^5$.
4. Build the phase diagram in $(\log \Delta, \rho_*)$.
5. Test the hypothesis $\lambda_2 \leftrightarrow \min(\varphi_{\text{periph}}, \varphi_{\text{mod}})$.
6. Formulate empirical hypotheses for the order of λ_2 in each regime.
7. Attempt an analytical derivation for the simplest case (a mixed-regular graph with two degree types).
8. Prepare the results as a preprint (arXiv: math.SP, math.CO, q-bio.MN).

A Numerical Implementation

File	Purpose
<code>run_experiments.py</code>	orchestration of the four ensembles, CSV output, α estimation
<code>analyze_results.py</code>	scaling exponents, phase diagram, regime classification
<code>src/generators.py</code>	degree sequences, erased configuration model, planted block model
<code>src/diagnostics.py</code>	λ_2 (G/giant/2-core), sweep cut, φ, Δ, ρ , IPR, $\varphi(\rho)$

The smallest eigenvalues are computed in a numerically stable way via $M = I - \frac{1}{2}L = \frac{1}{2}(I + D^{-1/2}AD^{-1/2})$: small λ correspond to large eigenvalues of M , so we use `eigsh(M, which="LA")` and then transform $\lambda = 2(1 - \mu)$.

The code is validated on graphs with known spectra: K_n ($\lambda_2 = n/(n-1)$), C_n ($\lambda_2 = 1 - \cos(2\pi/n)$), P_n ($\lambda_2 = 1 - \cos(\pi/(n-1))$), $K_{a,b}$ ($\lambda_2 = 1$), and disjoint unions ($\lambda_2 = 0$).

References

- [1] E. A. Bender, E. R. Canfield. The asymptotic number of labeled graphs with given degree sequences. *Journal of Combinatorial Theory, Series A* **24**(3):296–307, 1978.
- [2] B. Bollobás, O. Riordan. The diameter of a scale-free random graph. *Combinatorica* **24**(1):5–34, 2004.
- [3] C. Bordenave, M. Lelarge, L. Massoulié. Non-backtracking spectrum of random graphs: community detection and non-regular Ramanujan graphs. *Annals of Probability* **46**(1):1–71, 2018.
- [4] F. Chung. *Spectral Graph Theory*. CBMS Regional Conference Series in Mathematics, vol. 92, AMS, 1997.
- [5] F. Chung, L. Lu. *Complex Graphs and Networks*. CBMS Regional Conference Series in Mathematics, vol. 107, AMS, 2006.
- [6] F. Chung, L. Lu, V. Vu. Spectra of random graphs with given expected degrees. *Proceedings of the National Academy of Sciences* **100**(11):6313–6318, 2003.
- [7] F. Chung, M. Radcliffe. On the spectra of general random graphs. *Electronic Journal of Combinatorics* **18**(1), P215, 2011.
- [8] A. Coja-Oghlan, S. Lanka. Finding planted partitions in random graphs with general degree distributions. *SIAM Journal on Discrete Mathematics* **23**(4):1682–1714, 2009.
- [9] A. Coja-Oghlan, S. Lanka. The spectral gap of random graphs with given expected degrees. *Electronic Journal of Combinatorics* **16**(1), R138, 2009.
- [10] J. Cheeger. A lower bound for the smallest eigenvalue of the Laplacian. In *Problems in Analysis*, Princeton University Press, 195–199, 1970.
- [11] R. Kannan, S. Vempala, A. Vetta. On clusterings: good, bad and spectral. *Journal of the ACM* **51**(3):497–515, 2004.
- [12] S. Arora, S. Rao, U. Vazirani. Expander flows, geometric embeddings and graph partitioning. *Journal of the ACM* **56**(2), 2009.
- [13] R. Andersen, F. Chung, K. Lang. Local graph partitioning using PageRank vectors. *FOCS 2006*, 475–486.

- [14] J. R. Lee, S. Oveis Gharan, L. Trevisan. Multi-way spectral partitioning and higher-order Cheeger inequalities. *STOC 2012*, 1117–1130.
- [15] M. Molloy, B. Reed. A critical point for random graphs with a given degree sequence. *Random Structures & Algorithms* **6**(2–3):161–180, 1995.
- [16] M. Molloy, B. Reed. The size of the giant component of a random graph with a given degree sequence. *Combinatorics, Probability and Computing* **7**(3):295–305, 1998.
- [17] B. Pittel, J. Spencer, N. Wormald. Sudden emergence of a giant k -core in a random graph. *Journal of Combinatorial Theory, Series B* **67**(1):111–151, 1996.
- [18] S. Janson, T. Łuczak, A. Ruciński. *Random Graphs*. Wiley-Interscience, 2000.
- [19] A.-L. Barabási, R. Albert. Emergence of scaling in random networks. *Science* **286**(5439):509–512, 1999.
- [20] M. Faloutsos, P. Faloutsos, C. Faloutsos. On power-law relationships of the Internet topology. *SIGCOMM 1999*, 251–262.
- [21] S. N. Dorogovtsev, A. V. Goltsev, J. F. F. Mendes, A. N. Samukhin. Spectra of complex networks. *Physical Review E* **68**, 046109, 2003.
- [22] B. Söderberg. General formalism for inhomogeneous random graphs. *Physical Review E* **66**, 066121, 2002.
- [23] M. E. J. Newman, M. Girvan. Finding and evaluating community structure in networks. *Physical Review E* **69**, 026113, 2004.
- [24] M. E. J. Newman. Modularity and community structure in networks. *PNAS* **103**(23):8577–8582, 2006.
- [25] A. Decelle, F. Krzakala, C. Moore, L. Zdeborová. Asymptotic analysis of the stochastic block model for modular networks and its algorithmic applications. *Physical Review E* **84**, 066106, 2011.
- [26] E. Abbe. Community detection and stochastic block models: recent developments. *Journal of Machine Learning Research* **18**(177):1–86, 2018.
- [27] R. Albert, H. Jeong, A.-L. Barabási. Error and attack tolerance of complex networks. *Nature* **406**:378–382, 2000.
- [28] R. Albert, A.-L. Barabási. Statistical mechanics of complex networks. *Reviews of Modern Physics* **74**(1):47–97, 2002.
- [29] M. E. J. Newman. *Networks: An Introduction*. Oxford University Press, 2010.
- [30] A. Barrat, M. Barthélemy, A. Vespignani. *Dynamical Processes on Complex Networks*. Cambridge University Press, 2008.