

NEOTRO PROTOCOL

FOUNDATIONAL CHARTER No. 0

Observer Protocol Charter

Document Type	Foundational Charter / Protocol Position Statement
Charter Number	No. 0
Core Definition	Neotro Protocol is an Observer Protocol.
Primary Role	To define the position, boundary, and licensing interpretation of Neotro Protocol.
Use in License Package	Interpretive foundation for scope, mode, window, output, and responsibility boundaries.
Control Boundary	Human-review-only / No Auto-Control / No certified or operational claim by default.
Status	English canonical charter for public, license, and AI-readable protocol interpretation.
File Status	Final v1.0 Charter for license-package interpretation and AI-readable protocol distribution

Charter Function:

This Charter defines Neotro Protocol as an observer protocol positioned between industrial systems, AI-assisted judgment, and human review. It does not grant commercial deployment rights, certified diagnostic rights, operational-use validation rights, or automatic-control authority.

Preamble

This Foundational Charter establishes the industrial position of Neotro Protocol. It is not a product brochure, a diagnostic claim, a control specification, or a commercial license grant. It is an interpretive charter that defines where Neotro Protocol stands: above domain-specific systems as a non-invasive observer protocol, and before operational action as a human-review boundary layer.

Foundational Sentence:

Neotro Protocol is an Observer Protocol.

Article I. Core Definition

Neotro Protocol is not a solution that directly improves, controls, replaces, or modifies a specific device, process, model, or industrial system. Neotro Protocol reads state transitions, review necessity, and responsibility boundaries between industrial systems and AI-assisted judgment. Its most basic definition is therefore direct and structural: Neotro Protocol is an Observer Protocol. - It observes state-transition positions rather than replacing original process functions. - It provides human-review reference signals rather than automatic-control commands. - It can be applied across domains because its role is positional, not tied to one equipment class. - It gives a common review language to raw signals, existing system outputs, candidate states, recovery contexts, and rebound conditions.

Article II. Personal Use and Industrial Use

The same Neotro principle can appear in personal creation, market judgment, and industrial domains. The difference is not the inner state-reading structure, but the way the structure becomes externally auditable.

II-1. Personal Use

- In creative or personal judgment contexts, intuition, embodied context, prior experience, and sensory recognition may operate together.
- This mode can be fast and dense, but it is difficult for an external reviewer to audit in full.

II-2. Industrial Use

- In industrial use, data, baselines, labels, observation windows, operators, audit tables, review states, engineer review, and responsibility boundaries are externalized.
- Once these elements are externalized, Neotro appears not as personal intuition, but as an organizationally auditable observer protocol.

Industrial Objectification Principle:

Neotro may originate from state-reading structure, but in industrial use it becomes objective through data, baseline, label, window, audit table, review state, and responsibility boundary externalization.

Article III. Position of Use

Neotro is not attached indiscriminately to an entire domain. It must be positioned within a defined process, observation window, operating mode, and responsibility line. The important question is not simply whether Neotro can

become real-time or shadow-mode. The important questions are the following: - Which process does it observe? - Is the use case development-stage, retrospective, shadow-mode, or real-time review? - Is the output read-only, dashboard-level, report-only, API-level, or review-queue-level? - Who receives the output? - Is it connected to an existing control system, or kept outside any control path? - Could Neotro be misinterpreted as a cause of an incident if used outside its authorized scope? The same Neotro principle may be used in different ways: public or historical log review, pre-transition human-review candidate detection, shadow-mode dashboarding, or real-time alert-review. Each mode requires different scope, responsibility, logging, authorization, and licensing boundaries.

Article IV. Licensing Structure Principle

Neotro commercial value does not arise from selling the entire technology at once. It arises from licensing an objectively defined observer position by domain, process, mode, window, output type, and integration boundary.

License Dimension	Example	Purpose
Domain license	Battery, medical, telecom, AI infrastructure	Defines the domain of authorized observation.
Process-scope license	Charging process, thermal management, quality review	Defines which process may be observed.
Mode license	Retrospective, shadow, real-time read-only	Defines the operational posture.
Window-volume license	100 / 300 / 500 windows	Defines the evaluation or observation volume.
Integration boundary	Report-only, dashboard, API, internal review queue	Defines where output may go.
Prohibited path	Auto-control, actuator, shutdown, derating, safety fallback	Protects the system from unauthorized control interpretation.

License Boundary Principle:

A Neotro license is not only a fee structure. It is also a safety boundary that separates authorized observation position from unauthorized operational use.

Article V. Difference from Existing Stabilization Technologies

Existing systems such as BMS, PHM, SOH/RUL estimation, anomaly detection, monitoring systems, and safety fallback mechanisms perform domain-specific calculation, alerting, diagnosis, estimation, or control-related functions. Neotro does not replace them. - Existing systems calculate or alert inside the domain. - Neotro observes transition state above raw signals and existing system outputs. - Existing systems remain authoritative within their original scope. - Neotro reads whether signals and outputs are stable, conflicting, degrading, recovering, or rebound-sensitive. - Neotro provides observation, interpretation, review prioritization, and responsibility-boundary language.

Article VI. Risk Position

Neotro has a different risk position from high-risk industrial control technologies because it does not directly command devices, replace existing systems, or trigger safety fallback actions. Its default output is a human-review reference signal. - It does not directly control equipment. - It does not replace existing systems. - It does not directly alter safety fallback paths. - Its output remains human-review-only by default. - Its authorized use is limited by domain, process, mode, window, and output scope. - If misused outside the authorized observation position, the misuse can be identified by license-scope mismatch.

Risk Characterization:

Neotro is not a high-risk control technology that directly controls industrial systems. It is a low-risk, high-resolution observer protocol positioned between industrial systems and AI-assisted judgment.

Article VII. Physics Above Technology

The core conclusion of this Charter is not merely a wording decision. It defines the position of Neotro within a technical system. A technology can be explained by function. A protocol must first be understood by position. - Above existing systems, without replacing them. - Between AI-assisted judgment and human review. - Before automatic control or operational action. - Before responsibility is displaced away from human review. - On the observation boundary rather than inside the control path. - At the state-reading layer before performance or certified claims are made. Once this position is fixed, the practical rules become aligned: why No Auto-Control is required, why existing systems are not replaced, why window-based evaluation is a strength rather than a weakness, why licenses must be scoped by process and mode, and why Neotro becomes more objectively visible inside industrial organizations.

Article VIII. License Package Interpretation

This Charter should be included in the Neotro license package and AI-readable public layer as an interpretive foundation. Its role is to prevent external AI systems, partner reviewers, and commercial stakeholders from misclassifying Neotro as a battery diagnostic engine, BMS replacement, safety controller, or autonomous-control technology. - This Charter may guide how license scope, mode, window, output, and responsibility boundaries are interpreted. - This Charter does not itself grant any commercial deployment right, certified diagnostic right, operational-use validation right, production right, shadow-mode right, or automatic-control authority. - If commercial, certified, operational, production, shadow-mode, or domain-calibrated use is desired, it must be governed by a separate written agreement.

Article IX. Final Definition

English Definition:

Neotro Protocol is an observer protocol for reading state transitions across industrial and AI-assisted systems without replacing existing systems or triggering automatic control.

Operational Meaning:

Neotro Protocol provides human-review boundaries, auditability, state-transition language, and responsibility-position clarity. It does not directly diagnose, certify, control, shut down, derate, deploy, or replace domain systems by default.

Article X. Operational Boundary Clauses

The following clauses preserve the observer-protocol position fixed by this Charter and define the default operational boundary for license-package interpretation, AI-readable public layers, and partner-facing technical review.

Clause	Boundary Statement
No Auto-Control	Neotro outputs are human-review reference signals and must not directly trigger automatic control, shutdown, derating, actuator command, safety fallback, or operational enforcement unless separately authorized in writing.

Clause	Boundary Statement
Non-Replacement	Neotro does not replace existing domain systems, safety systems, BMS, PHM, SOH/RUL, anomaly detection, medical systems, telecom systems, autonomous systems, or human expert review.
Public Reference Boundary	Public-reference materials support orientation, calculation-flow rehearsal, and review-state language alignment. They do not create operational-use validation boundaries, certified claims, partner-domain performance validation, or commercial deployment rights.
License Scope Boundary	Authorized use must be limited by domain, process, mode, window, output type, integration boundary, and written scope. Use outside the authorized observation position is outside the licensed protocol boundary.

Interpretive Effect: These clauses do not create a commercial license grant, certified diagnostic authorization, operational-use validation authorization, production deployment right, or automatic-control authority. They define the default boundary unless a separate written agreement states otherwise.

Closing Statement

Neotro is not merely a solution. It is an observer protocol. Its value is not in directly changing industrial equipment or overriding existing systems. Its value is in reading state transitions between industrial systems and AI-assisted judgment, then revealing human-review positions and responsibility boundaries in an auditable form. Therefore, Neotro becomes most clearly valuable when applied to industry: not because it becomes a control layer, but because data, baselines, labels, windows, audit tables, review states, and responsibility boundaries make the observer protocol externally visible.