

Lab 7. Interactive geovisualization with Folium library

```
import folium
from folium.plugins import
MarkerCluster
import pandas as pd
df_incidents = pd.read_csv('
Police_Department_Incidents_-
_Previous_Year__2016_.csv')
limit = 1000
df_incidents =
df_incidents.iloc[0:limit, :]
df_incidents.shape
```

```
# San Francisco latitude and longitude
values // Сан-Франциско значення
широти і довготи
latitude = 37.77
longitude = -122.42
```

```
sanfran_map = folium.Map(location =
[latitude, longitude], zoom_start = 12)
```

```
sanfran_map
# instantiate a feature group for the
incidents in the dataframe
```

So the dataframe consists of 150,500 crimes, which took place in the year 2016. In order to reduce computational cost, let's just work with the first 1000 incidents in this dataset.

Let's confirm that our dataframe now consists only of 1000 crimes

Now that we reduced the data a little bit, let's visualize where these crimes took place in the city of San Francisco. We will use the default style and we will initialize the zoom level to 12.

Now that we reduced the data a little bit, let's visualize where these crimes took place in the city of San Francisco. We will use the default style and we will initialize the zoom level to 12

Now let's superimpose the locations of the crimes onto the map. The way to do that

```
# Продемонструвати групу функцій  
для інцидентів на кадрі даних  
incidents =  
folium.map.FeatureGroup()
```

```
# loop through the 1000 crimes and  
add each to the incidents feature  
group
```

```
# Петлю через 1000 злочинів і  
додати кожен до групи об'єктів  
інцидентів
```

```
for lat, lng, in zip(df_incidents.Y,  
df_incidents.X):  
    incidents.add_child(  
        folium.features.CircleMarker(  
            [lat, lng],  
            radius = 5, # define how big  
you want the circle markers to be  
            color = "yellow",  
            fill_color = "blue",  
            fill_opacity=0.6  
        )  
    )
```

```
# add incidents to map
```

```
# Додавати інциденти на карту  
sanfran_map.add_child(incidents)  
sanfran_map = folium.Map(location =  
[latitude, longitude], zoom_start = 12)
```

```
# instantiate a mark cluster object for  
the incidents in the dataframe
```

in **Folium** is to create a *feature group* with its own features and style and then add it to the `sanfran_map`. You can also add some pop-up text that would get displayed when you hover over a marker. Let's make each marker display the category of the crime when hovered over.

To implement this, we start off by instantiating a *MarkerCluster* object and adding all the data points in the dataframe to this object.

```
# # Інстанція об'єкта кластерів міток  
для випадків на кадрі даних  
incidents =  
MarkerCluster().add_to(sanfran_map)
```

```
# loop through the dataframe and  
add each data point to the mark  
cluster  
# Петля через кадр даних і додати  
кожну точку даних до кластеру  
позначок  
for lat, lng, label, in zip(df_incidents.Y,  
df_incidents.X,  
df_incidents.Category):  
    folium.Marker(  
        location = [lat, lng],  
        icon = None,  
        popup = label,  
    ).add_to(incidents)
```

```
sanfran_map
```