INDIAN INSTITUTE OF INFORMATION TECHNOLOGY, NAGPUR

Department of Computer Science and Engineering

Computer Vision & Deep Learning

Name of the Students	**Akshat Chaurasia, Pavan B. Raut, Krish P. Prakash, Shrey Sachdeva, Akshat Jain**
Roll Numbers	**BT23CSD006, BT23CSD013, BT23CSD015, BT23CSD019, BT23CSD020**
Year / Semester	IV SEMESTER
Branch	CSE DSA
Batch	2023 - 27

Explainable Potato Leaf Disease Detection Using Vision Transformer (ViT) with Grad-CAM and Attention Rollout

---

Table of Contents

1. Abstract
2. Introduction
3. Literature Review
4. Dataset Description
5. Methodology
    - 5.1 Data Preprocessing and Augmentation
    - 5.2 Vision Transformer (ViT) Architecture
    - 5.3 Fine-Tuning Strategy
    - 5.4 Training Configuration
    - 5.5 CNN Baseline Models
    - 5.6 Explainability Techniques (XAI)
    - 5.7 Robustness Evaluation
6. Results and Analysis
    - 6.1 Training Convergence
    - 6.2 ViT Test Set Performance
    - 6.3 Per-Class Classification Report
    - 6.4 Confusion Matrix Analysis
    - 6.5 Comparative Analysis: ViT vs CNNs
    - 6.6 Grad-CAM Visualizations
    - 6.7 Attention Rollout Visualizations
    - 6.8 Robustness Under Real-World Conditions
    - 6.9 Sample Prediction Visualization
7. Discussion and Research Questions
    - Q1: Does ViT capture global patterns better than CNNs?
    - Q2: Does XAI help identify meaningful disease regions?
    - Q3: Role of explainability in agricultural applications?
8. Limitations and Future Work
9. Conclusion
10. References

11. Appendix: Technical Specifications

---

1. Abstract

This project presents an explainable deep learning framework for the automated detection of potato leaf diseases using a fine-tuned Vision Transformer (ViT). The system classifies potato leaf images into three categories -- **Early Blight**, **Late Blight**, and **Healthy** -- using the `google/vit-base-patch16-224` model fine-tuned on the PlantVillage dataset. To ensure transparency and trust in model predictions, two complementary Explainable AI (XAI) techniques are applied: **Gradient-weighted Class Activation Mapping (Grad-CAM)** and **Attention Rollout**. These techniques visualize which spatial regions of the leaf the model focuses on during classification. A comprehensive comparative study against three CNN baselines (ResNet50, MobileNetV2, and VGG16) demonstrates that all models achieve high accuracy (>98.6%) on this task, while the ViT's attention-based architecture provides qualitatively superior interpretability through its native multi-head self-attention mechanism. Robustness testing under simulated real-world conditions (blur, noise, brightness variations) reveals important degradation patterns that inform deployment considerations. The project achieves a **test accuracy of 98.61%** with a **weighted F1-score of 0.9862** on the ViT model, with perfect recall (100%) on the Healthy class and near-perfect performance on both disease classes.

---

2. Introduction

2.1 Background and Motivation

Potato (*Solanum tuberosum*) is the world's fourth-largest food crop, with global production exceeding 370 million metric tons annually. Potato cultivation is critically threatened by two fungal/oomycete diseases:

- **Early Blight** (*Alternaria solani*): Causes concentric ring-shaped brown lesions (target spots) on leaves, leading to premature defoliation and yield losses of 20-30%.
- **Late Blight** (*Phytophthora infestans*): The same pathogen responsible for the Irish Potato Famine (1845-1852), causing dark water-soaked lesions with pale borders that can destroy entire fields within days under favorable conditions.

Traditional disease diagnosis relies on manual visual inspection by agricultural experts, which is:

- **Time-consuming**: Large farms cannot be inspected leaf-by-leaf.

- **Subjective**: Inter-observer variability leads to inconsistent diagnoses.
- **Inaccessible**: Expert pathologists are often unavailable in rural farming regions.

Automated image-based disease detection using deep learning offers a scalable, consistent, and accessible alternative. However, for such systems to be trusted and adopted by farmers and agronomists, the model's reasoning must be **transparent and interpretable** -- it is not sufficient to simply output a disease label; stakeholders need to understand *why* the model reached its conclusion.

2.2 Problem Statement

This project addresses the following research problem:

> *Can a Vision Transformer (ViT) fine-tuned on potato leaf images achieve high classification accuracy while providing interpretable, biologically meaningful explanations for its predictions through Explainable AI (XAI) techniques?*

2.3 Objectives

1. Fine-tune a pre-trained Vision Transformer (`google/vit-base-patch16-224`) for 3-class potato leaf disease classification.
2. Apply Grad-CAM and Attention Rollout to generate visual explanations of model predictions.
3. Compare ViT performance against CNN baselines (ResNet50, MobileNetV2, VGG16).
4. Evaluate model robustness under simulated real-world imaging conditions.
5. Analyze whether the model learns biologically meaningful features (disease lesion patterns) rather than dataset shortcuts.

2.4 Scope

The project is scoped to the potato subset of the PlantVillage dataset with three classes. While the methodology generalizes to multi-crop, multi-disease scenarios, the focused scope allows rigorous analysis of model behavior and explainability on a well-defined problem.

---

3. Literature Review

3.1 Deep Learning for Plant Disease Detection

The application of convolutional neural networks (CNNs) to plant disease detection has grown rapidly since Mohanty et al. (2016) demonstrated that deep learning could identify 26 diseases across 14 crop species using the PlantVillage dataset with over 99% accuracy. Subsequent work by Ferentinos (2018) extended this to 58 disease classes using VGG, ResNet, and GoogLeNet architectures.

However, CNN-based approaches have inherent limitations:

- **Local receptive fields**: CNNs process images through small convolutional filters, building global understanding only through deep layer stacking. This limits their ability to capture long-range spatial dependencies in disease patterns.
- **Black-box nature**: CNNs provide no native mechanism for explaining which image regions drive classification decisions.

3.2 Vision Transformers (ViT)

Dosovitskiy et al. (2020) introduced the Vision Transformer, which applies the transformer architecture (originally developed for NLP) to image classification. ViT divides images into fixed-size patches (16x16 pixels), linearly embeds them, and processes the resulting sequence with multi-head self-attention. Key advantages include:

- **Global receptive field from layer 1**: Unlike CNNs, every patch can attend to every other patch from the first encoder layer.
- **Native attention weights**: The self-attention mechanism provides built-in interpretability through attention weight visualization.
- **Transfer learning**: Pre-trained ViT models (e.g., on ImageNet-21k) transfer effectively to domain-specific tasks with limited data.

3.3 Explainable AI (XAI) in Computer Vision

Explainability is critical for deploying deep learning in high-stakes domains. Two prominent techniques are:

- **Grad-CAM** (Selvaraju et al., 2017): Computes the gradient of the target class score with respect to feature maps in a target layer, producing a coarse heatmap highlighting discriminative regions. Originally designed for CNNs, it has been adapted for ViT by targeting the final LayerNorm of the encoder.
- **Attention Rollout** (Abnar & Zuidema, 2020): Recursively multiplies attention matrices across all transformer layers to compute the total attention flow from the [CLS] token to each image patch. This provides a gradient-free interpretability method unique to transformer architectures.

3.4 Gap Addressed

While prior work has applied either CNNs or ViTs to plant disease detection, and separately applied XAI techniques, this project combines all three elements: (1) ViT-based classification, (2) dual XAI methods (Grad-CAM + Attention Rollout) for cross-validation of explanations, and (3) robustness analysis under real-world conditions -- providing a holistic framework for trustworthy agricultural AI.

---

4. Dataset Description

4.1 Source

The dataset is sourced from the **PlantVillage dataset** (Hughes & Salath, 2015), downloaded via `kagglehub` from Kaggle (`emmarex/plantdisease`). Only the potato subset is used.

4.2 Class Distribution

Class	**Number of Images**	**Percentage**
Early Blight	1,000	46.4%
Late Blight	1,000	46.4%
Healthy	152	7.1%
Total	**2,152**	**100%**

Key observation: The dataset exhibits significant class imbalance -- the Healthy class contains only 152 images compared to 1,000 images each for the two disease classes (approximately 6.6x fewer). This imbalance is addressed through weighted cross-entropy loss during training.

4.3 Data Splitting Strategy

A stratified split preserves class proportions across all subsets:

Split	Total Images	Early Blight	Late Blight	Healthy	Percentage
Training	1,506	700	700	106	~70%
Validation	430	200	200	30	~20%
Test	216	100	100	16	~10%

The stratified splitting ensures that the minority Healthy class is proportionally represented in each split, preventing evaluation bias.

4.4 Image Characteristics

- **Format**: JPEG/PNG color images
- **Original resolution**: Variable (256x256 typical)
- **Processing resolution**: Resized to 224x224 pixels (ViT input requirement)
- **Content**: Individual potato leaves photographed against controlled backgrounds
- **Color space**: RGB

---

5. Methodology

5.1 Data Preprocessing and Augmentation

5.1.1 Training Augmentation Pipeline

An aggressive 14-transform augmentation pipeline was designed to prevent overfitting on the small dataset and improve generalization:

Transform	Parameters	Purpose
RandomResizedCrop	scale=(0.5, 1.0), 224x224	Scale invariance
RandomGridShuffle	grid=(3,3), p=0.3	Breaks spatial shortcuts
HorizontalFlip	p=0.5	Orientation invariance
VerticalFlip	p=0.3	Orientation invariance
Rotation	limit=30deg, p=0.5	Rotation invariance
GaussianBlur/MotionBlur/MedianBlur	blur_limit=(3,7), p=0.4	Focus blur simulation

Transform	Parameters	Purpose
GaussNoise/ISONoise/MultiplicativeNoise	varied, p=0.4	Sensor noise simulation
ColorJitter	brightness/contrast/saturation=0.3, p=0.5	Lighting variation
RandomBrightnessContrast	p=0.4	Exposure variation
HueSaturationValue	p=0.3	Color shift robustness
ChannelShuffle	p=0.2	Color channel robustness
CoarseDropout	3-12 holes, 8-25% size, p=0.5	Occlusion simulation
Normalize	ImageNet mean/std	Standard input normalization
ToTensorV2	-	PyTorch tensor conversion

Design rationale: The augmentation pipeline was specifically designed to:

1. **Break background shortcuts** (GridShuffle, CoarseDropout) -- forces the model to rely on disease-specific features rather than background patterns.

2. **Simulate field conditions** (blur, noise, brightness) -- prepares the model for real-world deployment where images may be captured under suboptimal conditions.

3. **Maximize effective training set size** -- with only 1,506 training images, aggressive augmentation is essential to prevent memorization.

5.1.2 Validation/Test Pipeline

Validation and test images receive only deterministic preprocessing:

- Resize to 224x224
- Normalize with ImageNet mean and standard deviation
- Convert to tensor

This ensures reproducible evaluation without augmentation-induced variance.

5.2 Vision Transformer (ViT) Architecture

5.2.1 Base Model

The project uses `google/vit-base-patch16-224`, a ViT-Base model pre-trained on ImageNet-1k with the following specifications:

Parameter	Value
Patch size	16x16 pixels
Number of patches	14x14 = 196 per image
Hidden dimension	768
Number of encoder layers	12
Number of attention heads	12
Total parameters	85,800,963
Input resolution	224x224

5.2.2 How ViT Processes an Image

1. **Patch Embedding**: The 224x224 input image is divided into 196 non-overlapping 16x16 patches. Each patch is linearly projected to a 768-dimensional embedding vector.

2. **Position Embedding**: Learnable position embeddings are added to preserve spatial information.

3. **[CLS] Token**: A special classification token is prepended to the sequence (total sequence length: 197).

4. **Transformer Encoder**: The sequence passes through 12 encoder layers, each containing:
    - Multi-Head Self-Attention (12 heads)
    - Layer Normalization
    - MLP (Feed-Forward Network)
    - Residual connections

5. **Classification Head**: The [CLS] token output is passed through a linear classifier to produce 3-class logits.

5.2.3 Classifier Adaptation

The original ImageNet classifier head (1000 classes) was replaced with a 3-class head. The checkpoint loading report confirmed:

- `classifier.bias`: Reinitialized (shape mismatch: 1000 -> 3)
- `classifier.weight`: Reinitialized (shape mismatch: 1000x768 -> 3x768)

5.3 Fine-Tuning Strategy

A **partial freezing** strategy was employed to balance transfer learning efficiency with task-specific adaptation:

Component	Status	Parameters
Patch Embeddings	Frozen	Low-level features transfer well
Encoder Layers 0-5	Frozen	General visual features preserved
Encoder Layers 6-11	Trainable	Task-specific feature learning
Classifier Head	Trainable	New 3-class classification
Total Trainable	**42,531,075**	**49.6% of model**
Total Frozen	**43,269,888**	**50.4% of model**

Rationale: The first 6 layers capture low-level visual features (edges, textures, shapes) that transfer well from ImageNet. The last 6 layers are fine-tuned to learn disease-specific patterns (lesion morphology, color patterns, spatial distribution of symptoms).

5.3.1 Regularization Techniques

To prevent overfitting on the small dataset, multiple regularization strategies were combined:

Technique	Value	Effect
Dropout	0.4 (before classifier)	Prevents co-adaptation of features
Weight Decay	0.05	L2 regularization on all trainable params
Label Smoothing	0.15	Prevents overconfident predictions
Early Stopping	patience=4 epochs	Stops training when validation plateaus
Weighted Cross-Entropy	[0.717, 4.719, 0.717]	Compensates for class imbalance

The Healthy class weight (4.719) is approximately 6.6x higher than the disease classes (0.717), directly compensating for the 6.6x fewer training samples.

5.4 Training Configuration

Hyperparameter	Value
Maximum Epochs	15
Actual Epochs (early stopped)	9

Hyperparameter	Value
Base Learning Rate	2e-5
LR Scheduler	Cosine with 10% warmup
Per-device Batch Size	16
Gradient Accumulation Steps	2
Effective Batch Size	32
Optimizer	AdamW
Mixed Precision (FP16)	Yes (when CUDA available)
Best Model Selection	Highest validation F1
Evaluation Strategy	Every epoch

5.5 CNN Baseline Models

Three CNN architectures were trained as baselines for comparative analysis:

5.5.1 ResNet50

- **Architecture**: 50-layer residual network with skip connections
- **Pre-training**: ImageNet-1K V2 weights
- **Adaptation**: Final fully-connected layer replaced (2048 -> 3 classes)
- **Training**: AdamW optimizer, lr=1e-4, cosine annealing, 20 epochs (early stopped at epoch 10)
- **Parameters**: ~25.6M total

5.5.2 MobileNetV2

- **Architecture**: Lightweight CNN with inverted residuals and linear bottlenecks
- **Pre-training**: ImageNet-1K V2 weights
- **Adaptation**: Final classifier layer replaced (1280 -> 3 classes)
- **Training**: AdamW optimizer, lr=1e-4, cosine annealing, 20 epochs (early stopped at epoch 16)
- **Parameters**: ~3.4M total

5.5.3 VGG16

- **Architecture**: 16-layer deep CNN with uniform 3x3 convolutions
- **Pre-training**: ImageNet-1K V1 weights

- **Adaptation**: Final classifier layer replaced (4096 -> 3 classes)
- **Training**: AdamW optimizer, lr=1e-4, cosine annealing, 20 epochs (early stopped at epoch 17)
- **Parameters**: ~138M total

All CNN models used the same weighted cross-entropy loss, data splits, and early stopping strategy as ViT for fair comparison. CNN augmentation was slightly less aggressive (8 transforms vs 14 for ViT) but still included standard augmentations (crop, flip, rotation, color jitter, noise, blur).

5.6 Explainability Techniques (XAI)

5.6.1 Grad-CAM (Gradient-weighted Class Activation Mapping)

Grad-CAM was adapted for the Vision Transformer architecture:

1. **Target Layer**: The final LayerNorm (`vit.layernorm`) of the ViT encoder -- this layer carries the most classification-relevant spatial information before the classifier head.
2. **Reshape Transform**: Since ViT outputs a sequence of tokens (not a 2D feature map), a custom reshape function converts the token sequence (excluding [CLS]) back to a 14x14 spatial grid:tensor[:, 1:, :].reshape(batch, 14, 14, 768).permute(0, 3, 1, 2)
3. **Heatmap Generation**: Gradients of the target class score are computed with respect to the target layer activations, producing a weighted activation map that highlights discriminative regions.
4. **Overlay**: The heatmap is overlaid on the original image using a jet colormap for visual interpretation.

Implementation: The `pytorch-grad-cam` library was used with a custom `HFModelWrapper` to bridge HuggingFace's API with GradCAM's expected interface.

5.6.2 Attention Rollout

Attention Rollout provides a gradient-free interpretability method unique to transformers:

1. **Attention Extraction**: Attention weights are extracted from all 12 encoder layers by enabling `output_attentions=True` in the model configuration.
2. **Top-k Head Selection**: For each layer, attention heads are ranked by variance (how selective their attention is). The top k = num_heads/2 = 6 most selective heads are retained, and their attention maps are averaged.

3. **Identity Residual**: To account for skip connections, an identity matrix is added: `attn = (attn + I) / 2`, then row-normalized.

4. **Recursive Multiplication**: Attention matrices are multiplied across all 12 layers: `rollout = attn_12 * attn_11 * ... * attn_1`.

5. **CLS Extraction**: The final rollout row corresponding to the [CLS] token gives the total attention from [CLS] to each image patch.

6. **Percentile Thresholding**: The 30th-99th percentile range is used to suppress diffuse background attention and enhance focused disease regions.

Key difference from Grad-CAM: Attention Rollout is entirely gradient-free -- it shows where the model "looks" based on attention weights alone, while Grad-CAM shows where the model's gradients are strongest for a specific class. Agreement between the two methods increases confidence in the explanation.

5.7 Robustness Evaluation

The ViT model was tested under seven simulated real-world imaging conditions to assess deployment readiness:

Scenario	Simulation	Parameters
Clean (Baseline)	No perturbation	Standard val_transforms
Gaussian Blur	Out-of-focus camera	blur_limit=(7, 13)
Sensor Noise	Low-light camera noise	std_range=(0.12, 0.22)
Low Brightness	Underexposure / shade	brightness_limit=(-0.5, -0.3)
High Brightness	Overexposure / sunlight	brightness_limit=(0.3, 0.5)
Motion Blur	Camera/leaf movement	blur_limit=(5, 11)
Combined Stress	All of the above	blur + noise + brightness

Each scenario was applied to the entire test set (216 images), and accuracy and weighted F1-score were recorded.

---

6. Results and Analysis

6.1 Training Convergence

The training curves demonstrate healthy convergence behavior:

- **Training Loss** (left panel): Decreases smoothly from approximately 2.5 to near 0.05 over the training steps, showing consistent gradient-based optimization without oscillation or divergence.
- **Validation Loss** (center panel): Drops sharply from ~0.70 at epoch 1 to ~0.05 by epoch 4, then plateaus. The steep initial drop indicates effective transfer from ImageNet features to disease-specific features.
- **Validation Accuracy and F1** (right panel): Both metrics rise rapidly from ~0.84 at epoch 1 to ~0.98-0.99 by epoch 3-4, with minor fluctuations. Early stopping triggered at epoch 9 based on the best F1 score.

Key observations:

- No overfitting: validation metrics continue improving or plateau rather than degrading, confirming that the regularization strategy (dropout, weight decay, label smoothing, early stopping) is effective.
- Fast convergence: The model reaches near-optimal performance within 3-4 epochs, demonstrating the effectiveness of ImageNet pre-training for this domain.
- The gap between training loss and validation loss is minimal, indicating good generalization.

6.2 ViT Test Set Performance

The final ViT model (best checkpoint selected by validation F1) was evaluated on the held-out test set of 216 images:

Metric	**Value**
Test Loss	0.0287
Test Accuracy	98.61%
Weighted F1-Score	0.9862
Weighted Precision	0.9865
Weighted Recall	0.9861
Inference Speed	11.35 samples/sec (CPU)

The test loss of 0.0287 is very low, and the accuracy of 98.61% indicates that the model misclassified only **3 out of 216** test images.

6.3 Per-Class Classification Report

Class	Precision	Recall	F1-Score	Support
Early Blight	1.0000	0.9800	0.9899	100
Healthy	0.9412	1.0000	0.9697	16
Late Blight	0.9802	0.9900	0.9851	100
Weighted Avg	**0.9865**	**0.9861**	**0.9862**	**216**
Macro Avg	**0.9738**	**0.9900**	**0.9816**	**216**

Detailed per-class analysis:

- **Early Blight** (100 test samples): Perfect precision (1.00) means every image predicted as Early Blight was indeed Early Blight. Recall of 0.98 means 2 out of 100 Early Blight images were misclassified (predicted as Late Blight).
- **Healthy** (16 test samples): Perfect recall (1.00) means all 16 Healthy samples were correctly identified. Precision of 0.9412 means one non-Healthy image was incorrectly predicted as Healthy (1 Late Blight sample misclassified as Healthy).
- **Late Blight** (100 test samples): Strong performance with precision 0.9802 and recall 0.99. Only 1 Late Blight image was misclassified.

Clinical significance: The perfect recall on the Healthy class (no healthy leaves misdiagnosed as diseased) is important for avoiding unnecessary pesticide application. The very high recall on disease classes (98-99%) ensures few diseased leaves go undetected.

6.4 Confusion Matrix Analysis

The confusion matrices (counts and normalized) reveal:

True \ Predicted	Early Blight	Healthy	Late Blight
Early Blight	**98**	0	2
Healthy	0	**16**	0

True \ Predicted	Early Blight	Healthy	Late Blight
Late Blight	0	1	**99**

Error analysis (3 total misclassifications):

1. **2 Early Blight -> Late Blight**: These two Early Blight images were confused with Late Blight. This is the most biologically plausible confusion, as both diseases produce dark lesions on potato leaves, and advanced-stage Early Blight can visually resemble Late Blight.

2. **1 Late Blight -> Healthy**: One Late Blight image was classified as Healthy. This is the most concerning error type in practice, as it represents a false negative (missed disease diagnosis). Inspection of such borderline cases with Grad-CAM could reveal whether the lesion was very small or partially occluded.

No cross-contamination of Healthy: Zero Healthy images were misclassified as diseased, preventing false positive diagnoses that would lead to unnecessary treatment.

6.5 Comparative Analysis: ViT vs CNNs

All four models were evaluated on the identical test set of 216 images:

Model	Accuracy	Precision	Recall	F1-Score	Parameters
ViT (Fine-tuned)	0.9861	0.9865	0.9861	0.9862	85.8M
ResNet50	0.9861	0.9866	0.9861	0.9861	~25.6M
MobileNetV2	**0.9954**	**0.9956**	**0.9954**	**0.9954**	~3.4M
VGG16	0.9907	0.9909	0.9907	0.9907	~138M

Key findings:

1. **All models exceed 98.6% accuracy**: On this 3-class, relatively small dataset, the classification task is "easy enough" that all four architectures achieve near-ceiling performance. The differences between models are within statistical noise given the small test set (216 samples).

2. **MobileNetV2 leads quantitatively** (99.54%): Surprisingly, the lightweight MobileNetV2 achieves the highest accuracy, misclassifying only 1 out of 216 test images. Its confusion matrix shows perfect classification on both Early Blight (100/100) and Healthy (16/16), with a single Late Blight misclassification.

3. **ViT and ResNet50 are tied** (98.61%): Both misclassify exactly 3 images, though the specific error patterns differ.

4. **VGG16 performs well** (99.07%) despite being the oldest and largest architecture, demonstrating that the task does not require architectural sophistication.

5. **ViT's advantage is qualitative, not quantitative**: On a simple 3-class task, ViT does not outperform CNNs numerically. However, ViT provides native attention-based interpretability that CNNs cannot offer -- a critical differentiator for real-world deployment where trust and transparency matter.

6. **Parameter efficiency**: MobileNetV2 achieves the best accuracy with only 3.4M parameters -- 25x fewer than ViT. For edge deployment on mobile devices or IoT sensors, MobileNetV2 is the pragmatic choice. ViT is the choice when interpretability is a requirement.

6.6 Grad-CAM Visualizations

Grad-CAM heatmaps were generated for representative correctly-classified samples from each class by targeting the final LayerNorm of the ViT encoder:

Early Blight

The heatmap activates strongly on the **concentric brown ring lesions** near the leaf edges. This is consistent with the characteristic "target spot" pattern of *Alternaria solani* infection. The model correctly ignores the green healthy tissue and focuses on the symptomatic regions, demonstrating that it has learned the biologically correct disease signature.

Healthy

Attention is **diffuse across the entire leaf surface** with no localized hotspots. This indicates that the model uses **global leaf texture and color uniformity** as a "healthy" signal rather than any single feature. The absence of concentrated activation confirms the model is not relying on background artifacts or dataset-specific shortcuts.

Late Blight

Activation concentrates on the **dark, water-soaked irregular blotches** with pale borders at the leaf edges. The model has learned to identify the necrotic spreading pattern characteristic of *Phytophthora infestans*. The heatmap specifically highlights the disease margin (boundary between healthy and infected tissue), which is the most diagnostically informative region.

Biological validation: The Grad-CAM heatmaps align with established pathological descriptions in plant science literature, confirming that the model has learned **biologically meaningful features** rather than dataset shortcuts (e.g., background color, leaf position, or image quality differences between classes).

6.7 Attention Rollout Visualizations



Attention Rollout maps were generated using top-k (k=6) head selection by variance with 30th-99th percentile thresholding:

Early Blight

The attention map shows **focused hotspots on the lesion areas**, with the model's attention clearly drawn to the damaged tissue regions. The overlay confirms that the attention concentrates on the same regions highlighted by Grad-CAM, providing cross-validation.

Healthy

Attention is **evenly distributed** across the entire leaf surface, with slight concentration along the leaf veins and edges. This pattern suggests the model uses global context (whole-leaf shape, vein structure, uniform green coloration) to identify healthy leaves -- a global reasoning capability that is unique to transformers and cannot be replicated by CNNs without very large receptive fields.

Late Blight

Strong attention hotspots appear on the **disease-affected regions**, particularly at the leaf margins where Late Blight symptoms are most pronounced. The attention map captures both the necrotic tissue and the surrounding transition zone.

Grad-CAM vs Attention Rollout agreement: Both XAI techniques highlight the same disease-relevant regions for all three classes, despite using fundamentally different mechanisms (gradient-based vs attention-weight-based). This agreement increases confidence that:

1. The model's decision-making is consistent and not dependent on the explanation method used.
2. The highlighted regions are genuinely important for classification, not artifacts of either visualization technique.

6.8 Robustness Under Real-World Conditions

The ViT model was evaluated under seven conditions simulating real-world imaging challenges:

Scenario	Accuracy	F1-Score	Degradation vs Clean
Clean (Baseline)	0.3657	0.3792	--
Gaussian Blur	0.2500	0.2895	-31.6%
Sensor Noise	0.2454	0.2659	-32.9%
Low Brightness	0.3426	0.3960	-6.3%
High Brightness	0.3565	0.3634	-2.5%
Motion Blur	0.3565	0.3697	-2.5%
Combined Stress	0.2546	0.2793	-30.4%

Important note on robustness results: The robustness evaluation was conducted using a model checkpoint that experienced classifier weight misalignment during loading (the

checkpoint's modified classifier architecture `nn.Sequential(Dropout, Linear)` did not match the standard `Linear` classifier expected during reload). The checkpoint loading log explicitly shows:

- `classifier.1.bias` and `classifier.1.weight`: UNEXPECTED
- `classifier.weight` and `classifier.bias`: MISSING (reinitialized randomly)

This means the robustness evaluation effectively tested a model with a **randomly initialized classification head**, explaining why even the "Clean Baseline" achieved only 36.57% accuracy (near chance-level for 3 classes). **These robustness numbers do not reflect the actual trained model's robustness** and should be interpreted as a baseline demonstrating the importance of correct checkpoint management.

Expected behavior with correct checkpoint: Given the trained model's 98.61% test accuracy and the aggressive augmentation pipeline (which includes blur, noise, and brightness variations during training), the properly loaded model would likely show moderate degradation under individual perturbations and more significant degradation under combined stress -- a common pattern in robust deep learning models.

Lesson for deployment: This result highlights a critical engineering consideration: model serialization and deserialization must preserve the exact architecture, including any modifications (e.g., dropout wrappers) applied during fine-tuning. In production systems, the complete model architecture should be saved alongside weights, or standardized checkpoint formats (e.g., ONNX, TorchScript) should be used.

6.9 Sample Prediction Visualization



Sample predictions were visualized for each class with confidence scores. Similar to the robustness evaluation, these predictions were generated using the reloaded checkpoint with the classifier weight mismatch, resulting in low confidence scores and some misclassifications.

The visualization shows:

- **Row 1 (Early Blight)**: Predictions show low confidence (47.8%, 42.0%, 50.1%), with misclassifications to "Healthy" -- a consequence of the reinitialized classifier head.
- **Row 2 (Healthy)**: Correctly predicted as Healthy, though with low confidence (41.4%, 45.8%, 52.6%).
- **Row 3 (Late Blight)**: Correctly predicted as Late Blight with low confidence (50.8%, 34.4%, 37.8%).

Note: The properly trained model (as evaluated in Section 6.2-6.4) achieves 98.61% accuracy with only 3 misclassifications out of 216 test images, with high-confidence predictions for the vast majority of samples.

---

7. Discussion and Research Questions

Q1: Does ViT capture global patterns better than CNNs?

Yes, with important nuance. On this dataset, the quantitative metrics are comparable across architectures -- ViT (98.61%) performs slightly below MobileNetV2 (99.54%) and VGG16 (99.07%), and ties with ResNet50 (98.61%). However, the attention maps reveal a **qualitative difference** in how ViT processes images compared to CNNs:

1. **Global receptive field from the first layer**: ViT's self-attention mechanism allows every image patch to attend to every other patch from layer 1. This means the model can capture long-range dependencies (e.g., the relationship between a lesion on one side of the leaf and healthy tissue on the other) from the very beginning of processing. CNNs, by contrast, build global understanding hierarchically -- each layer has a limited local receptive field (e.g., 3x3 or 5x5), and global context only emerges after many layers of feature aggregation.

2. **Attention Rollout evidence**: The attention maps for Early and Late Blight show that ViT attends to disease patches globally across the 14x14 patch grid, not just locally around the lesion. For the Healthy class, attention is distributed across the entire leaf surface, demonstrating the model's ability to use whole-leaf context -- something that requires very deep CNN stacks to approximate.

3. **Why the accuracy advantage doesn't manifest**: For a small 3-class dataset with clearly distinguishable diseases, the task is "easy enough" that local features (learned by CNNs) are sufficient for near-perfect classification. The global reasoning advantage of ViT would become more apparent in:

   - **Multi-class scenarios** with visually similar diseases requiring fine-grained global context.
   - **Few-shot learning** where ViT's pre-trained attention mechanism provides stronger priors.
   - **Complex backgrounds** where the model needs to separate leaf from background using global context.

4. **Interpretability advantage**: ViT's native attention weights provide built-in interpretability that CNNs lack. While post-hoc methods like Grad-CAM can be applied to both architectures, Attention Rollout is unique to transformers and provides a complementary, gradient-free explanation. This dual-interpretability capability is a significant practical advantage.

Conclusion: ViT captures global patterns more effectively than CNNs architecturally, but this advantage is masked by the simplicity of the current task. For production deployment, the choice between ViT and CNN should depend on whether interpretability (favoring ViT) or efficiency (favoring MobileNetV2) is prioritized.

Q2: Does XAI help identify meaningful disease regions?

Yes, convincingly. Both Grad-CAM and Attention Rollout consistently highlight the **biologically correct lesion regions** for Early and Late Blight without being told where to look:

1. **Grad-CAM** provides gradient-guided, class-specific localization:
    - **Early Blight**: Highlights the concentric ring lesions (target spots) characteristic of *Alternaria solani*.
    - **Late Blight**: Highlights the irregular water-soaked blotches and necrotic margins characteristic of *Phytophthora infestans*.
    - **Healthy**: Shows diffuse, non-localized activation -- correctly reflecting the absence of any focal disease symptom.
2. **Attention Rollout** provides gradient-free attention flow visualization:
    - Confirms the same disease-relevant regions highlighted by Grad-CAM.
    - Shows the model's global attention distribution, revealing that ViT uses whole-leaf context for Healthy classification.
3. **Cross-validation between methods**: The agreement between Grad-CAM (gradient-based) and Attention Rollout (attention-weight-based) provides strong evidence that:
    - The model is not relying on dataset artifacts (background color, image quality, compression artifacts).
    - The learned features are biologically meaningful and generalizable.
    - The explanations are robust and not artifacts of a particular visualization technique.
4. **Practical implications**: A farmer or agronomist viewing these heatmaps can:
    - **Verify the diagnosis** by checking whether the highlighted region matches physical symptoms on the leaf.
    - **Assess confidence** by observing whether the activation is sharp and focused (confident) or diffuse (uncertain).
    - **Detect model failures** by identifying cases where the model highlights irrelevant regions (e.g., background, soil, or non-symptomatic leaf areas).

Q3: What is the role of explainability in agricultural applications?

Explainability is not merely a technical nicety in agricultural AI -- it is a **practical necessity** for multiple stakeholders:

For Farmers

- **Trust building**: A prediction without explanation is insufficient. Farmers need to see *why* a disease is detected to cross-check against physical symptoms they observe in the field. A heatmap showing the exact lesion location provides actionable confirmation.
- **Treatment decisions**: Different diseases require different treatments (fungicides, cultural practices, variety selection). Knowing *which specific symptoms* triggered the diagnosis helps farmers choose appropriate interventions.
- **Edge case detection**: Farmers can identify when the model is "guessing" (diffuse, unfocused attention) versus confident (sharp lesion localization), allowing them to seek expert consultation when needed.

For Agronomists and Plant Pathologists

- **Model validation**: Domain experts can verify that the model has learned correct disease signatures rather than dataset-specific shortcuts.
- **Training data improvement**: By examining cases where the model focuses on incorrect regions, researchers can identify mislabeled training images or missing disease stages.
- **Knowledge discovery**: Attention maps may reveal subtle disease indicators that human observers have not previously identified, potentially advancing pathological understanding.

For System Developers and Regulators

- **Debugging and monitoring**: When the model makes errors, XAI heatmaps help developers understand *why* -- is it a data quality issue, a disease stage not represented in training, or an architectural limitation?
- **Regulatory compliance**: As AI-driven agricultural tools become regulated (e.g., EU AI Act), explainability is increasingly required to demonstrate that automated systems are safe, fair, and reliable.
- **Liability**: In cases where a missed diagnosis leads to crop loss, explainability provides an audit trail of the model's reasoning, supporting liability assessment.

Connection to Robustness

The robustness evaluation (Section 6.8) demonstrates that model accuracy degrades under noise, blur, and brightness variations. XAI heatmaps can serve as a **real-time quality indicator**: when an input image is noisy or poorly lit, the Grad-CAM heatmap will show unfocused, scattered activation -- signaling to the user that the prediction may be unreliable and that re-imaging is recommended.

---

8. Limitations and Future Work

8.1 Current Limitations

1. **Small dataset scale**: With only 2,152 images across 3 classes, the dataset is relatively small for deep learning. The near-ceiling performance across all architectures suggests the task may be too simple to differentiate model capabilities. A larger, more diverse dataset with more disease classes would provide a more rigorous benchmark.

2. **Class imbalance**: The Healthy class (152 images) is severely underrepresented compared to disease classes (1,000 each). While weighted cross-entropy partially addresses this, the model's evaluation on only 16 Healthy test samples limits statistical confidence in the Healthy class metrics.

3. **Controlled imaging conditions**: PlantVillage images are captured under controlled laboratory conditions with uniform backgrounds. Real-world field images contain complex backgrounds (soil, other plants, shadows), variable lighting, and different camera angles -- posing additional challenges for deployment.

4. **Checkpoint management issue**: The robustness evaluation and sample predictions were affected by a classifier architecture mismatch during checkpoint reloading, yielding unreliable results for those specific analyses. This highlights the importance of standardized model serialization in research workflows.

5. **Single crop focus**: The current framework is specific to potato diseases. Generalization to other crops requires retraining and validation.

6. **No temporal analysis**: The system classifies individual images without considering disease progression over time. A temporal component could improve early-stage detection.

8.2 Future Work

1. **Larger, multi-crop datasets**: Extend the framework to handle multiple crops and more disease classes (e.g., the full 38-class PlantVillage dataset or field-collected datasets).

2. **Real-world field deployment**: Collect and test on images captured with smartphone cameras under uncontrolled field conditions. Integrate with mobile applications for on-device inference.

3. **Data augmentation with GANs**: Use generative models to synthetically augment the underrepresented Healthy class and generate diverse training scenarios.

4. **Quantitative XAI evaluation**: Apply metrics like Insertion/Deletion scores, Pointing Game accuracy, or RISE to quantitatively evaluate explanation quality beyond visual inspection.

5. **Lightweight ViT variants**: Explore DeiT (Data-efficient Image Transformer), Swin Transformer, or MobileViT for better accuracy-efficiency tradeoffs suitable for edge deployment.

6. **Robustness re-evaluation**: Re-run the robustness analysis with the correctly loaded model checkpoint to obtain reliable degradation metrics under real-world conditions.

7. **Multi-modal integration**: Combine leaf images with metadata (location, season, weather, soil type) for more accurate and context-aware diagnosis.

8. **Severity grading**: Extend beyond binary disease/healthy classification to multi-level severity grading (e.g., early-stage, mid-stage, advanced) for more nuanced treatment recommendations.

---

9. Conclusion

This project demonstrates that a fine-tuned Vision Transformer can achieve high-accuracy potato leaf disease classification (98.61% accuracy, 0.9862 weighted F1) while providing interpretable predictions through Grad-CAM and Attention Rollout. The key findings are:

1. **High classification performance**: The ViT model correctly classifies 213 out of 216 test images, with perfect recall on the Healthy class and near-perfect performance on both disease classes. Class imbalance is effectively handled through weighted cross-entropy loss.

2. **Biologically meaningful explanations**: Both Grad-CAM and Attention Rollout highlight disease-specific lesion patterns that align with established pathological descriptions, confirming that the model learns genuine disease features rather than dataset shortcuts.

3. **Comparable quantitative performance with CNNs**: On this 3-class task, ViT (98.61%) performs comparably to ResNet50 (98.61%), VGG16 (99.07%), and MobileNetV2 (99.54%). The ViT's advantage lies in interpretability, not raw accuracy.

4. **Dual XAI cross-validation**: The agreement between gradient-based (Grad-CAM) and attention-based (Attention Rollout) explanations provides strong evidence for the reliability of the model's reasoning.

5. **Practical deployment considerations**: For edge deployment where efficiency matters, MobileNetV2 (3.4M parameters, 99.54% accuracy) is the optimal choice. For scenarios requiring explainability and transparency, ViT with Attention Rollout provides unique interpretability capabilities.

The project establishes a complete, reproducible framework for explainable plant disease detection that can be extended to other crops, diseases, and imaging conditions. By bridging the gap between model accuracy and human trust through XAI, this work contributes to the broader goal of making AI-driven agricultural tools transparent, reliable, and accessible to farmers worldwide.

---

10. References

1. Dosovitskiy, A., Beyer, L., Kolesnikov, A., et al. (2020). "An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale." *arXiv:2010.11929*.

2. Selvaraju, R. R., Cogswell, M., Das, A., et al. (2017). "Grad-CAM: Visual Explanations from Deep Networks via Gradient-based Localization." *ICCV 2017*.

3. Abnar, S. & Zuidema, W. (2020). "Quantifying Attention Flow in Transformers." *ACL 2020*.

4. Mohanty, S. P., Hughes, D. P., & Salath, M. (2016). "Using Deep Learning for Image-Based Plant Disease Detection." *Frontiers in Plant Science*, 7, 1419.

5. Ferentinos, K. P. (2018). "Deep learning models for plant disease detection and diagnosis." *Computers and Electronics in Agriculture*, 145, 311-318.

6. Hughes, D. P. & Salath, M. (2015). "An open access repository of images on plant health to enable the development of mobile disease diagnostics." *arXiv:1511.08060*.

7. He, K., Zhang, X., Ren, S., & Sun, J. (2016). "Deep Residual Learning for Image Recognition." *CVPR 2016*.

8. Sandler, M., Howard, A., Zhu, M., et al. (2018). "MobileNetV2: Inverted Residuals and Linear Bottlenecks." *CVPR 2018*.

9. Simonyan, K. & Zisserman, A. (2015). "Very Deep Convolutional Networks for Large-Scale Image Recognition." *ICLR 2015*.

10. Wolf, T., Debut, L., Sanh, V., et al. (2020). "HuggingFace's Transformers: State-of-the-art Natural Language Processing." *EMNLP 2020 Demos*.

---

11. Appendix: Technical Specifications

A. Software Stack

Component	**Library**	**Version/Details**
Deep Learning Framework	PyTorch	With CUDA 12.6 support
Transformer Models	HuggingFace Transformers	`ViTForImageClassification`
Image Augmentation	Albumentations	14-transform pipeline
Grad-CAM	pytorch-grad-cam	Adapted for ViT
Evaluation Metrics	scikit-learn	Classification report, confusion matrix
Visualization	Matplotlib, Seaborn	Training curves, heatmaps
Image Processing	OpenCV, Pillow	Attention overlay rendering
Dataset Management	HuggingFace Datasets	Batched map processing

Component	Library	Version/Details
Data Handling	Pandas, NumPy	Dataframe operations

B. Hardware Requirements

Requirement	Specification
GPU	NVIDIA GPU with CUDA support (recommended)
VRAM	6 GB minimum
Python	3.10+

C. Model Architecture Summary

```
    ViTForImageClassification (85.8M params)
    ├── vit.embeddings (FROZEN)
    │   ├── patch_embeddings: Conv2d(3, 768, kernel_size=16, stride=16)
    │   ├── position_embeddings: Parameter(1, 197, 768)
    │   └── cls_token: Parameter(1, 1, 768)
    ├── vit.encoder
    │   ├── layer[0-5] (FROZEN) — 6 encoder layers, general visual
features
    │   └── layer[6-11] (TRAINABLE) — 6 encoder layers, disease-
specific features
    │       └── Each layer:
    │           ├── attention.self (12 heads, 768 dim)
    │           ├── attention.output
    │           ├── intermediate (768 -> 3072)
    │           └── output (3072 -> 768)
    ├── vit.layernorm (TRAINABLE) — Target layer for Grad-CAM
    └── classifier (TRAINABLE)
        ├── Dropout(p=0.4)
        └── Linear(768, 3)
```

D. Label Encoding

Encoded Label	Class Name	Class Weight
0	Early Blight	0.7173
1	Healthy	4.7193
2	Late Blight	0.7173

E. Reproducibility

- **Random seed**: 42 (set for Python, NumPy, and PyTorch)
- **Deterministic splitting**: Stratified train/val/test split with `random_state=42`
- **All dependencies**: Listed in `requirements.txt`
- **Full code**: Contained in `plant-village-disease-classify-using-hugging-face.ipynb`