HI TECH GROUP

# Telephony API - Quick Start

Everything needed to reach a 200. Full reference attached separately.

## 1. Endpoint

`https://hrx.hitechgroup.in/api/telephony/v1`

| Path | Purpose |
|---|---|
| **`GET /health`** | Test your setup. **Start here.** |
| **`POST /events`** | One call event, as it happens |
| **`POST /events/batch`** | Drain a backlog after an outage (max 500) |
| **`POST /recordings/ready`** | Tell us a recording is available |
| **`POST /agent-sessions`** | Agent login, state, break, logout |

## 2. Credentials

| |
|---|
| API key |
| Shared secret |

Sent separately from this document. The shared secret is never transmitted - it only computes the signature below, which we verify at our end.

## 3. Authentication - four headers on every request

| Header | Value |
|---|---|
| **`Authorization`** | `Bearer <api key>` |
| **`X-HRX-Timestamp`** | Unix epoch seconds. Must be within **300s** of our clock. |
| **`X-HRX-Nonce`** | A fresh UUID per request. Remembered for 10 minutes. |
| **`X-HRX-Signature`** | `sha256=` + the HMAC below |

```
signable  = timestamp + "." + nonce + "." + raw_body
signature = "sha256=" + hex(HMAC_SHA256(shared_secret, signable))
```

Sign the exact bytes you send. Re-serialising the JSON first changes key order and whitespace, and every signature then fails - the most common cause of a 401 here.

## 4. Recordings - two ways, either is fine

| Option | What you send | Why |
|---|---|---|
| **A. Signed URL** preferred | `recording_uid` only, plus expose `GET /recordings/{uid}/signed-url` | We ask for a short-lived link at play time. Nothing durable is stored, so a leak is worth little. |
| **B. Push the link** | `recording_url` (or `url`), optionally `url_expires_at` | Nothing to build at your end. We store the link and refresh it whenever you send a newer one. |

Either way HRX streams the audio itself rather than handing the link to the browser, so every playback is permission-checked and logged. You may also send the recording block inside `call.completed` - the CDR and the audio then arrive in a single request.

## 5. Two things we need confirmed in writing

| | |
|---|---|
| **1** | **Every call must be reported, including calls dialled manually on the handset** - not only API-placed calls. Inbound, IVR, predictive, callback and forwarded too. Much of our floor dials manually, so this is go/no-go. |
| **2** | **Which IP will your webhooks originate from?** An allowlist is already enforced, so anything from an address we have not been told about is refused with `403 ip_not_allowed`. It is often not the same host as your agent API - please confirm rather than assume. |

## 6. Responses

| Status | Meaning | Status | Meaning |
|---|---|---|---|
| **`202`** | Accepted and stored | **`401`** | `stale_timestamp` - clock over 300s out, run NTP |
| **`200`** | Duplicate `event_id`. Safe - do retry | **`401`** | `replayed_nonce` - reuse of a nonce |
| **`401`** | `invalid_api_key` - key wrong or missing | **`403`** | `ip_not_allowed` - tell us your IP |
| **`401`** | `invalid_signature` - usually re-serialised JSON | **`422`** | `validation_failed` - field missing or malformed |

Every rejection carries a `request_id` - quote it and we can say exactly what was refused. Send `event_id` as a UUID and reuse it on retries; that is what makes a retry safe.

## 7. First step

Run `GET /health`. A **200** confirms your key, secret, clock and source IP at once - please do not send call data until it passes. The attached `curl-recording-ready.sh` is a runnable signed example; the pack has the full field list, OpenAPI file and Postman collection.

Questions: Nagender Kumar, Hi Tech Group