HI TECH GROUP | HRX

Push a call recording to HRX

1. The endpoint

`POST https://hrx.hitechgroup.in/api/telephony/v1/recordings/ready`

2. Your credentials

API key
Shared secret

3. The four headers

Header	Value
`Authorization`	`Bearer <api key>`
`X-HRX-Timestamp`	Unix epoch seconds. Within **300s** of our clock.
`X-HRX-Nonce`	A fresh UUID every request.
`X-HRX-Signature`	`sha256=` + HMAC-SHA256 of the string below

```
signable  = timestamp + "." + nonce + "." + raw_body
signature = "sha256=" + hex(HMAC_SHA256(shared_secret, signable))
```

Sign the exact bytes you send. Re-serialising the JSON changes key order and whitespace and every signature then fails - the usual cause of a 401.

4. Copy and run

```
API_KEY="hrx_..."
SECRET="..."
URL="https://hrx.hitechgroup.in/api/telephony/v1/recordings/ready"

EVENT_ID=$(uuidgen | tr 'A-Z' 'a-z')
NONCE=$(uuidgen | tr 'A-Z' 'a-z')
TS=$(date +%s)

BODY="{\"event\":\"recording.ready\",\"event_id\":\"$EVENT_ID\",\
\"occurred_at\":\"$(date +%Y-%m-%dT%H:%M:%S%z)\",\
\"call_uid\":\"CV-20260907-000512\",\"recording_uid\":\"REC-20260907-000512\",\
\"recording_url\":\"https://your-gateway/rec/REC-20260907-000512.wav\",\
\"recording_type\":\"call\",\"duration_seconds\":198,\"format\":\"wav\"}"

SIG=$(printf '%s.%s.%s' "$TS" "$NONCE" "$BODY" \
      | openssl dgst -sha256 -hmac "$SECRET" -r | cut -d' ' -f1)

curl -X POST "$URL" \
  -H "Authorization: Bearer $API_KEY" \
  -H "X-HRX-Timestamp: $TS" \
  -H "X-HRX-Nonce: $NONCE" \
  -H "X-HRX-Signature: sha256=$SIG" \
  -H "Content-Type: application/json" \
  --data-raw "$BODY"
```

5. The fields

Field	Required	Notes
`event_id`	yes	A UUID. Reuse it on retries - that is what makes a retry safe.
`call_uid`	yes	The same RID/UID shown on your own CDR screen.
`recording_uid`	yes	Your identifier for the recording.
`recording_url`	no	Where we can fetch the audio. `url` is accepted as an alias.
`url_expires_at`	no	If the link above is time-limited, say when it dies.
`recording_type`	no	`call` (default), transfer_leg, conference, voicemail
`duration_seconds` `format`, `channels` `size_bytes`	no	Metadata. Stereo preferred - agent and customer on separate channels.

6. What you get back

Code	Meaning	Code	Meaning
`202`	Accepted and stored	**`401`**	`stale_timestamp` - clock over 300s out
`200`	Duplicate event_id. Safe.	**`403`**	`ip_not_allowed` - tell us your source IP
`401`	`invalid_api_key`	**`422`**	`validation_failed` - a field is missing
`401`	`invalid_signature`	**`429`**	Over 600 requests a minute

Test with `GET /api/telephony/v1/health` first - same four headers, empty body. A **200** confirms your key, secret, clock and source IP together. Tell us the IP your webhooks come from: an allowlist is enforced and anything else gets a 403.

Nagender Kumar, Hi Tech Group