HI TECH GROUP

Telephony API - Quick Start

Everything needed to reach a 200. Full reference attached separately.

1. Endpoint

`https://hrx.hitechgroup.in/api/telephony/v1`

Path	Purpose
`GET /health`	Test your setup. **Start here.**
`POST /events`	One call event, as it happens
`POST /events/batch`	Drain a backlog after an outage (max 500)
`POST /recordings/ready`	Tell us a recording is available
`POST /agent-sessions`	Agent login, state, break, logout

2. Credentials

API key
Shared secret

Sent to you separately from this document. The shared secret is never transmitted - it only computes the signature below, which we verify at our end.

3. Authentication - four headers on every request

Header	Value
`Authorization`	`Bearer <api key>`
`X-HRX-Timestamp`	Unix epoch seconds. Must be within **300s** of our clock.
`X-HRX-Nonce`	A fresh UUID per request. Remembered for 10 minutes.
`X-HRX-Signature`	`sha256=` + the HMAC below

```
signable  = timestamp + "." + nonce + "." + raw_body
signature = "sha256=" + hex(HMAC_SHA256(shared_secret, signable))
```

Sign the exact bytes you are about to send. Do not parse the JSON and re-serialise it before signing - key order and whitespace will differ and every signature will fail. This is the most common cause of a 401.

4. Recordings

Send `recording_uid` only - **not a playable URL**. When a permitted HRX user presses play, HRX asks your `GET /recordings/{uid}/signed-url` endpoint for a short-lived link and streams the audio itself, so recordings never leave your gateway unauthenticated. A URL sent to us is discarded - there is no field for it.

5. Two things we need confirmed in writing

1	**Every call must be reported, including calls dialled manually on the handset** - not only calls placed through an API request. Inbound, IVR, predictive, callback and forwarded too. A large share of our calls are dialled manually, so this is a go/no-go point for us.
2	**Which IP address will your webhooks originate from?** We will allowlist it. It is often not the same host as your agent API, so please confirm rather than assume.

6. Responses

Status	Meaning	Status	Meaning
`202`	Accepted and stored	**`401`**	`stale_timestamp` - clock over 300s out, run NTP
`200`	Duplicate `event_id`. Safe - do retry	**`401`**	`replayed_nonce` - reuse of a nonce
`401`	`invalid_api_key` - key wrong or missing	**`403`**	`ip_not_allowed` - tell us your IP
`401`	`invalid_signature` - usually re-serialised JSON	**`422`**	`validation_failed` - field missing or malformed

Every rejection carries a `request_id`. Quote it and we can tell you exactly what was refused and why. Send `event_id` as a UUID and reuse it on retries - that is what makes a retry safe.

7. First step

Run `GET /health`. A **200** confirms your API key, your shared secret, your server clock and your source IP in a single call. Please do not begin sending call data until it passes. The attached `curl-recording-ready.sh` is a runnable, already-signed example; the attached pack has the full field list, the OpenAPI file and a Postman collection.

Questions: Nagender Kumar, Hi Tech Group