HI TECH GROUP

Telephony API - Quick Start

Everything needed to reach a 200. Full reference attached separately.

1. Endpoint

`https://hrx.hitechgroup.in/api/telephony/v1`

Path	Purpose
`GET /health`	Test your setup. **Start here.**
`POST /events`	One call event, as it happens
`POST /events/batch`	Drain a backlog after an outage (max 500)
`POST /recordings/ready`	Tell us a recording is available
`POST /agent-sessions`	Agent login, state, break, logout

2. Credentials

API key
Shared secret

Sent separately from this document. The shared secret is never transmitted - it only computes the signature below, which we verify at our end.

3. Authentication - four headers on every request

Header	Value
`Authorization`	`Bearer <api key>`
`X-HRX-Timestamp`	Unix epoch seconds. Must be within **300s** of our clock.
`X-HRX-Nonce`	A fresh UUID per request. Remembered for 10 minutes.
`X-HRX-Signature`	`sha256=` + the HMAC below

```
signable  = timestamp + "." + nonce + "." + raw_body
signature = "sha256=" + hex(HMAC_SHA256(shared_secret, signable))
```

Sign the exact bytes you send. Re-serialising the JSON first changes key order and whitespace, and every signature then fails - the most common cause of a 401 here.

4. Recordings - two ways, either is fine

Option	What you send	Why
A. Signed URL preferred	`recording_uid` only, plus expose `GET /recordings/{uid}/signed-url`	We ask for a short-lived link at play time. Nothing durable is stored, so a leak is worth little.
B. Push the link	`recording_url` (or `url`), optionally `url_expires_at`	Nothing to build at your end. We store the link and refresh it whenever you send a newer one.

Either way HRX streams the audio itself rather than handing the link to the browser, so every playback is permission-checked and logged. You may also send the recording block inside `call.completed` - the CDR and the audio then arrive in a single request.

5. Two things we need confirmed in writing

1	**Every call must be reported, including calls dialled manually on the handset** - not only API-placed calls. Inbound, IVR, predictive, callback and forwarded too. Much of our floor dials manually, so this is go/no-go.
2	**Which IP will your webhooks originate from?** We will allowlist it. It is often not the same host as your agent API, so please confirm.

6. Responses

Status	Meaning	Status	Meaning
`202`	Accepted and stored	**`401`**	`stale_timestamp` - clock over 300s out, run NTP
`200`	Duplicate `event_id`. Safe - do retry	**`401`**	`replayed_nonce` - reuse of a nonce
`401`	`invalid_api_key` - key wrong or missing	**`403`**	`ip_not_allowed` - tell us your IP
`401`	`invalid_signature` - usually re-serialised JSON	**`422`**	`validation_failed` - field missing or malformed

Every rejection carries a `request_id` - quote it and we can say exactly what was refused. Send `event_id` as a UUID and reuse it on retries; that is what makes a retry safe.

7. First step

Run `GET /health`. A **200** confirms your key, secret, clock and source IP at once - please do not send call data until it passes. The attached `curl-recording-ready.sh` is a runnable signed example; the pack has the full field list, OpenAPI file and Postman collection.

Questions: Nagender Kumar, Hi Tech Group