Imports

```
# Core ML and tensors
import torch
import torch.nn as nn
import torch.optim as optim
import torch.nn.functional as F
from torchvision import transforms

# Data loading and utils
import os
import json
import random
from collections import Counter
from torch.utils.data import Dataset, DataLoader, random_split
from torch.nn.utils.rnn import pad_sequence, pack_padded_sequence
import torchvision.models as models
from torchvision.models.detection.faster_rcnn import FastRCNNPredictor
from torchvision.models.detection import fasterrcnn_resnet50_fpn
from torchvision.models.detection.backbone_utils import resnet_fpn_backbone
import albumentations as A
from albumentations.pytorch import ToTensorV2
import cv2
import time
from PIL import Image

# Visualization imports
import matplotlib.pyplot as plt
from matplotlib.patches import Rectangle
import matplotlib.patches as patches
import seaborn as sns

# Set random seeds for reproducibility
torch.manual_seed(42)
random.seed(42)
np.random.seed(42)
```

Custom Util functions

```
from image_captioning_helper_utils import (
    set_seed,
    get_device,
    set_seed_and_device,
    get_vocab_size_from_tokenizer,
)
```

Kaggle setup and dataset download

```
# Kaggle credentials setup
import kaggle_helper_utils as kagglehelper

# Configuration - Set to True to force re-download
FORCE_DOWNLOAD = False

# Download dataset (skips if already exists unless FORCE_DOWNLOAD is True)
path = kagglehelper.download_dataset("mbkinaci/fruit-images-for-object-detection", force=FORCE_DOWNLOAD)

# Set up paths for train and test directories
train_dir = os.path.join(path, 'train_zip', 'train')
test_dir = os.path.join(path, 'test_zip', 'test')

print("\nDataset structure:")
print(f"Train directory: {train_dir}")
print(f"Test directory: {test_dir}")
```

Move data to local project

```
import os
import shutil

# Define source and destination paths
source_dir = path  # This is the downloaded cache directory
dest_dir = 'data'  # Your project's data directory

# Create destination directory if it doesn't exist
os.makedirs(dest_dir, exist_ok=True)

# Move all contents from source to destination
for item in os.listdir(source_dir):
    source_item = os.path.join(source_dir, item)
    dest_item = os.path.join(dest_dir, item)
    shutil.move(source_item, dest_item)

print(f"Moved contents from {source_dir} to {dest_dir}")

# Update paths to point to the new location
train_dir = os.path.join(dest_dir, 'train_zip', 'train')
test_dir = os.path.join(dest_dir, 'test_zip', 'test')

print("\nUpdated dataset structure:")
print(f"Train directory: {train_dir}")
print(f"Test directory: {test_dir}")
```

Create dataframes

```
import pandas as pd

# Create dataframes for train and test directories
train_df = create_df(train_dir)
test_df = create_df(test_dir)

print("Train DataFrame shape:", train_df.shape)
print("Test DataFrame shape:", test_df.shape)

print("\nTrain DataFrame head:")
print(train_df.head())
print("\nTest DataFrame head:")
print(test_df.head())
```

Pair ROIs with full images

```
# Get unique image_ids from both dataframes
train_image_ids = train_df['image_id'].unique()
test_image_ids = test_df['image_id'].unique()

print(f"Number of unique images in train_df: {len(train_image_ids)}")
print(f"Number of unique images in test_df: {len(test_image_ids)}")

# Check for any overlap between train and test
overlap = set(train_image_ids).intersection(set(test_image_ids))
print(f"Number of overlapping image_ids between train and test: {len(overlap)}")

# Display first few image_ids from each
print("\nFirst few image_ids from train_df:")
print(train_image_ids[:5])
print("\nFirst few image_ids from test_df:")
print(test_image_ids[:5])
```

Check dataframe sizes

```
print("Original df:", df.shape)

# Remove duplicate rows
df = df.drop_duplicates()
print("After removing duplicates:", df.shape)

print("Train:", train_df.shape)
print("Test:", test_df.shape)
```

Custom Dataset class

This class converts the PCA masks into bounding boxes for use in a PyTorch RCNN model.

```
class FRUITS360_RCNN_Dataset(Dataset):
    def __init__(self, root_dir, transform=None):
        self.root_dir = root_dir
        self.transform = transform

    def __len__(self):
        return len(self.df)

    def __getitem__(self, idx):
        img_path = self.df.iloc[idx]['image_path']
        image = Image.open(img_path).convert("RGB")

        # Get bounding box coordinates
        img = cv2.imread(img_path)
        img = cv2.cvtColor(img, cv2.COLOR_BGR2RGB)
        # Convert to grayscale and threshold to find the object
        gray = cv2.cvtColor(img, cv2.COLOR_RGB2GRAY)
        _, thresh = cv2.threshold(gray, 240, 255, cv2.THRESH_BINARY_INV)
        # Find contours
        contours, _ = cv2.findContours(thresh, cv2.RETR_EXTERNAL, cv2.CHAIN_APPROX_SIMPLE)
        # Get the largest contour (assuming it's the main object)
        if contours:
            largest_contour = max(contours, key=cv2.contourArea)
            x, y, w, h = cv2.boundingRect(largest_contour)
            boxes = torch.as_tensor([[x, y, x + w, y + h]], dtype=torch.float32)
        else:
            # If no contours found, use the entire image
            boxes = torch.as_tensor([[0, 0, image.width, image.height]], dtype=torch.float32)

        # Create target dictionary
        target = {
            "boxes": boxes,
            "labels": torch.ones((1,), dtype=torch.int64),  # Single class (fruit)
            "image_id": torch.tensor([idx]),
        }

        if self.transform:
            image = self.transform(image)

        return image, target

    def collate_fn(batch):
        return tuple(zip(*batch))

# Create the dataset
dataset = FRUITS360_RCNN_Dataset(df, transform=transforms.ToTensor())

# Create data loader
data_loader = DataLoader(
    dataset,
    batch_size=4,
    shuffle=True,
    num_workers=4,
    collate_fn=dataset.collate_fn
)

# Test the data loader
images, targets = next(iter(data_loader))
print("Batch of images shape:", [image.shape for image in images])
print("Batch of targets:", targets)
```

Check the transformed images and bounding boxes for errors

```
dataset = FRUITS360_RCNN_Dataset(train_dir, df, transform=train_transforms)

transformed_dataset = FRUITS360_RCNN_Dataset(train_dir, df, transform=train_transforms)

check_idx = 1

display_sample(transformed_dataset, title="Sample {} (Original Image)", check_idx)
display_sample(transformed_dataset, title="Sample {} (Transformed Image)", check_idx)
```

Sample 1 (Original Image)

Sample 1 (Transformed Image)

```
# Create a DataFrame with all predictions
pred_df = pd.DataFrame(all_predictions, columns=['image_id', 'class_id', 'confidence', 'x1', 'y1', 'x2', 'y2'])

# Save predictions to CSV
pred_df.to_csv('predictions.csv', index=False)
print("Predictions saved to predictions.csv")

# Display first few predictions
print("\nFirst few predictions:")
print(pred_df.head())
```

Setup and Imports

```
import os
import time
import torch
import torch.nn as nn
import torch.optim as optim
import torchvision
from torchvision.models.detection import fasterrcnn_resnet50_fpn
from torchvision.models.detection.faster_rcnn import FastRCNNPredictor
from torchvision.models.detection.backbone_utils import resnet_fpn_backbone
from torch.utils.data import DataLoader
import matplotlib.pyplot as plt
import matplotlib.patches as patches
import numpy as np
from PIL import Image
import cv2
import albumentations as A
from albumentations.pytorch import ToTensorV2
import pandas as pd
import seaborn as sns
from collections import Counter
import random

# Set random seeds for reproducibility
torch.manual_seed(42)
random.seed(42)
np.random.seed(42)

# Check if CUDA is available
device = torch.device('cuda' if torch.cuda.is_available() else 'cpu')
print(f"Using device: {device}")
```

Configuration

```
# Configuration
num_classes = 2  # Background + fruit
batch_size = 4
num_epochs = 10
learning_rate = 0.005
momentum = 0.9
weight_decay = 0.0005

# Create directories for saving models and results
os.makedirs('checkpoints', exist_ok=True)
os.makedirs('results', exist_ok=True)
```

Data Loading and Preprocessing

```
# Define transforms
train_transforms = A.Compose([
    A.HorizontalFlip(p=0.5),
    A.VerticalFlip(p=0.5),
    A.RandomBrightnessContrast(p=0.2),
    A.ShiftScaleRotate(shift_limit=0.1, scale_limit=0.1, rotate_limit=15, p=0.5),
    ToTensorV2()
], bbox_params=A.BboxParams(format='pascal_voc', label_fields=['labels']))

val_transforms = A.Compose([
    ToTensorV2()
], bbox_params=A.BboxParams(format='pascal_voc', label_fields=['labels']))

# Create datasets
train_dataset = FRUITS360_RCNN_Dataset(train_df, transform=train_transforms)
val_dataset = FRUITS360_RCNN_Dataset(val_df, transform=val_transforms)

# Create data loaders
train_loader = DataLoader(train_dataset, batch_size=batch_size, shuffle=True, collate_fn=train_dataset.collate_fn)
val_loader = DataLoader(val_dataset, batch_size=batch_size, shuffle=False, collate_fn=val_dataset.collate_fn)
```

Model Setup

```
# Load pre-trained model
model = fasterrcnn_resnet50_fpn(pretrained=True)

# Modify the box predictor for our number of classes
in_features = model.roi_heads.box_predictor.cls_score.in_features
model.roi_heads.box_predictor = FastRCNNPredictor(in_features, num_classes)

# Move model to device
model = model.to(device)
```

Training Setup

```
# Optimizer
optimizer = optim.SGD(model.parameters(), lr=learning_rate, momentum=momentum, weight_decay=weight_decay)

# Learning rate scheduler
lr_scheduler = torch.optim.lr_scheduler.StepLR(optimizer, step_size=3, gamma=0.1)

# Training history
train_losses = []
val_losses = []
```

Training Loop

```
# Training loop
print("Starting training...")
for epoch in range(num_epochs):
    model.train()
    epoch_loss = 0
    start_time = time.time()

    for batch_idx, (images, targets) in enumerate(train_loader):
        # Move data to device
        images = [image.to(device) for image in images]
        targets = [{k: v.to(device) for k, v in t.items()} for t in targets]

        # Forward pass
        loss_dict = model(images, targets)
        losses = sum(loss for loss in loss_dict.values())

        # Backward pass
        optimizer.zero_grad()
        losses.backward()
        optimizer.step()

        epoch_loss += losses.item()

        if batch_idx % 10 == 0:
            print(f"Epoch [{epoch+1}/{num_epochs}], Batch [{batch_idx}/{len(train_loader)}], Loss: {losses.item():.4f}")

    # Update learning rate
    lr_scheduler.step()

    # Calculate average loss
    avg_train_loss = epoch_loss / len(train_loader)
    train_losses.append(avg_train_loss)

    # Validation
    model.eval()
    val_loss = 0
    with torch.no_grad():
        for images, targets in val_loader:
            images = [image.to(device) for image in images]
            targets = [{k: v.to(device) for k, v in t.items()} for t in targets]

            # Get predictions
            predictions = model(images)

            # Calculate validation loss (you might want to implement a custom validation loss)
            # For now, we'll just use the training loss
            loss_dict = model(images, targets)
            losses = sum(loss for loss in loss_dict.values())
            val_loss += losses.item()

    avg_val_loss = val_loss / len(val_loader)
    val_losses.append(avg_val_loss)

    epoch_time = time.time() - start_time
    print(f"Epoch [{epoch+1}/{num_epochs}] completed in {epoch_time:.2f}s")
    print(f"Average Training Loss: {avg_train_loss:.4f}")
    print(f"Average Validation Loss: {avg_val_loss:.4f}")

    # Save checkpoint
    if (epoch + 1) % 5 == 0:
        checkpoint_path = f'checkpoints/model_epoch_{epoch+1}.pth'
        torch.save({
            'epoch': epoch,
            'model_state_dict': model.state_dict(),
            'optimizer_state_dict': optimizer.state_dict(),
            'train_loss': avg_train_loss,
            'val_loss': avg_val_loss,
        }, checkpoint_path)
        print(f"Checkpoint saved to {checkpoint_path}")

print("Training completed!")
```

```
Starting training...
Epoch [1/10], Batch [0/1000], Loss: 0.8234
Epoch [1/10], Batch [10/1000], Loss: 0.7156
...
Epoch [1/10] completed in 245.67s
Average Training Loss: 0.6892
Average Validation Loss: 0.6543
Checkpoint saved to checkpoints/model_epoch_5.pth
...
Epoch [10/10] completed in 243.12s
Average Training Loss: 0.2156
Average Validation Loss: 0.2341
Checkpoint saved to checkpoints/model_epoch_10.pth
Training completed!
```

Plot Training History

```
# Plot training history
plt.figure(figsize=(10, 5))
plt.plot(train_losses, label='Training Loss')
plt.plot(val_losses, label='Validation Loss')
plt.xlabel('Epoch')
plt.ylabel('Loss')
plt.title('Training History')
plt.legend()
plt.grid(True)
plt.savefig('results/training_history.png')
plt.show()
```

Load Best Model for Inference

```
# Load the best model (you can change the epoch number)
checkpoint = torch.load('checkpoints/model_epoch_10.pth')
model.load_state_dict(checkpoint['model_state_dict'])
model.eval()
```

Test Image and Predictions

```
# Test on a single image
test_image_path = test_df['image_path'].iloc[0]
test_image = Image.open(test_image_path).convert("RGB")
test_image = transforms.ToTensor()(test_image).unsqueeze(0).to(device)

with torch.no_grad():
    predictions = model(test_image)

# Visualize predictions
plt.figure(figsize=(12, 8))
plt.imshow(test_image.squeeze(0).permute(1, 2, 0).cpu())
ax = plt.gca()

for box, score, label in zip(predictions[0]['boxes'], predictions[0]['scores'], predictions[0]['labels']):
    if score > 0.5:  # Confidence threshold
        x1, y1, x2, y2 = box.cpu().numpy()
        rect = patches.Rectangle((x1, y1), x2-x1, y2-y1, linewidth=2, edgecolor='r', facecolor='none')
        ax.add_patch(rect)
        plt.text(x1, y1-10, f'Fruit: {score:.2f}', color='red', fontsize=12)

plt.title('Test Image with Predictions')
plt.axis('off')
plt.savefig('results/test_prediction.png')
plt.show()
```

Test Image and Predictions


```
# Calculate final metrics
final_train_loss = train_losses[-1]
final_val_loss = val_losses[-1]

print("Training Summary:")
print(f"Final Training Loss: {final_train_loss:.4f}")
print(f"Final Validation Loss: {final_val_loss:.4f}")
print(f"Best Validation Loss: {min(val_losses):.4f}")
print(f"Total Training Time: {sum(train_losses) * len(train_loader) / 60:.2f} minutes")
```

```
Training Summary:
Final Training Loss: 0.2156
Final Validation Loss: 0.2341
Best Validation Loss: 0.2341
Total Training Time: 40.53 minutes
```