

The codelst Package

A **Typst** package to render source code

v1.0.0

2023-07-19

Jonas NEUGEBAUER

<https://github.com/jneug/typst-codelst>

CODELST is a **Typst** package inspired by LaTeX packages like **LISTINGS**. It adds functionality to render source code with line numbers, highlighted lines and more.

Table of contents

I. About

II. Usage

II.1. Use as a package (Typst 0.9.0 and later)	3
II.2. Use as a module	3
II.3. Rendering source code	3
II.4. Formatting	10
II.4.1. Using CODELST for all raw text .	
12	
II.5. Command overview	13

III. Limiations and alternatvies

III.1. Limitations and Issues	19
III.2. Alternatives	19

IV. Index

Part I.

About

This package was created to render source code on my exercise sheets for my computer science classes. The exercises required source code to be set with line numbers that could be referenced from other parts of the document, to highlight certain lines and to load code from external files into my documents.

Since I used LaTeX before, I got inspired by packages like [LISTINGS](#)¹ and attempted to replicate some of its functionality. [CODELST](#) is the result of this effort.

This document is a full description of all available commands and options. The first part provides examples of the major features. The second part is a command reference for [CODELST](#).

See `example.typ/example.pdf` for some quick examples how to use [CODELST](#).

¹<https://ctan.org/package/listings>

Part II. Usage

II.1. Use as a package (Typst 0.9.0 and later)

For Typst 0.9.0 and later, `CODELST` can be imported from the preview repository:

```
#import "@preview/codelst:1.0.0": sourcecode
```

Alternatively, the package can be downloaded and saved into the system dependent local package repository.

Either download the current release from GitHub² and unpack the archive into your system dependent local repository folder³ or clone it directly:

```
git clone https://github.com/jneug/typst-codelst.git codelst-1.0.0
```

In either case, make sure the files are placed in a folder with the correct version number: `codelst-1.0.0`

After installing the package, just import it inside your `typ` file:

```
#import "@local/codelst:1.0.0": sourcecode
```

II.2. Use as a module

To use `CODELST` as a module for one project, get the file `codelst.typ` from the repository and save it in your project folder.

Import the module as usual:

```
#import "codelst.typ": sourcecode
```

II.3. Rendering source code

`CODELST` adds the `#sourcecode()` command with various options to render code blocks. It wraps around any `#raw()` block to add some functionality and formatting options to it:

²<https://github.com/jneug/typst-codelst/releases/latest>

³<https://github.com/typst/packages#local-packages>

2.3 Rendering source code

```
1 #sourcecode[```typ
2   #show "ArtosFlow": name => box[
3     #box(image(
4       "logo.svg",
5       height: 0.7em,
6     ))
7     #name
8   ]
9
10   This report is embedded in the
11   ArtosFlow project. ArtosFlow is a
12   project of the Artos Institute.
13 ```]
```

```
1 #show "ArtosFlow": name => box[
2   #box(image(
3     "logo.svg",
4     height: 0.7em,
5   ))
6   #name
7 ]
8
9 This report is embedded in the
10 ArtosFlow project. ArtosFlow is a
11 project of the Artos Institute.
```

CODELST adds line numbers and some default formatting to the code. Line numbers can be configured with a variety of options and `<frame>` sets a custom wrapper function for the code. Setting `<frame>`: `none` disables the code frame.

```

1  #sourcecode(
2    numbers-side: right,
3    numbering: "I",
4    numbers-start: 10,
5    numbers-first: 11,
6    numbers-step: 4,
7    numbers-style: (i) => align(right, text(fill:blue, emph(i))),
8    frame: none
9  )[``typ
10 #show "ArtosFlow": name => box[
11   #box(image(
12     "logo.svg",
13     height: 0.7em,
14   ))
15   #name
16 ]
17
18 This report is embedded in the
19 ArtosFlow project. ArtosFlow is a
20 project of the Artos Institute.
21 ``]

```

```

#show "ArtosFlow": name => box[
  #box(image(
    "logo.svg",
    height: 0.7em,
  ))
  #name
]

```

XI

XV

```

This report is embedded in the
ArtosFlow project. ArtosFlow is a
project of the Artos Institute.

```

XIX

Since it is common to highlight code blocks by putting them inside a `#block()` element, `CODELST` does so with a light gray background and a border.

The frame can be modified by setting `<frame>` to a function with one argument. To do this globally, an alias for the `#sourcecode()` command can be created:

2.3 Rendering source code

```
1 #let codelst-sourcecode = sourcecode
2 #let sourcecode = codelst-sourcecode.with(
3   frame: block.with(
4     fill: fuchsia.lighten(96%),
5     stroke: 1pt + fuchsia,
6     radius: 2pt,
7     inset: (x: 10pt, y: 5pt)
8   )
9 )
10
11 #sourcecode[``typ
12 #show "ArtosFlow": name => box[
13   #box(image(
14     "logo.svg",
15     height: 0.7em,
16   ))
17   #name
18 ]
19
20 This report is embedded in the
21 ArtosFlow project. ArtosFlow is a
22 project of the Artos Institute.
23 ```]
```

```
1 #show "ArtosFlow": name => box[
2   #box(image(
3     "logo.svg",
4     height: 0.7em,
5   ))
6   #name
7 ]
8
9 This report is embedded in the
10 ArtosFlow project. ArtosFlow is a
11 project of the Artos Institute.
```

Line numbers can be formatted with the `numbers-style` option:

2.3 Rendering source code

```
1 #sourcecode(  
2   gutter:2em,  
3   numbers-style: (lno) => text(fill:luma(120), size:10pt, emph(lno) +  
   sym.arrow.r)  
4 )[``typ  
5 #show "ArtosFlow": name => box[  
6   #box(image(  
7     "logo.svg",  
8     height: 0.7em,  
9   ))  
10  #name  
11 ]  
12  
13 This report is embedded in the  
14 ArtosFlow project. ArtosFlow is a  
15 project of the Artos Institute.  
16 ``]
```

```
1→ #show "ArtosFlow": name => box[  
2→   #box(image(  
3→     "logo.svg",  
4→     height: 0.7em,  
5→   ))  
6→   #name  
7→ ]  
8→  
9→ This report is embedded in the  
10→ ArtosFlow project. ArtosFlow is a  
11→ project of the Artos Institute.
```

CODELST handles whitespace in the code to save space and display the code as intended (and indented). Unnecessary blank lines at the beginning and end will be removed, alongside superfluous indentation:

```
1 #sourcecode[``java  
2  
3   class HelloWorld {  
4     public static void main( String[] args ) {  
5       System.out.println("Hello World!");  
6     }  
7   }  
8  
9  
10 ``]
```

```
1 class HelloWorld {  
2   public static void main( String[] args ) {  
3     System.out.println("Hello World!");  
4   }  
5 }
```

2.3 Rendering source code

This behavior can be disabled or modified:

```
1 #sourcecode(showlines:true, gobble:1, tab-size:4)[``java
2
3     class HelloWorld {
4         public static void main( String[] args ) {
5             System.out.println("Hello World!");
6         }
7     }
8
9
10 ``]
```

```
1
2     class HelloWorld {
3         public static void main( String[] args ) {
4             System.out.println("Hello World!");
5         }
6     }
7
8
```

To show code from a file, load it with `#read()` and pass the result to `#sourcefile()` alongside the filename:

```
1 #sourcefile(read("typst.toml"), file:"typst.toml")
```

```
1 [package]
2 name = "codelst"
3 version = "1.0.0"
4 entrypoint = "codelst.typ"
5 authors = ["Jonas Neugebauer"]
6 license = "MIT"
7 description = "A typst package to render sourcecode."
8 repository = "https://github.com/jneug/typst-codelst"
9 exclude = ["example.typ", "example.pdf", "manual.pdf", "manual.typ",
10 "tbump.toml"]
11 compiler = "0.0.9"
12 keywords = ["sourcecode", "code", "syntax-highlighting", "raw", "line
13 numbers"]
```

It is useful to define an alias for `#sourcefile()`:

```
let codelst-sourcefile = sourcefile
let sourcefile( filename, ..args ) = codelst-sourcefile(
    read(filename), file:filename, ..args
)
```

`#sourcefile()` takes the same arguments as `#sourcecode()`. For example, to limit the output to a range of lines:

2.3 Rendering source code

```
1 #sourcefile(  
2   showrange: (2, 4),  
3   read("typst.toml"),  
4   file:"typst.toml"  
5 )  
  
2 name = "codelst"  
3 version = "1.0.0"  
4 entrypoint = "codelst.typ"
```

Specific lines can be highlighted:

```
1 #sourcefile(  
2   highlighted: (2, 3, 4),  
3   read("typst.toml"),  
4   file:"typst.toml"  
5 )  
  
1 [package]  
2 name = "codelst"  
3 version = "1.0.0"  
4 entrypoint = "codelst.typ"  
5 authors = ["Jonas Neugebauer"]  
6 license = "MIT"  
7 description = "A typst package to render sourcecode."  
8 repository = "https://github.com/jneug/typst-codelst"  
9 exclude = ["example.typ", "example.pdf", "manual.pdf", "manual.typ",  
10 "tbump.toml"]  
11 compiler = "0.0.9"  
12 keywords = ["sourcecode", "code", "syntax-highlighting", "raw", "line  
   numbers"]
```

To reference a line from other parts of the document, `CODELST` looks for labels in the source code and makes them available to Typst. The regex to look for labels can be modified to be compatible with different source syntaxes:

```

1 #sourcefile(
2   label-regex: regex("\(codelst.typ\)"),
3   highlight-labels: true,
4   highlight-color: lime,
5   read("typst.toml"),
6   file:"typst.toml"
7 )
8
9 See #lineref(<codelst.typ>) for the _entrypoint_.

```

```

1 [package]
2 name = "codelst"
3 version = "1.0.0"
4 entrypoint =
5 authors = ["Jonas Neugebauer"]
6 license = "MIT"
7 description = "A typst package to render sourcecode."
8 repository = "https://github.com/jneug/typst-codelst"
9 exclude = ["example.typ", "example.pdf", "manual.pdf", "manual.typ",
10 "tbump.toml"]
11 compiler = "0.0.9"
12 keywords = ["sourcecode", "code", "syntax-highlighting", "raw", "line
    numbers"]

```

See line 4 for the *entrypoint*. (Note how the label was removed from the sourcecode before highlighting.)

II.4. Formatting

`#sourcecode()` can be used inside `#figure()` and will show the correct supplement. It is recommended to allow page breaks for raw figures:

```

1 #show figure.where(kind: raw): set block(breakable: true)


```

Instead of the build in styles, custom functions can be used:

```

1 #sourcecode(
2   numbers-style: (lno) => text(
3     size: 2em,
4     fill:rgb(220, 65, 241),
5     font:("Comic Sans MS"),
6     str(lno)
7   ),
8   frame: (code) => block(
9     width:100%,
10    inset:(x:10%, y:0pt),
11    block(fill: green, width:100%, code)
12  ), raw("*some*
13  _source_
14  = code", lang:"typc"))

```



```

1 *some*
2 _source_
3 = code

```

Using other packages like [SHOWYBOX](#) is easy:

```

1 #import "@preview/showybox:2.0.1": showybox
2
3 #let showycode = sourcecode.with(
4   frame: (code) => showybox(
5     frame: (
6       title-color: red.darken(40%),
7       body-color: red.lighten(90%),
8       border-color: black,
9       thickness: 2pt
10    ),
11    title: "Source code",
12    code
13  )
14 )
15
16 #showycode[```typ
17 *some*
18 _source_
19 = code
20 ```]

```



Source code

```

1 *some*
2 _source_
3 = code

```

This is nice in combination with figures:

```

1 #import "@preview/showybox:2.0.1": showybox
2
3 #show figure.where(kind: raw): (fig) => showybox(
4   frame: (
5     title-color: red.darken(40%),
6     body-color: red.lighten(90%),
7     border-color: black,
8     thickness: 2pt
9   ),
10  title: [#fig.caption.body #h(1fr) #fig.supplement #fig.counter.display()],
11  fig.body
12 )
13
14 #figure(
15   sourcecode(frame: none)[``typ
16     *some*
17     _source_
18     = code
19   ``],
20   caption: "Some code"
21 )

```

Some code

Listing 1

```

1 *some*
2 _source_
3 = code

```

II.4.1. Using `codelst` for all raw text

Since Typst 0.9.0 using a `#show` rule should become possible, but not yet fully implemented in `CODELST`.

Using a `#show` rule to set all `#raw()` blocks inside `#sourcecode()` is not possible, since the command internally creates a new `#raw()` block and would cause Typst to crash with an overflow error. Using a custom `<lang>` can work around this, though:

```

1 #show raw.where(lang: "clst-typ"): (code) => sourcecode(lang:"typ", code)
2
3 ``clst-typ
4 *some*
5 _source_
6 = code
7 ``

```

```

1 *some*
2 _source_
3 = code

```

2.4.1 Formatting

`CODELST` provides two ways to get around this issue, however. One is to set up a custom language that is directly followed by a colon and the true language tag:

```
1 :typ
2 *some*
3 _source_
4 = code
```

This is a robust way to send anything to `CODELST`. But since this might prevent proper syntax highlighting in IDEs, a reversed syntax is possible:

```
1 :codelst
2 *some*
3 _source_
4 = code
```

This will look at the first line of every raw text and if it matches `:codelst`, it will remove the activation tag and send the code to `#sourcecode()`.

Setting up one of these catchall methods is easily done by using the `#codelst()` function in a `#show` rule. Any arguments will be passed on to `#sourcecode()`:

```
1 #show: codelst( ..sourcecode-args )
2
3 // or
4
5 #show: codelst( reversed: true, ..sourcecode-args )
```

II.5. Command overview

```
#sourcecode(
  <lang>: auto,
  <numbering>: "1",
  <numbers-start>: auto,
  <numbers-side>: left,
  <numbers-width>: auto,
  <numbers-style>: "function",
  <numbers-first>: 1,
  <numbers-step>: 1,
  <gutter>: 10pt,
  <tab-indent>: 2,
  <gobble>: auto,
  <highlighted>: (),
  <highlight-color>: rgb("#eaeabd"),
  <label-regex>: regex("// <([a-z-]{3,})>$"),
  <highlight-labels>: false,
  <showrange>: none,
```

2.5 Command overview

```
<showlines>: false,  
<frame>: "code-frame"  
)[<code>]
```

—Argument—

<numbering>: "1" string | function | none

A numbering pattern to use for line numbers. Set to none to disable line numbers.

—Argument—

<numbers-start>: auto integer | auto

The number of the first code line. If set to auto, the first line will be set to the start of <showrange> or 1 otherwise.

—Argument—

<numbers-side>: left | right alignment

On which side of the code the line numbers should appear.

—Argument—

<numbers-width>: auto auto | length

The width of the line numbers column. Setting this to auto will measure the maximum size of the line numbers and size the column accordingly. Giving a negative length will move the numbers out of the frame into the margin.

—Argument—

<numbers-first>: 1 none

The first line number to show. Compared to <numbers-start>, this will not change the numbers but hide all numbers before the given number.

—Argument—

<numbers-step>: 1 none

The step size for line numbers. For <numbers-step>: n only every n -th line number is shown.

—Argument—

<numbers-style>: (i) => i function

A function of one argument to format the line numbers. Should return content.

—Argument—

<gutter>: 10pt none

Gutter between line numbers and code lines.

—Argument—

<tab-indent>: 2 none

Number of spaces to replace tabs at the start of each line with.

—Argument—

2.5 Command overview

How many whitespace characters to remove from each line. By default, the number is automatically determined by finding the maximum number of whitespace all lines have in common. If `<gobble>`: **false**, no whitespace is removed.

Note that the numbers will respect `<numbers-start>`. To highlight the second line with `<numbers-start>`: `15`, pass `<highlighted>`: `(17,)`

Color for highlighting lines.

To reference a line, `#lineref()` should be used.

If set to `true`, lines matching `<label-regex>` will be highlighted.

If settings this and `<numbers-start>`: **auto**, the line numbers will start at the number indicated by the first number in `<showrange>`. Otherwise, the numbering will start as specified with `<numbers-start>`.

15

`<showlines>: false``none`

If set to `true`, no blank lines will be stripped from the start and end of the code. Otherwise, those lines will be removed from the output.

Line numbering will not be adjusted to the removed lines (other than with `<showrange>`).

—Argument—

`<frame>: "code-frame"``function`

A function of one argument to frame the source code. The default is `#code-frame()`. `none` disables any frame.

`#sourcefile(<code>, <file>: none, <lang>: auto, ..<args>)`

Takes a text string `<code>` loaded via the `#read()` function and passes it to `#sourcecode()` for display. If `<file>` is given, the code language is guessed by the file's extension. Otherwise, `<lang>` can be provided explicitly.

Any other `<args>` will be passed to `#sourcecode()`.

```
1 #sourcefile(read("typst.toml"), file:"typst.toml")
```

```
1 [package]
2 name = "codelst"
3 version = "1.0.0"
4 entrypoint = "codelst.typ"
5 authors = ["Jonas Neugebauer"]
6 license = "MIT"
7 description = "A typst package to render sourcecode."
8 repository = "https://github.com/jneug/typst-codelst"
9 exclude = ["example.typ", "example.pdf", "manual.pdf", "manual.typ",
10 "tbump.toml"]
11 compiler = "0.0.9"
12 keywords = ["sourcecode", "code", "syntax-highlighting", "raw", "line
  numbers"]
```

The idea for `#sourcefile()` was to read the provided filename without the need for the user to call `#read()`. Due to the security measure, that packages can only read files from their own directory, the call to `#read()` needs to happen outside `#sourcefile()` in the document.

For this reason, the command differs from `#sourcecode()` only insofar as it accepts a `string` instead of raw `content`.

Future releases might use the `<filename>` for other purposes, though.

To deal with this, simply add the following code to the top of your document to define a local alias for `#sourcefile()`:

```
#let codelst-sourcefile = sourcefile
#let sourcefile( filename, ..args ) = codelst-sourcefile(read(filename),
file:filename, ..args)
```


#lineref(<label>, <supplement>: "line")

Creates a reference to a code line with a label. <label> is the label to reference.

```
1 #sourcecode[```java
2 class HelloWorld {
3     public static void main( String[] args ) { // <main-method>
4         System.out.println("Hello World!");
5     }
6 }
7 ```]
8
9 See #lineref(<main-method>) for a main method in Java.
```

```
1 class HelloWorld {
2     public static void main( String[] args ) {
3         System.out.println("Hello World!");
4     }
5 }
```

See line 2 for a main method in Java.

How to set labels for lines, refer to the documentation of <label-regex> at #name().

#code-frame(<fill>: luma(98.04%), <stroke>: 1pt + luma(78.43%), <inset>: (x: 5pt, y: 10pt), <radius>: 4pt)[<code>]

Convenience function to create a #block() to wrap code inside. The arguments are passed to block.

The default values create the default gray box around source code.

Should be used with the <frame> argument in #sourcecode().

```
1 #code-frame(lorem(20))
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat.

```
1 #sourcecode(
2     frame: code-frame.with(
3         fill: green.lighten(90%),
4         stroke: green
5     )
6 )[```typc
7 lorem(20)
8 ```]
```

```
1 lorem(20)
```

2.5 Command overview

`#code1st(<tag>: "code1st", <reversed>: false, ..<sourcecode-args>)`

Sets up a default style for raw blocks. Read Section II.4.1 for details on how it works.

```
1 #show: code1st()
```

Part III.

Limitations and alternatives

III.1. Limitations and Issues

To lay out the code and line numbers correctly, **CODELST** needs to know the available space before calculating the correct sizes. This will lead to problems when changing the layout of the code later on, for example with a **#show** rule.

The way line numbers are laid out, the alignment might drift off for large code blocks. Page breaks are a major cause for this. If applicable, it can help to split large blocks of code into smaller chunks, for example by using `<showrange>`.

The insets for line highlights are slightly off.

III.2. Alternatives

There are some alternatives to **CODELST** that fill similar purposes, but have more or other functionality. If **CODELST** does not suit your needs, one of those might do the trick.

platformer/typst-algorithms⁴ *Typst module for writing algorithms. Use the `algo` function for writing pseudocode and the `code` function for writing code blocks with line numbers.*

hugo-s29/typst-algo⁵ *This package helps you typeset [pseudo] algorithms in Typst.*

⁴<https://github.com/platformer/typst-algorithms>

⁵<https://github.com/hugo-s29/typst-algo>

Part IV.

Index

C

`#code-frame` 16, 17

`#code1st` 13, 18

F

`#figure` 10

L

`#lineref` 15, 17

N

`numbers-style` 6

R

`#read` 8, 16

S

`#sourcecode` 3, 13

`#sourcefile` 8, 16