Deep Compression: Compressing Deep Neural Networks with Pruning, Trained Quantization and Huffman Coding

Song Han, Huizi Man, William J. Dally


Presented by Glazkova Ekaterina

Deep Learning on Mobile. Tasks




Deep Learning on Mobile. Problems


- Memory Limit
 - Device memory limits
 - App markets limits
- Energy Consumption
- Execution Time




Deep Compression Pipeline



Deep Compression Pipeline. Pruning




Pruning. Reduce Number of Weights




Synapses and neurons before and after pruning [Image Source: <u>Han et al. Learning both Weights and Connections for Efficient Neural Networks</u>]

Pruning. Weights Representation




Representing the matrix sparsity with relative index. Padding filler zero to prevent overflow

Deep Compression Pipeline. Quantization



Trained Quantization and Weight Sharing




Within-cluster sum of squares (WCSS)

$$\underset{C}{\operatorname{arg\,min}} \sum_{i=1}^{k} \sum_{w \in c_i} |w - c_i|^2$$

Quantization. Initialization of Shared Weights

- Forgy (random)
- Density-based
- Linear



Quantization. Feed-Forward and Back-Propagation

$$\frac{\partial \mathcal{L}}{\partial C_k} = \sum_{i,j} \frac{\partial \mathcal{L}}{\partial W_{ij}} \frac{\partial W_{ij}}{\partial C_k} = \sum_{i,j} \frac{\partial \mathcal{L}}{\partial W_{ij}} \mathbb{1}(I_{ij} = k)$$

L - Loss

W - weights

C - cluster centroids

I[i,j] - centroid index of element W[i,j]

Quantization. Compression rate


$$r = \frac{nb}{nlog_2(k) + kb}$$

n - number of connections in network


b - one connection representation (in bits)

k - number of clusters

Quantization. Working Together with Pruning





Deep Compression Pipeline. Pruning



Huffman Coding

- Optimal Prefix Code
- Codewords instead of symbols
- More common symbols represented with fewer bits





[Image Source: Wikipedia]

Huffman Coding. Weights Distribution before HC




Figure 5: Distribution for weight (Left) and index (Right). The distribution is biased.

Experiments. Compression Statistics. LeNet

Table 2: Compression statistics for LeNet-300-100. P: pruning, Q:quantization, H:Huffman coding.

Layer	#Weights	Weights% (P)	Weight bits (P+Q)	Weight bits (P+Q+H)	Index bits (P+Q)	Index bits (P+Q+H)	Compress rate (P+Q)	Compress rate (P+Q+H)
ip1	235K	8%	6	4.4	5	3.7	3.1%	2.32%
ip2	30K	9%	6	4.4	5	4.3	3.8%	3.04%
ip3	1K	26%	6	4.3	5	3.2	15.7%	12.70%
Total	266K	$8\%(12\times)$	6	5.1	5	3.7	$3.1\% (32 \times)$	2.49% (40×)

Table 3: Compression statistics for LeNet-5. P: pruning, Q:quantization, H:Huffman coding.

Layer	#Weights	Weights% (P)	Weight bits (P+Q)	Weight bits (P+Q+H)	Index bits (P+Q)	Index bits (P+Q+H)	Compress rate (P+Q)	Compress rate (P+Q+H)
conv1	0.5K	66%	8	7.2	5	1.5	78.5%	67.45%
conv2	25K	12%	8	7.2	5	3.9	6.0%	5.28%
ip1	400K	8%	5	4.5	5	4.5	2.7%	2.45%
ip2	5K	19%	5	5.2	5	3.7	6.9%	6.13%
Total	431K	$8\%(12\times)$	5.3	4.1	5	4.4	3.05% (33 ×)	$2.55\% (39 \times)$


Experiments. Compression Statistics. AlexNet

3101	2000-1200-1200	Weights%	Weight	Weight	Index	Index	Compress	Compress
Layer	#Weights		bits	bits	bits	bits	rate	rate
	195,300,0	(P)	(P+Q)	(P+Q+H)	(P+Q)	(P+Q+H)	(P+Q)	(P+Q+H)
conv1	35K	84%	8	6.3	4	1.2	32.6%	20.53%
conv2	307K	38%	8	5.5	4	2.3	14.5%	9.43%
conv3	885K	35%	8	5.1	4	2.6	13.1%	8.44%
conv4	663K	37%	8	5.2	4	2.5	14.1%	9.11%
conv5	442K	37%	8	5.6	4	2.5	14.0%	9.43%
fc6	38M	9%	5	3.9	4	3.2	3.0%	2.39%
fc7	17M	9%	5	3.6	4	3.7	3.0%	2.46%
fc8	4 M	25%	5	4	4	3.2	7.3%	5.85%
Total	61M	$11\%(9\times)$	5.4	4	4	3.2	$3.7\% (27 \times)$	2.88% (35 ×)

Experiments. Accuracy

Network	Top-1 Error	Top-5 Error	Parameters	Compress Rate
LeNet-300-100 Ref	1.64%	-	1070 KB	
LeNet-300-100 Compressed	1.58%	-	27 KB	40 ×
LeNet-5 Ref	0.80%	-	1720 KB	
LeNet-5 Compressed	0.74%	-	44 KB	39 ×
AlexNet Ref	42.78%	19.73%	240 MB	
AlexNet Compressed	42.78%	19.70%	6.9 MB	$35 \times$
VGG-16 Ref	31.50%	11.32%	552 MB	
VGG-16 Compressed	31.17%	10.91%	11.3 MB	49 ×

Experiments. Speedup and Energy Efficiency



[Source:

20

Experiments. Other methods on AlexNet

Network	Top-1 Error	Top-5 Error	Parameters	Compress Rate
Baseline Caffemodel (BVLC)	42.78%	19.73%	240MB	1×
Fastfood-32-AD (Yang et al., 2014)	41.93%	-	131MB	$2\times$
Fastfood-16-AD (Yang et al., 2014)	42.90%	-	64MB	$3.7 \times$
Collins & Kohli (Collins & Kohli, 2014)	44.40%	-	61MB	$4\times$
SVD (Denton et al., 2014)	44.02%	20.56%	47.6MB	$5 \times$
Pruning (Han et al., 2015)	42.77%	19.67%	27MB	$9\times$
Pruning+Quantization	42.78%	19.70%	8.9MB	$27\times$
Pruning+Quantization+Huffman	42.78%	19.70%	6.9MB	$35 \times$

Conclusion

- Deep Compression 3 stage approach
- The same or better accuracy
- Weights are compressed in 35-49 times
- Model works faster and uses less energy

References

- 1. S. Han, H. Mao, and W. J. Dally. Deep compression: Compressing deep neural network with pruning, trained quantization and huffman coding, 2016. <u>arXiv: 1510.00149</u>
- 2. S.Han, J.Pool, J.Tran, W.Dally. Learning both Weights and Connections for Efficient Neural Networks, 2015. arXiv: 1506.02626
- 3. A. Howard, M. Zhu, Bo Chen, D.Kalenichenko, W. Wang, T. Weyand, M. Andreetto, H. Adam MobileNets: Efficient Convolutional Neural Networks for Mobile Vision Applications, 2017 arXiv: 1704.04861
- 4. Deep compression on ICLR 2016 (Video lecture)
- 5. Wikipedia Huffman coding (<u>link</u>)