原生Python

Astra Automation 21.12

NetApp
July 12, 2022

This PDF was generated from https://docs.netapp.com/zh-tw/astra-automation-2112/python/python_before.html on July 12, 2022. Always check docs.netapp.com for the latest.

目錄

原生Python 1
開始之前 1
列出託管應用程式 1

原生Python

開始之前

Python是熱門的開發語言、尤其是資料中心自動化。在將Python的原生功能與數個通用套件搭配使用之前、您必須先準備環境和所需的輸入檔。

> 除了直接使用Python存取Astra Control REST API之外、NetApp也提供工具套件、可擷取API並移除部分複雜性。請參閱 "NetApp Astra Control Python SDK" 以取得更多資訊。

準備環境

執行Python指令碼的基本組態需求如下所述。

您需要安裝最新版本的Python 3。

必須安裝*請求*和* urllib3*程式庫。您可以根據環境使用pip或其他Python管理工具。

執行指令碼的工作站必須具備網路存取權、而且必須能夠連線到Astra Control。使用Astra Control Service時、您必須連線至網際網路、才能連線至https://astra.netapp.io`上的服務。

您需要具有帳戶識別碼和API權杖的有效Astra帳戶。請參閱 "取得API權杖" 以取得更多資訊。

建立Json輸入檔

Python指令碼仰賴Json輸入檔中包含的組態資訊。範例檔案如下所示。

> 您需要視環境的需求更新範例。

下列檔案包含API權杖和Astra帳戶。您需要使用「-I」（或「-identity」）CLI參數、將此檔案傳遞給Python指令碼。

```
{
  "api_token": "kH4CA_uVIa8q9UuPzhJaAHaGlaR7-no901DkkrVjIXk=",
  "account_id": "5131dfdf-03a4-5218-ad4b-fe84442b9786"
}
```

列出託管應用程式

您可以使用下列指令碼來列出Astra帳戶的託管應用程式。

> 請參閱 "開始之前" 以取得所需Json輸入檔的範例。

```
#!/usr/bin/env python3
```

```
##-----------------------------------------------------------------------
------
#
# Usage: python3 list_man_apps.py -i identity_file.json
#
# (C) Copyright 2021 NetApp, Inc.
#
# This sample code is provided AS IS, with no support or warranties of
# any kind, including but not limited for warranties of merchantability
# or fitness of any kind, expressed or implied. Permission to use,
# reproduce, modify and create derivatives of the sample code is granted
# solely for the purpose of researching, designing, developing and
# testing a software application product for use with NetApp products,
# provided that the above copyright notice appears in all copies and
# that the software application product is distributed pursuant to terms
# no less restrictive than those set forth herein.
#
##-----------------------------------------------------------------------
------

import argparse
import json
import requests
import urllib3
import sys

# Global variables
api_token = ""
account_id = ""

def get_managed_apps():
    ''' Get and print the list of managed apps '''

    # Global variables
    global api_token
    global account_id

    # Create an HTTP session
    sess1 = requests.Session()

    # Suppress SSL unsigned certificate warning
    urllib3.disable_warnings(urllib3.exceptions.InsecureRequestWarning)

    # Create URL
    url1 = "https://astra.netapp.io/accounts/" + account_id +
"/k8s/v1/managedApps"
```

```
    # Headers and response output
    req_headers  = {}
    resp_headers = {}
    resp_data    = {}

    # Prepare the request headers
    req_headers.clear
    req_headers['Authorization'] = "Bearer " + api_token
    req_headers['Content-Type'] = "application/astra-managedApp+json"
    req_headers['Accept'] = "application/astra-managedApp+json"

    # Make the REST call
    try:
        resp1 = sess1.request('get', url1, headers=req_headers,
allow_redirects=True, verify=False)

    except requests.exceptions.ConnectionError:
        print("Connection failed")
        sys.exit(1)

    # Retrieve the output
    http_code = resp1.status_code
    resp_headers = resp1.headers

    # Print the list of managed apps
    if resp1.ok:
        resp_data = json.loads(resp1.text)
        items = resp_data['items']
        for i in items:
            print(" ")
            print("Name: " + i['name'])
            print("ID: " + i['id'])
            print("State: " + i['state'])
    else:
        print("Failed with HTTP status code: " + str(http_code))

    print(" ")

    # Close the session
    sess1.close()

    return

def read_id_file(idf):
    ''' Read the identity file and save values '''

    # Global variables
```

```
    global api_token
    global account_id

    with open(idf) as f:
        data = json.load(f)

    api_token = data['api_token']
    account_id = data['account_id']

    return

def main(args):
    ''' Main top level function '''

    # Global variables
    global api_token
    global account_id

    # Retrieve name of JSON input file
    identity_file = args.id_file

    # Get token and account
    read_id_file(identity_file)

    # Issue REST call
    get_managed_apps()

    return

def parseArgs():
        ''' Parse the CLI input parameters '''

        parser = argparse.ArgumentParser(description='Astra REST API -
List the managed apps',
                                add_help = True)
        parser.add_argument("-i", "--identity", action="store", dest
="id_file", default=None,
                                help='(Req) Name of the identity input file',
required=True)

        return parser.parse_args()

if __name__ == '__main__':
    ''' Begin here '''

    # Parse input parameters
    args = parseArgs()
```

```
    # Call main function
    main(args)
```

版權資訊

Copyright©2022 NetApp、Inc.版權所有。美國印製本文件中版權所涵蓋的任何部分、不得以任何形式或任何方式（包括影印、錄製、 在未事先取得版權擁有者書面許可的情況下、在電子擷取系統中進行錄音或儲存。

衍生自受版權保護之NetApp資料的軟體必須遵守下列授權與免責聲明：

本軟體係由NetApp「依現狀」提供、不含任何明示或暗示的保證、包括但不限於適售性及特定用途適用性的暗示保證、特此聲明。在任何情況下、NetApp均不對任何直接、間接、偶發、特殊、示範、 或衍生性損害（包括但不限於採購替代商品或服務；使用損失、資料或利潤損失； 或業務中斷）、無論是在合約、嚴格責任或侵權行為（包括疏忽或其他）中、無論是因使用本軟體而產生的任何責任理論（包括疏忽或其他）、即使已被告知可能造成此類損害。

NetApp保留隨時變更本文所述之任何產品的權利、恕不另行通知。除非NetApp以書面明確同意、否則NetApp不承擔因使用本文所述產品而產生的任何責任或責任。使用或購買本產品並不代表NetApp擁有任何專利權利、商標權利或任何其他智慧財產權。

本手冊所述產品可能受到一或多個美國國家/地區的保護專利、國外專利或申請中。

限制權利圖例：政府使用、複製或揭露受DFARS 252.277-7103（1988年10月）和FAR 52-227-19（1987年6月）技術資料與電腦軟體權利條款（c）（1）（ii）分段所述限制。

商標資訊

NetApp、NetApp標誌及所列的標章 http://www.netapp.com/TM 為NetApp、Inc.的商標。其他公司和產品名稱可能為其各自所有者的商標。