使用 Python

Astra Automation 22.04

NetApp
August 03, 2022

This PDF was generated from https://docs.netapp.com/zh-cn/astra-automation-2204/python/astra_toolkits.html on August 03, 2022. Always check docs.netapp.com for the latest.

目录

使用 Python 1
NetApp Astra Control Python SDK 1
原生 Python 2

使用 Python

NetApp Astra Control Python SDK

NetApp Astra Control Python SDK 是一个开源软件包，可用于自动部署 Astra Control 。该软件包也是了解 Astra Control REST API 的宝贵资源，或许可以在创建您自己的自动化平台时使用。

> 为了简单起见，本页其余部分将 NetApp Astra Control Python SDK 称为 * SDK * 。

两个相关软件工具

SDK 包含两个不同但相关的工具，这些工具在访问 Astra Control REST API 时在不同的抽象级别运行。

Astra SDK 提供核心平台功能。它包括一组 Python 类，用于抽象化底层 REST API 调用。这些类支持对各种 Astra Control 资源执行管理操作，包括应用程序，备份，快照和集群。

Astra SDK 是该软件包的一部分，并在单个 `astraSDK.py` 文件中提供。您可以将此文件导入到您的环境中并直接使用这些类。

> NetApp Astra Control Python SDK* （或仅 SDK ）是整个软件包的名称。* Astra SDK* 是指单个文件 `astraSDK.py` 中的核心 Python 类。

除了 Astra SDK 文件之外，还可以使用 `toolkup.py` 脚本。此脚本可通过访问内部定义为 Python 函数的独立管理操作，在较高的抽象级别下运行。该脚本将导入 Astra SDK 并根据需要调用类。

如何访问

您可以通过以下方式访问 SDK 。

SDK 可从获取 "Python 软件包索引" 名称为 * NetApp-Astra-toolkits* 。软件包将分配一个版本号，并将根据需要继续更新。您必须使用 * Pip* 软件包管理实用程序将软件包安装到您的环境中。

请参见 "PyPI： NetApp Astra Control Python SDK" 有关详细信息 …

此外，还可以从 GitHub 获取 SDK 源代码。存储库包括以下内容：

- `astraSDK.py` （采用 Python 类的 Astra SDK ）
- `toolkit .py` （基于函数的高级脚本）
- 详细的安装要求和说明
- 安装脚本
- 其他文档

您可以克隆 "GitHub： NetApp/NetApp-Astra-toolkits." 存储库连接到本地环境。

安装和基本要求

在安装软件包并准备使用该软件包时，需要考虑多个选项和要求。

您可以通过以下方式之一安装 SDK：

- 使用 Pip 将 PyPI 中的软件包安装到 Python 环境中
- 克隆 Git Hub 存储库，然后执行以下任一操作：
  - 将软件包部署为 Docker 容器（其中包括您需要的所有内容）
  - 复制这两个核心 Python 文件，以便可以通过 Python 客户端代码访问它们

有关详细信息，请参见 PyPI 和 GitHub 页面。

无论是直接使用 Astra SDK 中的 Python 类，还是使用 `toolkape.py` 脚本中的功能，最终您将在部署 Astra Control 时访问 REST API 。因此，您需要一个 Astra 帐户以及一个 API 令牌。请参见 "开始之前" 有关详细信息，请参见本文档 * 入门 * 一节中的其他页面。

SDK 具有与本地 Python 环境相关的几个前提条件。例如，您必须使用 Python 3.5 或更高版本。此外，还需要几个 Python 软件包。有关详细信息，请参见 GitHub 存储库页面或 PyPI 软件包页面。

有用资源摘要

下面是您开始使用所需的一些资源。

- "PyPI： NetApp Astra Control Python SDK"
- "GitHub： NetApp/NetApp-Astra-toolkits."

原生 Python

开始之前

Python 是一种受欢迎的开发语言，尤其适用于数据中心自动化。在将 Python 的原生功能与多个通用软件包结合使用之前，您需要准备环境和所需的输入文件。

> 除了使用 Python 直接访问 Astra Control REST API 之外， NetApp 还提供了一个工具包软件包，用于抽象化 API 并消除一些复杂性。请参见 "NetApp Astra Control Python SDK" 有关详细信息…

准备环境

下面介绍了运行 Python 脚本的基本配置要求。

您需要安装最新版本的 Python 3 。

必须安装 * 请求 * 和 * urllib3* 库。您可以根据环境需要使用 pip 或其他 Python 管理工具。

运行脚本的工作站必须能够访问网络并访问 Astra Control 。使用 Astra 控制服务时，您必须连接到互联网，并且能够连接到 `https://astra.netapp.io` 上的服务。

您需要一个具有帐户标识符和 API 令牌的有效 Astra 帐户。请参见 "获取 API 令牌" 有关详细信息 ...

创建 **JSON** 输入文件

Python 脚本依赖于 JSON 输入文件中包含的配置信息。下面提供了示例文件。

> 您需要根据环境的具体情况更新这些示例。

以下文件包含 API 令牌和 Astra 帐户。您需要使用 `-i` （或 `-identity`） CLI 参数将此文件传递到 Python 脚本。

```
{
  "api_token": "kH4CA_uVIa8q9UuPzhJaAHaGlaR7-no901DkkrVjIXk=",
  "account_id": "5131dfdf-03a4-5218-ad4b-fe84442b9786"
}
```

列出受管应用程序

您可以使用以下脚本列出 Astra 帐户的受管应用程序。

> 请参见 "开始之前" 所需 JSON 输入文件的示例。

```
#!/usr/bin/env python3
##-----------------------------------------------------------------------
------
#
# Usage: python3 list_man_apps.py -i identity_file.json
#
# (C) Copyright 2021 NetApp, Inc.
#
# This sample code is provided AS IS, with no support or warranties of
# any kind, including but not limited for warranties of merchantability
# or fitness of any kind, expressed or implied. Permission to use,
# reproduce, modify and create derivatives of the sample code is granted
# solely for the purpose of researching, designing, developing and
# testing a software application product for use with NetApp products,
# provided that the above copyright notice appears in all copies and
# that the software application product is distributed pursuant to terms
# no less restrictive than those set forth herein.
#
##-----------------------------------------------------------------------
------

import argparse
import json
```

```python
import requests
import urllib3
import sys

# Global variables
api_token = ""
account_id = ""

def get_managed_apps():
    ''' Get and print the list of managed apps '''

    # Global variables
    global api_token
    global account_id

    # Create an HTTP session
    sess1 = requests.Session()

    # Suppress SSL unsigned certificate warning
    urllib3.disable_warnings(urllib3.exceptions.InsecureRequestWarning)

    # Create URL
    url1 = "https://astra.netapp.io/accounts/" + account_id +
"/k8s/v1/managedApps"

    # Headers and response output
    req_headers  = {}
    resp_headers = {}
    resp_data    = {}

    # Prepare the request headers
    req_headers.clear
    req_headers['Authorization'] = "Bearer " + api_token
    req_headers['Content-Type'] = "application/astra-managedApp+json"
    req_headers['Accept'] = "application/astra-managedApp+json"

    # Make the REST call
    try:
        resp1 = sess1.request('get', url1, headers=req_headers,
allow_redirects=True, verify=False)

    except requests.exceptions.ConnectionError:
        print("Connection failed")
        sys.exit(1)

    # Retrieve the output
    http_code = resp1.status_code
```

```
    resp_headers = resp1.headers

    # Print the list of managed apps
    if resp1.ok:
        resp_data = json.loads(resp1.text)
        items = resp_data['items']
        for i in items:
            print(" ")
            print("Name: " + i['name'])
            print("ID: " + i['id'])
            print("State: " + i['state'])
    else:
        print("Failed with HTTP status code: " + str(http_code))

    print(" ")

    # Close the session
    sess1.close()

    return

def read_id_file(idf):
    ''' Read the identity file and save values '''

    # Global variables
    global api_token
    global account_id

    with open(idf) as f:
        data = json.load(f)

    api_token = data['api_token']
    account_id = data['account_id']

    return

def main(args):
    ''' Main top level function '''

    # Global variables
    global api_token
    global account_id

    # Retrieve name of JSON input file
    identity_file = args.id_file

    # Get token and account
```

```
    read_id_file(identity_file)

    # Issue REST call
    get_managed_apps()

    return

def parseArgs():
        ''' Parse the CLI input parameters '''

        parser = argparse.ArgumentParser(description='Astra REST API -
List the managed apps',
                                add_help = True)
        parser.add_argument("-i", "--identity", action="store", dest
="id_file", default=None,
                                help='(Req) Name of the identity input file',
required=True)

        return parser.parse_args()

if __name__ == '__main__':
    ''' Begin here '''

    # Parse input parameters
    args = parseArgs()

    # Call main function
    main(args)
```

版权信息

版权所有©2022 NetApp、Inc.。保留所有权利。Printed in the U.S.版权所涵盖的本文档的任何部分不得以任何形式或任何手段复制、包括影印、录制、 磁带或存储在电子检索系统中—未经版权所有者事先书面许可。

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

本软件由NetApp按"原样"提供、不含任何明示或默示担保、包括但不限于适销性和特定用途适用性的默示担保、特此声明不承担任何责任。IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice.NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp.The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S.patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

商标信息

NetApp、NetApp标识和中列出的标记 http://www.netapp.com/TM 是NetApp、Inc.的商标。其他公司和产品名称可能是其各自所有者的商标。