# Task

## Astra Automation

NetApp
April 28, 2023

This PDF was generated from https://docs.netapp.com/fr-fr/astra-automation-2211/reference/task_overview.html on April 28, 2023. Always check docs.netapp.com for the latest.

# Table des matières

Task . . . . . 1
Task overview . . . . . 1
List all tasks . . . . . 1
Retrieve a task . . . . . 15

# Task

## Task overview

The Task App API provides CRUD (Create-Read-Update-Delete) access to managed task resources in order to represent long-running tasks.

## List all tasks

GET `/accounts/{account_id}/core/v1/tasks`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br><br>• example: {{.Account}} |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id" |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
|---|---|---|---|
| items | array[Any of: task_1.0_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

#### Example response

```
{
  "type": "application/astra-tasks",
  "version": "1.0",
  "items": [
```

```
    {
      "type": "application/astra-task",
      "version": "1.0",
      "id": "ae1e6561-9e22-406c-8a5a-762f4604da00",
      "name": "astra.backup.prep",
      "summary": "Backup preparation",
      "description": "Task to prepare for the application backup",
      "service": "nautilus",
      "parentTaskID": "9cc8c321-6af1-406c-8158-2c6582c247f8",
      "resourceID": "626a0978-d55f-4841-8b7c-dc0c0f592c6f",
      "resourceURI": "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/k8s/v1/apps/7c8bef49-697e-4fb4-810c-
675cef4cf6c9/appSnaps/5cb608f9-571b-492e-a520-5bfb900a9b9c",
      "resourceCollectionURI": [
        "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/f8b58091-4b9c-4c64-9b40-
018dbaf7c5de/apps/f670bf11-8850-44bd-b330-815af6186a06/appSnaps/5cb608f9-
571b-492e-a520-5bfb900a9b9c",
        "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/923708f8-0435-45b5-8c00-
fbdef3ffaf25/apps/f670bf11-8850-44bd-b330-815af6186a06/appSnaps/5cb608f9-
571b-492e-a520-5bfb900a9b9c"
      ],
      "state": "running",
      "stateTransitions": [
        {
          "from": "running",
          "to": [
            "paused",
            "cancelled"
          ]
        },
        {
          "from": "paused",
          "to": [
            "running",
            "cancelled"
          ]
        }
      ],
      "stateDetails": [],
      "orderHint": 0,
```

```
      "percentDone": 20.25,
      "startTime": "2020-08-06T12:24:52.256624Z",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "00000000-0000-0000-0000-000000000000"
      }
    },
    {
      "type": "application/astra-task",
      "version": "1.0",
      "id": "bc1e6561-9e22-406c-8a5a-762f4604da00",
      "name": "astra.backup",
      "summary": "Backup",
      "description": "Task to take a Backup for an application",
      "service": "nautilus",
      "resourceID": "736a0978-d55f-4841-8b7c-dc0c0f592c6f",
      "resourceURI": "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/k8s/v1/apps/7c8bef49-697e-4fb4-810c-
675cef4cf6c9/appBackups/736a0978-d55f-4841-8b7c-dc0c0f592c6f",
      "resourceCollectionURI": [
        "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/f8b58091-4b9c-4c64-9b40-
018dbaf7c5de/apps/f670bf11-8850-44bd-b330-
815af6186a06/appBackups/736a0978-d55f-4841-8b7c-dc0c0f592c6f",
        "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/923708f8-0435-45b5-8c00-
fbdef3ffaf25/apps/f670bf11-8850-44bd-b330-
815af6186a06/appBackups/736a0978-d55f-4841-8b7c-dc0c0f592c6f"
      ],
      "state": "completed",
      "stateTransitions": [
        {
          "from": "running",
          "to": [
            "paused",
            "cancelled"
          ]
        },
        {
          "from": "paused",
```

```
            "to": [
              "running",
              "cancelled"
            ]
          }
        ],
        "stateDetails": [],
        "orderHint": 0,
        "percentDone": 100,
        "startTime": "2020-08-06T12:24:52.256624Z",
        "endTime": "2020-08-06T12:26:52.256624Z",
        "metadata": {
          "labels": [],
          "creationTimestamp": "2020-08-06T12:24:52.256624Z",
          "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
          "createdBy": "00000000-0000-0000-0000-000000000000"
        }
      }
    ],
    "metadata": {
      "labels": [],
      "creationTimestamp": "2022-10-06T20:58:16.305662Z",
      "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
      "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
    }
  }
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

type_astra_stateTransitions

| Name | Type | Required | Description |
|---|---|---|---|
| from | string | True | |
| to | array[string] | True | |

type_astra_stateDetails

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

task_1.0_get_response_body

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-task"<br>• example: application/astra-task |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• example: 1.0 |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: b1c006b2-2ebf-5dfb-994e-e807c184ac0a |
| name | string | True | JSON string containing a dot notation (.) hierarchical name for the task. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 127<br>• Defined regex is: "^[a-z])(\.([a-z])+$"<br>• example: astra.backup.prep |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| summary | string | True | JSON string containing the short-form summary of the task. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 63<br>• example: Backup preparation |
| description | string | True | JSON string containing a description of the task. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 511<br>• example: Task to prepare for application backup |
| service | string | False | JSON string containing the name of the service that is managing the task. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 31<br>• example: nautilus |
| parentTaskID | string | False | JSON string containing a globally unique identifier of a parent task of the task. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 9cc8c321-6af1-406c-8158-2c6582c247f8 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| resourceID | string | True | JSON string containing a globally unique identifier of the resource associated with the task. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 626a0978-d55f-4841-8b7c-dc0c0f592c6f |
| resourceURI | string | True | JSON string containing the URI associated with the task. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 4095<br>• example: /accounts/fdaa655c-15ab-4d34-aa61-1e9098e67be0/k8s/v1/apps/7c8bef49-697e-4fb4-810c-675cef4cf6c9/appBackups/5cb608f9-571b-492e-a520-5bfb900a9b9c |
| resourceCollectionURI | array[string] | True | JSON array of JSON strings, each indicating the fully-expanded access URL of the resource associated with the task. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 4095 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | JSON string containing a value indicating the operational state of the task. Defined values are:<br>• "notStarted" - The task has not started executing.<br>• "running" - The task is running.<br>• "completed" - The task has completed.<br>• "pausing" - The task was requested to pause.<br>• "paused" - The task is paused.<br>• "cancelling" - The task was requested to cancel.<br>• "cancelled" - The task is cancelled.<br>• "failed" - The task has failed.<br>• Minimum length: 1<br>• Maximum length: 31<br>• example: completed |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateTransitions | array[type_astra_stateTransitions] | True | JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.<br>• Minimum length: 1<br>• Maximum length: 31 For example: "stateTransitions" : [ { "from": "running", "to": ["paused", "cancelled"] }, { "from": "paused", "to": ["running", "cancelled"] }, ] |
| stateDetails | array[type_astra_stateDetails] | True | JSON array of JSON objects that lists additional details about the current "state". This field indicates when there are conditions or errors that prevent the actual state from matching the desired state. If no details are available, this array will be empty.<br>• Minimum Items: 0 |
| orderHint | number | False | JSON number representing the order of subtasks. This field can be used by the client to sort subtasks from smallest to largest.<br>• example: 1 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| percentDone | number | False | JSON number containing the percentage complete for a running task. When the task is completed, this is set to "100".<br>• example: 99.99 |
| startTime | string | False | JSON string containing the timestamp indicating when the task started. Defined values are:<br>• Conforms to the ISO-8601 Date Time Schema<br>• example: 2020-08-06T12:24:52.256624Z |
| endTime | string | False | JSON string containing the timestamp indicating when the task ended. Defined values are:<br>• Conforms to the ISO-8601 Date Time Schema<br>• example: 2020-08-06T12:28:52.256624Z |
| cancelTime | string | False | JSON string containing the timestamp indicating when the task was cancelled. Defined values are:<br>• Conforms to the ISO-8601 Date Time Schema<br>• example: 2020-08-06T12:26:52.256624Z |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve a task

GET `/accounts/{account_id}/core/v1/tasks/{task_id}`

Returns the stored Task API resource in the JSON response body.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| task_id | string | path | True | ID of the task collection to list |

## Response

```
Status: 200, Returns the stored Task API resource in the JSON response
body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-task"<br>• example: application/astra-task |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• example: 1.0 |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: b1c006b2-2ebf-5dfb-994e-e807c184ac0a |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | JSON string containing a dot notation (.) hierarchical name for the task. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 127<br>• Defined regex is: "^[a-z])(\.([a-z])+$"<br>• example: astra.backup.prep |
| summary | string | True | JSON string containing the short-form summary of the task. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 63<br>• example: Backup preparation |
| description | string | True | JSON string containing a description of the task. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 511<br>• example: Task to prepare for application backup |
| service | string | False | JSON string containing the name of the service that is managing the task. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 31<br>• example: nautilus |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| parentTaskID | string | False | JSON string containing a globally unique identifier of a parent task of the task. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 9cc8c321-6af1-406c-8158-2c6582c247f8 |
| resourceID | string | True | JSON string containing a globally unique identifier of the resource associated with the task. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 626a0978-d55f-4841-8b7c-dc0c0f592c6f |
| resourceURI | string | True | JSON string containing the URI associated with the task. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 4095<br>• example: /accounts/fdaa655c-15ab-4d34-aa61-1e9098e67be0/k8s/v1/apps/7c8bef49-697e-4fb4-810c-675cef4cf6c9/appBackups/5cb608f9-571b-492e-a520-5bfb900a9b9c |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| resourceCollectionURI | array[string] | True | JSON array of JSON strings, each indicating the fully-expanded access URL of the resource associated with the task. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 4095 |
| state | string | True | JSON string containing a value indicating the operational state of the task. Defined values are:<br>• "notStarted" - The task has not started executing.<br>• "running" - The task is running.<br>• "completed" - The task has completed.<br>• "pausing" - The task was requested to pause.<br>• "paused" - The task is paused.<br>• "cancelling" - The task was requested to cancel.<br>• "cancelled" - The task is cancelled.<br>• "failed" - The task has failed.<br>• Minimum length: 1<br>• Maximum length: 31<br>• example: completed |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateTransitions | array[type_astra_stateTransitions] | True | JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.<br>• Minimum length: 1<br>• Maximum length: 31 For example: "stateTransitions" : [ { "from": "running", "to": ["paused", "cancelled"] }, { "from": "paused", "to": ["running", "cancelled"] }, ] |
| stateDetails | array[type_astra_stateDetails] | True | JSON array of JSON objects that lists additional details about the current "state". This field indicates when there are conditions or errors that prevent the actual state from matching the desired state. If no details are available, this array will be empty.<br>• Minimum Items: 0 |
| orderHint | number | False | JSON number representing the order of subtasks. This field can be used by the client to sort subtasks from smallest to largest.<br>• example: 1 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| percentDone | number | False | JSON number containing the percentage complete for a running task. When the task is completed, this is set to "100".<br><br>• example: 99.99 |
| startTime | string | False | JSON string containing the timestamp indicating when the task started. Defined values are:<br><br>• Conforms to the ISO-8601 Date Time Schema<br>• example: 2020-08-06T12:24:52.256624Z |
| endTime | string | False | JSON string containing the timestamp indicating when the task ended. Defined values are:<br><br>• Conforms to the ISO-8601 Date Time Schema<br>• example: 2020-08-06T12:28:52.256624Z |
| cancelTime | string | False | JSON string containing the timestamp indicating when the task was cancelled. Defined values are:<br><br>• Conforms to the ISO-8601 Date Time Schema<br>• example: 2020-08-06T12:26:52.256624Z |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**


```
{
  "type": "application/astra-task",
  "version": "1.0",
  "id": "b1c006b2-2ebf-5dfb-994e-e807c184ac0a",
  "name": "astra.backup.prep",
  "summary": "Backup preparation",
  "description": "Task to prepare for the application backup",
  "service": "nautilus",
  "parentTaskID": "9cc8c321-6af1-406c-8158-2c6582c247f8",
  "resourceID": "626a0978-d55f-4841-8b7c-dc0c0f592c6f",
  "resourceURI": "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/k8s/v1/apps/7c8bef49-697e-4fb4-810c-
675cef4cf6c9/appSnaps/2b6dafc3-2172-4431-a482-6306b2703130",
  "resourceCollectionURI": [
    "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/f8b58091-4b9c-4c64-9b40-
018dbaf7c5de/apps/f670bf11-8850-44bd-b330-815af6186a06/appSnaps/2b6dafc3-
2172-4431-a482-6306b2703130",
    "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/923708f8-0435-45b5-8c00-
fbdef3ffaf25/apps/f670bf11-8850-44bd-b330-815af6186a06/appSnaps/2b6dafc3-
2172-4431-a482-6306b2703130"
  ],
  "state": "running",
```

```
  "stateTransitions": [
    {
      "from": "running",
      "to": [
        "paused",
        "cancelled"
      ]
    },
    {
      "from": "paused",
      "to": [
        "running",
        "cancelled"
      ]
    }
  ],
  "stateDetails": [],
  "orderHint": 0,
  "percentDone": 20.25,
  "startTime": "2020-08-06T12:24:52.256624Z",
  "endTime": "2020-08-06T12:26:52.256624Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

type_astra_stateTransitions

| Name | Type | Required | Description |
|---|---|---|---|
| from | string | True | |
| to | array[string] | True | |

type_astra_stateDetails

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

**Informations sur le copyright**

Copyright © 2023 NetApp, Inc. Tous droits réservés. Imprimé aux États-Unis. Aucune partie de ce document protégé par copyright ne peut être reproduite sous quelque forme que ce soit ou selon quelque méthode que ce soit (graphique, électronique ou mécanique, notamment par photocopie, enregistrement ou stockage dans un système de récupération électronique) sans l'autorisation écrite préalable du détenteur du droit de copyright.

Les logiciels dérivés des éléments NetApp protégés par copyright sont soumis à la licence et à l'avis de non-responsabilité suivants :

CE LOGICIEL EST FOURNI PAR NETAPP « EN L'ÉTAT » ET SANS GARANTIES EXPRESSES OU TACITES, Y COMPRIS LES GARANTIES TACITES DE QUALITÉ MARCHANDE ET D'ADÉQUATION À UN USAGE PARTICULIER, QUI SONT EXCLUES PAR LES PRÉSENTES. EN AUCUN CAS NETAPP NE SERA TENU POUR RESPONSABLE DE DOMMAGES DIRECTS, INDIRECTS, ACCESSOIRES, PARTICULIERS OU EXEMPLAIRES (Y COMPRIS L'ACHAT DE BIENS ET DE SERVICES DE SUBSTITUTION, LA PERTE DE JOUISSANCE, DE DONNÉES OU DE PROFITS, OU L'INTERRUPTION D'ACTIVITÉ), QUELLES QU'EN SOIENT LA CAUSE ET LA DOCTRINE DE RESPONSABILITÉ, QU'IL S'AGISSE DE RESPONSABILITÉ CONTRACTUELLE, STRICTE OU DÉLICTUELLE (Y COMPRIS LA NÉGLIGENCE OU AUTRE) DÉCOULANT DE L'UTILISATION DE CE LOGICIEL, MÊME SI LA SOCIÉTÉ A ÉTÉ INFORMÉE DE LA POSSIBILITÉ DE TELS DOMMAGES.

NetApp se réserve le droit de modifier les produits décrits dans le présent document à tout moment et sans préavis. NetApp décline toute responsabilité découlant de l'utilisation des produits décrits dans le présent document, sauf accord explicite écrit de NetApp. L'utilisation ou l'achat de ce produit ne concède pas de licence dans le cadre de droits de brevet, de droits de marque commerciale ou de tout autre droit de propriété intellectuelle de NetApp.

Le produit décrit dans ce manuel peut être protégé par un ou plusieurs brevets américains, étrangers ou par une demande en attente.

LÉGENDE DE RESTRICTION DES DROITS : L'utilisation, la duplication ou la divulgation par le gouvernement sont sujettes aux restrictions énoncées dans le sous-paragraphe (b)(3) de la clause Rights in Technical Data-Noncommercial Items du DFARS 252.227-7013 (février 2014) et du FAR 52.227-19 (décembre 2007).

Les données contenues dans les présentes se rapportent à un produit et/ou service commercial (tel que défini par la clause FAR 2.101). Il s'agit de données propriétaires de NetApp, Inc. Toutes les données techniques et tous les logiciels fournis par NetApp en vertu du présent Accord sont à caractère commercial et ont été exclusivement développés à l'aide de fonds privés. Le gouvernement des États-Unis dispose d'une licence limitée irrévocable, non exclusive, non cessible, non transférable et mondiale. Cette licence lui permet d'utiliser uniquement les données relatives au contrat du gouvernement des États-Unis d'après lequel les données lui ont été fournies ou celles qui sont nécessaires à son exécution. Sauf dispositions contraires énoncées dans les présentes, l'utilisation, la divulgation, la reproduction, la modification, l'exécution, l'affichage des données sont interdits sans avoir obtenu le consentement écrit préalable de NetApp, Inc. Les droits de licences du Département de la Défense du gouvernement des États-Unis se limitent aux droits identifiés par la clause 252.227-7015(b) du DFARS (février 2014).

**Informations sur les marques commerciales**

NETAPP, le logo NETAPP et les marques citées sur le site http://www.netapp.com/TM sont des marques déposées ou des marques commerciales de NetApp, Inc. Les autres noms de marques et de produits sont des marques commerciales de leurs propriétaires respectifs.