# Upgrade

## Astra Automation

NetApp
April 28, 2023

This PDF was generated from https://docs.netapp.com/ja-jp/astra-automation-2211/reference/upgrade_overview.html on April 28, 2023. Always check docs.netapp.com for the latest.

# 目次

Upgrade . . . . . 1
Upgrade overview . . . . . 1
List all upgrades . . . . . 1
Retrieve an upgrade . . . . . 12
Modify an upgrade . . . . . 22

# Upgrade

## Upgrade overview

The Upgrade App API provides CRUD (Create-Read-Update-Delete) access to software components that are eligible for upgrade, and to initiate upgrades. The availability of upgrades is determined based on packages registered with the Packages API.

## List all upgrades

GET `/accounts/{account_id}/core/v1/upgrades`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br><br>• example: {{.Account}} |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id"<br><br>• example: id,componentName,upgradeVersion |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
|---|---|---|---|
| items | array[Any of: upgrade_1.1_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

#### Example response

```
{
  "type": "application/astra-upgrades",
  "version": "1.1",
  "items": [
    [
      "01982783-b1eb-4dca-a3fe-a385a3186c53",
      "acc",
      "21.07.1"
    ],
    [
      "0a5abab2-39b2-4101-87b9-0d9b8f537ca1",
      "acc",
      "21.07.2"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

type_astra_stateDetails

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

upgrade_1.1_get_response_body

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-upgrade"<br>• example: application/astra-upgrade |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• example: 1.1 |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: aa9a8e88-c012-55b1-b514-7cd94dc79008 |
| componentName | string | True | JSON string containing the name of the type of software that can be upgraded. Defined values are:<br>• "acc"<br>• "acs"<br>• "trident"<br>• "kubernetes"<br>• example: trident |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| componentInstance | string | True | JSON string containing the URI of the component that can be upgraded. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 4095<br>• example: <a href="https://<dns_name>/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/fdda3ff3-a46a-43a4-902e-444fde2baeba/storageBackends/72d19c3c-eb43-4bec-b23e-a228c900aded</dns_name>" class="bare">https://<dns_name>/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/fdda3ff3-a46a-43a4-902e-444fde2baeba/storageBackends/72d19c3c-eb43-4bec-b23e-a228c900aded</dns_name></a><br><br></dns_name> |
| componentID | string | True | JSON string containing a globally unique identifier of the component that can be upgraded. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 72d19c3c-eb43-4bec-b23e-a228c900aded |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| upgradeVersion | string | True | JSON string containing the SemVer of the software image file that can be upgraded to. Defined values are:<br>• Conforms to the SemVer Schema<br>• example: 21.07.1 |
| currentVersion | string | True | JSON string containing the current SemVer of the entity to be upgraded. Defined values are:<br>• Conforms to the SemVer Schema<br>• example: 21.04.1 |
| dependencies | array[string] | True | JSON array of JSON strings, each containing the UUID of an upgrade that must be completed before this upgrade can proceed. Used to determine which upgrades will be performed as prerequisites and in which order. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | JSON string containing a value indicating the operational state of the upgrade. If auto-upgrade is enabled, upgrades will start in the "scheduled" state. Otherwise, upgrades will start in the "proposed" state. Defined values are:<br>• "unavailable" - The upgrade is not available at this time<br>• "proposed" - The upgrade is proposed but will not automatically run until approved<br>• "scheduled" - The upgrade is approved but is not ready to be installed due to dependencies, time windows, or available resources<br>• "running" - The upgrade is in progress<br>• "complete" - The upgrade has completed<br>• "failed" - The upgrade did not complete<br>• example: scheduled |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | True | JSON string containing a value indicating the desired state for "state". This field is only included when the user can directly request a change in the state of the resource. Defined values are:<br>• "proposed" - The upgrade is not approved and must not be performed<br>• "scheduled" - The upgrade is approved and must be performed in the specified time window<br>• "running" - The upgrade must be performed immediately, regardless of the time window<br>• example: scheduled |
| stateDetails | array[type_astra_stateDetails] | True | JSON array of JSON objects that lists additional details about the current "state". If no details are available, this array will be empty.<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
|---|---|---|---|
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
|---|---|---|---|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve an upgrade

GET `/accounts/{account_id}/core/v1/upgrades/{upgrade_id}`

Returns the stored Upgrade API resource in the JSON response body.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| upgrade_id | string | path | True | ID of the upgrade collection to list |

## Response

```
Status: 200, Returns the stored Upgrade API resource in the JSON response
body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-upgrade"<br>• example: application/astra-upgrade |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• example: 1.1 |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: aa9a8e88-c012-55b1-b514-7cd94dc79008 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| componentName | string | True | JSON string containing the name of the type of software that can be upgraded. Defined values are:<br>• "acc"<br>• "acs"<br>• "trident"<br>• "kubernetes"<br>• example: trident |
| componentInstance | string | True | JSON string containing the URI of the component that can be upgraded. Defined values are:<br>• Minimum length: 3<br>• Maximum length: 4095<br>• example: <a href="https://<dns_name>/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/fdda3ff3-a46a-43a4-902e-444fde2baeba/storageBackends/72d19c3c-eb43-4bec-b23e-a228c900aded</dns_name>" class="bare">https://<dns_name>/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/fdda3ff3-a46a-43a4-902e-444fde2baeba/storageBackends/72d19c3c-eb43-4bec-b23e-a228c900aded</dns_name></a><br><br></dns_name> |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| componentID | string | True | JSON string containing a globally unique identifier of the component that can be upgraded. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 72d19c3c-eb43-4bec-b23e-a228c900aded |
| upgradeVersion | string | True | JSON string containing the SemVer of the software image file that can be upgraded to. Defined values are:<br>• Conforms to the SemVer Schema<br>• example: 21.07.1 |
| currentVersion | string | True | JSON string containing the current SemVer of the entity to be upgraded. Defined values are:<br>• Conforms to the SemVer Schema<br>• example: 21.04.1 |
| dependencies | array[string] | True | JSON array of JSON strings, each containing the UUID of an upgrade that must be completed before this upgrade can proceed. Used to determine which upgrades will be performed as prerequisites and in which order. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | JSON string containing a value indicating the operational state of the upgrade. If auto-upgrade is enabled, upgrades will start in the "scheduled" state. Otherwise, upgrades will start in the "proposed" state. Defined values are:<br>• "unavailable" - The upgrade is not available at this time<br>• "proposed" - The upgrade is proposed but will not automatically run until approved<br>• "scheduled" - The upgrade is approved but is not ready to be installed due to dependencies, time windows, or available resources<br>• "running" - The upgrade is in progress<br>• "complete" - The upgrade has completed<br>• "failed" - The upgrade did not complete<br>• example: scheduled |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | True | JSON string containing a value indicating the desired state for "state". This field is only included when the user can directly request a change in the state of the resource. Defined values are:<br>• "proposed" - The upgrade is not approved and must not be performed<br>• "scheduled" - The upgrade is approved and must be performed in the specified time window<br>• "running" - The upgrade must be performed immediately, regardless of the time window<br>• example: scheduled |
| stateDetails | array[type_astra_stateDetails] | True | JSON array of JSON objects that lists additional details about the current "state". If no details are available, this array will be empty.<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**

```
{
  "type": "application/astra-upgrade",
  "version": "1.1",
  "id": "aa9a8e88-c012-55b1-b514-7cd94dc79008",
  "componentName": "trident",
  "componentInstance": "https://<dns_name>/accounts/0b311ae7-d89a-4a11-
a52c-1349ca090415/topology/v1/clouds/fdda3ff3-a46a-43a4-902e-
444fde2baeba/storageBackends/72d19c3c-eb43-4bec-b23e-a228c900aded",
  "componentID": "72d19c3c-eb43-4bec-b23e-a228c900aded",
  "upgradeVersion": "21.07.1",
  "currentVersion": "21.04.1",
  "dependencies": [],
  "state": "scheduled",
  "stateDesired": "scheduled",
  "stateDetails": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

type_astra_stateDetails

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Modify an upgrade

PUT `/accounts/{account_id}/core/v1/upgrades/{upgrade_id}`

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are

not user-modifiable.

**Side Effects**

- Upgrades are scheduled or run based on desired state.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| upgrade_id | string | path | True | ID of the upgrade collection to list |

## Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

**Side Effects**

- Upgrades are scheduled or run based on desired state.

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-upgrade"<br>• example: application/astra-upgrade |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• example: 1.1 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | False | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: aa9a8e88-c012-55b1-b514-7cd94dc79008 |
| componentName | string | False | JSON string containing the name of the type of software that can be upgraded. Defined values are:<br>• "acc"<br>• "acs"<br>• "trident"<br>• "kubernetes"<br>• example: trident |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| componentInstance | string | False | JSON string containing the URI of the component that can be upgraded. Defined values are:<br><br>• Minimum length: 3<br>• Maximum length: 4095<br>• example: <a href="https://<dns_name>/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/fdda3ff3-a46a-43a4-902e-444fde2baeba/storageBackends/72d19c3c-eb43-4bec-b23e-a228c900aded</dns_name>" class="bare">https://<dns_name>/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/fdda3ff3-a46a-43a4-902e-444fde2baeba/storageBackends/72d19c3c-eb43-4bec-b23e-a228c900aded</dns_name></a><br><br></dns_name> |
| componentID | string | False | JSON string containing a globally unique identifier of the component that can be upgraded. Defined values are:<br><br>• Conforms to the Astra Identifier Schema<br>• example: 72d19c3c-eb43-4bec-b23e-a228c900aded |

| Name | Type | Required | Description |
|---|---|---|---|
| upgradeVersion | string | False | JSON string containing the SemVer of the software image file that can be upgraded to. Defined values are:<br>• Conforms to the SemVer Schema<br>• example: 21.07.1 |
| currentVersion | string | False | JSON string containing the current SemVer of the entity to be upgraded. Defined values are:<br>• Conforms to the SemVer Schema<br>• example: 21.04.1 |
| dependencies | array[string] | False | JSON array of JSON strings, each containing the UUID of an upgrade that must be completed before this upgrade can proceed. Used to determine which upgrades will be performed as prerequisites and in which order. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | False | JSON string containing a value indicating the operational state of the upgrade. If auto-upgrade is enabled, upgrades will start in the "scheduled" state. Otherwise, upgrades will start in the "proposed" state. Defined values are:<br>• "unavailable" - The upgrade is not available at this time<br>• "proposed" - The upgrade is proposed but will not automatically run until approved<br>• "scheduled" - The upgrade is approved but is not ready to be installed due to dependencies, time windows, or available resources<br>• "running" - The upgrade is in progress<br>• "complete" - The upgrade has completed<br>• "failed" - The upgrade did not complete<br>• example: scheduled |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | False | JSON string containing a value indicating the desired state for "state". This field is only included when the user can directly request a change in the state of the resource. Defined values are:<br>• "proposed" - The upgrade is not approved and must not be performed<br>• "scheduled" - The upgrade is approved and must be performed in the specified time window<br>• "running" - The upgrade must be performed immediately, regardless of the time window<br>• example: scheduled |
| stateDetails | array[type_astra_stateDetails] | False | JSON array of JSON objects that lists additional details about the current "state". If no details are available, this array will be empty.<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

#### Example request

```
{
  "type": "application/astra-upgrade",
  "version": "1.1",
  "stateDesired": "running"
}
```

## Response

```
Status: 204, Indicates if the upgrade resource was updated.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

type_astra_stateDetails

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid request body field |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| reason | string | True | Reason why the request body field is invalid |

著作権に関する情報

Copyright © 2023 NetApp, Inc. All Rights Reserved. Printed in the U.S.このドキュメントは著作権によって保護されています。著作権所有者の書面による事前承諾がある場合を除き、画像媒体、電子媒体、および写真複写、記録媒体、テープ媒体、電子検索システムへの組み込みを含む機械媒体など、いかなる形式および方法による複製も禁止します。

ネットアップの著作物から派生したソフトウェアは、次に示す使用許諾条項および免責条項の対象となります。

このソフトウェアは、ネットアップによって「現状のまま」提供されています。ネットアップは明示的な保証、または商品性および特定目的に対する適合性の暗示的保証を含み、かつこれに限定されないいかなる暗示的な保証も行いません。ネットアップは、代替品または代替サービスの調達、使用不能、データ損失、利益損失、業務中断を含み、かつこれに限定されない、このソフトウェアの使用により生じたすべての直接的損害、間接的損害、偶発的損害、特別損害、懲罰的損害、必然的損害の発生に対して、損失の発生の可能性が通知されていたとしても、その発生理由、根拠とする責任論、契約の有無、厳格責任、不法行為（過失またはそうでない場合を含む）にかかわらず、一切の責任を負いません。

ネットアップは、ここに記載されているすべての製品に対する変更を随時、予告なく行う権利を保有します。ネットアップによる明示的な書面による合意がある場合を除き、ここに記載されている製品の使用により生じる責任および義務に対して、ネットアップは責任を負いません。この製品の使用または購入は、ネットアップの特許権、商標権、または他の知的所有権に基づくライセンスの供与とはみなされません。

このマニュアルに記載されている製品は、1つ以上の米国特許、その他の国の特許、および出願中の特許によって保護されている場合があります。

権利の制限について：政府による使用、複製、開示は、DFARS 252.227-7013（2014年2月）およびFAR 5252.227-19（2007年12月）のRights in Technical Data -Noncommercial Items（技術データ - 非商用品目に関する諸権利）条項の(b)(3)項、に規定された制限が適用されます。

本書に含まれるデータは商用製品および / または商用サービス（FAR 2.101の定義に基づく）に関係し、データの所有権はNetApp, Inc.にあります。本契約に基づき提供されるすべてのネットアップの技術データおよびコンピュータ ソフトウェアは、商用目的であり、私費のみで開発されたものです。米国政府は本データに対し、非独占的かつ移転およびサブライセンス不可で、全世界を対象とする取り消し不能の制限付き使用権を有し、本データの提供の根拠となった米国政府契約に関連し、当該契約の裏付けとする場合にのみ本データを使用できます。前述の場合を除き、NetApp, Inc.の書面による許可を事前に得ることなく、本データを使用、開示、転載、改変するほか、上演または展示することはできません。国防総省にかかる米国政府のデータ使用権については、DFARS 252.227-7015(b)項（2014年2月）で定められた権利のみが認められます。

商標に関する情報

NetApp、NetAppのロゴ、http://www.netapp.com/TMに記載されているマークは、NetApp, Inc.の商標です。その他の会社名と製品名は、それを所有する各社の商標である場合があります。