# Execution hook

## Astra Automation

NetApp
May 31, 2023

This PDF was generated from https://docs.netapp.com/it-it/astra-automation/reference/execution_hook_overview.html on May 31, 2023. Always check docs.netapp.com for the latest.

# Sommario

Execution hook . . . 1
- Execution hook overview . . . 1
- Create a new execution hook . . . 1
- List all execution hooks . . . 17
- Retrieve an execution hook . . . 32
- Modify an execution hook . . . 43
- Delete an execution hook . . . 53
- Create a new execution hook for an app . . . 56
- List the execution hooks for an app . . . 72
- Retrieve an execution hook for an app . . . 87
- Modify an execution hook for an app . . . 98
- Delete an execution hook for an app . . . 108

# Execution hook

## Execution hook overview

The Execution Hook API enables simple management of execution hooks. Execution hooks contain additional configuration and references to a hook source resource.

## Create a new execution hook

POST `/accounts/{account_id}/core/v1/executionHooks`

Indicates the desired values for the Execution Hook API resource to be created.

### Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |

### Request Body

Indicates the desired values for the Execution Hook API resource to be created.

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | True | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |
| matchingCriteria | array[matchingCriteria] | False | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| action | string | True | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |
| stage | string | True | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | True | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |
| appID | string | True | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | False | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example request**

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "name": "Payroll",
  "hookType": "custom",
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook"
}
```

## Response

```
Status: 201, Returns the newly created executionHook resource in the JSON
response body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: 946e60cb-980b-5374-9e6e-9fe1f6780352 |
| name | string | True | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | True | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |
| matchingCriteria | array[matchingCriteria] | True | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| matchingContainers | array[matchingContainers] | False | JSON array of JSON objects of each container that matches the configured matching criteria within the defined app. |
| matchingImages | array[string] | False | JSON array of JSON strings for the matching container images. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 4095<br>• Minimum length: 1<br>• Maximum length: 255 |
| action | string | True | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stage | string | True | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | True | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| appID | string | False | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | True | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**


```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "id": "946e60cb-980b-5374-9e6e-9fe1f6780352",
  "name": "Payroll",
  "hookType": "custom",
  "matchingCriteria": [],
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an
idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | False | JSON string identifying the match criteria type. |
| value | string | False | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | JSON string identifying the match criteria type. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| value | string | True | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_k8s_label

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | |
| value | string | True | |

matchingContainers

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| podName | string | False | JSON string of matching container's pod name. |
| podLabels | array[type_k8s_label] | False | JSON array of label objects of matching container's pod's labels. |
| containerImage | string | False | JSON string of matching container's image. |
| containerName | string | False | JSON string of matching container's name. |
| namespaceName | string | False | JSON string of matching container's pod's namespace name. |

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

# List all execution hooks

GET `/accounts/{account_id}/core/v1/executionHooks`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name | Type | In | Required | Description |
| --- | --- | --- | --- | --- |
| account_id | string | path | True | ID of the containing account resource<br><br>• example: {{.Account}} |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id" |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
|---|---|---|---|
| items | array[Any of: executionHook_1.2_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

#### Example response

```
{
  "type": "application/astra-executionHooks",
  "version": "1.2",
  "items": [
```

```
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "4c64792c-806b-4457-938d-8e325a37c593",
      "name": "Payroll",
      "hookType": "custom",
      "matchingCriteria": [
        {
          "type": "containerImage",
          "value": "payroll"
        },
        {
          "type": "podName",
          "value": "^payroll-master"
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
      "arguments": [
        "freeze"
      ],
      "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
      "enabled": "true",
      "description": "Payroll production hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
      "name": "Order Processing",
      "hookType": "custom",
      "matchingCriteria": [
        {
          "type": "containerName",
          "value": "^order-processing$"
        },
        {
          "type": "podLabel",
          "value": "^app=master$|^app=data$"
```

```
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "63f4d6fd-b7f0-4eaa-9890-0b11123604b1",
      "arguments": [
        "freeze"
      ],
      "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
      "enabled": "true",
      "description": "Order processing hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
      "name": "NetApp Postgres Hook",
      "hookType": "netapp",
      "matchingCriteria": [
        {
          "type": "podName",
          "value": "^postgres"
        },
        {
          "type": "containerImage",
          "value": "3.8"
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "3601ed09-1a74-4156-a1bd-9cb7144bac0e",
      "arguments": [
        "freeze"
      ],
      "enabled": "true",
      "description": "Order processing hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
```

```
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
      "name": "Redis Hook",
      "hookType": "custom",
      "matchingCriteria": [
        {
          "type": "containerName",
          "value": "^redis-01$"
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "3601ed09-1a74-4156-a1bd-9cb7144bac0e",
      "arguments": [
        "freeze"
      ],
      "enabled": "true",
      "description": "Order processing hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | JSON string identifying the match criteria type. |
| value | string | True | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_k8s_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

matchingContainers

| Name | Type | Required | Description |
|---|---|---|---|
| podName | string | False | JSON string of matching container's pod name. |
| podLabels | array[type_k8s_label] | False | JSON array of label objects of matching container's pod's labels. |
| containerImage | string | False | JSON string of matching container's image. |
| containerName | string | False | JSON string of matching container's name. |
| namespaceName | string | False | JSON string of matching container's pod's namespace name. |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

executionHook_1.2_get_response_body

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: 946e60cb-980b-5374-9e6e-9fe1f6780352 |
| name | string | True | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | True | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| matchingCriteria | array[matchingCriteria] | True | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |
| matchingContainers | array[matchingContainers] | False | JSON array of JSON objects of each container that matches the configured matching criteria within the defined app. |
| matchingImages | array[string] | False | JSON array of JSON strings for the matching container images. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 4095<br>• Minimum length: 1<br>• Maximum length: 255 |
| action | string | True | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stage | string | True | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | True | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| appID | string | False | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | True | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve an execution hook

GET `/accounts/{account_id}/core/v1/executionHooks/{executionHook_id}`

Returns the stored Execution Hook API resource in the JSON response body. Also populates matchingContainers and matchingImages based on the current matchingCriteria and the defined app.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| executionHook_id | string | path | True | ID of the executionHook collection to list |

## Response

```
Status: 200, Returns the stored Execution Hook API resource in the JSON
response body. Also populates matchingContainers and matchingImages based
on the current matchingCriteria and the defined app.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: 946e60cb-980b-5374-9e6e-9fe1f6780352 |
| name | string | True | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | True | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |
| matchingCriteria | array[matchingCriteria] | True | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| matchingContainers | array[matchingContainers] | False | JSON array of JSON objects of each container that matches the configured matching criteria within the defined app. |
| matchingImages | array[string] | False | JSON array of JSON strings for the matching container images. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 4095<br>• Minimum length: 1<br>• Maximum length: 255 |
| action | string | True | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stage | string | True | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | True | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| appID | string | False | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | True | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**


```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "id": "946e60cb-980b-5374-9e6e-9fe1f6780352",
  "name": "Payroll",
  "hookType": "custom",
  "matchingCriteria": [
    {
      "type": "podLabel",
      "value": "^env=production$"
    },
    {
      "type": "containerName",
      "value": "^payroll-master"
    }
  ],
  "matchingImages": [
    "docker.io/bitnami/payroll:3.7.8",
    "docker.io/bitnami/payroll:4.1.2"
  ],
  "matchingContainers": [
    {
      "namespaceName": "payroll-east",
      "podName": "payroll-release3-7",
```

```
      "podLabels": [
        {
          "name": "env",
          "value": "production"
        },
        {
          "name": "app.kubernetes.io/managed-by",
          "value": "Helm"
        }
      ],
      "containerName": "payroll-master-0",
      "containerImage": "docker.io/bitnami/payroll:3.7.8"
    },
    {
      "namespaceName": "payroll-east",
      "podName": "payroll-release3-7",
      "podLabels": [
        {
          "name": "env",
          "value": "production"
        },
        {
          "name": "app.kubernetes.io/managed-by",
          "value": "Helm"
        }
      ],
      "containerName": "payroll-master-1",
      "containerImage": "docker.io/bitnami/payroll:3.7.8"
    }
  ],
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | JSON string identifying the match criteria type. |
| value | string | True | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_k8s_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

matchingContainers

| Name | Type | Required | Description |
|---|---|---|---|
| podName | string | False | JSON string of matching container's pod name. |
| podLabels | array[type_k8s_label] | False | JSON array of label objects of matching container's pod's labels. |
| containerImage | string | False | JSON string of matching container's image. |
| containerName | string | False | JSON string of matching container's name. |
| namespaceName | string | False | JSON string of matching container's pod's namespace name. |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Modify an execution hook

PUT `/accounts/{account_id}/core/v1/executionHooks/{executionHook_id}`

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

**Side Effects**

- Updating an existing execution hook will impact any future actions of applications that use the updated execution hook.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| executionHook_id | string | path | True | ID of the executionHook collection to list |

## Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Side Effects

- Updating an existing execution hook will impact any future actions of applications that use the updated execution hook.

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | False | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: 946e60cb-980b-5374-9e6e-9fe1f6780352 |
| name | string | False | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | False | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |
| matchingCriteria | array[matchingCriteria] | False | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| action | string | False | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |
| stage | string | False | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | False | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |

| Name | Type | Required | Description |
|---|---|---|---|
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |
| appID | string | False | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | False | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example request**

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "arguments": [
    "freeze",
    "10"
  ]
}
```

## Response

```
Status: 204, Indicates if the executionHook resource was updated.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an
idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | False | JSON string identifying the match criteria type. |
| value | string | False | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

# Delete an execution hook

DELETE `/accounts/{account_id}/core/v1/executionHooks/{executionHook_id}`

Removes the specified Execution Hook API resource.

**Side Effects**

- The deleted execution hook will no longer run as part of future actions.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| executionHook_id | string | path | True | ID of the executionHook collection to list |

## Response

```
Status: 204, Indicates if the executionHook resource was deleted.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Create a new execution hook for an app

POST `/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks`

Indicates the desired values for the Execution Hook API resource to be created.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |

## Request Body

Indicates the desired values for the Execution Hook API resource to be created.

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |
| name | string | True | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | True | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| matchingCriteria | array[matchingCriteria] | False | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |
| action | string | True | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |
| stage | string | True | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| hookSourceID | string | True | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |
| appID | string | True | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| enabled | string | False | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example request**

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "name": "Payroll",
  "hookType": "custom",
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook"
}
```

## Response

```
Status: 201, Returns the newly created executionHook resource in the JSON
response body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: 946e60cb-980b-5374-9e6e-9fe1f6780352 |
| name | string | True | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | True | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |
| matchingCriteria | array[matchingCriteria] | True | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| matchingContainers | array[matchingContainers] | False | JSON array of JSON objects of each container that matches the configured matching criteria within the defined app. |
| matchingImages | array[string] | False | JSON array of JSON strings for the matching container images. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 4095<br>• Minimum length: 1<br>• Maximum length: 255 |
| action | string | True | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stage | string | True | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | True | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| appID | string | False | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | True | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "id": "946e60cb-980b-5374-9e6e-9fe1f6780352",
  "name": "Payroll",
  "hookType": "custom",
  "matchingCriteria": [],
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an
idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | False | JSON string identifying the match criteria type. |
| value | string | False | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | JSON string identifying the match criteria type. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| value | string | True | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_k8s_label

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | |
| value | string | True | |

matchingContainers

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| podName | string | False | JSON string of matching container's pod name. |
| podLabels | array[type_k8s_label] | False | JSON array of label objects of matching container's pod's labels. |
| containerImage | string | False | JSON string of matching container's image. |
| containerName | string | False | JSON string of matching container's name. |
| namespaceName | string | False | JSON string of matching container's pod's namespace name. |

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

# List the execution hooks for an app

GET `/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name | Type | In | Required | Description |
| --- | --- | --- | --- | --- |
| account_id | string | path | True | ID of the containing account resource<br><br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id" |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| items | array[Any of: executionHook_1.2_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

**Example response**


```
{
  "type": "application/astra-executionHooks",
  "version": "1.2",
  "items": [
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "4c64792c-806b-4457-938d-8e325a37c593",
      "name": "Payroll",
      "hookType": "custom",
      "matchingCriteria": [
        {
          "type": "containerImage",
          "value": "payroll"
        },
        {
          "type": "podName",
          "value": "^payroll-master"
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
      "arguments": [
        "freeze"
      ],
      "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
      "enabled": "true",
      "description": "Payroll production hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
```

```
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
      "name": "Order Processing",
      "hookType": "custom",
      "matchingCriteria": [
        {
          "type": "containerName",
          "value": "^order-processing$"
        },
        {
          "type": "podLabel",
          "value": "^app=master$|^app=data$"
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "63f4d6fd-b7f0-4eaa-9890-0b11123604b1",
      "arguments": [
        "freeze"
      ],
      "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
      "enabled": "true",
      "description": "Order processing hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
      "name": "NetApp Postgres Hook",
      "hookType": "netapp",
      "matchingCriteria": [
        {
          "type": "podName",
          "value": "^postgres"
        },
        {
          "type": "containerImage",
          "value": "3.8"
        }
```

```
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "3601ed09-1a74-4156-a1bd-9cb7144bac0e",
      "arguments": [
        "freeze"
      ],
      "enabled": "true",
      "description": "Order processing hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
      "name": "Redis Hook",
      "hookType": "custom",
      "matchingCriteria": [
        {
          "type": "containerName",
          "value": "^redis-01$"
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "3601ed09-1a74-4156-a1bd-9cb7144bac0e",
      "arguments": [
        "freeze"
      ],
      "enabled": "true",
      "description": "Order processing hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    }
  ],
  "metadata": {
    "labels": [],
```

```
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

| Name | Type | Required | Description |
|---|---|---|---|
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | JSON string identifying the match criteria type. |
| value | string | True | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_k8s_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

matchingContainers

| Name | Type | Required | Description |
|---|---|---|---|
| podName | string | False | JSON string of matching container's pod name. |
| podLabels | array[type_k8s_label] | False | JSON array of label objects of matching container's pod's labels. |
| containerImage | string | False | JSON string of matching container's image. |
| containerName | string | False | JSON string of matching container's name. |
| namespaceName | string | False | JSON string of matching container's pod's namespace name. |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

executionHook_1.2_get_response_body

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: 946e60cb-980b-5374-9e6e-9fe1f6780352 |
| name | string | True | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | True | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| matchingCriteria | array[matchingCriteria] | True | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |
| matchingContainers | array[matchingContainers] | False | JSON array of JSON objects of each container that matches the configured matching criteria within the defined app. |
| matchingImages | array[string] | False | JSON array of JSON strings for the matching container images. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 4095<br>• Minimum length: 1<br>• Maximum length: 255 |
| action | string | True | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stage | string | True | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | True | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| appID | string | False | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | True | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve an execution hook for an app

GET `/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks/{executionHook_id}`

Returns the stored Execution Hook API resource in the JSON response body. Also populates matchingContainers and matchingImages based on the current matchingCriteria and the defined app.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| executionHook_id | string | path | True | ID of the executionHook collection to list |

## Response

```
Status: 200, Returns the stored Execution Hook API resource in the JSON
response body. Also populates matchingContainers and matchingImages based
on the current matchingCriteria and the defined app.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: 946e60cb-980b-5374-9e6e-9fe1f6780352 |
| name | string | True | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | True | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| matchingCriteria | array[matchingCriteria] | True | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |
| matchingContainers | array[matchingContainers] | False | JSON array of JSON objects of each container that matches the configured matching criteria within the defined app. |
| matchingImages | array[string] | False | JSON array of JSON strings for the matching container images. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 4095<br>• Minimum length: 1<br>• Maximum length: 255 |
| action | string | True | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stage | string | True | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | True | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| appID | string | False | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | True | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**


```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "id": "946e60cb-980b-5374-9e6e-9fe1f6780352",
  "name": "Payroll",
  "hookType": "custom",
  "matchingCriteria": [
    {
      "type": "podLabel",
      "value": "^env=production$"
    },
    {
      "type": "containerName",
      "value": "^payroll-master"
    }
  ],
  "matchingImages": [
    "docker.io/bitnami/payroll:3.7.8",
    "docker.io/bitnami/payroll:4.1.2"
  ],
  "matchingContainers": [
    {
      "namespaceName": "payroll-east",
      "podName": "payroll-release3-7",
```

```
      "podLabels": [
        {
          "name": "env",
          "value": "production"
        },
        {
          "name": "app.kubernetes.io/managed-by",
          "value": "Helm"
        }
      ],
      "containerName": "payroll-master-0",
      "containerImage": "docker.io/bitnami/payroll:3.7.8"
    },
    {
      "namespaceName": "payroll-east",
      "podName": "payroll-release3-7",
      "podLabels": [
        {
          "name": "env",
          "value": "production"
        },
        {
          "name": "app.kubernetes.io/managed-by",
          "value": "Helm"
        }
      ],
      "containerName": "payroll-master-1",
      "containerImage": "docker.io/bitnami/payroll:3.7.8"
    }
  ],
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | JSON string identifying the match criteria type. |
| value | string | True | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_k8s_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

matchingContainers

| Name | Type | Required | Description |
|---|---|---|---|
| podName | string | False | JSON string of matching container's pod name. |
| podLabels | array[type_k8s_label] | False | JSON array of label objects of matching container's pod's labels. |
| containerImage | string | False | JSON string of matching container's image. |
| containerName | string | False | JSON string of matching container's name. |
| namespaceName | string | False | JSON string of matching container's pod's namespace name. |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Modify an execution hook for an app

PUT `/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks/{executionHook_id}`

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

**Side Effects**

- Updating an existing execution hook will impact any future actions of applications that use the updated execution hook.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| executionHook_id | string | path | True | ID of the executionHook collection to list |

## Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Side Effects

- Updating an existing execution hook will impact any future actions of applications that use the updated execution hook.

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-executionHook"<br>• example: application/astra-executionHook |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2"<br>• example: 1.2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | False | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema<br>• example: 946e60cb-980b-5374-9e6e-9fe1f6780352 |
| name | string | False | JSON string containing a user-specified name for the resource. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63 Name must be unique across all execution hook resources.<br>• example: Payroll |
| hookType | string | False | JSON string defining the hook type. Defined values are:<br>• "netapp" - NetApp provided execution hook.<br>• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.<br>• example: custom |
| matchingCriteria | array[matchingCriteria] | False | JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 10 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| action | string | False | JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:<br>• "snapshot"<br>• "backup"<br>• "restore"<br>• example: snapshot |
| stage | string | False | JSON string indicating the stage during the action that the hook will be executed. Defined values are:<br>• "pre" - The execution hook will be run before the specified action.<br>• "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".<br>• example: pre |
| hookSourceID | string | False | JSON string containing the hook source ID that is run through this execution hook. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 36fbdaad-0044-4954-b96c-5d200993be61 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| arguments | array[string] | False | JSON array of JSON strings for the arguments to the source. Defined values are:<br>• Minimum items: 0<br>• Maximum items: 16<br>• Minimum length: 0<br>• Maximum length: 127 |
| appID | string | False | JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:<br>• Conforms to the Astra Identifier Schema<br>• example: 7be5ae7c-151d-4230-ac39-ac1d0b33c2a9 |
| enabled | string | False | JSON string that indicates if the execution hook is enabled. Defined values are:<br>• "true" - The execution hook is enabled and will be run as specified.<br>• "false" - The execution hook is disabled and will never run. The default value is "true".<br>• example: true |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| description | string | False | JSON string containing a user-specified description for the hook source. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 511<br>• example: Payroll execution hook pre-post v1.2 |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example request**

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "arguments": [
    "freeze",
    "10"
  ]
}
```

## Response

```
Status: 204, Indicates if the executionHook resource was updated.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an
idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

matchingCriteria

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | False | JSON string identifying the match criteria type. |
| value | string | False | JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

# Delete an execution hook for an app

DELETE `/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks/{executionHook_id}`

Removes the specified Execution Hook API resource.

**Side Effects**

- The deleted execution hook will no longer run as part of future actions.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| executionHook_id | string | path | True | ID of the executionHook collection to list |

## Response

```
Status: 204, Indicates if the executionHook resource was deleted.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

### See Definitions

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

**Informazioni sul copyright**

Copyright © 2023 NetApp, Inc. Tutti i diritti riservati. Stampato negli Stati Uniti d'America. Nessuna porzione di questo documento soggetta a copyright può essere riprodotta in qualsiasi formato o mezzo (grafico, elettronico o meccanico, inclusi fotocopie, registrazione, nastri o storage in un sistema elettronico) senza previo consenso scritto da parte del detentore del copyright.

Il software derivato dal materiale sottoposto a copyright di NetApp è soggetto alla seguente licenza e dichiarazione di non responsabilità:

IL PRESENTE SOFTWARE VIENE FORNITO DA NETAPP "COSÌ COM'È" E SENZA QUALSIVOGLIA TIPO DI GARANZIA IMPLICITA O ESPRESSA FRA CUI, A TITOLO ESEMPLIFICATIVO E NON ESAUSTIVO, GARANZIE IMPLICITE DI COMMERCIABILITÀ E IDONEITÀ PER UNO SCOPO SPECIFICO, CHE VENGONO DECLINATE DAL PRESENTE DOCUMENTO. NETAPP NON VERRÀ CONSIDERATA RESPONSABILE IN ALCUN CASO PER QUALSIVOGLIA DANNO DIRETTO, INDIRETTO, ACCIDENTALE, SPECIALE, ESEMPLARE E CONSEQUENZIALE (COMPRESI, A TITOLO ESEMPLIFICATIVO E NON ESAUSTIVO, PROCUREMENT O SOSTITUZIONE DI MERCI O SERVIZI, IMPOSSIBILITÀ DI UTILIZZO O PERDITA DI DATI O PROFITTI OPPURE INTERRUZIONE DELL'ATTIVITÀ AZIENDALE) CAUSATO IN QUALSIVOGLIA MODO O IN RELAZIONE A QUALUNQUE TEORIA DI RESPONSABILITÀ, SIA ESSA CONTRATTUALE, RIGOROSA O DOVUTA A INSOLVENZA (COMPRESA LA NEGLIGENZA O ALTRO) INSORTA IN QUALSIASI MODO ATTRAVERSO L'UTILIZZO DEL PRESENTE SOFTWARE ANCHE IN PRESENZA DI UN PREAVVISO CIRCA L'EVENTUALITÀ DI QUESTO TIPO DI DANNI.

NetApp si riserva il diritto di modificare in qualsiasi momento qualunque prodotto descritto nel presente documento senza fornire alcun preavviso. NetApp non si assume alcuna responsabilità circa l'utilizzo dei prodotti o materiali descritti nel presente documento, con l'eccezione di quanto concordato espressamente e per iscritto da NetApp. L'utilizzo o l'acquisto del presente prodotto non comporta il rilascio di una licenza nell'ambito di un qualche diritto di brevetto, marchio commerciale o altro diritto di proprietà intellettuale di NetApp.

Il prodotto descritto in questa guida può essere protetto da uno o più brevetti degli Stati Uniti, esteri o in attesa di approvazione.

LEGENDA PER I DIRITTI SOTTOPOSTI A LIMITAZIONE: l'utilizzo, la duplicazione o la divulgazione da parte degli enti governativi sono soggetti alle limitazioni indicate nel sottoparagrafo (b)(3) della clausola Rights in Technical Data and Computer Software del DFARS 252.227-7013 (FEB 2014) e FAR 52.227-19 (DIC 2007).

I dati contenuti nel presente documento riguardano un articolo commerciale (secondo la definizione data in FAR 2.101) e sono di proprietà di NetApp, Inc. Tutti i dati tecnici e il software NetApp forniti secondo i termini del presente Contratto sono articoli aventi natura commerciale, sviluppati con finanziamenti esclusivamente privati. Il governo statunitense ha una licenza irrevocabile limitata, non esclusiva, non trasferibile, non cedibile, mondiale, per l'utilizzo dei Dati esclusivamente in connessione con e a supporto di un contratto governativo statunitense in base al quale i Dati sono distribuiti. Con la sola esclusione di quanto indicato nel presente documento, i Dati non possono essere utilizzati, divulgati, riprodotti, modificati, visualizzati o mostrati senza la previa approvazione scritta di NetApp, Inc. I diritti di licenza del governo degli Stati Uniti per il Dipartimento della Difesa sono limitati ai diritti identificati nella clausola DFARS 252.227-7015(b) (FEB 2014).

**Informazioni sul marchio commerciale**

NETAPP, il logo NETAPP e i marchi elencati alla pagina http://www.netapp.com/TM sono marchi di NetApp, Inc. Gli altri nomi di aziende e prodotti potrebbero essere marchi dei rispettivi proprietari.