# AppMirror

## Astra Automation

NetApp
March 17, 2024

This PDF was generated from https://docs.netapp.com/ko-kr/astra-automation/reference/appmirror_overview.html on March 17, 2024. Always check docs.netapp.com for the latest.

# 목차

AppMirror . . . 1
- AppMirror overview . . . 1
- Create a new AppMirror resource . . . 1
- List all AppMirror resources . . . 24
- Retrieve an AppMirror resource . . . 49
- Modify an AppMirror resource . . . 66
- Delete an AppMirror resource . . . 83
- Create a new AppMirror resource for an app . . . 86
- List the AppMirror resources for an app . . . 109
- Retrieve an AppMirror resource for an app . . . 134
- Modify an AppMirror resource for an app . . . 151
- Delete an AppMirror resource for an app . . . 168

# AppMirror

## AppMirror overview

The AppMirror API enables management of AppMirror relationships.

## Create a new AppMirror resource

POST `/accounts/{account_id}/k8s/v1/appMirrors`

Indicates the desired values for the AppMirror API resource to be created.

### Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |

### Request Body

Indicates the desired values for the AppMirror API resource to be created.

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-appMirror" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| sourceAppID | string | True | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationClusterID | string | True | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |
| stateDesired | string | True | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example request**

```
{
  "type": "application/astra-appMirror",
  "version": "1.1",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "stateDesired": "established"
}
```

## Response

```
Status: 201, Returns the newly created appMirror resource in the JSON
response body.
```

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | Media type of the resource. Defined values are:<br><br>• "application/astra-appMirror" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| sourceAppID | string | True | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| sourceClusterID | string | True | Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|---|---|---|---|
| destinationAppID | string | False | Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationClusterID | string | True | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | The state of the relationship. Defined values are:<br>• "establishing" - The relationship is being created.<br>• "established" - The relationship is created.<br>• "failingOver" - Failover of the application to the destination cluster is in progress.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleting" - Resources created by the relationship are being cleaned up.<br>• "deleted" - The relationship was cleaned up and deleted. |
| stateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions. The following state transitions are possible for this resource:<br>• "establishing": "established", "deleting"<br>• "established": "failingOver", "deleting"<br>• "failingOver": "failedOver", "deleting"<br>• "failedOver": "establishing", "deleting"<br>• "deleting": "deleted"<br>• "deleted": |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | True | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |
| stateAllowed | array[string] | False | States that can be requested in a given state. The following states can be requested in each defined state:<br>• "establishing": "established", "deleted"<br>• "established": "failedOver", "deleted"<br>• "failingOver": "failedOver", "deleted"<br>• "failedOver": "established", "deleted"<br>• "deleting": "deleted"<br>• "deleted": "deleted" |
| stateDetails | array[type_astra_stateDetail] | True | Additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| transferState | string | False | State of the current or most recent snapshot transfer. Defined values are:<br>• "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried.<br>• "idle" - There is currently no transfer in progress. |
| transferStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "transferring": "idle"<br>• "idle": "transferring" |
| transferStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthState | string | True | Health state of the resource. Defined values are:<br>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)<br>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification<br>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification<br>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification |
| healthStateTransitions | array[type_astra_stateTransition] | True | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "indeterminate": "normal", "warning", "critical"<br>• "normal": "indeterminate", "warning", "critical"<br>• "warning": "indeterminate", "normal", "critical"<br>• "critical": "indeterminate", "normal", "warning" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthStateDetails | array[type_astra_stateDetail] | True | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br><br>• Minimum Items: 0 |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**


```
{
  "type": "application/astra-appMirror",
  "version": "1.1",
  "id": "512c8dac-b7d4-5be9-836e-ee672965866a",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
  "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "state": "establishing",
  "stateTransitions": [
    {
      "from": "establishing",
      "to": [
        "established",
        "deleting"
      ]
    },
    {
      "from": "established",
      "to": [
        "failingOver",
        "deleting"
      ]
    },
    {
      "from": "failingOver",
      "to": [
        "failedOver",
        "deleting"
      ]
    },
    {
      "from": "failedOver",
      "to": [
        "establishing",
        "deleting"
      ]
    },
    {
      "from": "deleting",
      "to": [
        "deleted"
      ]
    }
```

```
  ],
  "stateDesired": "established",
  "stateAllowed": [
    "deleted"
  ],
  "stateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/3",
      "title": "AppMirror is being established",
      "detail": "The AppMirror relationship is in the process of being
established."
    }
  ],
  "healthState": "warning",
  "healthStateTransitions": [
    {
      "from": "indeterminate",
      "to": [
        "normal",
        "warning",
        "critical"
      ]
    },
    {
      "from": "normal",
      "to": [
        "indeterminate",
        "warning",
        "critical"
      ]
    },
    {
      "from": "warning",
      "to": [
        "indeterminate",
        "normal",
        "critical"
      ]
    },
    {
      "from": "critical",
      "to": [
        "indeterminate",
        "normal",
        "warning"
      ]
```

```
    }
  ],
  "healthStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/4",
      "title": "AppMirror not yet established",
      "detail": "The AppMirror relationship is not protecting the app
data yet because the relationship is in the process of being
established."
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response


```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

namespaceMapping

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the namespaces are specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaces | array[string] | False | List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63<br>• Conforms to the DNS 1123 Label Schema |
| role | string | False | The initial role for this namespace definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

storageClasses

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the storage class is specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| storageClassName | string | False | Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| role | string | False | The initial role for this storage class definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

type_astra_label

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

type_astra_stateTransition

| Name | Type | Required | Description |
|---|---|---|---|
| from | string | True | |
| to | array[string] | True | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

# List all AppMirror resources

GET `/accounts/{account_id}/k8s/v1/appMirrors`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br><br>• example: {{.Account}} |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id" |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
|---|---|---|---|
| items | array[Any of: appMirror_1.1_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

**Example response**


```
{
  "type": "application/astra-appMirrors",
  "version": "1.1",
  "items": [
    {
      "type": "application/astra-appMirror",
      "version": "1.1",
      "id": "f1c98c2e-6391-42d3-8b21-3e75dac048a3",
      "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
      "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
      "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
      "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
      "namespaceMapping": [
        {
          "clusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
          "namespaces": [
            "ns1-src",
            "ns2-src"
          ]
        },
        {
          "clusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
          "namespaces": [
            "ns1-dest",
            "ns2-dest"
          ]
        }
      ],
      "state": "established",
      "stateTransitions": [
        {
          "from": "establishing",
          "to": [
            "established",
            "deleting"
          ]
        },
        {
          "from": "established",
          "to": [
            "failingOver",
            "deleting"
          ]
        },
```

```
        {
          "from": "failingOver",
          "to": [
            "failedOver",
            "deleting"
          ]
        },
        {
          "from": "failedOver",
          "to": [
            "establishing",
            "deleting"
          ]
        },
        {
          "from": "deleting",
          "to": [
            "deleted"
          ]
        }
      ],
      "stateDesired": "established",
      "stateAllowed": [
        "failedOver",
        "deleted"
      ],
      "stateDetails": [
        {
          "type": "https://astra.netapp.io/stateDetails/1",
          "title": "AppMirror relationship established",
          "detail": "The AppMirror relationship has been successfully
established."
        }
      ],
      "healthState": "normal",
      "healthStateTransitions": [
        {
          "from": "indeterminate",
          "to": [
            "normal",
            "warning",
            "critical"
          ]
        },
        {
          "from": "normal",
```

```
          "to": [
            "indeterminate",
            "warning",
            "critical"
          ]
        },
        {
          "from": "warning",
          "to": [
            "indeterminate",
            "normal",
            "critical"
          ]
        },
        {
          "from": "critical",
          "to": [
            "indeterminate",
            "normal",
            "warning"
          ]
        }
      ],
      "healthStateDetails": [
        {
          "type": "https://astra.netapp.io/stateDetails/2",
          "title": "SnapMirror syncing successfully",
          "detail": "All SnapMirror relationships are synchronizing as
expected."
        }
      ],
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa"
      }
    },
    {
      "type": "application/astra-appMirror",
      "version": "1.1",
      "id": "114633f0-5b59-4bd7-adce-a9ba4423a1bd",
      "sourceAppID": "eaf8b854-211d-460a-ac18-d093d8e2ac70",
      "sourceClusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
      "destinationAppID": "e829c5e0-750f-44ad-a684-aee85be2c2bb",
      "destinationClusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
```

```
      "namespaceMapping": [
        {
          "clusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
          "namespaces": [
            "app-namespace"
          ],
          "role": "source"
        },
        {
          "clusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
          "namespaces": [
            "destination-app-namespace"
          ],
          "role": "destination"
        }
      ],
      "storageClasses": [
        {
          "storageClassName": "destination-sc",
          "clusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
          "role": "destination"
        }
      ],
      "state": "established",
      "stateTransitions": [
        {
          "from": "establishing",
          "to": [
            "established",
            "deleting"
          ]
        },
        {
          "from": "established",
          "to": [
            "failingOver",
            "deleting"
          ]
        },
        {
          "from": "failingOver",
          "to": [
            "failedOver",
            "deleting"
          ]
        },
```

```
      {
        "from": "failedOver",
        "to": [
          "establishing",
          "deleting"
        ]
      }
    ],
    "stateDesired": "established",
    "stateAllowed": [
      "failedOver",
      "deleted"
    ],
    "stateDetails": [],
    "transferState": "idle",
    "transferStateTransitions": [
      {
        "from": "transferring",
        "to": [
          "idle"
        ]
      },
      {
        "from": "idle",
        "to": [
          "transferring"
        ]
      }
    ],
    "transferStateDetails": [
      {
        "type": "https://astra.netapp.io/stateDetails/24",
        "title": "Snapshot replication completed",
        "detail": "A snapshot was replicated to the destination.",
        "additionalDetails": {
          "completionTime": "2023-07-06T22:46:39Z",
          "snapshotID": "ae60820d-e963-4eab-8bb3-9159e9f012f0",
          "startTime": "2023-07-06T22:46:08Z"
        }
      }
    ],
    "healthState": "normal",
    "healthStateTransitions": [],
    "healthStateDetails": [
      {
        "type": "https://astra.netapp.io/stateDetails/24",
```

```
          "title": "Snapshot replication completed",
          "detail": "A snapshot was replicated to the destination.",
          "additionalDetails": {
            "completionTime": "2023-07-06T22:46:39Z",
            "snapshotID": "ae60820d-e963-4eab-8bb3-9159e9f012f0",
            "startTime": "2023-07-06T22:46:08Z"
          }
        }
      ],
      "metadata": {
        "labels": [],
        "creationTimestamp": "2023-07-06T22:45:24Z",
        "modificationTimestamp": "2023-07-06T22:45:24Z",
        "createdBy": "cc420827-f968-4da7-9e72-df8a0fd52f94"
      }
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

namespaceMapping

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the namespaces are specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaces | array[string] | False | List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63<br>• Conforms to the DNS 1123 Label Schema |
| role | string | False | The initial role for this namespace definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

storageClasses

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the storage class is specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| storageClassName | string | False | Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| role | string | False | The initial role for this storage class definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

type_astra_stateTransition

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| from | string | True | |
| to | array[string] | True | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

appMirror_1.1_get_response_body

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-appMirror" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br><br>• Conforms to the UUIDv4 Schema |
| sourceAppID | string | True | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| sourceClusterID | string | True | Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| destinationAppID | string | False | Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationClusterID | string | True | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | The state of the relationship. Defined values are:<br>• "establishing" - The relationship is being created.<br>• "established" - The relationship is created.<br>• "failingOver" - Failover of the application to the destination cluster is in progress.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleting" - Resources created by the relationship are being cleaned up.<br>• "deleted" - The relationship was cleaned up and deleted. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions. The following state transitions are possible for this resource:<br>• "establishing": "established", "deleting"<br>• "established": "failingOver", "deleting"<br>• "failingOver": "failedOver", "deleting"<br>• "failedOver": "establishing", "deleting"<br>• "deleting": "deleted"<br>• "deleted": |
| stateDesired | string | True | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateAllowed | array[string] | False | States that can be requested in a given state. The following states can be requested in each defined state:<br>• "establishing": "established", "deleted"<br>• "established": "failedOver", "deleted"<br>• "failingOver": "failedOver", "deleted"<br>• "failedOver": "established", "deleted"<br>• "deleting": "deleted"<br>• "deleted": "deleted" |
| stateDetails | array[type_astra_stateDetail] | True | Additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| transferState | string | False | State of the current or most recent snapshot transfer. Defined values are:<br>• "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried.<br>• "idle" - There is currently no transfer in progress. |
| transferStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "transferring": "idle"<br>• "idle": "transferring" |
| transferStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthState | string | True | Health state of the resource. Defined values are:<br>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)<br>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification<br>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification<br>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthStateTransitions | array[type_astra_stateTransition] | True | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "indeterminate": "normal", "warning", "critical"<br>• "normal": "indeterminate", "warning", "critical"<br>• "warning": "indeterminate", "normal", "critical"<br>• "critical": "indeterminate", "normal", "warning" |
| healthStateDetails | array[type_astra_stateDetail] | True | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve an AppMirror resource

GET `/accounts/{account_id}/k8s/v1/appMirrors/{appMirror_id}`

Returns the stored AppMirror API resource in the JSON response body.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| appMirror_id | string | path | True | ID of the appMirror collection to list |

## Response

```
Status: 200, Returns the stored AppMirror API resource in the JSON
response body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-appMirror" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| sourceAppID | string | True | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| sourceClusterID | string | True | Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationAppID | string | False | Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| destinationClusterID | string | True | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | The state of the relationship. Defined values are:<br>• "establishing" - The relationship is being created.<br>• "established" - The relationship is created.<br>• "failingOver" - Failover of the application to the destination cluster is in progress.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleting" - Resources created by the relationship are being cleaned up.<br>• "deleted" - The relationship was cleaned up and deleted. |
| stateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions. The following state transitions are possible for this resource:<br>• "establishing": "established", "deleting"<br>• "established": "failingOver", "deleting"<br>• "failingOver": "failedOver", "deleting"<br>• "failedOver": "establishing", "deleting"<br>• "deleting": "deleted"<br>• "deleted": |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | True | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |
| stateAllowed | array[string] | False | States that can be requested in a given state. The following states can be requested in each defined state:<br>• "establishing": "established", "deleted"<br>• "established": "failedOver", "deleted"<br>• "failingOver": "failedOver", "deleted"<br>• "failedOver": "established", "deleted"<br>• "deleting": "deleted"<br>• "deleted": "deleted" |
| stateDetails | array[type_astra_stateDetail] | True | Additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| transferState | string | False | State of the current or most recent snapshot transfer. Defined values are:<br>• "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried.<br>• "idle" - There is currently no transfer in progress. |
| transferStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "transferring": "idle"<br>• "idle": "transferring" |
| transferStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthState | string | True | Health state of the resource. Defined values are:<br>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)<br>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification<br>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification<br>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification |
| healthStateTransitions | array[type_astra_stateTransition] | True | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "indeterminate": "normal", "warning", "critical"<br>• "normal": "indeterminate", "warning", "critical"<br>• "warning": "indeterminate", "normal", "critical"<br>• "critical": "indeterminate", "normal", "warning" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthStateDetails | array[type_astra_stateDetail] | True | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br><br>• Minimum Items: 0 |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**


```
{
  "type": "application/astra-appMirror",
  "version": "1.1",
  "id": "512c8dac-b7d4-5be9-836e-ee672965866a",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
  "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "namespaceMapping": [
    {
      "clusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
      "namespaces": [
        "ns1-src",
        "ns2-src"
      ]
    },
    {
      "clusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
      "namespaces": [
        "ns1-dest",
        "ns2-dest"
      ]
    }
  ],
  "state": "established",
  "stateTransitions": [
    {
      "from": "establishing",
      "to": [
        "established",
        "deleting"
      ]
    },
    {
      "from": "established",
      "to": [
        "failingOver",
        "deleting"
      ]
    },
    {
      "from": "failingOver",
      "to": [
        "failedOver",
```

```
        "deleting"
      ]
    },
    {
      "from": "failedOver",
      "to": [
        "establishing",
        "deleting"
      ]
    },
    {
      "from": "deleting",
      "to": [
        "deleted"
      ]
    }
  ],
  "stateDesired": "established",
  "stateAllowed": [
    "failedOver",
    "deleted"
  ],
  "stateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/1",
      "title": "AppMirror relationship established",
      "detail": "The AppMirror relationship has been successfully
established."
    }
  ],
  "healthState": "normal",
  "healthStateTransitions": [
    {
      "from": "indeterminate",
      "to": [
        "normal",
        "warning",
        "critical"
      ]
    },
    {
      "from": "normal",
      "to": [
        "indeterminate",
        "warning",
        "critical"
```

```
      ]
    },
    {
      "from": "warning",
      "to": [
        "indeterminate",
        "normal",
        "critical"
      ]
    },
    {
      "from": "critical",
      "to": [
        "indeterminate",
        "normal",
        "warning"
      ]
    }
  ],
  "healthStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/2",
      "title": "SnapMirror syncing successfully",
      "detail": "All SnapMirror relationships are synchronizing as
expected."
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

namespaceMapping

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the namespaces are specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaces | array[string] | False | List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63<br>• Conforms to the DNS 1123 Label Schema |
| role | string | False | The initial role for this namespace definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

storageClasses

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the storage class is specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| storageClassName | string | False | Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| role | string | False | The initial role for this storage class definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

type_astra_stateTransition

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| from | string | True | |
| to | array[string] | True | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Modify an AppMirror resource

PUT `/accounts/{account_id}/k8s/v1/appMirrors/{appMirror_id}`

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

**Side Effects**

- Various side effects based on desiredState.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| appMirror_id | string | path | True | ID of the appMirror collection to list |

## Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Side Effects

- Various side effects based on desiredState.

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-appMirror" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |
| id | string | False | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| sourceAppID | string | False | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| sourceClusterID | string | False | Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationAppID | string | False | Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| destinationClusterID | string | False | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | False | The state of the relationship. Defined values are:<br>• "establishing" - The relationship is being created.<br>• "established" - The relationship is created.<br>• "failingOver" - Failover of the application to the destination cluster is in progress.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleting" - Resources created by the relationship are being cleaned up.<br>• "deleted" - The relationship was cleaned up and deleted. |
| stateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions. The following state transitions are possible for this resource:<br>• "establishing": "established", "deleting"<br>• "established": "failingOver", "deleting"<br>• "failingOver": "failedOver", "deleting"<br>• "failedOver": "establishing", "deleting"<br>• "deleting": "deleted"<br>• "deleted": |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | False | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |
| stateAllowed | array[string] | False | States that can be requested in a given state. The following states can be requested in each defined state:<br>• "establishing": "established", "deleted"<br>• "established": "failedOver", "deleted"<br>• "failingOver": "failedOver", "deleted"<br>• "failedOver": "established", "deleted"<br>• "deleting": "deleted"<br>• "deleted": "deleted" |
| stateDetails | array[type_astra_stateDetail] | False | Additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| transferState | string | False | State of the current or most recent snapshot transfer. Defined values are:<br>• "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried.<br>• "idle" - There is currently no transfer in progress. |
| transferStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "transferring": "idle"<br>• "idle": "transferring" |
| transferStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthState | string | False | Health state of the resource. Defined values are:<br>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)<br>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification<br>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification<br>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification |
| healthStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "indeterminate": "normal", "warning", "critical"<br>• "normal": "indeterminate", "warning", "critical"<br>• "warning": "indeterminate", "normal", "critical"<br>• "critical": "indeterminate", "normal", "warning" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br><br>• Minimum Items: 0 |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example request**

```
{
  "type": "application/astra-appMirror",
  "version": "1.1",
  "stateDesired": "failedOver"
}
```

## Response

```
Status: 204, Indicates if the appMirror resource was updated.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

namespaceMapping

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the namespaces are specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaces | array[string] | False | List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63<br>• Conforms to the DNS 1123 Label Schema |
| role | string | False | The initial role for this namespace definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

storageClasses

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the storage class is specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| storageClassName | string | False | Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| role | string | False | The initial role for this storage class definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

type_astra_stateTransition

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| from | string | True | |
| to | array[string] | True | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

# Delete an AppMirror resource

DELETE `/accounts/{account_id}/k8s/v1/appMirrors/{appMirror_id}`

Removes the specified AppMirror API resource. Starts a process to asynchronously remove the AppMirror resource, along with any resources on the source and destination clusters that were created as a result of the AppMirror relationship. The resources removed are dependent on the state of the relationship at the time of deletion.

**Side Effects**

- The stateDesired field is set to "deleted".
- The state field is set to "deleting".
- If state is "established", the TridentMirrorRelationships and PersistentVolumeClaims created by the AppMirror relationship will be deleted.
- If state is "failedOver", the TridentMirrorRelationships created by the AppMirror relationship will be deleted and the PersistentVolumeClaims in the destination application will be left in place.
- When the asynchronous delete operation is completed, the AppMirror API resource will be removed from both the source and destination applications.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| appMirror_id | string | path | True | ID of the appMirror collection to list |

## Response

```
Status: 204, Indicates if the appMirror resource was deleted.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

### Definitions

#### See Definitions

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

## Create a new AppMirror resource for an app

POST `/accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors`

Indicates the desired values for the AppMirror API resource to be created.

### Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |

### Request Body

Indicates the desired values for the AppMirror API resource to be created.

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-appMirror" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |
| sourceAppID | string | True | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| destinationClusterID | string | True | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |
| stateDesired | string | True | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example request**

```
{
  "type": "application/astra-appMirror",
  "version": "1.1",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "stateDesired": "established"
}
```

## Response

```
Status: 201, Returns the newly created appMirror resource in the JSON
response body.
```

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | Media type of the resource. Defined values are:<br><br>• "application/astra-appMirror" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| sourceAppID | string | True | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| sourceClusterID | string | True | Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| destinationAppID | string | False | Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationClusterID | string | True | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | The state of the relationship. Defined values are:<br>• "establishing" - The relationship is being created.<br>• "established" - The relationship is created.<br>• "failingOver" - Failover of the application to the destination cluster is in progress.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleting" - Resources created by the relationship are being cleaned up.<br>• "deleted" - The relationship was cleaned up and deleted. |
| stateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions. The following state transitions are possible for this resource:<br>• "establishing": "established", "deleting"<br>• "established": "failingOver", "deleting"<br>• "failingOver": "failedOver", "deleting"<br>• "failedOver": "establishing", "deleting"<br>• "deleting": "deleted"<br>• "deleted": |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | True | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |
| stateAllowed | array[string] | False | States that can be requested in a given state. The following states can be requested in each defined state:<br>• "establishing": "established", "deleted"<br>• "established": "failedOver", "deleted"<br>• "failingOver": "failedOver", "deleted"<br>• "failedOver": "established", "deleted"<br>• "deleting": "deleted"<br>• "deleted": "deleted" |
| stateDetails | array[type_astra_stateDetail] | True | Additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| transferState | string | False | State of the current or most recent snapshot transfer. Defined values are:<br>• "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried.<br>• "idle" - There is currently no transfer in progress. |
| transferStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "transferring": "idle"<br>• "idle": "transferring" |
| transferStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthState | string | True | Health state of the resource. Defined values are:<br>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)<br>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification<br>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification<br>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification |
| healthStateTransitions | array[type_astra_stateTransition] | True | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "indeterminate": "normal", "warning", "critical"<br>• "normal": "indeterminate", "warning", "critical"<br>• "warning": "indeterminate", "normal", "critical"<br>• "critical": "indeterminate", "normal", "warning" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthStateDetails | array[type_astra_stateDetail] | True | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br><br>• Minimum Items: 0 |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**


```
{
  "type": "application/astra-appMirror",
  "version": "1.1",
  "id": "512c8dac-b7d4-5be9-836e-ee672965866a",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
  "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "state": "establishing",
  "stateTransitions": [
    {
      "from": "establishing",
      "to": [
        "established",
        "deleting"
      ]
    },
    {
      "from": "established",
      "to": [
        "failingOver",
        "deleting"
      ]
    },
    {
      "from": "failingOver",
      "to": [
        "failedOver",
        "deleting"
      ]
    },
    {
      "from": "failedOver",
      "to": [
        "establishing",
        "deleting"
      ]
    },
    {
      "from": "deleting",
      "to": [
        "deleted"
      ]
    }
```

```
  ],
  "stateDesired": "established",
  "stateAllowed": [
    "deleted"
  ],
  "stateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/3",
      "title": "AppMirror is being established",
      "detail": "The AppMirror relationship is in the process of being
established."
    }
  ],
  "healthState": "warning",
  "healthStateTransitions": [
    {
      "from": "indeterminate",
      "to": [
        "normal",
        "warning",
        "critical"
      ]
    },
    {
      "from": "normal",
      "to": [
        "indeterminate",
        "warning",
        "critical"
      ]
    },
    {
      "from": "warning",
      "to": [
        "indeterminate",
        "normal",
        "critical"
      ]
    },
    {
      "from": "critical",
      "to": [
        "indeterminate",
        "normal",
        "warning"
      ]
```

```
    }
  ],
  "healthStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/4",
      "title": "AppMirror not yet established",
      "detail": "The AppMirror relationship is not protecting the app
data yet because the relationship is in the process of being
established."
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response


```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

namespaceMapping

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the namespaces are specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaces | array[string] | False | List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63<br>• Conforms to the DNS 1123 Label Schema |
| role | string | False | The initial role for this namespace definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

storageClasses

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the storage class is specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| storageClassName | string | False | Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| role | string | False | The initial role for this storage class definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

type_astra_label

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

type_astra_stateTransition

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| from | string | True | |
| to | array[string] | True | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

# List the AppMirror resources for an app

GET `/accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br><br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id" |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
|---|---|---|---|
| items | array[Any of: appMirror_1.1_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

**Example response**


```
{
  "type": "application/astra-appMirrors",
  "version": "1.1",
  "items": [
    {
      "type": "application/astra-appMirror",
      "version": "1.1",
      "id": "f1c98c2e-6391-42d3-8b21-3e75dac048a3",
      "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
      "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
      "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
      "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
      "namespaceMapping": [
        {
          "clusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
          "namespaces": [
            "ns1-src",
            "ns2-src"
          ]
        },
        {
          "clusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
          "namespaces": [
            "ns1-dest",
            "ns2-dest"
          ]
        }
      ],
      "state": "established",
      "stateTransitions": [
        {
          "from": "establishing",
          "to": [
            "established",
            "deleting"
          ]
        },
        {
          "from": "established",
          "to": [
            "failingOver",
            "deleting"
          ]
        },
```

```
        {
          "from": "failingOver",
          "to": [
            "failedOver",
            "deleting"
          ]
        },
        {
          "from": "failedOver",
          "to": [
            "establishing",
            "deleting"
          ]
        },
        {
          "from": "deleting",
          "to": [
            "deleted"
          ]
        }
      ],
      "stateDesired": "established",
      "stateAllowed": [
        "failedOver",
        "deleted"
      ],
      "stateDetails": [
        {
          "type": "https://astra.netapp.io/stateDetails/1",
          "title": "AppMirror relationship established",
          "detail": "The AppMirror relationship has been successfully
established."
        }
      ],
      "healthState": "normal",
      "healthStateTransitions": [
        {
          "from": "indeterminate",
          "to": [
            "normal",
            "warning",
            "critical"
          ]
        },
        {
          "from": "normal",
```

```
          "to": [
            "indeterminate",
            "warning",
            "critical"
          ]
        },
        {
          "from": "warning",
          "to": [
            "indeterminate",
            "normal",
            "critical"
          ]
        },
        {
          "from": "critical",
          "to": [
            "indeterminate",
            "normal",
            "warning"
          ]
        }
      ],
      "healthStateDetails": [
        {
          "type": "https://astra.netapp.io/stateDetails/2",
          "title": "SnapMirror syncing successfully",
          "detail": "All SnapMirror relationships are synchronizing as
expected."
        }
      ],
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa"
      }
    },
    {
      "type": "application/astra-appMirror",
      "version": "1.1",
      "id": "114633f0-5b59-4bd7-adce-a9ba4423a1bd",
      "sourceAppID": "eaf8b854-211d-460a-ac18-d093d8e2ac70",
      "sourceClusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
      "destinationAppID": "e829c5e0-750f-44ad-a684-aee85be2c2bb",
      "destinationClusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
```

```
      "namespaceMapping": [
        {
          "clusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
          "namespaces": [
            "app-namespace"
          ],
          "role": "source"
        },
        {
          "clusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
          "namespaces": [
            "destination-app-namespace"
          ],
          "role": "destination"
        }
      ],
      "storageClasses": [
        {
          "storageClassName": "destination-sc",
          "clusterID": "fcb27b51-ebb7-40ca-b8f1-1d23ebd06889",
          "role": "destination"
        }
      ],
      "state": "established",
      "stateTransitions": [
        {
          "from": "establishing",
          "to": [
            "established",
            "deleting"
          ]
        },
        {
          "from": "established",
          "to": [
            "failingOver",
            "deleting"
          ]
        },
        {
          "from": "failingOver",
          "to": [
            "failedOver",
            "deleting"
          ]
        },
```

```
        {
          "from": "failedOver",
          "to": [
            "establishing",
            "deleting"
          ]
        }
      ],
      "stateDesired": "established",
      "stateAllowed": [
        "failedOver",
        "deleted"
      ],
      "stateDetails": [],
      "transferState": "idle",
      "transferStateTransitions": [
        {
          "from": "transferring",
          "to": [
            "idle"
          ]
        },
        {
          "from": "idle",
          "to": [
            "transferring"
          ]
        }
      ],
      "transferStateDetails": [
        {
          "type": "https://astra.netapp.io/stateDetails/24",
          "title": "Snapshot replication completed",
          "detail": "A snapshot was replicated to the destination.",
          "additionalDetails": {
            "completionTime": "2023-07-06T22:46:39Z",
            "snapshotID": "ae60820d-e963-4eab-8bb3-9159e9f012f0",
            "startTime": "2023-07-06T22:46:08Z"
          }
        }
      ],
      "healthState": "normal",
      "healthStateTransitions": [],
      "healthStateDetails": [
        {
          "type": "https://astra.netapp.io/stateDetails/24",
```

```
            "title": "Snapshot replication completed",
            "detail": "A snapshot was replicated to the destination.",
            "additionalDetails": {
              "completionTime": "2023-07-06T22:46:39Z",
              "snapshotID": "ae60820d-e963-4eab-8bb3-9159e9f012f0",
              "startTime": "2023-07-06T22:46:08Z"
            }
          }
        ],
        "metadata": {
          "labels": [],
          "creationTimestamp": "2023-07-06T22:45:24Z",
          "modificationTimestamp": "2023-07-06T22:45:24Z",
          "createdBy": "cc420827-f968-4da7-9e72-df8a0fd52f94"
        }
      }
    ],
    "metadata": {
      "labels": [],
      "creationTimestamp": "2022-10-06T20:58:16.305662Z",
      "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
      "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
    }
  }
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

namespaceMapping

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the namespaces are specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaces | array[string] | False | List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63<br>• Conforms to the DNS 1123 Label Schema |
| role | string | False | The initial role for this namespace definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

storageClasses

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the storage class is specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| storageClassName | string | False | Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| role | string | False | The initial role for this storage class definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

type_astra_stateTransition

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| from | string | True | |
| to | array[string] | True | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

appMirror_1.1_get_response_body

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-appMirror" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br><br>• Conforms to the UUIDv4 Schema |
| sourceAppID | string | True | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| sourceClusterID | string | True | Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| destinationAppID | string | False | Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationClusterID | string | True | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | The state of the relationship. Defined values are:<br>• "establishing" - The relationship is being created.<br>• "established" - The relationship is created.<br>• "failingOver" - Failover of the application to the destination cluster is in progress.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleting" - Resources created by the relationship are being cleaned up.<br>• "deleted" - The relationship was cleaned up and deleted. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions. The following state transitions are possible for this resource:<br>• "establishing": "established", "deleting"<br>• "established": "failingOver", "deleting"<br>• "failingOver": "failedOver", "deleting"<br>• "failedOver": "establishing", "deleting"<br>• "deleting": "deleted"<br>• "deleted": |
| stateDesired | string | True | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateAllowed | array[string] | False | States that can be requested in a given state. The following states can be requested in each defined state:<br>• "establishing": "established", "deleted"<br>• "established": "failedOver", "deleted"<br>• "failingOver": "failedOver", "deleted"<br>• "failedOver": "established", "deleted"<br>• "deleting": "deleted"<br>• "deleted": "deleted" |
| stateDetails | array[type_astra_stateDetail] | True | Additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| transferState | string | False | State of the current or most recent snapshot transfer. Defined values are:<br>• "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried.<br>• "idle" - There is currently no transfer in progress. |
| transferStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "transferring": "idle"<br>• "idle": "transferring" |
| transferStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthState | string | True | Health state of the resource. Defined values are:<br>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)<br>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification<br>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification<br>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthStateTransitions | array[type_astra_stateTransition] | True | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "indeterminate": "normal", "warning", "critical"<br>• "normal": "indeterminate", "warning", "critical"<br>• "warning": "indeterminate", "normal", "critical"<br>• "critical": "indeterminate", "normal", "warning" |
| healthStateDetails | array[type_astra_stateDetail] | True | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve an AppMirror resource for an app

GET `/accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors/{appMirror_id}`

Returns the stored AppMirror API resource in the JSON response body.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| appMirror_id | string | path | True | ID of the appMirror collection to list |

## Response

```
Status: 200, Returns the stored AppMirror API resource in the JSON
response body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-appMirror" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| sourceAppID | string | True | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| sourceClusterID | string | True | Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationAppID | string | False | Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|---|---|---|---|
| destinationClusterID | string | True | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | True | The state of the relationship. Defined values are:<br>• "establishing" - The relationship is being created.<br>• "established" - The relationship is created.<br>• "failingOver" - Failover of the application to the destination cluster is in progress.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleting" - Resources created by the relationship are being cleaned up.<br>• "deleted" - The relationship was cleaned up and deleted. |
| stateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions. The following state transitions are possible for this resource:<br>• "establishing": "established", "deleting"<br>• "established": "failingOver", "deleting"<br>• "failingOver": "failedOver", "deleting"<br>• "failedOver": "establishing", "deleting"<br>• "deleting": "deleted"<br>• "deleted": |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | True | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |
| stateAllowed | array[string] | False | States that can be requested in a given state. The following states can be requested in each defined state:<br>• "establishing": "established", "deleted"<br>• "established": "failedOver", "deleted"<br>• "failingOver": "failedOver", "deleted"<br>• "failedOver": "established", "deleted"<br>• "deleting": "deleted"<br>• "deleted": "deleted" |
| stateDetails | array[type_astra_stateDetail] | True | Additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| transferState | string | False | State of the current or most recent snapshot transfer. Defined values are:<br>• "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried.<br>• "idle" - There is currently no transfer in progress. |
| transferStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "transferring": "idle"<br>• "idle": "transferring" |
| transferStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthState | string | True | Health state of the resource. Defined values are:<br>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)<br>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification<br>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification<br>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification |
| healthStateTransitions | array[type_astra_stateTransition] | True | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "indeterminate": "normal", "warning", "critical"<br>• "normal": "indeterminate", "warning", "critical"<br>• "warning": "indeterminate", "normal", "critical"<br>• "critical": "indeterminate", "normal", "warning" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthStateDetails | array[type_astra_stateDetail] | True | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br><br>• Minimum Items: 0 |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example response**


```
{
  "type": "application/astra-appMirror",
  "version": "1.1",
  "id": "512c8dac-b7d4-5be9-836e-ee672965866a",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
  "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "namespaceMapping": [
    {
      "clusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
      "namespaces": [
        "ns1-src",
        "ns2-src"
      ]
    },
    {
      "clusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
      "namespaces": [
        "ns1-dest",
        "ns2-dest"
      ]
    }
  ],
  "state": "established",
  "stateTransitions": [
    {
      "from": "establishing",
      "to": [
        "established",
        "deleting"
      ]
    },
    {
      "from": "established",
      "to": [
        "failingOver",
        "deleting"
      ]
    },
    {
      "from": "failingOver",
      "to": [
        "failedOver",
```

```
        "deleting"
      ]
    },
    {
      "from": "failedOver",
      "to": [
        "establishing",
        "deleting"
      ]
    },
    {
      "from": "deleting",
      "to": [
        "deleted"
      ]
    }
  ],
  "stateDesired": "established",
  "stateAllowed": [
    "failedOver",
    "deleted"
  ],
  "stateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/1",
      "title": "AppMirror relationship established",
      "detail": "The AppMirror relationship has been successfully
established."
    }
  ],
  "healthState": "normal",
  "healthStateTransitions": [
    {
      "from": "indeterminate",
      "to": [
        "normal",
        "warning",
        "critical"
      ]
    },
    {
      "from": "normal",
      "to": [
        "indeterminate",
        "warning",
        "critical"
```

```
      ]
    },
    {
      "from": "warning",
      "to": [
        "indeterminate",
        "normal",
        "critical"
      ]
    },
    {
      "from": "critical",
      "to": [
        "indeterminate",
        "normal",
        "warning"
      ]
    }
  ],
  "healthStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/2",
      "title": "SnapMirror syncing successfully",
      "detail": "All SnapMirror relationships are synchronizing as
expected."
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

namespaceMapping

| Name | Type | Required | Description |
|---|---|---|---|
| clusterID | string | False | Identifier of the cluster for which the namespaces are specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaces | array[string] | False | List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63<br>• Conforms to the DNS 1123 Label Schema |
| role | string | False | The initial role for this namespace definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

storageClasses

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the storage class is specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| storageClassName | string | False | Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| role | string | False | The initial role for this storage class definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

type_astra_stateTransition

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| from | string | True | |
| to | array[string] | True | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Modify an AppMirror resource for an app

PUT `/accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors/{appMirror_id}`

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

**Side Effects**

- Various side effects based on desiredState.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| appMirror_id | string | path | True | ID of the appMirror collection to list |

## Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Side Effects

- Various side effects based on desiredState.

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-appMirror" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1" |
| id | string | False | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| sourceAppID | string | False | Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| sourceClusterID | string | False | Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |
| destinationAppID | string | False | Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:<br><br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| destinationClusterID | string | False | Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaceMapping | array[namespaceMapping] | False | The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| storageClasses | array[storageClasses] | False | The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster. If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster. Defined values are:<br>• Minimum length: 0<br>• Maximum length: 2 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| state | string | False | The state of the relationship. Defined values are:<br>• "establishing" - The relationship is being created.<br>• "established" - The relationship is created.<br>• "failingOver" - Failover of the application to the destination cluster is in progress.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleting" - Resources created by the relationship are being cleaned up.<br>• "deleted" - The relationship was cleaned up and deleted. |
| stateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions. The following state transitions are possible for this resource:<br>• "establishing": "established", "deleting"<br>• "established": "failingOver", "deleting"<br>• "failingOver": "failedOver", "deleting"<br>• "failedOver": "establishing", "deleting"<br>• "deleting": "deleted"<br>• "deleted": |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| stateDesired | string | False | The desired state for the relationship. At creation, the only valid value is "established". Defined values are:<br>• "established" - The relationship is created.<br>• "failedOver" - Failover of the application to the destination cluster has completed.<br>• "deleted" - The relationship was successfully cleaned up and deleted. |
| stateAllowed | array[string] | False | States that can be requested in a given state. The following states can be requested in each defined state:<br>• "establishing": "established", "deleted"<br>• "established": "failedOver", "deleted"<br>• "failingOver": "failedOver", "deleted"<br>• "failedOver": "established", "deleted"<br>• "deleting": "deleted"<br>• "deleted": "deleted" |
| stateDetails | array[type_astra_stateDetail] | False | Additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| transferState | string | False | State of the current or most recent snapshot transfer. Defined values are:<br>• "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried.<br>• "idle" - There is currently no transfer in progress. |
| transferStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "transferring": "idle"<br>• "idle": "transferring" |
| transferStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br>• Minimum Items: 0 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthState | string | False | Health state of the resource. Defined values are:<br>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)<br>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification<br>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification<br>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification |
| healthStateTransitions | array[type_astra_stateTransition] | False | Permitted state transitions from a given defined state. The following state transitions are possible for this resource:<br>• "indeterminate": "normal", "warning", "critical"<br>• "normal": "indeterminate", "warning", "critical"<br>• "warning": "indeterminate", "normal", "critical"<br>• "critical": "indeterminate", "normal", "warning" |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| healthStateDetails | array[type_astra_stateDetail] | False | Additional details about the current state including why the current state was reached. If no details are available, this array will be empty. Defined values are:<br><br>• Minimum Items: 0 |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are:<br><br>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

**Example request**

```
{
  "type": "application/astra-appMirror",
  "version": "1.1",
  "stateDesired": "failedOver"
}
```

## Response

```
Status: 204, Indicates if the appMirror resource was updated.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 409, Conflict
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

namespaceMapping

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the namespaces are specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| namespaces | array[string] | False | List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 63<br>• Conforms to the DNS 1123 Label Schema |
| role | string | False | The initial role for this namespace definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

storageClasses

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | False | Identifier of the cluster for which the storage class is specified. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| storageClassName | string | False | Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| role | string | False | The initial role for this storage class definition. This parameter is optional except for when a same-cluster replication configuration is used. Defined values are:<br>• "source"<br>• "destination" |

type_astra_stateTransition

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| from | string | True | |
| to | array[string] | True | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

# Delete an AppMirror resource for an app

DELETE `/accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors/{appMirror_id}`

Removes the specified AppMirror API resource. Starts a process to asynchronously remove the AppMirror resource, along with any resources on the source and destination clusters that were created as a result of the AppMirror relationship. The resources removed are dependent on the state of the relationship at the time of deletion.

**Side Effects**

- The stateDesired field is set to "deleted".
- The state field is set to "deleting".
- If state is "established", the TridentMirrorRelationships and PersistentVolumeClaims created by the AppMirror relationship will be deleted.
- If state is "failedOver", the TridentMirrorRelationships created by the AppMirror relationship will be deleted and the PersistentVolumeClaims in the destination application will be left in place.
- When the asynchronous delete operation is completed, the AppMirror API resource will be removed from both the source and destination applications.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| appMirror_id | string | path | True | ID of the appMirror collection to list |

## Response

```
Status: 204, Indicates if the appMirror resource was deleted.
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

invalidParams

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

저작권 정보

Copyright © 2024 NetApp, Inc. All Rights Reserved. 미국에서 인쇄된 본 문서의 어떠한 부분도 저작권 소유자의 사전 서면 승인 없이는 어떠한 형식이나 수단(복사, 녹음, 녹화 또는 전자 검색 시스템에 저장하는 것을 비롯한 그래픽, 전자적 또는 기계적 방법)으로도 복제될 수 없습니다.

NetApp이 저작권을 가진 자료에 있는 소프트웨어에는 아래의 라이센스와 고지사항이 적용됩니다.

본 소프트웨어는 NetApp에 의해 '있는 그대로' 제공되며 상품성 및 특정 목적에의 적합성에 대한 명시적 또는 묵시적 보증을 포함하여(이에 제한되지 않음) 어떠한 보증도 하지 않습니다. NetApp은 대체품 또는 대체 서비스의 조달, 사용 불능, 데이터 손실, 이익 손실, 영업 중단을 포함하여(이에 국한되지 않음), 이 소프트웨어의 사용으로 인해 발생하는 모든 직접 및 간접 손해, 우발적 손해, 특별 손해, 징벌적 손해, 결과적 손해의 발생에 대하여 그 발생 이유, 책임론, 계약 여부, 엄격한 책임, 불법 행위(과실 또는 그렇지 않은 경우)와 관계없이 어떠한 책임도 지지 않으며, 이와 같은 손실의 발생 가능성이 통지되었다 하더라도 마찬가지입니다.

NetApp은 본 문서에 설명된 제품을 언제든지 예고 없이 변경할 권리를 보유합니다. NetApp은 NetApp의 명시적인 서면 동의를 받은 경우를 제외하고 본 문서에 설명된 제품을 사용하여 발생하는 어떠한 문제에도 책임을 지지 않습니다. 본 제품의 사용 또는 구매의 경우 NetApp에서는 어떠한 특허권, 상표권 또는 기타 지적 재산권이 적용되는 라이센스도 제공하지 않습니다.

본 설명서에 설명된 제품은 하나 이상의 미국 특허, 해외 특허 또는 출원 중인 특허로 보호됩니다.

제한적 권리 표시: 정부에 의한 사용, 복제 또는 공개에는 DFARS 252.227-7013(2014년 2월) 및 FAR 52.227-19(2007년 12월)의 기술 데이터-비상업적 품목에 대한 권리(Rights in Technical Data -Noncommercial Items) 조항의 하위 조항 (b)(3)에 설명된 제한사항이 적용됩니다.

여기에 포함된 데이터는 상업용 제품 및/또는 상업용 서비스(FAR 2.101에 정의)에 해당하며 NetApp, Inc.의 독점 자산입니다. 본 계약에 따라 제공되는 모든 NetApp 기술 데이터 및 컴퓨터 소프트웨어는 본질적으로 상업용이며 개인 비용만으로 개발되었습니다. 미국 정부는 데이터가 제공된 미국 계약과 관련하여 해당 계약을 지원하는 데에만 데이터에 대한 전 세계적으로 비독점적이고 양도할 수 없으며 재사용이 불가능하며 취소 불가능한 라이센스를 제한적으로 가집니다. 여기에 제공된 경우를 제외하고 NetApp, Inc.의 사전 서면 승인 없이는 이 데이터를 사용, 공개, 재생산, 수정, 수행 또는 표시할 수 없습니다. 미국 국방부에 대한 정부 라이센스는 DFARS 조항 252.227-7015(b)(2014년 2월)에 명시된 권한으로 제한됩니다.

상표 정보

NETAPP, NETAPP 로고 및 http://www.netapp.com/TM에 나열된 마크는 NetApp, Inc.의 상표입니다. 기타 회사 및 제품 이름은 해당 소유자의 상표일 수 있습니다.