# Namespace

## Astra Automation

NetApp
March 17, 2024

This PDF was generated from https://docs.netapp.com/zh-tw/astra-automation/reference/namespace_overview.html on March 17, 2024. Always check docs.netapp.com for the latest.

# 目錄

Namespace . . . 1
Namespace overview . . . 1
List the namespaces for a cloud . . . 1
Retrieve a namespace for a cloud . . . 12
List the namespaces for a cluster . . . 22
Retrieve a namespace for a cluster . . . 34
List all namespaces . . . 44
Retrieve a namespace . . . 56
List the namespaces for a managed cluster . . . 66
Retrieve a namespace for a managed cluster . . . 78

# Namespace

## Namespace overview

The Namespace API provides read-only access to namespace resources in order to describe namespaces associated with a given cluster.

## List the namespaces for a cloud

GET `/accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}/namespaces`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br><br>• example: {{.Account}} |
| cloud_id | string | path | True | ID of the containing cloud resource |
| cluster_id | string | path | True | ID of the containing cluster resource |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id"<br><br>• example: id,name,kubernetesLabels |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| items | array[Any of: namespace_1.2_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

**Example response**


```
{
  "type": "application/astra-namespaces",
  "version": "1.2",
  "items": [
    [
      "7d451d2f-196e-4234-aee9-7e2376047e63",
      "kube-system",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ],
    [
      "66b0873b-214f-4ac7-89d8-922432f941eb",
      "jenkins",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

targetSchema

accept-post

accept-put

hints

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | False | |
| allow | array[string] | False | |
| accept-post | accept-post | False | |
| permissions | array[string] | False | |
| accept-put | accept-put | False | |

type_astra_link

| Name | Type | Required | Description |
|---|---|---|---|
| rel | string | True | |
| href | string | True | |
| type | string | False | |
| targetSchema | targetSchema | False | |
| title | string | False | |
| hints | hints | False | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

namespace_1.2_get_response_body

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-namespace" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| links | array[type_astra_link] | True | Links describing supported operations against the resource. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | JSON string containing a value indicating the name of the namespace. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| namespaceState | string | True | JSON string containing a value indicating the state of the namespace. Defined values are:<br>• "discovered" - The namespace has been found in the cluster<br>• "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace |
| namespaceStateDetails | array[type_astra_stateDetail] | True | JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:<br>• Minimum items: 0 |
| kubernetesLabels | array[type_astra_label] | False | JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:<br>• Conforms to the Kubernetes Label Array Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| kubernetesUID | string | True | JSON string containing the Kubernetes generated UID of the namespace resource |
| clusterID | string | True | JSON string containing a globally unique identifier of the cluster that the namespace is contained in. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| systemType | string | False | JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only). Defined values are:<br>• "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system"<br>• "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring"<br>• "openshift" - An OpenShift system namespace, for example, "openshift-monitoring"<br>• "rke" - A Rancher namespace, for example, "cattle-logging"<br>• "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system" |
| metadata | type_astra_metadata | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema |

type_astra_metadata_list

| Name | Type | Required | Description |
|---|---|---|---|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve a namespace for a cloud

GET `/accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}/namespaces/{namespace_id}`

Returns the stored Namespace API resource in the JSON response body.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| cloud_id | string | path | True | ID of the containing cloud resource |
| cluster_id | string | path | True | ID of the containing cluster resource |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| namespace_id | string | path | True | ID of the namespace collection to list |

## Response

```
Status: 200, Returns the stored Namespace API resource in the JSON
response body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-namespace" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| links | array[type_astra_link] | True | Links describing supported operations against the resource. |
| name | string | True | JSON string containing a value indicating the name of the namespace. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceState | string | True | JSON string containing a value indicating the state of the namespace. Defined values are:<br>• "discovered" - The namespace has been found in the cluster<br>• "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace |
| namespaceStateDetails | array[type_astra_stateDetail] | True | JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:<br>• Minimum items: 0 |
| kubernetesLabels | array[type_astra_label] | False | JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:<br>• Conforms to the Kubernetes Label Array Schema |
| kubernetesUID | string | True | JSON string containing the Kubernetes generated UID of the namespace resource |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | True | JSON string containing a globally unique identifier of the cluster that the namespace is contained in. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| systemType | string | False | JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only). Defined values are:<br>• "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system"<br>• "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring"<br>• "openshift" - An OpenShift system namespace, for example, "openshift-monitoring"<br>• "rke" - A Rancher namespace, for example, "cattle-logging"<br>• "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system" |

| Name | Type | Required | Description |
|---|---|---|---|
| metadata | type_astra_metadata | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema |

**Example response**


```
{
  "type": "application/astra-namespace",
  "version": "1.2",
  "id": "214dc2eb-19a6-5444-b156-f4b6b551a81a",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-
1349ca090415/topology/v1/namespaces/7d451d2f-196e-4234-aee9-
7e2376047e63",
      "type": "application/vnd.netapp.astra.namespace"
    },
    {
      "rel": "collection",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-
1349ca090415/topology/v1/clouds/e0490197-872e-4de8-9287-
b04a938e801f/clusters/0f284377-e5dc-4dcd-bacd-3197f2b8a347/namespaces",
      "type": "application/vnd.netapp.astra.namespaces"
    }
  ],
  "name": "kube-system",
  "namespaceState": "discovered",
  "namespaceStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/9",
      "title": "Namespace Discovered",
      "detail": "The namespace was discovered in the indicated managed
cluster"
    }
  ],
  "kubernetesLabels": [
    {
      "name": "app.kubernetes.io/environment",
      "value": "dev"
    }
  ],
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "kubernetesUID": "4f28c377-e5dc-4dcd-b7cd-319cf2b8a345",
  "systemType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
```

```
    }
  }
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

targetSchema

accept-post

accept-put

hints

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | False | |
| allow | array[string] | False | |
| accept-post | accept-post | False | |
| permissions | array[string] | False | |
| accept-put | accept-put | False | |

type_astra_link

| Name | Type | Required | Description |
|---|---|---|---|
| rel | string | True | |
| href | string | True | |
| type | string | False | |
| targetSchema | targetSchema | False | |
| title | string | False | |
| hints | hints | False | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# List the namespaces for a cluster

GET `/accounts/{account_id}/topology/v1/clusters/{cluster_id}/namespaces`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| cluster_id | string | path | True | ID of the containing cluster resource |

| Name | Type | In | Required | Description |
| --- | --- | --- | --- | --- |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id"<br><br>• example: id,name,kubernetesLabels |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
|---|---|---|---|
| items | array[Any of: namespace_1.2_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

#### Example response


```
{
  "type": "application/astra-namespaces",
  "version": "1.2",
  "items": [
    [
      "7d451d2f-196e-4234-aee9-7e2376047e63",
      "kube-system",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ],
    [
      "66b0873b-214f-4ac7-89d8-922432f941eb",
      "jenkins",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

targetSchema

accept-post

accept-put

hints

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | False | |
| allow | array[string] | False | |
| accept-post | accept-post | False | |
| permissions | array[string] | False | |
| accept-put | accept-put | False | |

type_astra_link

| Name | Type | Required | Description |
|---|---|---|---|
| rel | string | True | |
| href | string | True | |
| type | string | False | |
| targetSchema | targetSchema | False | |
| title | string | False | |
| hints | hints | False | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

namespace_1.2_get_response_body

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-namespace" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| links | array[type_astra_link] | True | Links describing supported operations against the resource. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | JSON string containing a value indicating the name of the namespace. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| namespaceState | string | True | JSON string containing a value indicating the state of the namespace. Defined values are:<br>• "discovered" - The namespace has been found in the cluster<br>• "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace |
| namespaceStateDetails | array[type_astra_stateDetail] | True | JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:<br>• Minimum items: 0 |
| kubernetesLabels | array[type_astra_label] | False | JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:<br>• Conforms to the Kubernetes Label Array Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| kubernetesUID | string | True | JSON string containing the Kubernetes generated UID of the namespace resource |
| clusterID | string | True | JSON string containing a globally unique identifier of the cluster that the namespace is contained in. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| systemType | string | False | JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only). Defined values are:<br>• "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system"<br>• "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring"<br>• "openshift" - An OpenShift system namespace, for example, "openshift-monitoring"<br>• "rke" - A Rancher namespace, for example, "cattle-logging"<br>• "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system" |
| metadata | type_astra_metadata | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema |

type_astra_metadata_list

| Name | Type | Required | Description |
|---|---|---|---|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve a namespace for a cluster

GET `/accounts/{account_id}/topology/v1/clusters/{cluster_id}/namespaces/{namespace_id}`

Returns the stored Namespace API resource in the JSON response body.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| cluster_id | string | path | True | ID of the containing cluster resource |
| namespace_id | string | path | True | ID of the namespace collection to list |

## Response

```
Status: 200, Returns the stored Namespace API resource in the JSON
response body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-namespace" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| links | array[type_astra_link] | True | Links describing supported operations against the resource. |
| name | string | True | JSON string containing a value indicating the name of the namespace. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceState | string | True | JSON string containing a value indicating the state of the namespace. Defined values are:<br>• "discovered" - The namespace has been found in the cluster<br>• "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace |
| namespaceStateDetails | array[type_astra_stateDetail] | True | JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:<br>• Minimum items: 0 |
| kubernetesLabels | array[type_astra_label] | False | JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:<br>• Conforms to the Kubernetes Label Array Schema |
| kubernetesUID | string | True | JSON string containing the Kubernetes generated UID of the namespace resource |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | True | JSON string containing a globally unique identifier of the cluster that the namespace is contained in. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| systemType | string | False | JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only). Defined values are:<br>• "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system"<br>• "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring"<br>• "openshift" - An OpenShift system namespace, for example, "openshift-monitoring"<br>• "rke" - A Rancher namespace, for example, "cattle-logging"<br>• "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system" |

| Name | Type | Required | Description |
|---|---|---|---|
| metadata | type_astra_metadata | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema |

**Example response**


```
{
  "type": "application/astra-namespace",
  "version": "1.2",
  "id": "214dc2eb-19a6-5444-b156-f4b6b551a81a",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-
1349ca090415/topology/v1/namespaces/7d451d2f-196e-4234-aee9-
7e2376047e63",
      "type": "application/vnd.netapp.astra.namespace"
    },
    {
      "rel": "collection",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-
1349ca090415/topology/v1/clouds/e0490197-872e-4de8-9287-
b04a938e801f/clusters/0f284377-e5dc-4dcd-bacd-3197f2b8a347/namespaces",
      "type": "application/vnd.netapp.astra.namespaces"
    }
  ],
  "name": "kube-system",
  "namespaceState": "discovered",
  "namespaceStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/9",
      "title": "Namespace Discovered",
      "detail": "The namespace was discovered in the indicated managed
cluster"
    }
  ],
  "kubernetesLabels": [
    {
      "name": "app.kubernetes.io/environment",
      "value": "dev"
    }
  ],
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "kubernetesUID": "4f28c377-e5dc-4dcd-b7cd-319cf2b8a345",
  "systemType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
```

```
    }
  }
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

targetSchema

accept-post

accept-put

hints

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | False | |
| allow | array[string] | False | |
| accept-post | accept-post | False | |
| permissions | array[string] | False | |
| accept-put | accept-put | False | |

type_astra_link

| Name | Type | Required | Description |
|---|---|---|---|
| rel | string | True | |
| href | string | True | |
| type | string | False | |
| targetSchema | targetSchema | False | |
| title | string | False | |
| hints | hints | False | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# List all namespaces

GET `/accounts/{account_id}/topology/v1/namespaces`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |

| Name | Type | In | Required | Description |
| --- | --- | --- | --- | --- |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id"<br><br>• example: id,name,kubernetesLabels |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
|---|---|---|---|
| items | array[Any of: namespace_1.2_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

#### Example response


```
{
  "type": "application/astra-namespaces",
  "version": "1.2",
  "items": [
    [
      "7d451d2f-196e-4234-aee9-7e2376047e63",
      "kube-system",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ],
    [
      "66b0873b-214f-4ac7-89d8-922432f941eb",
      "jenkins",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

targetSchema

accept-post

accept-put

hints

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | False | |
| allow | array[string] | False | |
| accept-post | accept-post | False | |
| permissions | array[string] | False | |
| accept-put | accept-put | False | |

type_astra_link

| Name | Type | Required | Description |
|---|---|---|---|
| rel | string | True | |
| href | string | True | |
| type | string | False | |
| targetSchema | targetSchema | False | |
| title | string | False | |
| hints | hints | False | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

namespace_1.2_get_response_body

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-namespace" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| links | array[type_astra_link] | True | Links describing supported operations against the resource. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | JSON string containing a value indicating the name of the namespace. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| namespaceState | string | True | JSON string containing a value indicating the state of the namespace. Defined values are:<br>• "discovered" - The namespace has been found in the cluster<br>• "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace |
| namespaceStateDetails | array[type_astra_stateDetail] | True | JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:<br>• Minimum items: 0 |
| kubernetesLabels | array[type_astra_label] | False | JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:<br>• Conforms to the Kubernetes Label Array Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| kubernetesUID | string | True | JSON string containing the Kubernetes generated UID of the namespace resource |
| clusterID | string | True | JSON string containing a globally unique identifier of the cluster that the namespace is contained in. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| systemType | string | False | JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only). Defined values are:<br>• "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system"<br>• "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring"<br>• "openshift" - An OpenShift system namespace, for example, "openshift-monitoring"<br>• "rke" - A Rancher namespace, for example, "cattle-logging"<br>• "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system" |
| metadata | type_astra_metadata | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema |

type_astra_metadata_list

| Name | Type | Required | Description |
|---|---|---|---|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve a namespace

GET `/accounts/{account_id}/topology/v1/namespaces/{namespace_id}`

Returns the stored Namespace API resource in the JSON response body.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| namespace_id | string | path | True | ID of the namespace collection to list |

## Response

```
Status: 200, Returns the stored Namespace API resource in the JSON
response body.
```

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-namespace" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| links | array[type_astra_link] | True | Links describing supported operations against the resource. |
| name | string | True | JSON string containing a value indicating the name of the namespace. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceState | string | True | JSON string containing a value indicating the state of the namespace. Defined values are:<br>• "discovered" - The namespace has been found in the cluster<br>• "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace |
| namespaceStateDetails | array[type_astra_stateDetail] | True | JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:<br>• Minimum items: 0 |
| kubernetesLabels | array[type_astra_label] | False | JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:<br>• Conforms to the Kubernetes Label Array Schema |
| kubernetesUID | string | True | JSON string containing the Kubernetes generated UID of the namespace resource |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | True | JSON string containing a globally unique identifier of the cluster that the namespace is contained in. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| systemType | string | False | JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only). Defined values are:<br>• "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system"<br>• "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring"<br>• "openshift" - An OpenShift system namespace, for example, "openshift-monitoring"<br>• "rke" - A Rancher namespace, for example, "cattle-logging"<br>• "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system" |

| Name | Type | Required | Description |
|---|---|---|---|
| metadata | type_astra_metadata | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema |

**Example response**


```
{
  "type": "application/astra-namespace",
  "version": "1.2",
  "id": "214dc2eb-19a6-5444-b156-f4b6b551a81a",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-
1349ca090415/topology/v1/namespaces/7d451d2f-196e-4234-aee9-
7e2376047e63",
      "type": "application/vnd.netapp.astra.namespace"
    },
    {
      "rel": "collection",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-
1349ca090415/topology/v1/clouds/e0490197-872e-4de8-9287-
b04a938e801f/clusters/0f284377-e5dc-4dcd-bacd-3197f2b8a347/namespaces",
      "type": "application/vnd.netapp.astra.namespaces"
    }
  ],
  "name": "kube-system",
  "namespaceState": "discovered",
  "namespaceStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/9",
      "title": "Namespace Discovered",
      "detail": "The namespace was discovered in the indicated managed
cluster"
    }
  ],
  "kubernetesLabels": [
    {
      "name": "app.kubernetes.io/environment",
      "value": "dev"
    }
  ],
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "kubernetesUID": "4f28c377-e5dc-4dcd-b7cd-319cf2b8a345",
  "systemType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
```

```
    }
  }
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

targetSchema

accept-post

accept-put

hints

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | False | |
| allow | array[string] | False | |
| accept-post | accept-post | False | |
| permissions | array[string] | False | |
| accept-put | accept-put | False | |

type_astra_link

| Name | Type | Required | Description |
|---|---|---|---|
| rel | string | True | |
| href | string | True | |
| type | string | False | |
| targetSchema | targetSchema | False | |
| title | string | False | |
| hints | hints | False | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# List the namespaces for a managed cluster

GET
`/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/namespaces`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| managedCluster_id | string | path | True | ID of the containing managedCluster resource |

| Name | Type | In | Required | Description |
| --- | --- | --- | --- | --- |
| include | string | query | False | Indicates which fields should be returned when listing a collection.<br><br>URL examples: "include=id", "include=id,name"<br><br>OpenAPI examples: "id"<br><br>• example: id,name,kubernetesLabels |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples: "limit=2"<br><br>OpenAPI examples: "2" |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| filter | string | query | False | Indicates which fields should be matched in order to return a resource when listing a collection.<br><br>Supported operators are:<br><br>• eq - Equality<br>• lt/gt - Less than/Greater than<br>• lte/gte - Less than or equals to/Greater than or equals to<br><br>URL example: "filter=field%20eq%20%27value%27"<br><br>OpenAPI examples: "field eq 'value'" |

## Response

```
Status: 200, Returns a JSON array of all matching resources in the
collection. If individual fields are specified in the request, the items
JSON array will contain the fields requested for each matching resource in
the order specified.
```

| Name | Type | Required | Description |
|---|---|---|---|
| items | array[Any of: namespace_1.2_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

#### Example response


```
{
  "type": "application/astra-namespaces",
  "version": "1.2",
  "items": [
    [
      "7d451d2f-196e-4234-aee9-7e2376047e63",
      "kube-system",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ],
    [
      "66b0873b-214f-4ac7-89d8-922432f941eb",
      "jenkins",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```


## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

**Example response**

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

targetSchema

accept-post

accept-put

hints

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | False | |
| allow | array[string] | False | |
| accept-post | accept-post | False | |
| permissions | array[string] | False | |
| accept-put | accept-put | False | |

type_astra_link

| Name | Type | Required | Description |
|---|---|---|---|
| rel | string | True | |
| href | string | True | |
| type | string | False | |
| targetSchema | targetSchema | False | |
| title | string | False | |
| hints | hints | False | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

namespace_1.2_get_response_body

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-namespace" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| links | array[type_astra_link] | True | Links describing supported operations against the resource. |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| name | string | True | JSON string containing a value indicating the name of the namespace. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |
| namespaceState | string | True | JSON string containing a value indicating the state of the namespace. Defined values are:<br>• "discovered" - The namespace has been found in the cluster<br>• "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace |
| namespaceStateDetails | array[type_astra_stateDetail] | True | JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:<br>• Minimum items: 0 |
| kubernetesLabels | array[type_astra_label] | False | JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:<br>• Conforms to the Kubernetes Label Array Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| kubernetesUID | string | True | JSON string containing the Kubernetes generated UID of the namespace resource |
| clusterID | string | True | JSON string containing a globally unique identifier of the cluster that the namespace is contained in. Defined values are:<br>• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| systemType | string | False | JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only). Defined values are:<br>• "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system"<br>• "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring"<br>• "openshift" - An OpenShift system namespace, for example, "openshift-monitoring"<br>• "rke" - A Rancher namespace, for example, "cattle-logging"<br>• "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system" |
| metadata | type_astra_metadata | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema |

type_astra_metadata_list

| Name | Type | Required | Description |
|---|---|---|---|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

# Retrieve a namespace for a managed cluster

GET `/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/namespaces/{namespace_id}`

Returns the stored Namespace API resource in the JSON response body.

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| account_id | string | path | True | ID of the containing account resource<br>• example: {{.Account}} |
| managedCluster_id | string | path | True | ID of the containing managedCluster resource |
| namespace_id | string | path | True | ID of the namespace collection to list |

## Response

```
Status: 200, Returns the stored Namespace API resource in the JSON
response body.
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | Media type of the resource. Defined values are:<br>• "application/astra-namespace" |
| version | string | True | Version of the resource. Defined values are:<br>• "1.0"<br>• "1.1"<br>• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are:<br>• Conforms to the UUIDv4 Schema |
| links | array[type_astra_link] | True | Links describing supported operations against the resource. |
| name | string | True | JSON string containing a value indicating the name of the namespace. Defined values are:<br>• Minimum length: 1<br>• Maximum length: 255 |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| namespaceState | string | True | JSON string containing a value indicating the state of the namespace. Defined values are:<br>• "discovered" - The namespace has been found in the cluster<br>• "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace |
| namespaceStateDetails | array[type_astra_stateDetail] | True | JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:<br>• Minimum items: 0 |
| kubernetesLabels | array[type_astra_label] | False | JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:<br>• Conforms to the Kubernetes Label Array Schema |
| kubernetesUID | string | True | JSON string containing the Kubernetes generated UID of the namespace resource |

| Name | Type | Required | Description |
| --- | --- | --- | --- |
| clusterID | string | True | JSON string containing a globally unique identifier of the cluster that the namespace is contained in. Defined values are:<br>• Conforms to the Astra Identifier Schema |
| systemType | string | False | JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only). Defined values are:<br>• "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system"<br>• "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring"<br>• "openshift" - An OpenShift system namespace, for example, "openshift-monitoring"<br>• "rke" - A Rancher namespace, for example, "cattle-logging"<br>• "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system" |

| Name | Type | Required | Description |
|---|---|---|---|
| metadata | type_astra_metadata | True | Client and service-specified metadata associated with the resource. Defined values are:<br>• Conforms to the Astra Metadata Schema |

**Example response**


```
{
  "type": "application/astra-namespace",
  "version": "1.2",
  "id": "214dc2eb-19a6-5444-b156-f4b6b551a81a",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-
1349ca090415/topology/v1/namespaces/7d451d2f-196e-4234-aee9-
7e2376047e63",
      "type": "application/vnd.netapp.astra.namespace"
    },
    {
      "rel": "collection",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-
1349ca090415/topology/v1/clouds/e0490197-872e-4de8-9287-
b04a938e801f/clusters/0f284377-e5dc-4dcd-bacd-3197f2b8a347/namespaces",
      "type": "application/vnd.netapp.astra.namespaces"
    }
  ],
  "name": "kube-system",
  "namespaceState": "discovered",
  "namespaceStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/9",
      "title": "Namespace Discovered",
      "detail": "The namespace was discovered in the indicated managed
cluster"
    }
  ],
  "kubernetesLabels": [
    {
      "name": "app.kubernetes.io/environment",
      "value": "dev"
    }
  ],
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "kubernetesUID": "4f28c377-e5dc-4dcd-b7cd-319cf2b8a345",
  "systemType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
```

```
    }
  }
```

## Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

```
Status: 400, Bad request
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

```
Status: 403, Forbidden
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

```
Status: 404, Not found
```

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | True | |
| correlationID | string | False | |

**Example error response**

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

**See Definitions**

targetSchema

accept-post

accept-put

hints

| Name | Type | Required | Description |
|---|---|---|---|
| status | string | False | |
| allow | array[string] | False | |
| accept-post | accept-post | False | |
| permissions | array[string] | False | |
| accept-put | accept-put | False | |

type_astra_link

| Name | Type | Required | Description |
|---|---|---|---|
| rel | string | True | |
| href | string | True | |
| type | string | False | |
| targetSchema | targetSchema | False | |
| title | string | False | |
| hints | hints | False | |

additionalDetails

type_astra_stateDetail

| Name | Type | Required | Description |
|---|---|---|---|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| additionalDetails | additionalDetails | False | |

type_astra_label

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

| Name | Type | Required | Description |
|---|---|---|---|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|---|---|---|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

版權資訊

Copyright © 2024 NetApp, Inc. 版權所有。台灣印製。非經版權所有人事先書面同意，不得將本受版權保護文件的任何部分以任何形式或任何方法（圖形、電子或機械）重製，包括影印、錄影、錄音或儲存至電子檢索系統中。

由 NetApp 版權資料衍伸之軟體必須遵守下列授權和免責聲明：

此軟體以 NETAPP「原樣」提供，不含任何明示或暗示的擔保，包括但不限於有關適售性或特定目的適用性之擔保，特此聲明。於任何情況下，就任何已造成或基於任何理論上責任之直接性、間接性、附隨性、特殊性、懲罰性或衍生性損害（包括但不限於替代商品或服務之採購；使用、資料或利潤上的損失；或企業營運中斷），無論是在使用此軟體時以任何方式所產生的契約、嚴格責任或侵權行為（包括疏忽或其他）等方面，NetApp 概不負責，即使已被告知有前述損害存在之可能性亦然。

NetApp 保留隨時變更本文所述之任何產品的權利，恕不另行通知。NetApp 不承擔因使用本文所述之產品而產生的責任或義務，除非明確經過 NetApp 書面同意。使用或購買此產品並不會在依據任何專利權、商標權或任何其他 NetApp 智慧財產權的情況下轉讓授權。

本手冊所述之產品受到一項（含）以上的美國專利、國外專利或申請中專利所保障。

有限權利說明：政府機關的使用、複製或公開揭露須受 DFARS 252.227-7013（2014 年 2 月）和 FAR 52.227-19（2007 年 12 月）中的「技術資料權利 - 非商業項目」條款 (b)(3) 小段所述之限制。

此處所含屬於商業產品和 / 或商業服務（如 FAR 2.101 所定義）的資料均為 NetApp, Inc. 所有。根據本協議提供的所有 NetApp 技術資料和電腦軟體皆屬於商業性質，並且完全由私人出資開發。 美國政府對於該資料具有非專屬、非轉讓、非轉授權、全球性、有限且不可撤銷的使用權限，僅限於美國政府為傳輸此資料所訂合約所允許之範圍，並基於履行該合約之目的方可使用。除非本文另有規定，否則未經 NetApp Inc. 事前書面許可，不得逕行使用、揭露、重製、修改、履行或展示該資料。美國政府授予國防部之許可權利，僅適用於 DFARS 條款 252.227-7015(b)（2014 年 2 月）所述權利。

商標資訊

NETAPP、NETAPP 標誌及 http://www.netapp.com/TM 所列之標章均為 NetApp, Inc. 的商標。文中所涉及的所有其他公司或產品名稱，均為其各自所有者的商標，不得侵犯。