已知问题

Astra Control Center

NetApp
May 03, 2022

This PDF was generated from https://docs.netapp.com/zh-cn/astra-control-center/release-notes/known-issues-ads.html on May 03, 2022. Always check docs.netapp.com for the latest.

目录

已知问题 1
还原应用程序会导致 PV 大小大于原始 PV 1
使用特定版本的 PostgreSQL 时应用程序克隆失败 1
使用服务帐户级别 OCP 安全上下文限制（ SCC ）时应用程序克隆失败 1
使用设置的存储类部署应用程序后，应用程序克隆将失败 1
如果默认的 kubeconfig 文件包含多个上下文，则使用 Astra 控制中心管理集群将失败 2
当 Astra Trident 脱机时，应用程序数据管理操作失败，并显示内部服务错误（ 500 ） 2
使用 Snapshot 控制器 4.2.0 版时，快照可能会失败 2
了解更多信息 2
有关 Astra Data Store 预览版和此 Astra 控制中心版本的已知问题 2

已知问题

已知问题可确定可能妨碍您成功使用此版本产品的问题。

以下已知问题会影响当前版本：

应用程序

- [Restore of an app results in PV size larger than original PV]
- [App clones fail using a specific version of PostgreSQL]
- [App clones fail when using Service Account level OCP Security Context Constraints (SCC)]
- [App clones fail after an application is deployed with a set storage class]

集群

- [Managing a cluster with Astra Control Center fails when default kubeconfig file contains more than one context]

其他问题

- [App data management operations fail with Internal Service Error (500) when Astra Trident is offline]
- [Snapshots might fail with snapshot controller version 4.2.0]

还原应用程序会导致 PV 大小大于原始 PV

如果在创建备份后调整永久性卷的大小，然后从该备份还原，则此永久性卷的大小将与 PV 的新大小匹配，而不是使用备份的大小。

使用特定版本的 PostgreSQL 时应用程序克隆失败

使用 BitNami PostgreSQL 11.5.0 图表时，同一集群中的应用程序克隆始终会失败。要成功克隆，请使用图表的早期或更高版本。

使用服务帐户级别 OCP 安全上下文限制（SCC）时应用程序克隆失败

如果在 OpenShift 容器平台集群的命名空间中的服务帐户级别配置了原始安全上下文约束，则应用程序克隆可能会失败。如果应用程序克隆失败，它将显示在 Astra 控制中心的受管应用程序区域中，状态为 `removed` 。请参见 "知识库文章" 有关详细信息 …

使用设置的存储类部署应用程序后，应用程序克隆将失败

在使用显式设置的存储类（例如， `helm install …-set global.storageClass=netapp-cvs-perf-至 至至` ）部署应用程序后，后续克隆应用程序的尝试要求目标集群具有最初指定的存储类。将具有显式设置的存储类的应用程序克隆到没有相同存储类的集群将失败。此情况下没有恢复步骤。

如果默认的 kubeconfig 文件包含多个上下文，则使用 Astra 控制中心管理集群将失败

不能将 kubeconfig 与多个集群和上下文结合使用。请参见 "知识库文章" 有关详细信息 …

当 Astra Trident 脱机时，应用程序数据管理操作失败，并显示内部服务错误（ 500 ）

如果应用程序集群上的 Astra Trident 脱机（并恢复联机），并且在尝试应用程序数据管理时遇到 500 个内部服务错误，请重新启动应用程序集群中的所有 Kubernetes 节点以还原功能。

使用 Snapshot 控制器 4.2.0 版时，快照可能会失败

如果将 Kubernetes Snapshot-controller （也称为外部快照程序） 4.2.0 与 Kubernetes 1.20 或 1.21 结合使用，则快照最终可能会开始失败。要防止出现这种情况，请使用其他 "支持的版本" 使用 Kubernetes 版本 1.20 或 1.21 的外部快照程序，例如 4.2.1 版。

1. 运行 POST 调用，将更新后的 kubeconfig 文件添加到 `凭据` 端点，并从响应正文中检索分配的 `id` 。
2. 使用适当的集群 ID 从 `集群` 端点运行 PUT 调用，并将 `credentialId` 设置为上一步中的 `id` 值。

完成这些步骤后，将更新与集群关联的凭据，集群应重新连接并将其状态更新为 `Available` 。

了解更多信息

- "Astra Data Store prreview 和此 Astra Control Center 版本的已知问题"
- "已知限制"

有关 Astra Data Store 预览版和此 Astra 控制中心版本的已知问题

已知问题可确定可能妨碍您成功使用此版本产品的问题。

使用此最新版本的 Astra 控制中心时，以下已知问题会影响 Astra 数据存储的管理：

由于 MongoDB Pod 活跃度探针故障，无法将 Astra Data Store 预览用作 Astra 控制中心的存储类

在部署 Astra 控制中心期间，当您尝试使用 Astra Data Store 预览作为存储类配置程序时， MongoDB POD 活动性探针将失败，从而导致部署无法完成。

要更正此问题描述，请在完成时除了进行标准的 YAML 更改外，还进行以下更改 "Astra 控制中心安装过程"：

1. 编辑 "Astra 控制中心操作员部署 YAML （Astra_control_center_operator_deploy.yaml ）" 更改 Helm 安装超时：

```
- name: ACCOP_HELM_INSTALLTIMEOUT
  value: 20m
```

2. 编辑 "Astra 控制中心自定义资源（CR）文件（Astra_control_center_min.yaml）" 并在 `sPec` 下添加突出显示的其他值：

```
apiVersion: astra.netapp.io/v1
kind: AstraControlCenter
metadata:
  name: astra
spec:
  accountName: "Example"
  astraVersion: "ASTRA_VERSION"
  astraAddress: "astra.example.com"
  autoSupport:
    enrolled: true
  email: "[admin@example.com]"
  firstName: "SRE"
  lastName: "Admin"
  imageRegistry:
    name: "[your_registry_path]"
    secret: "astra-registry-cred"
  storageClass: "ontap-gold"
  additionalValues:
    polaris-mongodb:
      mongodb:
        livenessProbe:
          initialDelaySeconds: 400
      metrics:
        livenessProbe:
          initialDelaySeconds: 400
```

了解更多信息

- "已知问题"
- "已知限制"
- "Astra Data Store 文档"

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.