



Astra データストアを使用

Astra Data Store

NetApp
April 25, 2022

目次

Astra データストアを使用	1
kubectl コマンドを使用して Astra データストアのプレビューアセットを管理	1
テストアプリケーションを展開します	7
クラスタを管理	11
Cloud Insights で指標を監視	23
Prometheus と Grafana で指標を監視します	35
イベントログを設定して監視する	37
Astra Control Center with Astra のデータストアプレビューを使用	38
Astra データストアプレビューを自動スクリプトでアンインストールします	38
スクリプトを使用せずに Astra データストアプレビューをアンインストールする	45

Astra データストアを使用

kubectl コマンドを使用して Astra データストアのプレビューアセットを管理

kubectl コマンドを使用し、Kubernetes API 拡張機能を使用して、Astra データストアのプレビューアセットを管理できます。

サンプルアプリの展開方法については、を参照してください ["テストアプリケーションを展開します"](#)。

次のクラスタのメンテナンス情報については、を参照してください ["クラスタを管理"](#)：

- ノードをメンテナンスモードにします
- ドライブを交換します
- ノードを追加します
- ノードを交換

必要なもの

- にインストールした Astra データストアプレビュー用 kubectl プラグイン ["Astra データストアプレビューをインストールします"](#)

Astra データストアプレビュー用の Kubernetes カスタム API リソースを列挙

Kubernetes の内部で kubectl コマンドを使用して、Astra データストアプレビュークラスタとやり取りし、状態を確認できます。

「api-resources」コマンドにリストされている各項目は、Kubernetes カスタムリソース定義（CRD）を表しています。CRD は、アストラデータストアプレビューがクラスタを内部的に管理するために使用します。

このリストは、後で示すように、各 Astra Data Store プレビューオブジェクトの短い名前を取得して入力を減らすのに特に役立ちます。

1. Kubernetes のカスタム API リソースである Astra データストアプレビュー版のリストを表示します。

```
kubectl api-resources --api-group astrads.netapp.io
```

対応：

NAME	SHORTNAMES	APIGROUP	NAMESPACED	KIND
astradsversions	adsve	astrads.netapp.io	true	
AstraDSVersion				
astradsclusters	adscl	astrads.netapp.io	true	
AstraDSCluster				
astradslicenses	adsli	astrads.netapp.io	true	
AstraDSLICENSE				
astradsnodeinfoes	adsni	astrads.netapp.io	true	
AstraDSNodeInfo				
astradsvolumes	adsvo	astrads.netapp.io	true	
AstraDSVolume				
astradsqospolicies	adsqp	astrads.netapp.io	true	
AstraDSQosPolicy				
astradsexportpolicies	adsep	astrads.netapp.io	true	
AstraDSEExportPolicy				
astradsvolumesnapshots	adsvs	astrads.netapp.io	true	
AstraDSVolumeSnapshot				
astradsvolumefiles	adsvf	astrads.netapp.io	true	
AstraDSVolumeFiles				
astradsautosupports	adsas	astrads.netapp.io	true	
AstraDSAutoSupport				
astradsfaileddrives	adsfd	astrads.netapp.io	true	
AstraDSFailedDrive				
astradsnodemanagements	adsnm	astrads.netapp.io	true	
AstraDSNodeManagement				

2. Kubernetes クラスタ内の現在の Astra データストアプレビューオブジェクトをすべて取得するには、「`kubectl get ads-a`」コマンドを使用します。

```
kubectl get ads -A
```

対応：

NAMESPACE	NAME	AGE
astrads-system	astradsqospolicy.astrads.netapp.io/bronze	45h
astrads-system	astradsqospolicy.astrads.netapp.io/gold	45h
astrads-system	astradsqospolicy.astrads.netapp.io/silver	45h

NAMESPACE	NAME	STATUS	VERSION	SERIAL NUMBER	MVIP	AGE
astrads-system	astradscluster.astrads.netapp.io/	created	arda-9.11.1	e000000009	10.224.8.146	46h

```

AGE
astrads-system    astradsnodeinfo.astrads.netapp.io/englab.netapp.com
46h
astrads-system    astradsnodeinfo.astrads.netapp.io/englab.netapp.com
46h
astrads-system    astradsnodeinfo.astrads.netapp.io/englab.netapp.com
46h
astrads-system    astradsnodeinfo.astrads.netapp.io/englab.netapp.com
46h

NAMESPACE          NAME                                     AGE
astrads-system      astradsversion.astrads.netapp.io/astradsversion  46h

NAMESPACE          NAME                                     AGE
astrads-system      astradsvolumefiles.astrads.netapp.io/test23      27h
astrads-system      astradsvolumefiles.astrads.netapp.io/test234     27h
astrads-system      astradsvolumefiles.astrads.netapp.io/test2345    4h22m

NAMESPACE          NAME                                     SIZE   IP
CLUSTER            CREATED
astrads-system      astradsvolume.astrads.netapp.io/test234          21Gi
172.25.123.123      astrads-cluster-9f1 true
astrads-system      astradsvolume.astrads.netapp.io/test2345          21Gi
172.25.123.123      astrads-cluster-9f1 true

NAMESPACE          NAME
SEQUENCE COMPONENT      EVENT          TRIGGER      PRIORITY  SIZE
STATE
astrads-system      astradsautosupport.astrads.netapp.io/controlplane-
adsclustercreatesuccess-20211214t 9          controlplane
adsclustercreatesuccess k8sEvent  notice      0          uploaded
astrads-system      astradsautosupport.astrads.netapp.io/controlplane-
daily-20211215t0          15          controlplane  daily
periodic  notice      0          uploaded
astrads-system      astradsautosupport.astrads.netapp.io/controlplane-
daily-20211216t0          20          controlplane  daily
periodic  notice      0          uploaded
astrads-system      astradsautosupport.astrads.netapp.io/storage-
callhome.dbs.cluster.cannot.sync.blocks 10          storage
callhome.dbs.cluster.cannot.sync.blocks  firetapEvent  emergency  0
uploaded

NAMESPACE          NAME                                     ADSCLUSTER
VALID PRODUCT          EVALUATION ENDDATE      VALIDATED
astrads-system      astradslicense.astrads.netapp.io/e0      astrads-cluster-
9f1 true  Astra Data Store true          2022-02-07 2021-12-16T20:43:23Z

```

- 短縮名の 1 つを使用して、クラスタ内のボリュームの現在の状態を表示します。

```
kubectl get adsvo -A
```

対応：

NAMESPACE	NAME	SIZE	IP	CLUSTER
astrads-system	test234	21Gi	172.25.138.109	astrads-cluster-9f1c99f
astrads-system	test2345	21Gi	172.25.138.111	astrads-cluster-9f1c99f

kubectl 拡張子の help オプションを使用します

'kubectl astras コマンド'には'h'スイッチが含まれており'便利な使用法とフラグ・ドキュメントが提供されています'

- Astra Data Store preview kubectl 拡張機能のすべてのコマンドのヘルプを表示します。

```
kubectl astrads -h
```

対応：

A kubectl plugin for inspecting your AstraDS deployment

Usage:

astrads [command]

Available Commands:

asup	Manage AutoSupport
clusters	Manage clusters
drives	Manage drives in a cluster
faileddrive	Manage drive replacement in a cluster
help	Help about any command
license	Manage license in the astrads cluster
maintenance	Manage maintenance status of a node
monitoring	Manage Monitoring Output
nodes	Manage nodes in a cluster

Flags:

--as string	Username to impersonate for the operation
-------------	---

<code>--as-group stringArray</code>	Group to impersonate for the operation, this flag can be repeated to specify multiple groups.
<code>--cache-dir string</code>	Default HTTP cache directory (default <code>"/u/arda/.kube/http-cache"</code>)
<code>--certificate-authority string</code>	Path to a cert file for the certificate authority
<code>--client-certificate string</code>	Path to a client certificate file for TLS
<code>--client-key string</code>	Path to a client key file for TLS
<code>--cluster string</code>	The name of the kubeconfig cluster to use
<code>--context string</code>	The name of the kubeconfig context to use
<code>-h, --help</code>	help for astrads
<code>--insecure-skip-tls-verify</code>	If true, the server's certificate will not be checked for validity. This will make your HTTPS connections insecure
<code>--kubeconfig string</code>	Path to the kubeconfig file to use for CLI requests.
<code>-n, --namespace string</code>	If present, the namespace scope for this CLI request
<code>--request-timeout string</code>	The length of time to wait before giving up on a single server request. Non-zero values should contain a corresponding time unit (e.g. 1s, 2m, 3h).
<code>-s, --server string</code>	The address and port of the Kubernetes API server
<code>--token string</code>	Bearer token for authentication to the API server
<code>--user string</code>	The name of the kubeconfig user to use

2. コマンドの詳細については 'astrads [command]--help' を使用してください

```
kubectl astrads asup collect --help
```

対応：

Collect the autosupport bundle by specifying the component to collect. It will default to manual event.

Usage:

```
astrads asup collect [flags]
```

Examples:

```
# Control plane collection
```

```
kubectl astrads collect --component controlplane example1
```

```
# Storage collection for single node
```

```
kubectl astrads collect --component storage --nodes node1 example2
```

```
# Storage collection for all nodes
```

```
kubectl astrads collect --component storage --nodes all example3
```

```
# Collect but don't upload to support
```

```
kubectl astrads collect --component controlplane --local example4
```

NOTE:

```
--component storage and --nodes <name> are mutually inclusive.
```

```
--component controlplane and --nodes <name> are mutually exclusive.
```

Flags:

```
-c, --component string      Specify the component to collect:  
[storage , controlplane , vasaprovider, all]
```

```
-d, --duration int          Duration is the duration in hours from  
the startTime for collection  
of AutoSupport.
```

```
-e, --event string          This should be a positive integer  
(default "manual")         Specify the callhome event to trigger.
```

```
-f, --forceUpload           Configure an AutoSupport to upload if  
it is in the compressed state  
and not  
uploading because it was created with  
the 'local' option or if  
automatic uploads of AutoSupports is  
disabled
```

```
-h, --help                  help for collect  
-l, --local                 Only collect and compress the  
autosupport bundle. Do not upload
```


bundle after it is in

```
--nodes string  
component. (default "all")  
-t, --startTime string  
collection of AutoSupport.
```

time format.

01T15:20:25-05:00

```
-u, --usermessage string  
to include in the
```

CLI")

to support.

Use 'download' to copy the collected

the 'compressed' state

Specify nodes to collect for storage

StartTime is the starting time for

This should be in the ISO 8601 date

Example format accepted:

2021-01-01T15:20:25Z, 2021-01-

UserMessage is the additional message

AutoSupport subject.

(default "Manual event trigger from

テストアプリケーションを展開します

Astra データストアプレビューで利用できるテストアプリケーションを導入する手順は次のとおりです。

この例では、Helm リポジトリを使用して Bitnami から MongoDB チャートを導入します。

必要なもの

- Astra データストアプレビュークラスターの導入と構成
- Trident のインストールが完了しました

手順

1. Bitnami から Helm repo を追加します。

```
helm repo add bitnami https://charts.bitnami.com/bitnami
```

2. MongoDB の導入

```
helm install mongohelm4 --set persistence.storageClass=trident-csi  
bitnami/mongodb --namespace=ns-mongodb --create-namespace
```

3. MongoDB ポッドのステータスを確認します。

```
~% kubectl get pods -n ns-mongodb
```

NAME	READY	STATUS	RESTARTS	AGE
mongodb-9846ff8b7-rfr4r	1/1	Running	0	67s

4. MongoDB で使用した Persistent Volume Claim (PVC ; 永続ボリューム要求)を確認します。

```
~% kubectl get pvc -n ns-mongodb
```

NAME	STATUS	VOLUME	CAPACITY	ACCESS MODES
mongodb	Bound	pvc-1133453a-e2f5-48a5	8Gi	RWO
trident-csi	97s			

5. kubectl コマンド 'get astradsvolume' を使用して 'ボリュームを一覧表示します

```
~% kubectl get astradsvolume pvc-1133453a-e2f5-48a5 -n astrads-system
```

NAME	SIZE	IP	CLUSTER	CREATED
pvc-1133453a-e2f5-48a5	8830116Ki	10.192.2.192	jai-ads	true

6. kubectl コマンド 'describe astradsvolume' を使用して 'ボリュームを説明します

```
~% kubectl describe astradsvolume pvc-1133453a-e2f5-48a5 -n astrads-system
```

Name: pvc-1133453a-e2f5-48a5-a06c-d14b8aa7be07

Namespace: astrads-system

Labels: astrads.netapp.io/cluster=jai-ads
astrads.netapp.io/mip=10.192.1.39
astrads.netapp.io/volumeUUID=cf33fd38-a451-596c-b656-61b8270d2b5e
trident.netapp.io/cloud=on-prem
trident.netapp.io/creator=trident-dev
trident.netapp.io/performance=premium

Annotations: provisioning: {"provisioning":{"cloud":"on-prem","creator":"trident-dev","performance":"premium"}}
trident: {"trident":{"version":"21.10.0-test.jenkins-trident-stable-v21.10-2+e03219ce37294d9ba54ec476bbe788c1a7772548"},"backendUUID":"","platform":
...
API Version: astrads.netapp.io/v1alpha1
Kind: AstraDSVolume
Metadata:
Creation Timestamp: 2021-12-08T19:35:26Z

```
Finalizers:
  trident.netapp.io/astradsvolume-finalizer
  astrads.netapp.io/astradsvolume-finalizer
Generation: 1
Managed Fields:
  API Version:  astrads.netapp.io/v1alpha1
  Fields Type:  FieldsV1
  fieldsV1:
    f:metadata:
      f:labels:
        f:astrads.netapp.io/cluster:
        f:astrads.netapp.io/mip:
        f:astrads.netapp.io/volumeUUID:
    f:status:
      .:
      f:cluster:
      f:conditions:
      f:created:
      f:displayName:
      f:exportAddress:
      f:internalName:
      f:mip:
      f:permissions:
      f:qosPolicy:
      f:requestedSize:
      f:restoreCacheSize:
      f:size:
      f:snapshotReservePercent:
      f:state:
      f:volumePath:
      f:volumeUUID:
  Manager:      cluster-controller
  Operation:    Update
  Time:         2021-12-08T19:35:32Z
  API Version:  astrads.netapp.io/v1alpha1
  Fields Type:  FieldsV1
  fieldsV1:
    f:status:
      f:exportPolicy:
  Manager:      dms-controller
  Operation:    Update
  Subresource:  status
  Time:         2021-12-08T19:35:32Z
  API Version:  astrads.netapp.io/v1alpha1
  Fields Type:  FieldsV1
  fieldsV1:
```

```

f:metadata:
  f:annotations:
    .:
    f:provisioning:
    f:trident:
  f:finalizers:
    v:"trident.netapp.io/astradvolume-finalizer":
  f:labels:
    .:
    f:trident.netapp.io/cloud:
    f:trident.netapp.io/creator:
    f:trident.netapp.io/performance:
  f:spec:
    .:
    f:cluster:
    f:displayName:
    f:exportPolicy:
    f:noSnapDir:
    f:permissions:
    f:qosPolicy:
    f:size:
    f:snapshotReservePercent:
    f:type:
    f:volumePath:
  Manager:          trident_orchestrator
  Operation:        Update
  Time:              2021-12-08T19:35:34Z
  Resource Version: 12007115
  UID:               d522ae4f-e793-49ed-bbe0-9112d7f9167b
Spec:
  Cluster:          jai-ads
  Display Name:      pvc-1133453a-e2f5-48a5-a06c-d14b8aa7be07
  Export Policy:     pvc-1133453a-e2f5-48a5-a06c-d14b8aa7be07
  No Snap Dir:       true
  Permissions:       0777
  Qos Policy:        silver
  Size:              9042036412
  Snapshot Reserve Percent: 5
  Type:              ReadWrite
  Volume Path:       /pvc-1133453a-e2f5-48a5-a06c-d14b8aa7be07
Status:
  Cluster:  jai-ads
  Conditions:
    Last Transition Time:  2021-12-08T19:35:32Z
    Message:              Volume is online
    Reason:               VolumeOnline

```

```

Status:      True
Type:        AstraDSVolumeOnline
Last Transition Time: 2021-12-08T19:35:32Z
Message:     Volume creation request was successful
Reason:      VolumeCreated
Status:      True
Type:        AstraDSVolumeCreated
Created:     true
Display Name: pvc-1133453a-e2f5-48a5-a06c-d14b8aa7be07
Export Address: 10.192.2.192
Export Policy:  pvc-1133453a-e2f5-48a5-a06c-d14b8aa7be07
Internal Name:  pvc_1133453a_e2f5_48a5_a06c_d14b8aa7be07
Mip:          10.192.1.192
Permissions:   777
Qos Policy:    silver
Requested Size: 9042036412
Restore Cache Size: 0
Size:          8830116Ki
Snapshot Reserve Percent: 5
State:         online
Volume Path:   /pvc-1133453a-e2f5-48a5-a06c-d14b8aa7be07
Volume UUID:   cf33fd38-a451-596c-b656-61b8270d2b5e
Events:
  Type      Reason          Age   From                      Message
  ----      -
  Normal    VolumeCreated  3m9s  ADSClusterController     Volume creation
request was successful

```

クラスタを管理

クラスタを管理するには、`kubectl` コマンドを Astra データストアプレビューで使います。

- [\[Add a node\]](#)
- [\[Place a node in maintenance mode\]](#)
- [\[Replace a node\]](#)
- [\[Replace a drive\]](#)

必要なもの

- `kubectl` および `kubectl-astras` プラグインがインストールされたシステム。を参照してください ["Astra データストアプレビューをインストールします"](#)。

ノードを追加します

追加するノードは Kubernetes クラスタに含まれ、クラスタ内の他のノードと同様の設定である必要があります。

手順

1. 新しいノードの dataIP がまだ ADSCluster CR に含まれていない場合は、次の手順を実行します。
 - a. astadcluster CR を編集し、ADS Data Networks Addresses フィールドに追加の dataIP を追加します。

```
~% kubectl edit astradcluster <cluster-name> -n astrads-system
```

対応：

```
adsDataNetworks:
  -addresses: dataIP1,dataIP2,dataIP3,dataIP4,*newdataIP*
```

- a. CR を保存します。
- b. Astra データストアプレビュークラスタにノードを追加します。

```
~% kubectl astrads nodes add --cluster <cluster-name>
```

2. それ以外の場合は、ノードを追加するだけで済みます。

```
~% kubectl astrads nodes add --cluster <cluster-name>
```

3. ノードが追加されたことを確認します。

```
~% kubectl astrads nodes list
```

ノードをメンテナンスモードにします

ホストのメンテナンスやパッケージのアップグレードが必要な場合は、ノードをメンテナンスモードにする必要があります。



ノードは、Astra データストアプレビュークラスタにすでに含まれている必要があります。

ノードが保守モードのときは、クラスタにノードを追加できません。この例では、ノード「nhcitj1525」をメンテナンスモードにします。

手順

1. ノードの詳細を表示します。

```
~% kubectl get nodes
```

対応：

NAME	STATUS	ROLES	AGE	VERSION
nhcitjj1525	Ready	<none>	3d18h	v1.20.0
nhcitjj1526	Ready	<none>	3d18h	v1.20.0
nhcitjj1527	Ready	<none>	3d18h	v1.20.0
nhcitjj1528	Ready	<none>	3d18h	v1.20.0
scs000039783-1	Ready	control-plane,master	3d18h	v1.20.0

2. ノードがまだメンテナンスモードになっていないことを確認します。

```
~% kubectl astrads maintenance list
```

応答（メンテナンスモードのノードがありません）：

NAME	NODE NAME	IN MAINTENANCE	MAINTENANCE STATE	MAINTENANCE VARIANT
------	-----------	----------------	-------------------	------------------------

3. メンテナンスモードを有効にします。

```
~% kubectl astrads maintenance create <cr-name> --node-name=<<node  
-name>> --variant=Node
```

サンプル：

```
~% kubectl astrads maintenance create maint1 --node-name="nhcitjj1525"  
--variant=Node  
Maintenance mode astrads-system/maint1 created
```

4. ノードをリストします。

```
~% kubectl astrads nodes list
```

対応：

NODE NAME	NODE STATUS	CLUSTER NAME
nhcitjj1525	Added	ftap-astra-012
...		

5. メンテナンスモードのステータスを確認します。

```
~% kubectl astrads maintenance list
```

対応：

NAME	NODE NAME	IN MAINTENANCE	MAINTENANCE STATE	
MAINTENANCE VARIANT				
node4	nhcitjj1525	true	ReadyForMaintenance	Node

保守モードの場合は 'false' として起動し 'true' に変更します「保守状態」が「準備期間の保守」から「ReadyforMaintenance」に変更されます。

6. ノードのメンテナンスが完了したら、メンテナンスモードを無効にします。

```
~% kubectl astrads maintenance update maint1 --node-name="nhcitjj1525"
--variant=None
```

7. ノードが保守モードでなくなったことを確認します。

```
~% kubectl astrads maintenance list
```

ノードを交換

クラスタ内の障害が発生したノードを交換するには、kubectl コマンドを Astra Data Store preview とともに使用します。

手順

1. すべてのノードを一覧表示します。

```
~% kubectl astrads nodes list
```

対応：

NODE NAME	NODE STATUS	CLUSTER NAME
sti-rx2540-534d...	Added	cluster-multinodes-21209
sti-rx2540-535d...	Added	cluster-multinodes-21209
...		

2. クラスタについて説明します。


```
~% kubectl astrads clusters list
```

対応：

CLUSTER NAME	CLUSTER STATUS	NODE COUNT
cluster-multinodes-21209	created	4

3. 障害が発生したノードで 'Node HA' が 'false' としてマークされていることを確認します

```
~% kubectl describe astradscluster -n astrads-system
```

対応：

```
Name:          cluster-multinodes-21209
Namespace:     astrads-system
Labels:        <none>
Annotations:   kubectl.kubernetes.io/last-applied-configuration:

{"apiVersion":"astrads.netapp.io/v1alpha1","kind":"AstraDSCluster","meta
data":{"annotations":{},"name":"cluster-multinodes-21209","namespa...
API Version:   astrads.netapp.io/v1alpha1
Kind:          AstraDSCluster

State:         Disabled
Variant:       None
Node HA:       false
Node ID:       4
Node Is Reachable: false
Node Management IP: 172.21.192.192
Node Name:     sti-rx2540-532d.ct1.gdl.englab.netapp.com
Node Role:     Storage
Node UUID:     6f6b88f3-8411-56e5-b1f0-a8e8d0c946db
Node Version:  12.75.0.6167444
Status:        Added
```

4. 「AdsNode Count」の値を3に減らして、障害が発生したノードを削除するように astradscluster CR を変更します。

```
cat manifests/astradscluster.yaml
```

対応：

```

apiVersion: astrads.netapp.io/v1alpha1
kind: AstraDSCluster
metadata:
  name: cluster-multinodes-21209
  namespace: astrads-system
spec:
  # ADS Node Configuration per node settings
  adsNodeConfig:
    # Specify CPU limit for ADS components
    # Supported value: 9
    cpu: 9
    # Specify Memory Limit in GiB for ADS Components.
    # Your kubernetes worker nodes need to have at least this much RAM
    free
    # for ADS to function correctly
    # Supported value: 34
    memory: 34
    # [Optional] Specify raw storage consumption limit. The operator
    will only select drives for a node up to this limit
    capacity: 600
    # [Optional] Set a cache device if you do not want auto detection
    e.g. /dev/sdb
    # cacheDevice: ""
    # Set this regex filter to select drives for ADS cluster
    # drivesFilter: ".*"

    # [Optional] Specify node selector labels to select the nodes for
    creating ADS cluster
    # adsNodeSelector:
    #   matchLabels:
    #     customLabelKey: customLabelValue

    # Specify the number of nodes that should be used for creating ADS
    cluster
    adsNodeCount: 3

    # Specify the IP address of a floating management IP routable from any
    worker node in the cluster
    mvip: "172..."

    # Comma separated list of floating IP addresses routable from any host
    where you intend to mount a NetApp Volume
    # at least one per node must be specified
    # addresses: 10.0.0.1,10.0.0.2,10.0.0.3,10.0.0.4,10.0.0.5
    # netmask: 255.255.255.0
    adsDataNetworks:

```

```

- addresses: "172..."
  netmask: 255.255.252.0

# [Optional] Provide a k8s label key that defines which protection
domain a node belongs to
# adsProtectionDomainKey: ""

# [Optional] Provide a monitoring config to be used to setup/configure
a monitoring agent.
monitoringConfig:
  namespace: "netapp-monitoring"
  repo: "docker.repo.eng.netapp.com/global/astra"

autoSupportConfig:
  # AutoUpload defines the flag to enable or disable AutoSupport
  upload in the cluster (true/false)
  autoUpload: true
  # Enabled defines the flag to enable or disable automatic
  AutoSupport collection.
  # When set to false, periodic and event driven AutoSupport
  collection would be disabled.
  # It is still possible to trigger an AutoSupport manually while
  AutoSupport is disabled
  # enabled: true
  # CoredumpUpload defines the flag to enable or disable the upload of
  coredumps for this ADS Cluster
  # coredumpUpload: false
  # HistoryRetentionCount defines the number of local (not uploaded)
  AutoSupport Custom Resources to retain in the cluster before deletion
  historyRetentionCount: 25
  # DestinationURL defines the endpoint to transfer the AutoSupport
  bundle collection
  destinationURL: "https://testbed.netapp.com/put/AsupPut"
  # ProxyURL defines the URL of the proxy with port to be used for
  AutoSupport bundle transfer
  # proxyURL:
  # Periodic defines the config for periodic/scheduled AutoSupport
  objects
  periodic:
    # Schedule defines the Kubernetes Cronjob schedule
    - schedule: "0 0 * * *"
    # PeriodicConfig defines the fields needed to create the
    Periodic AutoSupports
    periodicconfig:
      - component:

```

```

        name: storage
        event: dailyMonitoring
        userMessage: Daily Monitoring Storage AutoSupport bundle
        nodes: all
- component:
    name: controlplane
    event: daily
    userMessage: Daily Control Plane AutoSupport bundle

```

5. ノードがクラスタから削除されたことを確認します。

```
~% kubectl get nodes --show-labels
```

対応：

NAME	STATUS	ROLES	AGE	VERSION
LABELS				
sti-astramaster-237	Ready	control-plane,master	24h	v1.20.0
sti-rx2540-532d	Ready	<none>	24h	v1.20.0
sti-rx2540-533d	Ready	<none>	24h	

```
~% kubectl astrads nodes list
```

対応：

NODE NAME	NODE STATUS	CLUSTER NAME
sti-rx2540-534d	Added	cluster-multinodes-21209
sti-rx2540-535d	Added	cluster-multinodes-21209
sti-rx2540-536d	Added	cluster-multinodes-21209

```
~% kubectl get nodes --show-labels
```

対応：

NAME	STATUS	ROLES	AGE	VERSION
LABELS				
sti-astramaster-237	Ready	control-plane,master	24h	v1.20.0
beta.kubernetes.io/arch=amd64,				
sti-rx2540-532d	Ready	<none>	24h	v1.20.0
astrads.netapp.io/node-removal				

```
~% kubectl describe astradscluster -n astrads-system
```

対応：

```
Name:          cluster-multinodes-21209
Namespace:     astrads-system
Labels:        <none>
Kind:          AstraDSCluster
Metadata:
...
```

6. クラスタ CR を変更して、交換用のノードをクラスタに追加します。ノード数は 4 に増えます。新しいノードが追加対象として選択されていることを確認します。

```
rvi manifests/astradscluster.yaml
cat manifests/astradscluster.yaml
apiVersion: astrads.netapp.io/v1alpha1
kind: AstraDSCluster
metadata:
  name: cluster-multinodes-21209
  namespace: astrads-system
```

```
~% kubectl apply -f manifests/astradscluster.yaml
```

対応：

```
astradscluster.astrads.netapp.io/cluster-multinodes-21209 configured
```

```
~% kubectl get pods -n astrads-system
```

対応：

NAME	READY	STATUS	RESTARTS	AGE
astrads-cluster-controller...	1/1	Running	1	24h
astrads-deployment-support...	3/3	Running	0	24h
astrads-ds-cluster-multinodes-21209	1/1	Running		

```
~% kubectl astrads nodes list
```

対応：

NODE NAME	NODE STATUS	CLUSTER NAME
sti-rx2540-534d...	Added	cluster-multinodes-21209
sti-rx2540-535d...	Added	cluster-multinodes-21209

```
~% kubectl astrads clusters list
```

対応：

CLUSTER NAME	CLUSTER STATUS	NODE COUNT
cluster-multinodes-21209	created	4

```
~% kubectl astrads drives list
```

対応：

DRIVE NAME	DRIVE ID	DRIVE STATUS	NODE NAME	CLUSTER NAME
scsi-36000...	c3e197f2...	Active	sti-rx2540...	cluster-multinodes-21209

ドライブを交換します

クラスタ内のドライブで障害が発生した場合は、データの整合性を確保するために、できるだけ早くドライブを交換する必要があります。ドライブで障害が発生すると、クラスタの CR ノードステータス、クラスタの健全性状態情報、および指標エンドポイントに、障害が発生したドライブの情報が表示されます。

nodeStatus.driveStatuses で障害が発生したドライブを示すクラスタの例

```
$ kubectl get adscl -A -o yaml
```

対応：

```
...
apiVersion: astrads.netapp.io/v1alpha1
kind: AstraDSCluster
...
nodeStatuses:
  - driveStatuses:
    - driveID: 31205e51-f592-59e3-b6ec-185fd25888fa
      driveName: scsi-36000c290ace209465271ed6b8589b494
      drivesStatus: Failed
    - driveID: 3b515b09-3e95-5d25-a583-bee531ff3f31
      driveName: scsi-36000c290ef2632627cb167a03b431a5f
      drivesStatus: Active
    - driveID: 0807fa06-35ce-5a46-9c25-f1669def8c8e
      driveName: scsi-36000c292c8fc037c9f7e97a49e3e2708
      drivesStatus: Active
  ...
```

障害が発生したドライブ CR は、障害が発生したドライブの UUID に対応する名前でクラスタ内に自動的に作成されます。

```
$ kubectl get adsfd -A -o yaml
```

対応：

```
...
apiVersion: astrads.netapp.io/v1alpha1
kind: AstraDSFailedDrive
metadata:
  name: c290a-5000-4652c-9b494
  namespace: astrads-system
spec:
  executeReplace: false
  replaceWith: ""
status:
  cluster: arda-6e4b4af
  failedDriveInfo:
    failureReason: AdminFailed
    inUse: false
    name: scsi-36000c290ace209465271ed6b8589b494
    path: /dev/disk/by-id/scsi-36000c290ace209465271ed6b8589b494
    present: true
    serial: 6000c290ace209465271ed6b8589b494
    node: sti-rx2540-300b.ctl.gdl.englab.netapp.com
  state: ReadyToReplace
```

```
~% kubectl astrads faileddrive list --cluster arda-6e4b4af
```

対応：

NAME	NODE	CLUSTER	STATE
AGE			
6000c290	sti-rx2540-300b.lab.netapp.com	ard-6e4b4af	ReadyToReplace
13m			

手順

1. 交換可能なドライブを 'kubectl astras show-replacements' コマンドで一覧表示しますこのコマンドは '交換の制限に適合するドライブをフィルタリングします (クラスタ内では未使用 'マウントなし' パーティションなし' または障害が発生したドライブ以上)

可能な交換用ドライブをフィルタリングせずにすべてのドライブを一覧表示するには '--all' を 'show-replacements' コマンドに追加します

```
~% kubectl astrads faileddrive show-replacements --cluster ard-6e4b4af
--name 6000c290
```

対応：

NAME	IDPATH	SERIAL	PARTITIONCOUNT	MOUNTED	SIZE
sdh	/scsi-36000c29417	45000c	0	false	100GB

2. パスしたシリアル番号でドライブを交換するには 'replace' コマンドを使用しますコマンドは置換を完了するか '--wait' 時間が経過すると失敗します

```
~% kubectl astrads faileddrive replace --cluster arda-6e4b4af --name
6000c290 --replaceWith 45000c --wait
Drive replacement completed successfully
```



kubectl の astrads faileddrive replace' が不適切なシリアル番号を使用して実行された場合、次のようなエラーが表示されます

```
~% kubectl astrads replacedrive replace --cluster astrads-cluster-
f51b10a --name 6000c2927 --replaceWith BAD_SERIAL_NUMBER
Drive 6000c2927 replacement started
Failed drive 6000c2927 has been set to use BAD_SERIAL_NUMBER as a
replacement
...
Drive replacement didn't complete within 25 seconds
Current status: {FailedDriveInfo:{InUse:false Present:true Name:scsi-
36000c2 FiretapUUID:444a5468 Serial:6000c Path:/scsi-36000c
FailureReason:AdminFailed Node:sti-b200-0214a.lab.netapp.com}
Cluster:astrads-cluster-f51b10a State:ReadyToReplace
Conditions:[{Message: "Replacement drive serial specified doesn't
exist", Reason: "DriveSelectionFailed", Status: False, Type:' Done']]}
```

3. ドライブ交換を再実行するには '前のコマンドで --force' を使用します

```
~% kubectl astrads replacedrive replace --cluster astrads-cluster-
f51b10a --name 6000c2927 --replaceWith VALID_SERIAL_NUMBER --force
```

を参照してください。

- ["kubectl コマンドを使用して Astra データストアのプレビューアセットを管理"](#)

Cloud Insights で指標を監視

Cloud Insights を使用して、Astra データストアのプレビュー指標を監視できます。

- [\[Complete Cloud Insights connection prerequisite tasks\]](#)

- [\[Acquisition Unit storage\]](#)
- [\[Download and run the installation script\]](#)
- [\[Edit the Cloud Insights connection\]](#)
- [\[Disconnect from Cloud Insights\]](#)

Cloud Insights に表示される Astra データストアプレビュー指標の例を次に示します。



を使用して、Astra データストアのプレビューで生成された指標のリストを表示することもできます [\[Open Metrics API help\]](#)。

Cloud Insights 接続の前提条件となる作業を完了する

Cloud Insights を使用して Astra データストアに接続する前に、次の作業を完了する必要があります。

- ["Astra Data Store Monitoring Operator をインストールします"](#) これは、Astra Data Store プレビューインストール手順の一部です。
- ["kubectl-astras バイナリをインストールします"](#) これは、Astra Data Store プレビューインストール手順の一部です。
- ["Cloud Insights アカウントを作成します"](#)。
- 'awk'、'curl'、'grep' および 'jq' の各コマンドが使用可能であることを確認します

次の情報を収集します。

- * Cloud Insights API アクセストークン *。各カテゴリに対する読み取り / 書き込み権限：Acquisition Unit、Data Collection、Data Ingestion、Log Ingestionこれは、読み取り / 書き込み処理、Acquisition Unit のセットアップ、およびデータの取り込みプロセスのセットアップに使用されます。
- * Kubernetes API サーバの IP アドレスとポート *。Astra データストアプレビュークラスタを監視するために使用します。

- * Kubernetes API トークン *。これは Kubernetes API を呼び出すために使用されます。
- * 永続ボリューム構成 *。永続ボリュームのプロビジョニング方法に関する情報。

Acquisition Unit のストレージ

Acquisition Unit には、インストールファイル、設定データ、およびログを格納するための永続ボリュームが 3 つ必要です。Monitoring Operator は、デフォルトのストレージクラスを使用して、永続的ボリューム要求を作成します。インストーラ・スクリプトの実行時に '-s' オプションを使用して '別のストレージ・クラス名を指定できます

Kubernetes クラスタにストレージプロビジョニングツール（NetApp Trident など）がない場合は、インストーラスクリプトの実行時に -r オプションを使用してローカルファイルシステムパスを提供できます。-r オプションが設定されている場合 'インストーラ・スクリプトは '指定されたディレクトリ内に 3 つの永続ボリュームを作成しますこのディレクトリには、150GB 以上の空きスペースが必要です。

インストールスクリプトをダウンロードして実行します

Cloud Insights では、Bash スクリプトを使用して Astra データストアのプレビュー監視を監視オペレータから有効にすることができます。インストールスクリプトは、Astra Data Store コレクタ、Telegraf エージェント、および Fluent ビットエージェントを備えた Acquisition Unit をインストールします。

Cloud Insights テナントのドメイン名と選択した Cloud Insights API アクセストークンは、ダウンロード時にインストーラスクリプトに組み込まれます。

その後、次のように指標が送信されます。

- Telegraf は指標を Cloud Insights データレイクに送信します。
- FLUENT ビットは、ログ取り込みサービスにログを送信します。

インストーラスクリプトのヘルプを表示します

インストーラスクリプトの完全なヘルプテキストを次に示します。

インストーラスクリプトのヘルプテキストを表示します。


```
./cloudinsights-ads-monitoring.sh -h
```

対応：

```
USAGE: cloudinsights-ads-monitoring.sh [OPTIONS]
Configure monitoring of Astra Data Store by Cloud Insights.
OPTIONS:
  -h                                Display this help message.
  -d ci_domain_name                 Cloud Insights tenant domain name.
  -i kubernetes_ip                  Kubernetes API server IP address.
  -k ci_api_key                     Cloud Insights API Access Token.
  -n namespace                      Namespace for monitoring components. (default:
netapp-monitoring)
  -p kubernetes_port                Kubernetes API server port. (default: 6443)
  -r root_pv_dir                    Create 3 Persistent Volumes in this directory
for the Acquisition Unit.
                                   Only specify this option if there is no Storage
Provisioner installed and the PVs do not already exist.
  -s storage_class                  Storage Class name for provisioning Acquisition
Unit PVs. If not specified, the default storage class will be used.
  -t kubernetes_token               Kubernetes API server token.
```

インストールスクリプトを実行します

1. Cloud Insights アカウントがない場合は作成します。
2. Cloud Insights にログインします。
3. Cloud Insights メニューから、**Admin>*Data Collector*** をクリックします。
4. 「* + Data Collector *」をクリックして、新しいコレクタを追加します。



5. 「* アストラデータストア *」 タイルをクリックします。
6. 正しい Cloud Insights API アクセストークンを選択するか、新しいトークンを作成します。
7. 指示に従って、インストーラスクリプトをダウンロードし、権限を更新し、スクリプトを実行します。

このスクリプトには、Cloud Insights テナントの URL と選択した Cloud Insights API アクセストークンが含まれています。



Select a Data Collector



Configure Collector



NetApp
Astra Data Store

Configure Collector

Configure Kubernetes Operator to monitor NetApp Astra Data Store (ADS).

What Operating System or Platform Are You Using?


Kubernetes

Select existing API Access Token or create a new one

default_ads_api_key1 (...d0gHof)

[+ API Access Token](#)

[Production Best Practices ?](#)

Configure Astra Data Store [Need Help?](#)

- 1

The commands *awk*, *curl*, *grep*, *jq*, *kubectl* and the *kubectl-astrads* plugin must be installed where the installer script is run. You will need the Kubernetes API server IP address and a Kubernetes API token to run this install script. See the documentation if you need help finding this information.
- 2

Copy Installer Script

☐ Reveal Installer Script

```
#!/usr/bin/env bash
SCRIPT='basename $0'

CI_DOMAIN_NAME="f49uaky.gstabler-ads.cloudinsights-dev.netapp.com"
CI_API_KEY="eyJraWQ1OiI5OTk5IiwidHlwIjoI5ldUIiwiaWxnIjoI5FMzODQifQ.eyJjcVhdG9yTG9naW41OiJhZG1pb2IiImRpc3BsYXl0YW1lIjoI5GVmYXVsdF9hZHNfYXBPX2tleTEgKG9uIGJlaGFsZiBvZiBhZG1pb2I"

```
- 3

Copy the above installer script and save it as *cloudinsights-ads-monitoring.sh*
- 4

Copy Permissions Command

☐ Reveal Permissions Command

```
chmod +x cloudinsights-ads-monitoring.sh

```
- 5

Paste the permissions command in a terminal to enable execute permissions on the installer script.
- 6

Copy Install Command

☐ Reveal Install Command

```
./cloudinsights-ads-monitoring.sh -i <KUBERNETES_IP> -t <KUBERNETES_TOKEN>

```
- 7

Paste the install command in a terminal, replace the placeholders with the correct values for your environment, and run the command. It will take several minutes to complete. The script will use the default namespace 'netapp-monitoring'. Additional options are available for customized environments. The default configuration for kubectl should point to the kubernetes cluster to be monitored.
- 8

Complete Setup

8. スクリプトが完了したら、[セットアップの完了]をクリックします。

インストールスクリプトが完了すると、「データソース」リストに「Astra Data Store」コレクタが表示されます。



エラーが原因でスクリプトが終了した場合は、エラーが解決してから再度実行できます。デフォルトの設定を使用しない環境では、Monitoring Operator 名前空間や Kubernetes API サーバポートなどの追加のパラメータがサポートされます。使い方とヘルプテキストを表示するには、cloudinsights-ads-monitoring.sh -h オプションを使用します。

設定が正常に完了すると、次のような出力が生成されます。

```
Configuring Cloud Insights monitoring for Astra Data Store . . .
Configuring monitoring namespace
...
Configuring output sink and Fluent Bit plugins
Configuring Telegraf plugins
Configuring Acquisition Unit
...
Acquisition Unit has been installed successfully.
Configuring Astra Data Store data collector
Astra Data Store collector data '<CLUSTER_NAME>' created
Configuration done!
```

エージェント CR の例

以下に、インストーラスクリプトの実行後の「Monitoring - NetApp」エージェントの CR の例を示します。

```
spec:
  au:
    isEnabled: true
    storageClassName: auto-sc
  cluster-name: meg-ads-21-22-29-30
  docker-repo: docker.repo.eng.netapp.com/global/astra
  fluent-bit:
  - name: ads-tail
    outputs:
    - sink: ADS_STDOUT
    substitutions:
    - key: TAG
      value: firetapems
    - key: LOG_FILE
      values:
      - /var/log/firetap/*/ems/ems
      - /var/log/firetap/ems/*/ems/ems
    - key: ADS_CLUSTER_NAME
      value: meg-ads-21-22-28-29-30
  - name: agent
  - name: ads-tail-ci
    outputs:
```

```

- sink: CI
substitutions:
- key: TAG
  value: netapp.ads
- key: LOG_FILE
  values:
  - /var/log/firetap/*/ems/ems
  - /var/log/firetap/ems/*/ems/ems
- key: ADS_CLUSTER_NAME
  value: meg-ads-21-22-28-29-30
output-sink:
- api-key: abcd
  domain-name: bz19ngz.gst-adsdemo.ci-dev.netapp.com
  name: CI
serviceAccount: sa-netapp-monitoring
telegraf:
- name: ads-open-metric
  outputs:
  - sink: CI
  run-mode:
  - ReplicaSet
  substitutions:
  - key: URLS
    values:
    - http://astrads-metrics-service.astrads-
system.svc.cluster.local:9341
  - key: METRIC_TYPE
    value: ads-metric
  - key: ADS_CATEGORY
    value: netapp_ads
  - key: ADS_CLUSTER_NAME
    value: meg-ads-21-22-28-29-30
- name: agent
status:
  au-pod-status: UP
  au-uuid: eddeccc6-3aa3-4dd2-a98c-220085fae6a9

```

Cloud Insights 接続を編集します

Kubernetes API トークンまたは Cloud Insights API アクセストークンはあとから編集できます。

- Kubernetes API トークンを更新する場合は、Cloud Insights UI から Astra データストアコレクタを編集する必要があります。
- テレメトリとログに使用される Cloud Insights API アクセストークンを更新する場合は、`kubectl` コマンドを使用して Monitoring Operator CR を編集する必要があります。

Kubernetes API トークンを更新します

1. Cloud Insights にログインします。
2. **[Admin>]** > **[* Data Collectors]** を選択して、**[Data Collectors]** ページにアクセスします。
3. Astra データストアクラスターのエントリを探します。
4. ページの右側にあるメニューをクリックし、「* 編集 *」を選択します。
5. Kubernetes API トークンフィールドを新しい値で更新します。
6. **[コレクタの保存*]** を選択します

Cloud Insights API アクセストークンを更新します

1. Cloud Insights にログインします。
2. **[Admin>*API Access*]** を選択し、**[*+API アクセストークン*]** をクリックして、新しい Cloud Insights API アクセストークンを作成します。
3. エージェント CR を編集します。

```
kubectl --namespace netapp-monitoring edit agent agent-monitoring-netapp
```

4. 「output-sink」セクションを探し、「ci」という名前のエントリを見つけます。
5. ラベル「api-key」の場合は、現在の値を新しい Cloud Insights API アクセストークンに置き換えます。

セクションは次のようになります。

```
output-sink:
  - api-key: <api key value>
    domain-name: <tenant url>
    name: CI
```

6. エディタウィンドウを保存して終了します。

モニタリングオペレータは、Tegraf ビットと Fluent ビットを更新して、新しい Cloud Insights API アクセストークンを使用します。

Cloud Insights から切断します

Cloud Insights から切断するには、最初に Cloud Insights UI から Astra データストアコレクタを削除する必要があります。これが完了したら、モニタリングオペレータから Acquisition Unit、Telegraf、および Fluent の各ビット設定を削除できます。

Astra Data Store プレビューコレクタを削除

1. Cloud Insights にログインします。
2. **[Admin>]** > **[* Data Collectors]** を選択して、**[Data Collectors]** ページにアクセスします。

3. Astra データストアクラスタのエントリを探します。
4. 画面の右側のメニューを選択し、「* 削除 *」を選択します。
5. 確認ページで * Delete * をクリックします。

Acquisition Unit、Telegraf、および Fluent ビットを削除します

1. エージェント CR を編集します。

```
kubectl --namespace netapp-monitoring edit agent agent-monitoring-netapp
```

2. 「au」セクションを探し、「IsEnabled」を「false」に設定します
3. 「FLUENT ビット」セクションを探し、「ADS テール CI」という名前のプラグインを削除します。プラグインがない場合は、「FLUENT - BIT」セクションを削除できます。
4. 「テレグラム」セクションを探し、「ads - オープンメトリック」という名前のプラグインを削除します。プラグインがない場合は、「テレグラム」セクションを削除できます。
5. 「output-sink」セクションを探し、「ci」という名前のシンクを取り外します。
6. エディタウィンドウを保存して終了します。

モニタリングオペレータが Telegraf および Fluent ビット設定を更新し、Acquisition Unit ポッドを削除します。

7. ストレージプロビジョニング担当者ではなく Acquisition Unit PVS にローカルディレクトリを使用した場合は、PVS を削除します。

```
kubectl delete pv au-lib au-log au-pv
```

次に、Acquisition Unit を実行していたノードの実際のディレクトリを削除します。

8. Acquisition Unit ポッドが削除されたら、Cloud Insights から Acquisition Unit を削除できます。
 - a. Cloud Insights メニューで、**Admin**>*Data Collector* を選択します。
 - b. [* Acquisition Units * (Acquisition Unit *)] タブをクリックします。
 - c. Acquisition Unit ポッドの横にあるメニューをクリックします。
 - d. 「* 削除」を選択します。

Monitoring Operator は、Telegraf および Fluent ビットの設定を更新し、Acquisition Unit を削除します。

Open Metrics API のヘルプを参照してください

Astra データストアプレビューから指標を収集するために使用できる API のリストを次に示します。

- 「help」行は指標を表します。
- 「type」行は、メトリックがゲージかカウンタかを示します。

```

# HELP astrads_cluster_capacity_logical_percent Percentage cluster logical
capacity that is used (0-100)
# TYPE astrads_cluster_capacity_logical_percent gauge
# HELP astrads_cluster_capacity_max_logical Max Logical capacity of the
cluster in bytes
# TYPE astrads_cluster_capacity_max_logical gauge
# HELP astrads_cluster_capacity_max_physical The sum of the space in the
cluster in bytes for storing data after provisioning efficiencies, data
reduction algorithms and replication schemes are applied
# TYPE astrads_cluster_capacity_max_physical gauge
# HELP astrads_cluster_capacity_ops The IO operations capacity of the
cluster
# TYPE astrads_cluster_capacity_ops gauge
# HELP astrads_cluster_capacity_physical_percent The percentage of cluster
physical capacity that is used (0-100)
# TYPE astrads_cluster_capacity_physical_percent gauge
# HELP astrads_cluster_capacity_used_logical The sum of the bytes of data
in all volumes in the cluster before provisioning efficiencies, data
reduction algorithms and replication schemes are applied
# TYPE astrads_cluster_capacity_used_logical gauge
# HELP astrads_cluster_capacity_used_physical Used Physical capacity of a
cluster in bytes
# TYPE astrads_cluster_capacity_used_physical gauge
# HELP astrads_cluster_other_latency The sum of the accumulated latency in
seconds for other IO operations of all the volumes in a cluster. Divide by
astrads_cluster_other_ops to get the average latency per other operation
# TYPE astrads_cluster_other_latency counter
# HELP astrads_cluster_other_ops The sum of the other IO operations of all
the volumes in a cluster
# TYPE astrads_cluster_other_ops counter
# HELP astrads_cluster_read_latency The sum of the accumulated latency in
seconds of read IO operations of all the volumes in a cluster. Divide by
astrads_cluster_read_ops to get the average latency per read operation
# TYPE astrads_cluster_read_latency counter
# HELP astrads_cluster_read_ops The sum of the read IO operations of all
the volumes in a cluster
# TYPE astrads_cluster_read_ops counter
# HELP astrads_cluster_read_throughput The sum of the read throughput of
all the volumes in a cluster in bytes
# TYPE astrads_cluster_read_throughput counter
# HELP astrads_cluster_storage_efficiency Efficacy of data reduction
technologies. (logical used / physical used)
# TYPE astrads_cluster_storage_efficiency gauge
# HELP astrads_cluster_total_latency The sum of the accumulated latency in
seconds of all IO operations of all the volumes in a cluster. Divide by
astrads_cluster_total_ops to get average latency per operation

```

```

# TYPE astrads_cluster_total_latency counter
# HELP astrads_cluster_total_ops The sum of the IO operations of all the
volumes in a cluster
# TYPE astrads_cluster_total_ops counter
# HELP astrads_cluster_total_throughput The sum of the read and write
throughput of all the volumes in a cluster in bytes
# TYPE astrads_cluster_total_throughput counter
# HELP astrads_cluster_utilization_factor The ratio of the current cluster
IO operations based on recent IO sizes to the cluster iops capacity. (0.0
- 1.0)
# TYPE astrads_cluster_utilization_factor gauge
# HELP astrads_cluster_volume_used The sum of used capacity of all the
volumes in a cluster in bytes
# TYPE astrads_cluster_volume_used gauge
# HELP astrads_cluster_write_latency The sum of the accumulated latency in
seconds of write IO operations of all the volumes in a cluster. Divide by
astrads_cluster_write_ops to get the average latency per write operation
# TYPE astrads_cluster_write_latency counter
# HELP astrads_cluster_write_ops The sum of the write IO operations of all
the volumes in a cluster
# TYPE astrads_cluster_write_ops counter
# HELP astrads_cluster_write_throughput The sum of the write throughput of
all the volumes in a cluster in bytes
# TYPE astrads_cluster_write_throughput counter
# HELP astrads_disk_base_seconds Base for busy, pending and queued.
Seconds since collection began
# TYPE astrads_disk_base_seconds counter
# HELP astrads_disk_busy Seconds the disk was busy. 100 *
(astrads_disk_busy / astrads_disk_base_seconds) = percent busy (0-100)
# TYPE astrads_disk_busy counter
# HELP astrads_disk_capacity Raw Capacity of a disk in bytes
# TYPE astrads_disk_capacity gauge
# HELP astrads_disk_io_pending Summation of the count of pending io
operations for a disk times time. Divide by astrads_disk_base_seconds to
get the average pending operation count
# TYPE astrads_disk_io_pending counter
# HELP astrads_disk_io_queued Summation of the count of queued io
operations for a disk times time. Divide by astrads_disk_base_seconds to
get the average queued operations count
# TYPE astrads_disk_io_queued counter
# HELP astrads_disk_read_latency Total accumulated latency in seconds for
disk reads. Divide by astrads_disk_read_ops to get the average latency per
read operation
# TYPE astrads_disk_read_latency counter
# HELP astrads_disk_read_ops Total number of read operations for a disk
# TYPE astrads_disk_read_ops counter

```

```

# HELP astrads_disk_read_throughput Total bytes read from a disk
# TYPE astrads_disk_read_throughput counter
# HELP astrads_disk_write_latency Total accumulated latency in seconds for
disk writes. Divide by astrads_disk_write_ops to get the average latency
per write operation
# TYPE astrads_disk_write_latency counter
# HELP astrads_disk_write_ops Total number of write operations for a disk
# TYPE astrads_disk_write_ops counter
# HELP astrads_disk_write_throughput Total bytes written to a disk
# TYPE astrads_disk_write_throughput counter
# HELP astrads_value_scrape_duration Duration to scrape values
# TYPE astrads_value_scrape_duration gauge
# HELP astrads_volume_capacity_available The minimum of the available
capacity of a volume and the available capacity of the cluster in bytes
# TYPE astrads_volume_capacity_available gauge
# HELP astrads_volume_capacity_available_logical Logical available
capacity of a volume in bytes
# TYPE astrads_volume_capacity_available_logical gauge
# HELP astrads_volume_capacity_percent Percentage of volume capacity
available (0-100). (capacity available / provisioned) * 100
# TYPE astrads_volume_capacity_percent gauge
# HELP astrads_volume_capacity_provisioned Provisioned capacity of a
volume in bytes after setting aside the snapshot reserve. (size - snapshot
reserve = provisioned)
# TYPE astrads_volume_capacity_provisioned gauge
# HELP astrads_volume_capacity_size Total capacity of a volume in bytes
# TYPE astrads_volume_capacity_size gauge
# HELP astrads_volume_capacity_snapshot_reserve_percent Snapshot reserve
percentage of a volume (0-100)
# TYPE astrads_volume_capacity_snapshot_reserve_percent gauge
# HELP astrads_volume_capacity_snapshot_used The amount of volume snapshot
data that is not in the active file system in bytes
# TYPE astrads_volume_capacity_snapshot_used gauge
# HELP astrads_volume_capacity_used Used capacity of a volume in bytes.
This is bytes in the active filesystem unless snapshots are consuming more
than the snapshot reserve. (bytes in the active file system + MAX(0,
snapshot_used-(snapshot_reserve_percent/100*size))
# TYPE astrads_volume_capacity_used gauge
# HELP astrads_volume_other_latency Total accumulated latency in seconds
for operations on a volume that are neither read or write. Divide by
astrads_volume_other_ops to get the average latency per other operation
# TYPE astrads_volume_other_latency counter
# HELP astrads_volume_other_ops Total number of operations for a volume
that are neither read or write
# TYPE astrads_volume_other_ops counter
# HELP astrads_volume_read_latency Total accumulated read latency in

```

```
seconds for a volume. Divide by astrads_volume_read_ops to get the average
latency per read operation
# TYPE astrads_volume_read_latency counter
# HELP astrads_volume_read_ops Total number of read operations for a
volume
# TYPE astrads_volume_read_ops counter
# HELP astrads_volume_read_throughput Total read throughput for a volume
in bytes
# TYPE astrads_volume_read_throughput counter
# HELP astrads_volume_total_latency Total accumulated latency in seconds
for all operations on a volume. Divide by astrads_volume_total_ops to get
the average latency per operation
# TYPE astrads_volume_total_latency counter
# HELP astrads_volume_total_ops Total number of operations for a volume
# TYPE astrads_volume_total_ops counter
# HELP astrads_volume_total_throughput Total throughput for a volume in
bytes
# TYPE astrads_volume_total_throughput counter
# HELP astrads_volume_write_latency Total accumulated write latency in
seconds for volume. Divide by astrads_volume_write_ops to get the average
latency per write operation
# TYPE astrads_volume_write_latency counter
# HELP astrads_volume_write_ops Total number of write operations for a
volume
# TYPE astrads_volume_write_ops counter
# HELP astrads_volume_write_throughput Total write throughput for a volume
in bytes
# TYPE astrads_volume_write_throughput counter
```

Prometheus と Grafana で指標を監視します

Prometheus と Grafana を使用して、Astra データストアのプレビュー指標を監視できます。Prometheus で Astra Data Store プレビュー Kubernetes クラスタ指標エンドポイントから指標を収集するように設定でき、Grafana を使用して指標データを表示できます。

必要なもの

- Prometheus パッケージと Grafana パッケージを Astra Data Store プレビュークラスタ、または Astra Data Store プレビュークラスタと通信可能な別のクラスタでダウンロードしてインストールしておく必要があります。公式ドキュメントの指示に従って、各ツールをインストールします。
 - ["Prometheus をインストールする"](#)
 - ["Grafana をインストールします"](#)
- Prometheus と Grafana が Astra データストアプレビュー Kubernetes クラスタと通信できる必要があります。Prometheus と Grafana が Astra Data Store プレビュークラスタにインストールされていない場合は、Astra Data Store プレビュークラスタで実行されている指標サービスと通信できることを確認する必要があります。

Prometheus を設定する

Astra Data Store プレビューでは、Kubernetes クラスタの TCP ポート 9341 で指標サービスが公開されます。このサービスから指標を収集するには、Prometheus を設定する必要があります。

手順

1. Prometheus インストール用の「prometheus.yml」構成ファイルを編集します。
2. Astra Data Store プレビューサービス名とそのポートを指すサービス目標を追加します。例：

```
scrape_configs:
static_configs:
- targets: ['astrads-metrics-service.astrads-system:9341']
```

3. Prometheus サービスを開始します。

Grafana を設定します

Prometheus で収集された指標を表示するように Grafana を設定できます。

手順

1. Grafana インストールの「datasources.yaml」設定ファイルを編集します。
2. Prometheus をデータソースとして追加します。例：

```
apiVersion: 1

datasources:
- name: astradatastore-prometheus
  type: prometheus
  access: proxy
  url: http://localhost:9090
  jsonData:
    manageAlerts: false
```

3. Grafana サービスを開始します。
4. Grafana のマニュアルに記載されている手順に従ってください ["始めましょう"](#)。

Grafana ダッシュボードテンプレートをインポートします

Astra Data Store Preview をインストールするためにダウンロードしたバンドルファイルには、Grafana からインポートできる Grafana ダッシュボードテンプレートファイルが含まれています。このダッシュボードテンプレートを使用すると、Astra データストアのプレビューで確認できる指標の種類とその表示方法を確認できます。

手順

1. Astra Data Store プレビューの tar.gz' バンドルを開きます
2. 'マニフェスト'ディレクトリを開きます
3. 「 graafana _cluster.json 」 ファイルと「 graafana _volume.json 」 ファイルを展開します。
4. Grafana Web UI の使用、 ["でのダッシュボードテンプレートファイルを Grafana にインポートします"](#)。

イベントログを設定して監視する

Event Management System （ EMS ； イベント管理システム） ログを監視するには、次の高度なタスクを実行します。

- [\[Configure monitoring in the Astra Data Store preview cluster custom resource \(CR\)\]](#)
- [\[Set up Cloud Insights\]](#)
- [\[Stream event logs to Elastic\]](#)。

Astra データストアプレビュークラスタカスタムリソース（ CR ）で監視を設定する

Astra Data Store プレビュークラスタ CR でモニタリングオプションが設定されていない場合は、「 astras 」拡張機能を使用して設定できます。

入力するコマンド

```
~% kubectl astrads monitoring setup -n <NAMESPACE OF AGENT INSTALLED>
-r <DOCKER REPO TO FIND FLUENT/TELEGRAF ETC IMAGES>
```

ここで、

- インストールされているエージェントのネームスペース： Monitoring Agent のネームスペースを入力します。この名前は、 Monitoring Operator のデフォルトの名前である NetApp CR になります。
- -r は 'Fluent イメージまたは Telegraf イメージが置かれている Docker レジストリをセットアップするためのオプションですデフォルトでは ' パスは docker.repo.eng.netapp.com/global/astra` に設定されていますこのパスは変更できます

Cloud Insights をセットアップする

ログを表示するには Cloud Insights の設定は任意ですが、 Cloud Insights を使用してデータを表示すると便利です。を参照してください ["NetApp Cloud Insights のセットアップ方法"](#) Astra データストアプレビュー版で使用できます。

イベントログを Elastic にストリーミングする

EMS イベントやその他のポッドログを Elastic などのサードパーティのエンドポイントにストリーミングするには、「 astrads 」拡張機能を使用します。

入力するコマンド

```
~% kubectl astrads monitoring --host <ELASTIC HOST NAME> --port <ELASTIC HOST PORT> es
```



Elastic ホスト名は IP アドレスでもかまいません。

Astra Control Center with Astra のデータストアプレビューを使用

Astra Control Center のユーザーインターフェース（UI）を使用して、Astra データストアのプレビュータスクを実行できます。

Astra Control Center for Astra のデータストアプレビューのセットアップ

Astra Data Store プレビュー用の Astra Control Center UI を使用するには、次のタスクを実行する必要があります。

- ["Astra データストアを実行している、基盤となる Kubernetes クラスタを Astra Control Center に追加します"](#)。
- ["Astra データストアのプレビューをストレージバックエンドとして Astra Control Center に追加"](#)。



ストレージバックエンドを追加し、Astra データストアプレビューを含む Kubernetes クラスタがない場合は、最初にクラスタを追加する必要があります。

Astra Control Center でできること

Astra Control Center for Astra Data Store プレビューをセットアップしたら、Astra Control Center UI を使用して次のタスクを実行できます。

- ["Astra Control Center を使用して、Astra データストアのプレビュー資産の健全性を監視"](#)。
- ["Astra データストアのプレビューバックエンドストレージを管理"](#)。
- ["ノード、ディスク、永続的ボリューム要求（PVC）を監視"](#)。

を参照してください。

- ["Astra ファミリーの紹介"](#)
- ["Astra Control Center のドキュメント"](#)
- ["Astra Control API の略"](#)

Astra データストアプレビューを自動スクリプトでアンインストールします

Astra データストアのプレビューとコントロールプレーンをアンインストールするには、ワークロード、バインド、ボリューム、エクスポートポリシー、Astra データストアクラスタ、ライセンス、導入環境、および

Astra データストアのプレビューネームスペースを削除します。

または、を使用することもできます ["スクリプトを使用せずに Astra データストアプレビューをアンインストールする"](#)。

必要なもの

- root 管理権限

Astra Data Store プレビューアンインストールプロセスでは、次の手順が簡単に実行できます。

- [\[Remove existing workloads and bindings\]](#)
- [\[Uninstall Astra Data Store cluster\]](#)
- [\[Validate the removal of the astrads-system namespace\]](#)
- [\[Ensure containers are not running on worker nodes\]](#)
- [\[Delete OpenShift Container Platform resources\]](#)
- [\[Troubleshoot the Astra Data Store preview uninstall process\]](#)

既存のワークロードとバインドを削除します

Astra データストアプレビューをアンインストールする前に、次の項目を削除する必要があります

- ストレージバックエンドとして Astra データストアプレビューを使用するすべてのアプリケーションワークロード
- バックエンドとして Astra データストアプレビューを使用する Trident バインディング

これにより、Kubernetes 環境をクリーンな状態のまま維持できます。これは、を再インストールする場合に重要です。

Astra データストアクラスタをアンインストールします

Astra Data Store プレビューをアンインストールするには、ネットアップサポートサイトからダウンロードした Astra Data Store tar ファイルで「uninstall.sh」スクリプトを使用します。

1. 'マニフェスト' ディレクトリの 'uninstall.sh' を探します
2. 次の「sed」コマンドを実行します。

```
sed -i -e 's~netappdsoperator.yaml~astradsoperator.yaml~' uninstall.sh
```

3. 次のスクリプトを実行して、アンインストールする項目を指定します。

```
./uninstall.sh
```

You must run this script with an argument specifying what should be uninstalled

To uninstall the ADS cluster run `./uninstall.sh cluster`

To uninstall everything run `./uninstall all`

4. クラスタのみをアンインストールする場合は、「`uninstall.sh <cluster>`」と入力します

それ以外の場合は、すべてをアンインストールするには、「`uninstall.sh`」と入力します



ほとんどの場合、すべてをアンインストールします。その後クラスタを再導入する場合は、クラスタだけをアンインストールすることもできます。

5. プロンプトで続行することを確認し、「`erasedata`」と入力します

対応：

```
./uninstall.sh all
```

```
Enter 'erasedata' to confirm you want proceed with the uninstall:
```

```
erasedata
```

```
+-----+
| Wed Feb  2 10:14:01 EST 2022          |
| ADS cluster uninstall started         |
+-----+
```

```
Deleting astradsvolumes
Deleted astradsvolumes
Deleting astradsexportpolicies
Deleted astradsexportpolicies
Deleting astradsvolumesnapshots
Deleted astradsvolumesnapshots
Deleting astradsclusters
Deleting astradsclusters
Deleting astradslicenses
Deleted astradslicenses
```

```
+-----+
| Wed Feb  2 10:15:18 EST 2022          |
| ADS cluster uninstall done            |
+-----+
```

```
+-----+
| Wed Feb  2 10:15:18 EST 2022          |
| ADS system uninstall started          |
+-----+
```

```

+-----+
Removing astradsversion
astradsversion.astrads.netapp.io "astradsversion" deleted
Removed astradsversion
Removing daemonsets
daemonset.apps "astrads-ds-nodeinfo-astradsversion" deleted
Removed daemonsets
Removing deployments
deployment.apps "astrads-cluster-controller" deleted
deployment.apps "astrads-license-controller" deleted
deployment.apps "astrads-operator" deleted
Removed deployments
Removing all other AstraDS resources
namespace "astrads-system" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsautosupports.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradscLOUDsnapshots.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsclusters.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsexportpolicies.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsfaileddrives.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradslICENSES.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsnfsOPTIONS.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsnodeinfoes.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsnodemANAGEMENTS.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsqospolicies.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsversions.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsvOLUMEFILES.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsvOLUMES.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsvOLUMESnapshots.astrads.netapp.io" deleted
role.rbac.authorization.k8s.io "astrads-astrads-system-admin-role"
deleted
role.rbac.authorization.k8s.io "astrads-astrads-system-reader-role"
deleted

```

```
role.rbac.authorization.k8s.io "astrads-astrads-system-writer-role"
deleted
role.rbac.authorization.k8s.io "astrads-leader-election-role" deleted
role.rbac.authorization.k8s.io "astrads-manager-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astrads-admin-
clusterrole" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astrads-reader-
clusterrole" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astrads-writer-
clusterrole" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsautosupport-
editor-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsautosupport-
viewer-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradscloudsnapshot-
editor-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradscloudsnapshot-
viewer-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradscluster-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradscluster-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsexportpolicy-
editor-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsexportpolicy-
viewer-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsfaileddrive-
editor-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsfaileddrive-
viewer-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradslicense-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradslicense-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsnfsoption-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsnfsoption-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsnodeinfo-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsnodeinfo-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsnodemanagement-
editor-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsnodemanagement-
viewer-role" deleted
```

```

clusterrole.rbac.authorization.k8s.io "astrads-astradsqospolicy-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsversion-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsversion-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsvolume-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsvolume-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsvolumefile-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsvolumefile-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsvolumesnapshot-
editor-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsvolumesnapshot-
viewer-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-manager-role" deleted
rolebinding.rbac.authorization.k8s.io "astrads-astrads-admin-
rolebinding" deleted
rolebinding.rbac.authorization.k8s.io "astrads-astrads-reader-
rolebinding" deleted
rolebinding.rbac.authorization.k8s.io "astrads-astrads-writer-
rolebinding" deleted
rolebinding.rbac.authorization.k8s.io "astrads-leader-election-
rolebinding" deleted
rolebinding.rbac.authorization.k8s.io "astrads-manager-rolebinding"
deleted
clusterrolebinding.rbac.authorization.k8s.io "astrads-astrads-admin-
rolebinding" deleted
clusterrolebinding.rbac.authorization.k8s.io "astrads-astrads-reader-
rolebinding" deleted
clusterrolebinding.rbac.authorization.k8s.io "astrads-astrads-writer-
rolebinding" deleted
clusterrolebinding.rbac.authorization.k8s.io "astrads-manager-
rolebinding" deleted
configmap "astrads-autosupport-cm" deleted
configmap "astrads-firetap-cm" deleted
configmap "astrads-kevents-asup" deleted
configmap "astrads-metrics-cm" deleted
secret "astrads-autosupport-certs" deleted
+-----+
| Wed Feb  2 10:16:36 EST 2022                |
| ADS system uninstall done                    |
+-----+

```

astrs-system 名前空間の削除を検証します

次のコマンドで結果が返されないことを確認します。

```
kubect1 get ns | grep astrads-system
```

ワーカーノードでコンテナが実行されていないことを確認します

'FIRETAAP' や 'netwd' などのコンテナがワーカー・ノードで実行されていないことを確認します各ノードで次のコマンドを実行します。

```
ssh <mynode1>  
# runc list
```

OpenShift Container Platform リソースを削除します

Red Hat OpenShift Container Platform (OCP) に Astra Data Store preview をインストールした場合は、OCP セキュリティコンテキスト制約 (SCC) と役割バインディングリソースをアンインストールできます。

OpenShift では、セキュリティコンテキスト制約 (SCC) を使用して、ポッドで実行できるアクションを制御します。

標準のアンインストールプロセスが完了したら、次の手順を実行します。

1. SCC リソースを削除します。

```
oc delete -f ads_privileged_scc.yaml
```

2. ロールバインドリソースを削除します

```
oc delete -f oc_role_bindings.yaml
```



これらの手順で「resources not found」エラーを無視します。

3. すべての Kubernetes ノードから /var/lib/kubebelet/config.yaml を削除します

Astra データストアプレビューアンインストールプロセスのトラブルシューティングを行う

Kubernetes v1.20 の Astra データストアプレビューアンインストールプロセスでは、原因 ポッドが終了状態のまま残ることがあります。

この問題が発生した場合は、次のコマンドを実行して、'astrs-system' 名前空間内のすべてのポッドを強制的

に削除します。

```
kubectl delete pods --all -n astrads-system --force --grace-period 0
```

スクリプトを使用せずに **Astra** データストアプレビューをアンインストールする

自動スクリプトを使用せずに Astra Data Store プレビューを手動でアンインストールするには、ワークロード、バインド、ボリューム、エクスポートポリシー、クラスタ、ライセンス、導入環境、Astra データストアプレビューネームスペース。

または、を使用することもできます ["Astra データストアプレビューをスクリプトでアンインストールします"](#)。

必要なもの

- root 管理権限

Astra Data Store プレビューアンインストールプロセスでは、次の手順が簡単に実行できます。

- [\[Remove existing workloads and bindings\]](#)
- [\[Uninstall the Astra Data Store preview cluster and control plane\]](#)
- [\[Delete the license\]](#)
- [\[Delete the Astra Data Store preview installation\]](#)
- [\[Validate the removal of the astrads-system namespace\]](#)
- [\[Ensure containers are not running on worker nodes\]](#)
- [\[Delete OpenShift Container Platform resources\]](#)
- [\[Troubleshoot the Astra Data Store preview uninstall process\]](#)

既存のワークロードとバインドを削除します

Astra データストアプレビューをアンインストールする前に、次の項目を削除する必要があります

- ストレージバックエンドとして Astra データストアプレビューを使用するすべてのアプリケーションワークロード
- バックエンドとして Astra データストアプレビューを使用する Trident バインディング

これにより、Kubernetes 環境をクリーンな状態のまま維持できます。これは、を再インストールする場合に重要です。

Astra データストアプレビュークラスタとコントロールプレーンをアンインストールします

Astra Data Store プレビューを手動でアンインストールするには、次の手順に従います。

ボリュームとエクスポートポリシーを削除します

クラスタを削除する前に、Astra データストアプレビューボリュームとエクスポートポリシーを削除する必要があります。



ボリュームとエクスポートポリシーを最初に削除しないと、Astra Data Store のプレビューボリュームオブジェクトが削除されるまで、クラスタの削除プロセスは一時停止します。クラスタの削除を開始する前に、それらの項目を削除の方が効率的です。

手順

1. ボリュームを削除します。

```
~% kubectl delete astradsvolumes --all -A
~% kubectl get astradsvolumes -A
```

2. エクスポートポリシーを削除します。

```
~% kubectl delete astradsexportpolicies --all -A
~% kubectl get astradsexportpolicies -A
```

Astra データストアプレビュークラスタを削除

クラスタを削除すると、Astra Data Store preview cluster object custom resource (CR) とクラスタを対象としたリソースのみが削除される。



オペレータ、nodeinfo ポッド、およびクラスタコントローラ (Kubernetes を対象としたリソース) は、クラスタを削除しても削除されません。

クラスタを削除すると、基盤となるオペレーティング・システムもノードからアンインストールされ、'FIRETAAP' および 'netwd' サービスが停止します。

アンインストーラが完了するまでに約 1 分かかります。次に、Astra データストアのプレビュー用リソースの削除が、クラスタを対象として開始します。

1. クラスタを削除します。

```
~% kubectl delete astradsclusters --all -A
~% kubectl get astradsclusters -A
```

ライセンスを削除します

1. クラスタ内の各ワーカー・ノードに SSH 接続し、ワーカー・ノードで 'FIRETAAP' または 'netwd' が実行されていないことを確認します。
2. Astra データストアプレビューライセンスを削除します。


```
~% kubectl delete astradslicenses --all -A
~% kubectl get astradslicenses -A
```

Astra データストアプレビューインストールを削除します

クラスタ内のコントローラ、演算子、ネームスペース、およびサポートポッドを削除します。

1. Astra Data Store プレビューインストールオブジェクトを削除します。

```
~% kubectl delete astradsversion astradsversion -n astrads-system
~% kubectl get astradsversion -n astrads-system
```

2. DemonSets データストアと Astra データストアのすべてのプレビューコントローラリソースを削除します。

```
~% kubectl delete ds --all -n astrads-system
~% kubectl get ds -n astrads-system

~% kubectl delete deployments --all -n astrads-system
~% kubectl get deployments -n astrads-system
```

3. 残りのアーティファクトと演算子 YAML ファイルを削除します。

```
~% kubectl delete -f ./manifests/astradsoperator.yaml
~% kubectl get pods -n astrads-system
```

astrs-system 名前空間の削除を検証します

次のコマンドで結果が返されないことを確認します。

```
~% kubectl get ns | grep astrads-system
```

ワーカーノードでコンテナが実行されていないことを確認します

'FIRETAAP' や 'netwd' などのコンテナがワーカー・ノードで実行されていないことを確認します各ノードで次のコマンドを実行します。

```
ssh <mynode1>
# runc list
```

OpenShift Container Platform リソースを削除します

Red Hat OpenShift Container Platform（OCP）に Astra Data Store preview をインストールした場合は、OCP セキュリティコンテキスト制約（SCC）と役割バインディングリソースをアンインストールできます。

OpenShift では、セキュリティコンテキスト制約（SCC）を使用して、ポッドで実行できるアクションを制御します。

標準のアンインストールプロセスが完了したら、次の手順を実行します。

1. SCC リソースを削除します。

```
oc delete -f ads_privileged_scc.yaml
```

2. ロールバインドリソースを削除します

```
oc delete -f oc_role_bindings.yaml
```



これらの手順で「resources not found errors」を無視します。

3. すべての Kubernetes ノードから /var/lib/kubelet/config.yaml を削除します

手動削除のサンプル

次に、手動アンインストールスクリプトの実行例を示します。

```
$ kubectl delete astradsvolumes --all -A
No resources found
$ kubectl delete astradsexportpolicies --all -A
No resources found
$ kubectl delete astradsclusters --all -A
astradscluster.astrads.netapp.io "astrads-sti-c6220-09-10-11-12" deleted

$ kubectl delete astradslicenses --all -A
astradslicense.astrads.netapp.io "e900000005" deleted

$ kubectl delete astradsdeployment astradsdeployment -n astrads-system
astradsdeployment.astrads.netapp.io "astradsdeployment" deleted

$ kubectl delete ds --all -n astrads-system
daemonset.apps "astrads-ds-astrads-sti-c6220-09-10-11-12" deleted
daemonset.apps "astrads-ds-nodeinfo-astradsdeployment" deleted
daemonset.apps "astrads-ds-support" deleted
```

```

$ kubectl delete deployments --all -n astrads-system
deployment.apps "astrads-cluster-controller" deleted
deployment.apps "astrads-deployment-support" deleted
deployment.apps "astrads-license-controller" deleted
deployment.apps "astrads-operator" deleted

$ kubectl delete -f ../../firetap/sds/manifests/netappsdsoperator.yaml
namespace "astrads-system" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsautosupports.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradscloudsnapshots.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsclusters.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsdeployments.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsexportpolicies.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsfaileddrives.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradslicenses.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsnfsoptions.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsnodeinfoes.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsqospolicies.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsvolumefiles.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsvolumes.astrads.netapp.io" deleted
customresourcedefinition.apiextensions.k8s.io
"astradsvolumesnapshots.astrads.netapp.io" deleted
role.rbac.authorization.k8s.io "astrads-leader-election-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradscloudsnapshot-
editor-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradscloudsnapshot-
viewer-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradscluster-editor-role"
deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradscluster-viewer-role"
deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradslicense-editor-role"
deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradslicense-viewer-role"

```

```

deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsvolume-editor-role"
deleted
clusterrole.rbac.authorization.k8s.io "astrads-astradsvolume-viewer-role"
deleted
clusterrole.rbac.authorization.k8s.io "astrads-autosupport-editor-role"
deleted
clusterrole.rbac.authorization.k8s.io "astrads-autosupport-viewer-role"
deleted
clusterrole.rbac.authorization.k8s.io "astrads-manager-role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-metrics-reader" deleted
clusterrole.rbac.authorization.k8s.io "astrads-netappexportpolicy-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-netappexportpolicy-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-netappsdsdeployment-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-netappsdsdeployment-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-netappsdsnfsoption-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-netappsdsnfsoption-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-netappsdsnodeinfo-editor-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-netappsdsnodeinfo-viewer-
role" deleted
clusterrole.rbac.authorization.k8s.io "astrads-proxy-role" deleted
rolebinding.rbac.authorization.k8s.io "astrads-leader-election-
rolebinding" deleted
clusterrolebinding.rbac.authorization.k8s.io "astrads-manager-rolebinding"
deleted
clusterrolebinding.rbac.authorization.k8s.io "astrads-proxy-rolebinding"
deleted
configmap "astrads-autosupport-cm" deleted
configmap "astrads-firetap-cm" deleted
configmap "astrads-fluent-bit-cm" deleted
configmap "astrads-kevents-asup" deleted
configmap "astrads-metrics-cm" deleted
service "astrads-operator-metrics-service" deleted
Error from server (NotFound): error when deleting
"/.../export/firetap/sds/manifests/netappsdsoperator.yaml":
deployments.apps "astrads-operator" not found

$ kubectl get ns | grep astrads-system

```

```
[root@sti-rx2540-535c ~]# runc list
```

ID	PID	STATUS	BUNDLE	CREATED	OWNER
----	-----	--------	--------	---------	-------

Astra データストアプレビューアンインストールプロセスのトラブルシューティングを行う

Kubernetes v1.20 の Astra データストアプレビューアンインストールプロセスでは、原因 ポッドが終了状態のまま残ることがあります。

この問題が発生した場合は、次のコマンドを実行して、'astrs-system' 名前空間内のすべてのポッドを強制的に削除します。

```
kubect1 delete pods --all -n astrads-system --force --grace-period 0
```

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.