



FAQ

Cloud Tiering

NetApp
February 12, 2024

This PDF was generated from <https://docs.netapp.com/us-en/cloud-tiering/faq.html> on February 12, 2024.
Always check docs.netapp.com for the latest.

Table of Contents

- Cloud Tiering technical FAQ 1
 - ONTAP 1
 - Object storage 1
 - NetApp Service Connector 2
 - Networking 3
 - Permissions 3

Cloud Tiering technical FAQ

This FAQ can help if you're just looking for a quick answer to a question.

ONTAP

The following questions relate to ONTAP.

What are the requirements for my ONTAP cluster?

It depends on where you tier the cold data. Refer to the following:

- [Preparing to tier inactive data to AWS S3](#)
- [Preparing to tier inactive data to Azure Blob storage](#)
- [Preparing to tier inactive data to Google Cloud Storage](#)
- [Preparing to tier inactive data to StorageGRID](#)

Does Cloud Tiering enable inactive data reporting?

Yes, Cloud Tiering enables inactive data reporting on each aggregate. This setting enables us to identify the amount of inactive data that can be tiered to low-cost object storage.

Can I tier data from NAS volumes and SAN volumes?

You can use Cloud Tiering to tier data from NAS volumes to the public cloud and from SAN volumes to a private cloud using StorageGRID.

What about Cloud Volumes ONTAP?

If you have Cloud Volumes ONTAP systems, you'll find them in the Cluster Dashboard so you see a full view of data tiering in your hybrid cloud infrastructure.

From the Cluster Dashboard, you can view tiering information similar to an on-prem ONTAP cluster: operational health, current savings, savings opportunities, details about volumes and aggregates, and more.

Cloud Volumes ONTAP systems are read-only from Cloud Tiering. You can't set up data tiering on Cloud Volumes ONTAP from Cloud Tiering. You'll still set up tiering the same way: from the working environment in Cloud Manager.

Object storage

The following questions relate to object storage.

Which object storage providers are supported?

Amazon S3, Azure Blob storage, Google Cloud Storage, and StorageGRID using the S3 protocol are supported.

Can I use my own bucket/container?

Yes, you can. When you set up data tiering, you have the choice to add a new bucket/container or to select an existing bucket/container.

Which public cloud regions are supported?

- [Supported AWS regions](#)
- [Supported Azure regions](#)
- [Supported Google Cloud regions](#)

Which S3 storage classes are supported?

Cloud Tiering supports data tiering to the *Standard*, *Standard-Infrequent Access*, *One Zone-IA*, or *Intelligent* storage class. See [Supported S3 storage classes](#) for more details.

Which Azure Blob access tiers are supported?

Cloud Tiering automatically uses the *Hot* access tier for your inactive data.

Which storage classes are supported for Google Cloud Storage?

Cloud Tiering uses the *Standard* storage class for inactive data.

Does Cloud Tiering use one object store for the entire cluster or one per aggregate?

One object store for the entire cluster.

Can I apply policies to my object store to move data around independent of tiering?

No, Cloud Tiering does not support object lifecycle management rules that move or delete data from object stores.

NetApp Service Connector

The following questions relate to the NetApp Service Connector.

What is the Service Connector?

The Service Connector is NetApp software that communicates with ONTAP clusters to discover information about active and inactive data, and to set up data tiering. For more details, see [How Cloud Tiering works](#).

Where can I run the Service Connector?

- When tiering cold data to S3, the Service Connector can reside in an AWS VPC or on your premises.
- When tiering cold data to Blob storage, the Service Connector must reside in an Azure VNet.
- When tiering cold data to Google Cloud Storage, the Service Connector must reside in a Google Cloud Platform VPC.

- When tiering cold data to StorageGRID, the Service Connector must reside on an on premises Linux host.

How do you name the instance/virtual machine for the Service Connector?

The name of the Service Connector is prefixed with "Service-connector."

Networking

The following questions relate to networking.

What are the networking requirements?

- The ONTAP cluster initiates an HTTPS connection over port 443 to your object storage provider.

ONTAP reads and writes data to and from object storage. The object storage never initiates, it just responds.

- For StorageGRID, the ONTAP cluster initiates an HTTPS connection over a user-specified port to StorageGRID (the port is configurable during tiering setup).
- The NetApp Service Connector needs an outbound HTTPS connection over port 443 to your ONTAP clusters, to the object store, and to the Cloud Tiering service.

For more details, see:

- [Preparing to tier inactive data to AWS S3](#)
- [Preparing to tier inactive data to Azure Blob storage](#)
- [Preparing to tier inactive data to Google Cloud Storage](#)
- [Preparing to tier inactive data to StorageGRID](#)

Permissions

The following questions relate to permissions.

What permissions are required in AWS?

Permissions are needed to install the Service Connector:

- [These permissions are required to deploy the Service Connector in an AWS VPC](#)
- [These permissions are required when you deploy the Service Connector on an on-premises Linux host](#)

A different set of permissions are required [to manage the S3 bucket](#).

What permissions are required in Azure?

Permissions are needed [to deploy the Service Connector in an Azure VNet](#).

During deployment, Cloud Tiering creates and assigns a role to the Service Connector that provides the required permissions so ONTAP can tier inactive data to Azure Blob storage.

What permissions are required in Google Cloud Platform?

- Permissions are needed for the GCP user who will deploy the Service Connector in GCP from Cloud Tiering.
- Permissions are needed for a service account that has storage access keys.
- Permissions are needed for a service account that you'll associate with the Service Connector VM instance.

For details, see [Preparing to tier inactive data to Google Cloud Storage](#).

What permissions are required for StorageGRID?

[S3 permissions are needed](#).

Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.