Single server load test with Login VSI

HCI

NetApp
October 20, 2020

This PDF was generated from https://docs.netapp.com/us-en/hci-solutions/hcvdivds_single_server_load_test_with_login_vsi.html on May 31, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Single server load test with Login VSI 1

Single server load test with Login VSI

The NetApp Virtual Desktop Service uses the Microsoft Remote Desktop Protocol to access virtual desktop sessions and applications, and the Login VSI tool determines the maximum number of users that can be hosted on a specific server model. Login VSI simulates user login at specific intervals and performs user operations like opening documents, reading and composing mails, working with Excel and PowerPoint, printing documents, compressing files, and taking random breaks. It then measures response times. User response time is low when server utilization is low and increases when more user sessions are added. Login VSI determines the baseline based on initial user login sessions and it reports the maximum user session when the user response exceeds 2 seconds from the baseline.

The following table contains the hardware used for this validation.

Model	Count	Description
NetApp HCI H610C	4	Three in a cluster for launchers, AD, DHCP, and so on. One server for load testing.
NetApp HCI H615C	1	2x24C Intel Xeon Gold 6282 @2.1GHz. 1.5TB RAM.

The following table contains the software used for this validation.

product	Description
NetApp VDS 5.4	Orchestration
VM Template Windows 2019 1809	Server OS for RDSH
Login VSI	4.1.32.1
VMware vSphere 6.7 Update 3	Hypervisor
VMware vCenter 6.7 Update 3f	VMware management tool

The Login VSI test results are as follows:

Model	VM configuration	Login VSI baseline	Login VSI Max
H610C	8 vCPU, 48GB RAM, 75GB disk, 8Q vGPU profile	799	178
H615C	12 vCPU, 128GB RAM, 75GB disk	763	272

Considering sub-NUMA boundaries and hyperthreading, the eight VMs chosen for VM testing and configuration depended on the cores available on the host.

We used 10 launcher VMs on the H610C, which used the RDP protocol to connect to the user session. The following figure depicts the Login VSI connection information.



The following figure displays the Login VSI response time versus the active sessions for the H610C.



The following figure displays the Login VSI response time versus the active sessions for the H615C.



The performance metrics from Cloud Insights during H615C Login VSI testing for vSphere host and VMs is shown in teh following figure.

Next: Management Portal

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.