DHCP を使用している環境で NetApp Deployment Engine にアクセスします

HCI

Michael Wallis, Aksel Davis
June 21, 2021

This PDF was generated from https://docs.netapp.com/ja-jp/hci/docs/task_nde_access_dhcp.html on July 01, 2021. Always check docs.netapp.com for the latest.

目次

DHCP を使用している環境で NetApp Deployment Engine にアクセスします 1

DHCP を使用している環境で NetApp Deployment Engine にアクセスします

IPv4 の設定を DHCP から自動的に取得するようにサーバを構成している環境では、いずれかのストレージノードの Bond1G インターフェイスに割り当てられた IPv4 アドレスを使用して NetApp Deployment Engine にアクセスできます。このストレージノードの IPv4 アドレスは USB メモリを使用して取得できます。NetApp Deployment Engine は、 DHCP から割り当てられた IPv4 アドレスを使用している他のコンピューティングノードとストレージノードを自動的に検出します。ネットワークに特別な要件がないかぎり、この方法は使用しないでください。

必要なもの

- 自分またはネットワーク管理者が、『セットアップガイド』ドキュメントのタスクを完了している。
- NetApp HCI ノードに物理的にアクセスできるようにしておきます。
- すべての NetApp HCI ノードの電源をオンにしておきます。
- NetApp HCI の管理ネットワークとストレージネットワークで DHCP を有効にしておきます。
- DHCP アドレスプールは、 NetApp HCI ノードごとに 2 つの IPv4 アドレスを格納するのに十分な大きさです。

> NetApp HCI を適切に導入するためには、環境内のすべてのノードの IPv4 アドレスを DHCP から取得したアドレスか自動で設定したアドレスのどちらかにする必要があります（ IPv4 アドレスの割り当て方法を混在させることはできません）。

DHCP をストレージネットワーク（ Bond10G インターフェイス）にのみ使用している場合は、リンクに記載されている手順を使用してください。 "DHCP を使用していない環境では、 NetApp Deployment Engine にアクセスします" NetApp Deployment Engine にアクセスします。

手順

1. ノードが IP アドレスを要求するまで数分待ちます。
2. ストレージノードを選択し、そのノードに USB メモリを挿入します。そのまま少なくとも 5 秒間待ちます。
3. USB スティックを取り外し、コンピュータに挿入します。
4. 'Re'DME.html' ファイルを開きますNetApp Deployment Engine のユーザインターフェイスが表示されます。

詳細については、こちらをご覧ください

- "NetApp HCI および NetApp Element のファームウェアとドライバのバージョン ソフトウェア"

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.