完全修飾ドメイン名 Web UI アクセスを設定します

HCI

Michael Wallis, Aksel Davis, Dave Bagwell
June 21, 2021

This PDF was generated from https://docs.netapp.com/ja-jp/hci/docs/task_nde_access_ui_fqdn.html on July 01, 2021. Always check docs.netapp.com for the latest.

目次

完全修飾ドメイン名 Web UI アクセスを設定します 1

完全修飾ドメイン名 Web UI アクセスを設定します

Element 12.2 以降を搭載した NetApp HCI では、 Fully Qualified Domain Name （ FQDN ；完全修飾ドメイン名）を使用してストレージクラスタの Web インターフェイスにアクセスできます。FQDN を使用して、 Element Web UI 、ノード UI 、管理ノード UI などの Web ユーザインターフェイスにアクセスする場合は、クラスタで使用される FQDN を特定するストレージクラスタ設定を最初に追加する必要があります。これにより、クラスタはログインセッションを適切にリダイレクトできるようになり、キー管理ツールやアイデンティティプロバイダなどの外部サービスとの統合が強化されて、多要素認証に対応できるようになります。

必要なもの

- この機能を使用するには、 Element 12.2 以降および管理サービスバージョン 2.15 以降が必要です。
- REST API を使用するには、バージョン 11.5 以降を実行する管理ノードを導入しておく必要があります。

手順

1. 環境で FQDN が解決されるように、 Element ストレージノードと管理ノードの DNS がネットワーク環境に対して正しく設定されていることを確認します。DNS を設定するには、ストレージノードのノード UI および管理ノードに移動し、 * Network Settings * > * Management Network * を選択します。
   a. ストレージ・ノードのノード単位の UI ： https://<storage_node_management_IP>:442`
   b. 管理ノード用のノード単位の UI ： https://<management_node_IP>:442`
2. Element API にアクセスし、「 CreateClusterInterfacePreference 」 API メソッドを使用して次のクラスタインターフェイス設定を作成し、設定値としてクラスタ MVIP FQDN を挿入します。
   - 名前 :「 mvip 」
   - Value ： < クラスタ MVIP の完全修飾ドメイン名 >

     たとえば、 FQDN は「 toragecluster.my.org`: 」です

```
https://<Cluster_MVIP>/json-rpc/12.2?method=CreateClusterInterfacePreference&name=mvip_fqdn&value=storagecluster.my.org
```

3. 管理ノードで REST API を使用して管理ノードの設定を変更します。
   a. 管理ノードの REST API UI にアクセスするには、管理ノードの IP アドレスに「 /mnode/2/」 を続けて入力します。例：

```
https://<management_node_IP>/mnode/2/
```

   b. 「 * Authorize * 」またはロックアイコンをクリックし、 Element クラスタのユーザ名とパスワードを入力します。
   c. クライアント ID を「 m node-client 」として入力します。

d. セッションを開始するには、 * Authorize * をクリックします。

e. ウィンドウを閉じます。

f. [*Get/settings] をクリックします。

g. [* 試してみてください *] をクリックします。

h. [* Execute] をクリックします。

i. プロキシが 'Use_proxy' では 'true' または 'false' で示されているように使用されているかどうかに注意してください

j. [* PUT / settings] をクリックします。

k. [* 試してみてください *] をクリックします。

l. 要求の本文領域で、管理ノードの FQDN を「 `m node_name 」パラメータの値として入力します。また 'use_proxy' パラメータにプロキシを使用するかどうかを指定します （ 前の手順の「 true 」または「 false 」 ）

```
{
  "mnode_fqdn": "mnode.my.org",
  "use_proxy": false
}
```

m. [* Execute] をクリックします。

詳細については、こちらをご覧ください

- "SolidFire および Element ドキュメントの CreateClusterInterfacePreference API 情報"
- "NetApp HCI のリソースページ"
- "SolidFire および Element ソフトウェアのドキュメント"

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.