(Consumer) Administration APIs

NetApp Keystone

Ciaran McNamara, David Peterson
October 29, 2020

This PDF was generated from https://docs.netapp.com/us-en/keystone/seapiref_@consumer@_administration_apis.html on June 11, 2021. Always check docs.netapp.com for the latest.

Table of Contents

(Consumer) Administration APIs 1

(Consumer) Administration APIs

The (consumer) administration APIs consist of methods that allow you to perform the following tasks:

- Sign in, set a password, and refresh an authentication token.
- Retrieve jobs and view job details.

  See Retrieve jobs and Retrieve a job-by-job ID.

- Retrieve regions.

  See Retrieve regions and Retrieve a region by name.

- Retrieve service levels.

  See Retrieve Service Levels and Retrieve Service Levels by Name.

- Work with subtenants.

  See:

  - Retrieve all subtenants
  - Retrieve a subtenant by ID
  - Modify a subtenant
  - Delete a subtenant by ID
- Work with subtenants.

  See:

  - Retrieve all tenants
  - Retrieve a tenant by ID
  - Create a tenant
  - Modify the tenant
  - Delete the tenant
- Retrieve users.

  Retrieve all users, Retrieve a user by ID, and Retrieve a user by user name.

- Retrieve zones.

  See Retrieve all zones and Retrieve a zone by name

The following table lists the consumer APIs documented in this section.

HTTP Method	Path	Description
`POST`	`/v2.1/auth/password`	Set the password for a user.

HTTP Method	Path	Description
`POST`	`/v2.1/auth/password`	Refresh authentication JWT.
`POST`	`/v2.1/auth/signin`	Sign in.
`GET`	`/v2.1/auth/regions`	Retrieve regions.
`GET`	`/v2.1/auth/regions/{name}`	Retrieve regions by name.
`GET`	`/v2.1/auth/zones`	Retrieve zones.
`GET`	`/v2.1/auth/zones/{name}`	Retrieve zones by name.
`GET`	`/v2.1/jobs/`	Retrieve jobs.
`GET`	`/v2.1/jobs/{id}`	Retrieve jobs by ID.

Reset user password

Use the method listed in the following table reset the user password.

HTTP Method	Path	Description	Parameters
`POST`	`/v2.1/auth/password`	Reset the password.	None

Required request body attributes: `username` (string), `new_password` (string)

Request body example:

```
{
  "username": "MyName",
  "old_password": "oldPassword",
  "new_password": "newPassword"
}
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "user": {
          "id": "5e61aa814559c20001df1a5f",
          "username": "MyName",
          "firstName": "MyFirstName",
          "lastName": "MySurname",
          "displayName": "CallMeMYF",
          "email": "user@example.com",
          "tenancies": [
            {
              "id": "5e5f1c4f253c820001877839",
              "name": "MyTenant",
              "code": "testtenantmh",
              "role": "user"
            }
          ]
        },
        "token":
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VybmFtZSI6Ik15TmFtZSIsImV4cCI6
MTU4MzgxNjg3MX0.ZuRXjDPVtc2pH-e9wqgmszVKCBYS2PLqux2YwQ5uoAM"
      }
    ]
  }
}
```


Refresh authentication token

Use the method listed in the following table to refresh the authentication token.

HTTP Method	Path	Description	Parameters
`POST`	`/v2.1/auth/refresh`	Refresh the authentication token.	None

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:


```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "user": {
          "id": "5d914547869caefed0f3a00c",
          "username": "myusername",
          "firstName": "myfirstname",
          "lastName": "",
          "displayName": "Myfirstname Mysurname",
          "email": "",
          "tenancies": [
            {
              "id": "5d914499869caefed0f39eee",
              "name": "MyOrg",
              "code": "myorg",
              "role": "admin"
            },
            {
              "id": "5d9417aa869caefed0f7b4f9",
              "name": "ABCsafe",
              "code": "abcsafe",
              "role": "admin"
            }
          ]
        },
        "token":
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VybmFtZSI6ImVsbGlvdCIsImV4cCI6
MTU4MzgxNzA2N30.FdKD3QhPoNdWdbMfZ0bzCMTHluIt6HNP311F482K9AY"
      }
    ]
  }
}
```

Sign in

Use the method listed in the following table to sign in.

HTTP Method	Path	Description	Parameters
`POST`	`/v2.1/auth/signin`	Log in as a user.	None

Required request body attributes: `username` (string), `new_password` (string)

Request body example:

```
{
  "username": "MyName",
  "password": "newPassword"
}
```

Response body example:

```
{
  "status": {
    "user_message": "Authentication succeeeded.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "user": {
          "id": "5e61aa814559c20001df1a5f",
          "username": "MyName",
          "firstName": "MyFirstName",
          "lastName": "MySurname",
          "displayName": "CallMeMYF",
          "email": "user@example.com",
          "tenancies": [
            {
              "id": "5e5f1c4f253c820001877839",
              "name": "MyTenant",
              "code": "testtenantmh",
              "role": "user"
            }
          ]
        },
        "token":
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VybmFtZSI6Ik15TmFtZSIsImV4cCI6
MTU4MzgxNzQwMH0._u_UyYrzg_RewF-9ClIGoKQhfZYWrixZYBrsj1kh1hI"
      }
    ]
  }
}
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.