File services APIs

NetApp Keystone

Reenu Jojo, Ciaran McNamara, David Peterson, Manini Mandal
June 10, 2021

This PDF was generated from https://docs.netapp.com/us-en/keystone/seapiref_file_services_apis.html on June 11, 2021. Always check docs.netapp.com for the latest.

Table of Contents

File services APIs 1
File Servers APIs 1
File Shares APIs 2

File services APIs

You can use File Services APIs to view and manage your file servers and file shares.

Before you create file shares, you have to create file servers to host them.

File Servers APIs

You can use File Servers APIs to view and manage your file servers. For more information on file servers, see Create a file server.

HTTP Verb	Path	Description	Mandatory parameters/Request body
`GET`	`/v2.1/file servers`	You can retrieve the details of all your file servers. Retrieves details of the file servers, such as file server ID, name, region, zone, tenant, and tags.	`offset`: The number of items to skip before starting to collect the result set. `limit`: The numbers of items to return.
`GET`	`/v2.1/file servers/{id}`	You can retrieve the details of a specific file server. Retrieves details of the file server, such as name, region, zone, tenant, and tags based on the entered ID.	`id`: The ID of the file server.
`POST`	`/v2.1/file servers`	You can create a file server. Add the values in the request body to create a file server with the specified parameters, such as name, subtenant ID, zone, subnet ID.	`name`: The name of the file server. `subtenant_id`: The ID of the subtenant. `zone`: The name of the zone. `subnet_id`: The ID of the subnet.
`POST`	`/v2.1/file servers/{id}/ tags`	You can create or replace tags for a file server. Add the ID of the file server and the values for the tags in the "key:value pair" format in the request body.	`id`: The ID of the file server.
`PUT`	`/v2.1/file servers/{id}`	You can modify any file server based on its ID. Add the ID of the file server, and the values that you want to modify in the request body, such as such as name, protocol, zone, region, and tags.	`id`: The ID of the file server.
`DELETE`	`/v2.1/file servers/{id}`	You can delete any file server by its ID.	`id`: The ID of the file server.

Before you delete a file server, you should delete all the file shares mapped to it.

After deleting CIFS-enabled file servers, the Active Directory computer object remains. Ask your Active Directory admin to manually remove the computer object for the deleted file server from Active Directory.

File Shares APIs

You can use File Shares APIs to view and manage your file shares. For more information on file shares, see Create a file share.

HTTP Verb	Path	Description	Mandatory parameters/Request body
`GET`	`/v2.1/file shares`	You can retrieve the details of all your file shares. Retrieves details of the file shares, such as ID, name, snapshot policy, protocols, file server IP, and tags.	`offset`: The number of items to skip before starting to collect the result set. `limit`: The numbers of items to return.
`GET`	`/v2.1/file shares/{id}`	You can retrieve the details of a specific file share. Retrieves details of the file share, such as such as ID, name, snapshot policy, protocols, file server IP, and tags based on the entered ID.	`id`: The ID of the file share.
`POST`	`/v2.1/file shares`	You can create a file share. Add the values in the request body to create a file share with the specified parameters, such as ID, name, snapshot policy, protocols, file server IP, and tags.	`name`: The name of the file share. `share_path`: The path of the file share. `fileserver_id`: The ID of the file server. `size_gb`: The size of the file share in GBs. `service_level`: The service level name applicable: Standard, Premium, Premium-Tiering, Extreme, or Extreme-Tiering. `protocol`: The protocol used to access the file share (NFS, CIFS, or multi-protocol). `security_style`: The security style (Unix or NTFS). `export_policy`: The export policy of the file share.

HTTP Verb	Path	Description	Mandatory parameters/Request body
POST	/v2.1/fileshares/{id}/snapshot/{name}	You can create a snapshot of a file share.	id: The ID of the file share. name: The name of the snapshot.
POST	/v2.1/fileshares/{id}/tags	You can create or replace tags for a file share. Add the ID of the file share and the values for the tags in the "key:value pair" format in the request body.	id: The ID of the file share.
PUT	/v2.1/fileshares/{id}	You can modify any file share based on its ID. Add the ID of the file server and the values that you want to modify in the request body, such as such as name, protocol, snapshot policy, backup policy, and tags.	id: The ID of the file share. name: The name of the file share. size_gb: The size of the file share in GBs. service_level: The service level name applicable: Standard, Premium, Premium-Tiering, Extreme, or Extreme-Tiering. protocol: The protocol used to access the file share (NFS, CIFS, or multi-protocol). export_policy: The export policy of the file share.
DELETE	/v2.1/fileshares/{id}	You can delete any file share by its ID.	id: The ID of the file share.
DELETE	/v2.1/fileshares/{id}/snapshot/{name}	You can delete any snapshot of a file share by the ID of the file share and the name of the snapshot.	id: The ID of the file share. name: The name of the snapshot.

For CIFS shares, adding a `$` character to the end of the share path will make it a hidden share, for example, `pathtomyhiddenshare$`.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.