Regions

NetApp Keystone

Ciaran McNamara, David Peterson
October 29, 2020

This PDF was generated from https://docs.netapp.com/us-en/keystone/seapiref_regions.html on June 11, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Regions 1

Regions

Use the methods listed in the following table to create, modify, and delete regions. For APIs that allow you to retrieve regions, see the (Consumer) Administration APIs.

HTTP Method	Path	Description
`GET`	`/v2.1/regions`	Get regions.
`GET`	`/v2.1/regions/{name}`	Get regions by name.
`POST`	`/v2.1/regions`	Create a new region.
`PUT`	`/v2.1/regions/{name}`	Modify the details of a region.
`DELETE`	`/v2.1/regions/{name}`	Delete a region.

Region attributes

The following table lists the region attributes.

Attribute	Type	Description
`id`	String	The unique identifier of the region.
`name`	String	The region name.
`description`	String	The description of the region.

Retrieve regions

Use the method listed in the following table to retrieve all regions or a subset of regions.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/regions`	Retrieve regions.	`offset` and `limit`– see Common Pagination

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "returned_records": 1,
    "total_records": 4,
    "sort_by": "created",
    "order_by": "desc",
    "offset": 0,
    "limit": 1,
    "records": [
      {
        "id": "5e7bf44daab46c00014ce77f",
        "name": "au-east8",
        "description": "This is the new region description",
        "zones": []
      }
    ]
  }
}
```


Retrieve a region by name

Use the method listed in the following table to retrieve a region by name.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/regions/{name}`	Retrieve a region by name.	`name (string)`: The region name.

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
{
  "status": {
    "user_message": "string",
    "verbose_message": "string",
    "code": "string"
  },
  "result": {
    "returned_records": 1,
    "records": [
      {
        "id": "5d2fb0fb4f47df00015274e3",
        "name": "au-east1",
        "description": "string",
        "zones": [
          "au-east1-a"
        ]
      }
    ]
  }
}
```

Create a region

Use the method listed in the following table to create a region.

HTTP Method	Path	Description	Parameters
`POST`	`/v2.1/regions`	Create a new region.	None

Required request body attributes: `name`

Request body example:

```
{
  "name": "MyRegionName",
  "description": "DescriptionOfMyRegion"
}
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. New resource created.",
    "verbose_message": "",
    "code": 201
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "id": "5e616f849b64790001fe9658",
        "name": "MyRegionName",
        "Description": "DescriptionOfMyRegion",
        "user_id": "5bbee380a2df7a04d43acaee",
        "created": "0001-01-01T00:00:00Z",
        "tags": null
      }
    ]
  }
}
```

Modify a region

Use the method listed in the following table to modify a region.

HTTP Method	Path	Description	Parameters
`PUT`	`/v2.1/regions/{name}`	Modify a region identified by name. You can change the name and description of the region.	`name (string)`: The name of the region.

Required request body attributes: `none`

Request body example:

```
{
  "name": "MyRegionName",
  "description": "NewDescriptionOfMyRegion"
}
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "id": "5e616f849b64790001fe9658",
        "name": "MyRegionName",
        "description": "NewDescriptionOfMyRegion",
        "zones": []
      }
    ]
  }
}
```

Delete a region

Use the method listed in the following table to delete a region.

HTTP Method	Path	Description	Parameters
`DELETE`	`/v2.1/regions{name}`	Delete a single region identified by name. All zones within a region must be deleted first.	`Name (string)`: The name of the region.

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
No content for succesful delete
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.