Service requests

NetApp Keystone

Ciaran McNamara, David Peterson
October 29, 2020

This PDF was generated from https://docs.netapp.com/us-en/keystone/seapiref_service_requests.html on June 11, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Service requests 1

Service requests

Use the methods listed in the following table to create and retrieve service requests.

HTTP Method	Path	Description
`GET`	`/v2.1/tenants/{tenant_id}/servicerequests`	Retrieve service requests.
`GET`	`/v2.1/tenants/{tenant_id}/servicerequests/{id}`	Retrieve a service request by ID.
`POST`	`/v2.1/tenants/{tenant_id}/servicerequests/`	Create a service request.
`GET`	`/v2.1/tenants/{tenant_id}/servicerequests/categories`	Retrieve service request categories.

Service request attributes

The following table lists the service request attributes.

Attribute	Type	Description
`Id`	String	An identifier for the service request. For example: `SRQ0035952014.`
`subject`	String	The subject of the service request.
`comment`	String	A comment on the service request
`category`	String	The category of the request: Backup, disaster recovery, technical, other, or subscription.
`priority`	String	The priority of the service request: very low, low, normal, high, or urgent.
`subscription`	String	The Zuora subscription number.
`commitment`	–	Subscription commitment details, including: • Service level (string): Service level: Standard, Premium, or Extreme. • New_commitment (integer): New total capacity required.
`zone`	String	The zone name.
`subtenant_id`	String	The subtenant identifier.
`storage_object_type`	String	Storage object type: File server or block store.

Attribute	Type	Description
`storage_object_id`	String	The identifier of the storage object. For example: `5d2fb0fb4f47df00015274e3`
`service_type`	String	The service type: File services, block storage, or object storage.

Retrieve service requests

Use the method listed in the following table to retrieve service request categories for the specified tenant.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/tenants/{tenant_id}/servicerequests`	Retrieve service requests.	`tenant_id`: (Optional) Return the service requests for the specified tenant. `offset` and `limit`– see Common Pagination

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "returned_records": 1,
    "total_records": 34,
    "sort_by": "created",
    "order_by": "desc",
    "offset": 6,
    "limit": 1,
    "records": [
      {
        "id": "SRQ0035952014",
        "subject": "DR Failover - fileserver",
        "description": "catgory:Disaster Recovery Failover \n   subtenant:
DefaultSubtenants2 \n  region: au-east2 \n zone: au-east2-a \n
fileserver: Demotsysserv1 \n tenant:MyOrg \n comments:comments",
        "priority": "Urgent",
        "status": "New",
        "createdDate": "2020-05-22T04:23:12+0000",
        "updatedDate": "2020-05-22T04:23:12+0000"
      }
    ]
  }
}
```


Retrieve a service request by ID

Use the method listed in the following table to retrieve a service request by service request ID.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/tenants/{tenant_id}/servicerequests/{id}`	Retrieve a service request by ID.	• `tenant_id`: Tenant ID • `id`: Service request IDFor example: SRQ0035952014

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:


```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "returned_records": 1,
    "records": [
      {
        "id": "SRQ0035952014",
        "subject": "DR Failover - fileserver",
        "description": "catgory:Disaster Recovery Failover \n   subtenant:
DefaultSubtenants2 \n  region: au-east2 \n zone: au-east2-a \n
fileserver: Demotsysserv1 \n tenant:MyOrg \n comments:comments",
        "priority": "Urgent",
        "status": "New",
        "createdDate": "2020-05-22T04:23:12+0000",
        "updatedDate": "2020-05-22T04:23:12+0000"
      }
    ]
  }
}
```


Create a service request

Use the method listed in the following table to create a service request.

HTTP Method	Path	Description	Parameters
`POST`	`/v2.1/tenants/{tenant_id}/servicerequests/categories`	Create a service request.	`tenant_id`: The tenant identifier.

Required request body attributes: the required attributes are dependent on the category of service request. The following table lists the request body attributes.

Category	Required
Subscription	`subscription` and `commitment`
Disaster recovery	`storage_object_type`, `subtenant_id`, and `storage_object_id`

Category	Required
Technical	`subtenant_id` and `service_type` If `service_type` is file services or block storage, zone is required.
Other	Zone

Request body example:

```
{
  "subject": "string",
  "comment": "string",
  "category": "subscription",
  "priority": "Normal",
  "subscription": "A-S00003969",
  "commitment": {
    "service_level": "standard",
    "new_commitment": 10
  },
  "zone": "au-east1-a",
  "subtenant_id": "5d2fb0fb4f47df00015274e3",
  "storage_object_type": "fileserver",
  "storage_object_id": "5d2fb0fb4f47df00015274e3",
  "service_type": "File Services"
}
```

Response body example:

```
{
  "status": {
    "user_message": "string",
    "verbose_message": "string",
    "code": "string"
  },
  "result": {
    "returned_records": 1,
    "records": [
      {
        "id": "string",
        "subject": "string",
        "description": "string",
        "status": "New",
        "priority": "Normal",
        "createdDate": "2020-05-12T03:18:25+0000",
        "UpdatedDate": "2020-05-12T03:18:25+0000"
      }
    ]
  }
```

Retrieve service request categories

The following table lists the retrieve service request categories for a specified tenant.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/tenants/{tenant_id}/servicerequests/categories`	Retrieve service requests categories.	`tenant_id:` (Optional) Return the service requests for a specified tenant.

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 5 records.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "returned_records": 5,
    "records": [
      {
        "key": "dr",
        "value": "Disaster Recovery Failover"
      },
      {
        "key": "technical",
        "value": "Technical Issue"
      },
      {
        "key": "other",
        "value": "Other"
      },
      {
        "key": "subscription",
        "value": "Subscription Management"
      },
      {
        "key": "backup",
        "value": "Backup Restore"
      }
    ]
  }
}
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.