Tenants

NetApp Keystone

Ciaran McNamara, David Peterson
October 29, 2020

This PDF was generated from https://docs.netapp.com/us-en/keystone/seapiref_tenants.html on June 11, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Tenants 1

Tenants

Use the methods listed in the following table to retrieve, create, modify, and delete tenants.

HTTP Method	Path	Description
`GET`	`/v2.1/tenants`	Retrieve a list of all tenants.
`GET`	`/v2.1/tenants/{id}`	Retrieve a tenant by the tenant ID.
`POST`	`/v2.1/tenants`	Create a new tenant.
`PUT`	`/v2.1/tenants/{id}`	Modify the details of a tenant.
`DELETE`	`/v2.1/tenants/{id}`	Delete a tenant.

Tenant attributes

The following table lists the tenant attributes.

Attribute	Type	Description
`id`	String	The unique identifier of the tenant.
`code`	String	A customer-specified (or default) code that represents the tenant. This attribute can contain lowercase letters, numbers, and underscores.
`name`	String	The tenant name.
`zuora_account_name`	String	The billing account name: the name of the subscription in Zuora.
`zuora_account_number`	String	The billing account number: the subscription number in Zuora.
`description`	String	The description of the tenant.
`usage`	–	The services and service details applicable to the tenant. For each service level, this attribute displays the following: **name:** Service level name **used_size_gb:** Service level name **role_name:** User role (user, admin, read, partner, or root)

Retrieve all tenants

Use the method listed in the following table to retrieve all tenants or a subset of all tenants.

HTTP Method	Path	Description	Parameters
GET	/v2.1/tenants	Retrieve all tenants.	offset and limit – see Common Pagination

Required request body attributes: none

Request body example:

```
none
```

Response body example:


```
{
  "status": {
    "user_message": "Okay. Returned 2 records.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "returned_records": 2,
    "total_records": 23,
    "sort_by": "created",
    "order_by": "desc",
    "offset": 0,
    "limit": 2,
    "records": [
      {
        "id": "5e7c3af7aab46c00014ce877",
        "name": "MyTenant",
        "zuora_account_name": "MyAccount",
        "zuora_account_number": "A00000415",
        "description": "",
        "code": "mytenantcode",
        "usage": {
          "A-S00003875": [
            {
              "service_level": "extreme",
              "consumed": 0,
              "committed": 10,
              "burst": 0
            },
            {
              "service_level": "standard",
              "consumed": 1.94,
              "committed": 30,
```

```
            "burst": 0
          }
        ],
        "A-S00004566": [
          {
            "service_level": "object",
            "consumed": 3.31,
            "committed": 300,
            "burst": 0
          }
        ]
      }
    },
    {
      "id": "5d914499869caefed0f39eee",
      "name": "MyOrg",
      "zuora_account_name": "MyOrg Inc",
      "zuora_account_number": "A00000415",
      "description": "",
      "code": "myorg",
      "usage": {
        "A-S00003875": [
          {
            "service_level": "standard",
            "consumed": 12.33,
            "committed": 30,
            "burst": 0
          },
          {
            "service_level": "object",
            "consumed": 0,
            "committed": 40,
            "burst": 0
          }
        ],
        "A-S00003969": [
          {
            "service_level": "extreme",
            "consumed": 0,
            "committed": 5,
            "burst": 0
          }
        ]
      }
    }
  ]
```

```
  }
}
```

Retrieve a tenant by ID

Use the method listed in the following table to retrieve a tenant by ID.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/tenants/{id}`	Retrieve the tenant specified by the ID.	`id (string)`: The unique identifier of the tenant.

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "returned_records": 1,
    "records": [
      {
        "id": "5e7c3af7aab46c00014ce877",
        "name": "MyTenant",
        "zuora_account_name": "MyAccount",
        "zuora_account_number": "A00000415",
        "description": "",
        "code": "mytenantcode",
        "usage": {
          "A-S00003875": [
            {
              "service_level": "extreme",
              "consumed": 0,
              "committed": 10,
              "burst": 0
            },
            {
```

```
              "service_level": "premium",
              "consumed": 2.4,
              "committed": 20,
              "burst": 0
            },
            {
              "service_level": "standard",
              "consumed": 1.94,
              "committed": 30,
              "burst": 0
            },
            {
              "service_level": "object",
              "consumed": 0,
              "committed": 40,
              "burst": 0
            }
          ],
          "A-S00003969": [
            {
              "service_level": "extreme",
              "consumed": 0,
              "committed": 5,
              "burst": 0
            },
            {
              "service_level": "standard",
              "consumed": 0,
              "committed": 30,
              "burst": 0
            }
          ],
          "A-S00004566": [
            {
              "service_level": "object",
              "consumed": 3.31,
              "committed": 300,
              "burst": 0
            }
          ]
        }
      }
    ]
  }
}
```

Create a tenant

Use the method listed in the following table to create a tenant.

HTTP Method	Path	Description	Parameters
`POST`	`/v2.1/tenants`	Create a new tenant.	None

Required request body attributes: `code`, `name`, `zuora_account_name`, `zuora_account_number`

Request body example:

```
{
  "name": "MyNewTenant",
  "code": "mytenant",
  "zuora_account_name": "string",
  "zuora_account_number": "A00000415",
  "description": "DescriptionOfMyTenant"
}
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. New resource created.",
    "verbose_message": "",
    "code": 201
  },
  "result": {
    "returned_records": 1,
    "records": [
      {
        "id": "5ed5ac802c356a0001a735af",
        "name": "MyNewTenant",
        "zuora_account_name": "string",
        "zuora_account_number": "A00000415",
        "description": "DescriptionOfMyTenant",
        "code": "mytenant",
        "usage": null
      }
    ]
  }
}
```

Modify the tenant

Use the method listed in the following table to modify the tenant.

HTTP Method	Path	Description	Parameters
`PUT`	`/v2.1/tenants/{id}`	Modify the tenant specified by the ID. You can change the name, the Zuora subscription details (account name or subscription number), and the description of the tenant.	`id (string)`: The unique identifier of the tenant.

Required request body attributes: `code`

Request body example:

```
{
  "name": "MyNewTenant",
  "code": "mytenant",
  "zuora_account_name": "string",
  "zuora_account_number": "A00000415",
  "description": "New description of my tenant"
}
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "returned_records": 1,
    "records": [
      {
        "id": "5ed5ac802c356a0001a735af",
        "name": "MyNewTenant",
        "zuora_account_name": "string",
        "zuora_account_number": "A00000415",
        "description": "New description of my tenant",
        "code": "mytenant",
        "usage": null
      }
    ]
  }
}
```

Delete the tenant

Use the method listed in the following table to delete the tenant.

HTTP Method	Path	Description	Parameters
`DELETE`	`/v2.1/tenants/{id}`	Delete the tenant specified by the ID.	`id (string)`: The unique identifier of the tenant.

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
No content for successful delete
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.