Users

NetApp Keystone

Ciaran McNamara, David Peterson
October 29, 2020

This PDF was generated from https://docs.netapp.com/us-en/keystone/seapiref_users.html on June 11, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Users 1

Users

Use the methods listed in the following table to retrieve, create, modify, and delete subtenants.

HTTP Method	Path	Description
`GET`	`/v2.1/users`	Retrieve a list of all users.
`GET`	`/v2.1/users/{id}`	Retrieve a user by the user ID.
`POST`	`/v2.1/users`	Create a new user.
`PUT`	`/v2.1/users/{id}`	Modify the details of a user.
`DELETE`	`/v2.1/users/{id}`	Delete a user.
`GET`	`/v2.1/users/{username}`	Retrieve a user by the user name.

User attributes

The following table lists the user attributes.

Attribute	Type	Description
`id`	String	The unique identifier of the user.
`username`	String	The user name.
`password`	String	The user's password.
`firstName`	String	The user's first name.
`lastName`	String	The user's last name.
`displayName`	String	The user's display name.
`email`	String	The user's email address.
`phone`	String	The user's phone number.
`profileImageURL`	String	The URL of the users' profile image.
`tenant_id`	String	The primary tenant identifier for this user.
`tenancies`	–	The tenancy to which the user belongs; an array consisting of: • `tenant_id`, and • `role_name` This is the user role; one of user, admin, read, partner, or root.

Attribute	Type	Description
`provider`	String	Authentication provider: `local` or `activeDirectory`
`provider data`	–	Authentication provider details, consisting of: • `email_address`, and • `member_of` (group membership)

Retrieve all users

Use the method listed in the following table to retrieve all users.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/users`	Retrieve all users.	None

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "id": "5dddbe0ef071fe0001b889fd",
        "username": "TestUser3",
        "firstName": "Test",
        "lastName": "User",
        "displayName": "",
        "email": "testuser@netapp.com",
        "tenancies": [
          {
            "id": "5d914499869caefed0f39eee",
            "name": "MyOrg",
            "code": "myorg",
            "role": "admin"
          }
        ]
      }
    ]
  }
}
```


Retrieve a user by ID

Use the method listed in the following table to retrieve a user by ID.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/users`	Retrieve a user by ID.	`id (string)`: The unique identifier of the user.

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "id": "5e585df6896bd80001dd4b44",
        "username": "testuser01",
        "firstName": "",
        "lastName": "",
        "displayName": "",
        "email": "",
        "tenancies": [
          {
            "id": "5d914499869caefed0f39eee",
            "name": "MyOrg",
            "code": "myorg",
            "role": "user"
          }
        ]
      }
    ]
  }
}
```


Retrieve a user by user name

Use the method listed in the following table to retrieve a user by the user name.

HTTP Method	Path	Description	Parameters
`GET`	`/v2.1/users`	Retrieve a user by user name.	`username (string)`: The user name of the user.

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "id": "5e61aa814559c20001df1a5f",
        "username": "MyName",
        "firstName": "MyFirstName",
        "lastName": "MySurname",
        "displayName": "CallMeMYF",
        "email": "user@example.com",
        "tenancies": [
          {
            "id": "5e5f1c4f253c820001877839",
            "name": "MyTenant",
            "code": "testtenantmh",
            "role": "user"
          }
        ]
      }
    ]
  }
}
```


Create a user

Use the method listed in the following table to create a user.

HTTP Method	Path	Description	Parameters
`POST`	`/v2.1/users`	Create a new user.	None

Required request body attributes: `username`, `tenant_id`, `tenancies, provider`

Request body example:

```
{
  "username": "MyUser",
  "password": "mypassword",
  "firstName": "My",
  "lastName": "User",
  "displayName": "CallMeMyUser",
  "email": "user@example.com",
  "phone": "string",
  "profileImageURL": "string",
  "tenant_id": "5e7c3af7aab46c00014ce877",
  "tenancies": [
    {
      "tenant_id": "5e7c3af7aab46c00014ce877",
      "role_name": "admin"
    }
  ],
  "provider": "local",
  "provider_data": {
    "email": "user@example.com",
    "member_of": "string"
  }
}
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. New resource created.",
    "verbose_message": "",
    "code": 201
  },
  "result": {
    "returned_records": 1,
    "records": [
      {
        "id": "5ed6f463129e5d000102f7e1",
        "username": "MyUser",
        "firstName": "My",
        "lastName": "User",
        "displayName": "CallMeMyUser",
        "email": "user@example.com",
        "tenancies": [
          {
            "id": "5e7c3af7aab46c00014ce877",
            "name": "MyTenant",
            "code": "mytenantcode",
            "role_name": "admin"
          }
        ]
      }
    ]
  }
}
```

Modify a user by ID

Use the method listed in the following table to modify a user by user ID.

HTTP Method	Path	Description	Parameters
`PUT`	`/v2.1/users/{id}`	Modify a user identified by the user ID. You can modify the user name, display name, password, email address, phone number, profile image URL, and tenancy details.	`id (string)`: The unique identifier of the user.

Required request body attributes: `none`

Request body example:

```
{
  "password": "MyNewPassword",
   "firstName": "MyFirstName",
   "lastName": "MySurname",
   "displayName": "CallMeMYF",
   "email": "user@example.com",
   "phone": "string",
  "profileImageURL": "string",
  "tenant_id": "5e5f1c4f253c820001877839",
  "tenancies": [
    {
      "tenant_id": "5e5f1c4f253c820001877839",
      "role_name": "user"
    }
  ]
}
```

Response body example:

```
{
  "status": {
    "user_message": "Okay. Returned 1 record.",
    "verbose_message": "",
    "code": 200
  },
  "result": {
    "total_records": 1,
    "records": [
      {
        "id": "5e61aa814559c20001df1a5f",
        "username": "MyName",
        "firstName": "MyFirstName",
        "lastName": "MySurname",
        "displayName": "CallMeMYF",
        "email": "user@example.com",
        "tenancies": [
          {
            "id": "5e5f1c4f253c820001877839",
            "name": "MyTenant",
            "code": "testtenantmh",
            "role": "user"
          }
        ]
      }
    ]
  }
}
```

Delete a user by ID

Use the method listed in the following table to delete a user by ID.

HTTP Method	Path	Description	Parameters
`DELETE`	`/v2.1/users/{name}`	Delete the user identified by the ID.	`id (string)`: The unique identifier of the user.

Required request body attributes: `none`

Request body example:

```
none
```

Response body example:

```
No content for succesful delete
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.