適用於AI部署的高效能工作範例ONTAP

NetApp Solutions

NetApp
June 17, 2022

This PDF was generated from https://docs.netapp.com/zh-tw/netapp-solutions/ai/aicp_example_high-performance_jobs_for_ontap_ai_deployments_overview.html on June 17, 2022. Always check docs.netapp.com for the latest.

目錄

適用於AI部署的高效能工作範例ONTAP 1
適用於AI部署的高效能工作範例ONTAP 1
執行單節點AI工作負載 1
執行同步分散式AI工作負載 5

適用於AI部署的高效能工作範例ONTAP

本節包括在ONTAP 將Kubernetes部署在AI Pod上時、可執行的各種高效能工作範例。

"下一步：執行單節點AI工作負載。"

適用於AI部署的高效能工作範例ONTAP

本節包括在ONTAP 將Kubernetes部署在AI Pod上時、可執行的各種高效能工作範例。

"下一步：執行單節點AI工作負載。"

執行單節點AI工作負載

若要在Kubernetes叢集中執行單節點AI和ML工作、請從部署跳接主機執行下列工作。有了Trident、您就能快速輕鬆地建立資料磁碟區、讓Kubernetes工作負載能夠存取可能含有PB資料的資料。若要從Kubernetes Pod中存取此類資料磁碟區、只需在Pod定義中指定一個PVc即可。此步驟為Kubernetes原生作業、不需要NetApp專業人員。

> 本節假設您已將您嘗試在Kubernetes叢集中執行的特定AI和ML工作負載（採用Docker容器格式）容器化。

1. 下列命令範例顯示使用ImageNet資料集的TensorFlow基準測試工作負載建立Kubernetes工作。如需ImageNet資料集的詳細資訊、請參閱 "ImageNet網站"。

   此範例工作要求八個GPU、因此可在單一GPU工作節點上執行、該工作節點具備八個或更多GPU。此範例工作可在叢集中提交、而具有八個以上GPU的工作節點不存在、或目前正與其他工作負載一起使用。如果是、則工作會維持在擱置狀態、直到該工作者節點可供使用為止。

   此外、為了將儲存頻寬最大化、包含所需訓練資料的磁碟區會在本工作所建立的Pod內掛載兩次。另外一個Volume也會掛載在Pod中。第二個磁碟區將用於儲存結果和指標。這些磁碟區會使用PVCS名稱在工作定義中參考。如需Kubernetes工作的詳細資訊、請參閱 "Kubernetes官方文件"。

   此範例所建立的Pod中、會將「medium」值為「mory」的「emtyDir"磁碟區掛載到「開發/ shm」。Docker Container執行時間所自動建立的「/dev/shm」虛擬磁碟區的預設大小、有時可能不足以滿足TensorFlow的需求。如以下範例所示、掛載「empyDir"磁碟區可提供足夠大的「/dev/shm」虛擬磁碟區。如需有關「empyDir" Volume的詳細資訊、請參閱 "Kubernetes官方文件"。

   在此範例工作定義中所指定的單一容器、其「優先」值為「true」。此值表示容器有效擁有主機的root存取權。在這種情況下會使用此註釋、因為執行的特定工作負載需要root存取權。具體而言、工作負載執行的清除快取作業需要root存取權。是否需要這種「特殊權限：真」註解、取決於您執行的特定工作負載需求。

```
$ cat << EOF > ./netapp-tensorflow-single-imagenet.yaml
apiVersion: batch/v1
kind: Job
metadata:
  name: netapp-tensorflow-single-imagenet
```

```
spec:
  backoffLimit: 5
  template:
    spec:
      volumes:
      - name: dshm
        emptyDir:
          medium: Memory
      - name: testdata-iface1
        persistentVolumeClaim:
          claimName: pb-fg-all-iface1
      - name: testdata-iface2
        persistentVolumeClaim:
          claimName: pb-fg-all-iface2
      - name: results
        persistentVolumeClaim:
          claimName: tensorflow-results
      containers:
      - name: netapp-tensorflow-py2
        image: netapp/tensorflow-py2:19.03.0
        command: ["python", "/netapp/scripts/run.py", "--
dataset_dir=/mnt/mount_0/dataset/imagenet", "--dgx_version=dgx1", "--
num_devices=8"]
        resources:
          limits:
            nvidia.com/gpu: 8
        volumeMounts:
        - mountPath: /dev/shm
          name: dshm
        - mountPath: /mnt/mount_0
          name: testdata-iface1
        - mountPath: /mnt/mount_1
          name: testdata-iface2
        - mountPath: /tmp
          name: results
        securityContext:
          privileged: true
      restartPolicy: Never
EOF
$ kubectl create -f ./netapp-tensorflow-single-imagenet.yaml
job.batch/netapp-tensorflow-single-imagenet created
$ kubectl get jobs
NAME                                        COMPLETIONS   DURATION   AGE
netapp-tensorflow-single-imagenet           0/1           24s        24s
```

2. 確認您在步驟1中建立的工作正在正確執行。下列範例命令可確認已為工作建立單一Pod（如工作定義所指定

）、而且此Pod目前正在其中一個GPU工作節點上執行。

```
$ kubectl get pods -o wide
NAME                                                READY   STATUS
RESTARTS   AGE
IP              NODE            NOMINATED NODE
netapp-tensorflow-single-imagenet-m7x92             1/1     Running     0
3m    10.233.68.61    10.61.218.154   <none>
```

3. 確認您在步驟1中建立的工作已成功完成。下列命令範例可確認工作已成功完成。

```
$ kubectl get jobs
NAME                                          COMPLETIONS   DURATION
AGE
netapp-tensorflow-single-imagenet             1/1           5m42s
10m
$ kubectl get pods
NAME                                                  READY   STATUS
RESTARTS   AGE
netapp-tensorflow-single-imagenet-m7x92               0/1     Completed
0          11m
$ kubectl logs netapp-tensorflow-single-imagenet-m7x92
[netapp-tensorflow-single-imagenet-m7x92:00008] PMIX ERROR: NO-
PERMISSIONS in file gds_dstore.c at line 702
[netapp-tensorflow-single-imagenet-m7x92:00008] PMIX ERROR: NO-
PERMISSIONS in file gds_dstore.c at line 711
Total images/sec = 6530.59125
================ Clean Cache !!! ==================
mpirun -allow-run-as-root -np 1 -H localhost:1 bash -c 'sync; echo 1 >
/proc/sys/vm/drop_caches'
==========================================
mpirun -allow-run-as-root -np 8 -H localhost:8 -bind-to none -map-by
slot -x NCCL_DEBUG=INFO -x LD_LIBRARY_PATH -x PATH python
/netapp/tensorflow/benchmarks_190205/scripts/tf_cnn_benchmarks/tf_cnn_be
nchmarks.py --model=resnet50 --batch_size=256 --device=gpu
--force_gpu_compatible=True --num_intra_threads=1 --num_inter_threads=48
--variable_update=horovod --batch_group_size=20 --num_batches=500
--nodistortions --num_gpus=1 --data_format=NCHW --use_fp16=True
--use_tf_layers=False --data_name=imagenet --use_datasets=True
--data_dir=/mnt/mount_0/dataset/imagenet
--datasets_parallel_interleave_cycle_length=10
--datasets_sloppy_parallel_interleave=False --num_mounts=2
--mount_prefix=/mnt/mount_%d --datasets_prefetch_buffer_size=2000
--datasets_use_prefetch=True --datasets_num_private_threads=4
--horovod_device=gpu >
/tmp/20190814_105450_tensorflow_horovod_rdma_resnet50_gpu_8_256_b500_ima
genet_nodistort_fp16_r10_m2_nockpt.txt 2>&1
```

4. *選用：*清除工作成品。下列命令範例顯示刪除在步驟1中建立的工作物件。

   刪除工作物件時、Kubernetes會自動刪除任何相關的Pod。

```
$ kubectl get jobs
NAME                                                COMPLETIONS   DURATION
AGE
netapp-tensorflow-single-imagenet                   1/1           5m42s
10m
$ kubectl get pods
NAME                                                       READY   STATUS
RESTARTS   AGE
netapp-tensorflow-single-imagenet-m7x92                    0/1     Completed
0          11m
$ kubectl delete job netapp-tensorflow-single-imagenet
job.batch "netapp-tensorflow-single-imagenet" deleted
$ kubectl get jobs
No resources found.
$ kubectl get pods
No resources found.
```

"下一步：執行同步分散式AI工作負載。"

執行同步分散式AI工作負載

若要在Kubernetes叢集中執行同步多節點AI和ML工作、請在部署跨接主機上執行下列工作。此程序可讓您利用儲存在NetApp磁碟區上的資料、並使用比單一工作節點更多的GPU。如需同步分散式AI工作的說明、請參閱下圖。

> 相較於非同步分散式工作、同步分散式工作有助於提升效能和訓練準確度。關於同步工作與非同步工作的優缺點的討論、不在本文的討論範圍之內。



1. 下列命令範例顯示建立一個工作者、以參與本節範例中單一節點上執行的相同TensorFlow基準測試工作之同步分散式執行 "執行單節點AI工作負載"。在此特定範例中、只會部署一名員工、因為該工作會在兩個工作節點之間執行。

   此範例的工作者部署要求八個GPU、因此可在單一GPU工作者節點上執行、該節點具備八個以上的GPU。

如果GPU工作節點的GPU功能超過八個GPU、為了發揮最大效能、您可能想要增加此數目、使其等於工作節點所使用的GPU數量。如需Kubernetes部署的詳細資訊、請參閱 "Kubernetes官方文件"。

在此範例中會建立Kubernetes部署、因為這個特定的容器化工作者永遠不會自行完成。因此、使用Kubernetes工作架構來部署IT並不合理。如果您的員工是自行設計或撰寫完成、則使用工作架構來部署您的員工可能是合理的做法。

本範例部署規格中所指定的Pod、其「hostNetwork」值為「true」。此值表示Pod使用主機工作節點的網路堆疊、而非Kubernetes通常為每個Pod建立的虛擬網路堆疊。此註釋用於此案例、因為特定工作負載仰賴Open MPI、NCCL和Horovod以同步分散的方式執行工作負載。因此、它需要存取主機網路堆疊。關於Open MPI、NCCL和Horovod的討論不在本文的討論範圍之內。是否需要此「hostNetwork：true」註釋、取決於您執行的特定工作負載需求。如需有關「hostNetwork」欄位的詳細資訊、請參閱 "Kubernetes官方文件"。

```
$ cat << EOF > ./netapp-tensorflow-multi-imagenet-worker.yaml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: netapp-tensorflow-multi-imagenet-worker
spec:
  replicas: 1
  selector:
    matchLabels:
      app: netapp-tensorflow-multi-imagenet-worker
  template:
    metadata:
      labels:
        app: netapp-tensorflow-multi-imagenet-worker
    spec:
      hostNetwork: true
      volumes:
      - name: dshm
        emptyDir:
          medium: Memory
      - name: testdata-iface1
        persistentVolumeClaim:
          claimName: pb-fg-all-iface1
      - name: testdata-iface2
        persistentVolumeClaim:
          claimName: pb-fg-all-iface2
      - name: results
        persistentVolumeClaim:
          claimName: tensorflow-results
      containers:
      - name: netapp-tensorflow-py2
        image: netapp/tensorflow-py2:19.03.0
        command: ["bash", "/netapp/scripts/start-slave-multi.sh",
"22122"]
```

```
        resources:
          limits:
            nvidia.com/gpu: 8
        volumeMounts:
        - mountPath: /dev/shm
          name: dshm
        - mountPath: /mnt/mount_0
          name: testdata-iface1
        - mountPath: /mnt/mount_1
          name: testdata-iface2
        - mountPath: /tmp
          name: results
        securityContext:
          privileged: true
EOF
$ kubectl create -f ./netapp-tensorflow-multi-imagenet-worker.yaml
deployment.apps/netapp-tensorflow-multi-imagenet-worker created
$ kubectl get deployments
NAME                                      DESIRED   CURRENT   UP-TO-DATE
AVAILABLE   AGE
netapp-tensorflow-multi-imagenet-worker   1         1         1
1           4s
```

2. 確認您在步驟1中建立的工作者部署已成功啟動。下列命令範例可確認已針對部署建立單一工作者Pod、如部署定義所示、而且此Pod目前正在其中一個GPU工作者節點上執行。

```
$ kubectl get pods -o wide
NAME                                                        READY
STATUS    RESTARTS   AGE
IP              NODE            NOMINATED NODE
netapp-tensorflow-multi-imagenet-worker-654fc7f486-v6725   1/1
Running   0          60s   10.61.218.154   10.61.218.154   <none>
$ kubectl logs netapp-tensorflow-multi-imagenet-worker-654fc7f486-v6725
22122
```

3. 為啟動、參與及追蹤同步多節點工作執行的主節點建立Kubernetes工作。下列命令範例可建立一個主磁片、用於啟動、參與及追蹤同一個TensorFlow基準測試工作的同步分散式執行、該工作是在本節範例的單一節點上執行 "執行單節點AI工作負載"。

   此範例主要工作要求八個GPU、因此可在具有八個以上GPU的單一GPU工作節點上執行。如果GPU工作節點的GPU功能超過八個GPU、為了發揮最大效能、您可能想要增加此數目、使其等於工作節點所使用的GPU數量。

   本範例工作定義中所指定的主Pod、其「主機網路」值為「真」、就如同在步驟1中給工作群組「主機網路」值「真」一樣。請參閱步驟1、瞭解為何需要此值的詳細資訊。

```
$ cat << EOF > ./netapp-tensorflow-multi-imagenet-master.yaml
apiVersion: batch/v1
kind: Job
metadata:
  name: netapp-tensorflow-multi-imagenet-master
spec:
  backoffLimit: 5
  template:
    spec:
      hostNetwork: true
      volumes:
      - name: dshm
        emptyDir:
          medium: Memory
      - name: testdata-iface1
        persistentVolumeClaim:
          claimName: pb-fg-all-iface1
      - name: testdata-iface2
        persistentVolumeClaim:
          claimName: pb-fg-all-iface2
      - name: results
        persistentVolumeClaim:
          claimName: tensorflow-results
      containers:
      - name: netapp-tensorflow-py2
        image: netapp/tensorflow-py2:19.03.0
        command: ["python", "/netapp/scripts/run.py", "--
dataset_dir=/mnt/mount_0/dataset/imagenet", "--port=22122", "--
num_devices=16", "--dgx_version=dgx1", "--
nodes=10.61.218.152,10.61.218.154"]
        resources:
          limits:
            nvidia.com/gpu: 8
        volumeMounts:
        - mountPath: /dev/shm
          name: dshm
        - mountPath: /mnt/mount_0
          name: testdata-iface1
        - mountPath: /mnt/mount_1
          name: testdata-iface2
        - mountPath: /tmp
          name: results
        securityContext:
          privileged: true
      restartPolicy: Never
EOF
```

```
$ kubectl create -f ./netapp-tensorflow-multi-imagenet-master.yaml
job.batch/netapp-tensorflow-multi-imagenet-master created
$ kubectl get jobs
NAME                                        COMPLETIONS   DURATION   AGE
netapp-tensorflow-multi-imagenet-master   0/1           25s        25s
```

4. 確認您在步驟3中建立的主要工作正在正確執行。下列範例命令可確認已為工作建立單一主Pod、如工作定義所示、而且此Pod目前正在其中一個GPU工作節點上執行。您也應該看到、您在步驟1中看到的工作者Pod仍在執行中、而且主要和工作者Pod正在不同的節點上執行。

```
$ kubectl get pods -o wide
NAME                                                          READY
STATUS    RESTARTS   AGE
IP              NODE            NOMINATED NODE
netapp-tensorflow-multi-imagenet-master-ppwwj               1/1
Running   0          45s   10.61.218.152   10.61.218.152   <none>
netapp-tensorflow-multi-imagenet-worker-654fc7f486-v6725   1/1
Running   0          26m   10.61.218.154   10.61.218.154   <none>
```

5. 確認您在步驟3中建立的主要工作已成功完成。下列命令範例可確認工作已成功完成。

```
$ kubectl get jobs
NAME                                        COMPLETIONS   DURATION   AGE
netapp-tensorflow-multi-imagenet-master   1/1           5m50s      9m18s
$ kubectl get pods
NAME                                                          READY
STATUS      RESTARTS   AGE
netapp-tensorflow-multi-imagenet-master-ppwwj               0/1
Completed   0          9m38s
netapp-tensorflow-multi-imagenet-worker-654fc7f486-v6725   1/1
Running     0          35m
$ kubectl logs netapp-tensorflow-multi-imagenet-master-ppwwj
[10.61.218.152:00008] WARNING: local probe returned unhandled
shell:unknown assuming bash
rm: cannot remove '/lib': Is a directory
[10.61.218.154:00033] PMIX ERROR: NO-PERMISSIONS in file gds_dstore.c at
line 702
[10.61.218.154:00033] PMIX ERROR: NO-PERMISSIONS in file gds_dstore.c at
line 711
[10.61.218.152:00008] PMIX ERROR: NO-PERMISSIONS in file gds_dstore.c at
line 702
[10.61.218.152:00008] PMIX ERROR: NO-PERMISSIONS in file gds_dstore.c at
line 711
Total images/sec = 12881.33875
================ Clean Cache !!! ==================
```

```
mpirun -allow-run-as-root -np 2 -H 10.61.218.152:1,10.61.218.154:1 -mca
pml ob1 -mca btl ^openib -mca btl_tcp_if_include enp1s0f0 -mca
plm_rsh_agent ssh -mca plm_rsh_args "-p 22122" bash -c 'sync; echo 1 >
/proc/sys/vm/drop_caches'
==========================================
mpirun -allow-run-as-root -np 16 -H 10.61.218.152:8,10.61.218.154:8
-bind-to none -map-by slot -x NCCL_DEBUG=INFO -x LD_LIBRARY_PATH -x PATH
-mca pml ob1 -mca btl ^openib -mca btl_tcp_if_include enp1s0f0 -x
NCCL_IB_HCA=mlx5 -x NCCL_NET_GDR_READ=1 -x NCCL_IB_SL=3 -x
NCCL_IB_GID_INDEX=3 -x
NCCL_SOCKET_IFNAME=enp5s0.3091,enp12s0.3092,enp132s0.3093,enp139s0.3094
-x NCCL_IB_CUDA_SUPPORT=1 -mca orte_base_help_aggregate 0 -mca
plm_rsh_agent ssh -mca plm_rsh_args "-p 22122" python
/netapp/tensorflow/benchmarks_190205/scripts/tf_cnn_benchmarks/tf_cnn_be
nchmarks.py --model=resnet50 --batch_size=256 --device=gpu
--force_gpu_compatible=True --num_intra_threads=1 --num_inter_threads=48
--variable_update=horovod --batch_group_size=20 --num_batches=500
--nodistortions --num_gpus=1 --data_format=NCHW --use_fp16=True
--use_tf_layers=False --data_name=imagenet --use_datasets=True
--data_dir=/mnt/mount_0/dataset/imagenet
--datasets_parallel_interleave_cycle_length=10
--datasets_sloppy_parallel_interleave=False --num_mounts=2
--mount_prefix=/mnt/mount_%d --datasets_prefetch_buffer_size=2000 --
datasets_use_prefetch=True --datasets_num_private_threads=4
--horovod_device=gpu >
/tmp/20190814_161609_tensorflow_horovod_rdma_resnet50_gpu_16_256_b500_im
agenet_nodistort_fp16_r10_m2_nockpt.txt 2>&1
```

6. 當您不再需要部署時、請刪除該員工部署。下列命令範例顯示刪除在步驟1中建立的工作者部署物件。

   當您刪除工作者部署物件時、Kubernetes會自動刪除任何關聯的工作者Pod。

```
$ kubectl get deployments
NAME                                        DESIRED   CURRENT   UP-TO-DATE
AVAILABLE   AGE
netapp-tensorflow-multi-imagenet-worker   1         1         1
1           43m
$ kubectl get pods
NAME                                                        READY
STATUS      RESTARTS   AGE
netapp-tensorflow-multi-imagenet-master-ppwwj              0/1
Completed   0          17m
netapp-tensorflow-multi-imagenet-worker-654fc7f486-v6725   1/1
Running     0          43m
$ kubectl delete deployment netapp-tensorflow-multi-imagenet-worker
deployment.extensions "netapp-tensorflow-multi-imagenet-worker" deleted
$ kubectl get deployments
No resources found.
$ kubectl get pods
NAME                                              READY   STATUS
RESTARTS   AGE
netapp-tensorflow-multi-imagenet-master-ppwwj   0/1     Completed   0
18m
```

7. *選用：*清除主要工作成品。下列命令範例顯示刪除在步驟3中建立的主要工作物件。

   刪除主工作物件時、Kubernetes會自動刪除任何相關的主Pod。

```
$ kubectl get jobs
NAME                                        COMPLETIONS   DURATION   AGE
netapp-tensorflow-multi-imagenet-master   1/1           5m50s      19m
$ kubectl get pods
NAME                                              READY   STATUS
RESTARTS   AGE
netapp-tensorflow-multi-imagenet-master-ppwwj   0/1     Completed   0
19m
$ kubectl delete job netapp-tensorflow-multi-imagenet-master
job.batch "netapp-tensorflow-multi-imagenet-master" deleted
$ kubectl get jobs
No resources found.
$ kubectl get pods
No resources found.
```

"下一步：效能測試。"

版權資訊

Copyright©2022 NetApp、Inc.版權所有。美國印製本文件中版權所涵蓋的任何部分、不得以任何形式或任何方式（包括影印、錄製、 在未事先取得版權擁有者書面許可的情況下、在電子擷取系統中進行錄音或儲存。

衍生自受版權保護之NetApp資料的軟體必須遵守下列授權與免責聲明：

本軟體係由NetApp「依現狀」提供、不含任何明示或暗示的保證、包括但不限於適售性及特定用途適用性的暗示保證、特此聲明。在任何情況下、NetApp均不對任何直接、間接、偶發、特殊、示範、 或衍生性損害（包括但不限於採購替代商品或服務；使用損失、資料或利潤損失； 或業務中斷）、無論是在合約、嚴格責任或侵權行為（包括疏忽或其他）中、無論是因使用本軟體而產生的任何責任理論（包括疏忽或其他）、即使已被告知可能造成此類損害。

NetApp保留隨時變更本文所述之任何產品的權利、恕不另行通知。除非NetApp以書面明確同意、否則NetApp不承擔因使用本文所述產品而產生的任何責任或責任。使用或購買本產品並不代表NetApp擁有任何專利權利、商標權利或任何其他智慧財產權。

本手冊所述產品可能受到一或多個美國國家/地區的保護專利、國外專利或申請中。

限制權利圖例：政府使用、複製或揭露受DFARS 252.277-7103（1988年10月）和FAR 52-227-19（1987年6月）技術資料與電腦軟體權利條款（c）（1）（ii）分段所述限制。

商標資訊

NetApp、NetApp標誌及所列的標章 http://www.netapp.com/TM 為NetApp、Inc.的商標。其他公司和產品名稱可能為其各自所有者的商標。