Deploy Advanced Cluster Management for Kubernetes: Red Hat OpenShift with NetApp

NetApp Solutions

Dorian Henderson, Nikhil M Kulkarni
June 14, 2021

This PDF was generated from https://docs.netapp.com/us-en/netapp-solutions/containers/rh-os-n_use_case_advanced_cluster_management_deployment.html on July 11, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Deploy Advanced Cluster Management for Kubernetes: Red Hat OpenShift with NetApp 1

Deploy Advanced Cluster Management for Kubernetes: Red Hat OpenShift with NetApp

To install Advanced Cluster Management for Kubernetes on an OpenShift cluster, complete the following steps:

1. Choose an OpenShift cluster as the hub cluster and log into it with cluster-admin privileges.
2. Navigate to `Operators` → `Operators Hub` and search for `Advanced Cluster Management for Kubernetes`.



3. Select the `Advanced Cluster Management for Kubernetes` and click `Install`.



4. On the Install Operator screen, provide the necessary details (NetApp recommends retaining the default

parameters) and click `Install`.

OperatorHub > Operator Installation

Install Operator

Install your Operator by subscribing to one of the update channels to keep the Operator up to date. The strategy determines either manual or automatic updates.

Update channel *

- ○ release-2.0
- ○ release-2.1
- ◉ release-2.2

Installation mode *

- ○ All namespaces on the cluster (default)
  This mode is not supported by this Operator
- ◉ A specific namespace on the cluster
  Operator will be available in a single Namespace only.

Installed Namespace *

- ◉ Operator recommended Namespace: PR open-cluster-management

Namespace creation
Namespace **open-cluster-management** does not exist and will be created.

- ○ Select a Namespace

Approval strategy *

- ◉ Automatic
- ○ Manual

Install Cancel

5. Wait for the operator installation to complete.

Advanced Cluster Management for Kubernetes
2.2.3 provided by Red Hat

Installing Operator

The Operator is being installed. This may take a few minutes.

View installed Operators in Namespace open-cluster-management

6. After the operator is installed, click `Create MultiClusterHub`.



7. On the `Create MultiClusterHub` screen, click `Create` after furnishing the details. This initiates the installation of a multi-cluster hub.



8. After all the pods move to the `Running` state in the open-cluster-management namespace and the operator moves to the `Succeeded` state, Advanced Cluster Management for Kubernetes is installed.



9. It takes some time to complete the hub installation, and, after it is done, the MultiCluster hub moves to `Running` state.



10. It creates a route in the open-cluster-management namespace, connect to the URL in the route to access the Advanced Cluster Management console.



Next: Features - Cluster Lifecycle Management.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.