



プロキシサーバを使用するためのコネクタの設定

Cloud Manager

Ben Cammett
April 24, 2021

目次

プロキシサーバを使用するためのコネクタの設定	1
コネクタでプロキシを有効にします	1
API の直接トラフィックを有効にします	2

プロキシサーバを使用するためのコネクタの設定

インターネットへのすべての HTTP 通信にプロキシサーバを使用するように企業のポリシーで指定されている場合は、そのプロキシサーバを使用するようにコネクタを設定する必要があります。プロキシサーバは、クラウドまたはネットワークに配置できます。

コネクタでプロキシを有効にします

プロキシサーバ、そのコネクタ、および管理対象の Cloud Volumes ONTAP システム（HA メディエーターを含む）を使用するようにコネクタを設定すると、すべてのでプロキシサーバが使用されます。

この操作により、コネクタが再起動されます。続行する前に、コネクタが操作を実行していないことを確認してください。

手順

1. "Cloud Manager SaaS インターフェイスにログインします" コネクターインスタンスへのネットワーク接続を持つマシンから。

コネクタにパブリック IP アドレスがない場合は、VPN 接続が必要です。そうでない場合は、コネクタと同じネットワークにあるジャンプホストから接続する必要があります。

2. [* コネクタ *（Connector *）] ドロップダウンをクリックし、特定のコネクターの [ローカル UI へ移動（* Go to local UI *）] をクリックする。



コネクタで実行されている Cloud Manager インターフェイスが新しいブラウザタブに表示されます。

- Cloud Manager コンソールの右上にある設定アイコンをクリックし、* コネクタ設定 * を選択します。



- [General] で、[*HTTP Proxy Configuration] をクリックします。
- プロキシを設定します。
 - [プロキシを有効にする *] をクリックします
 - 構文を使用してサーバを指定します `http://address:port[""]`
 - ベーシック認証の場合は、ユーザ名とパスワードを指定します サーバに必要です
 - [保存 (Save)] をクリックします。



Cloud Manager では、@ 文字を含むパスワードはサポートされていません。

プロキシサーバを指定すると、 AutoSupport メッセージの送信時にプロキシサーバを使用するように、新しい Cloud Volumes ONTAP システムが自動的に設定されます。ユーザが Cloud Volumes ONTAP システムを作成する前にプロキシサーバを指定しなかった場合は、 System Manager を使用して、各システムの AutoSupport オプションでプロキシサーバを手動で設定する必要があります。

API の直接トラフィックを有効にします

プロキシサーバを設定している場合は、プロキシを経由せずに Cloud Manager に API 呼び出しを直接送信できます。このオプションは、AWS または Google Cloud で実行されているコネクタでサポートされます。

手順

- Cloud Manager コンソールの右上にある設定アイコンをクリックし、* コネクタ設定 * を選択します。



- [General] で、[Support Direct API traffic*] をクリックします。
- チェックボックスをクリックしてオプションを有効にし、* 保存 * をクリックします。

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.