



# Setting up Cloud Volumes ONTAP

## Cloud Manager 3.5

Ben Cammett

November 01, 2018

This PDF was generated from [https://docs.netapp.com/us-en/occm35/task\\_setting\\_up\\_ontap\\_cloud.html](https://docs.netapp.com/us-en/occm35/task_setting_up_ontap_cloud.html) on December 04, 2020. Always check docs.netapp.com for the latest.

# Table of Contents

Setting up Cloud Volumes ONTAP ..... 1

# Setting up Cloud Volumes ONTAP

After you deploy Cloud Volumes ONTAP, you can set it up by synchronizing the system time using NTP and by performing a few optional tasks from either System Manager or the CLI.

Task	Description
Synchronize the system time using NTP	<p>Cloud Volumes ONTAP needs a Network Time Protocol (NTP) server to synchronize the time with clients and peered clusters. Problems can occur when the time is inaccurate.</p> <p>You can configure the NTP server using System Manager or the CLI. For instructions, see the System Manager Help or the <a href="#">ONTAP 9 System Administration Reference</a>.</p>
Optional: Configure AutoSupport	<p>AutoSupport proactively monitors the health of your system and automatically sends messages to NetApp technical support by default.</p> <p>If the Cloud Manager Admin added a proxy server to Cloud Manager before you launched your instance, Cloud Volumes ONTAP is configured to use that proxy server for AutoSupport messages.</p> <p>You should test AutoSupport to ensure that it can send messages. For instructions, see the System Manager Help or the <a href="#">ONTAP 9 System Administration Reference</a>.</p>
Optional: Configure EMS	<p>The Event Management System (EMS) collects and displays information about events that occur on Cloud Volumes ONTAP systems. To receive event notifications, you can set event destinations (email addresses, SNMP trap hosts, or syslog servers) and event routes for a particular event severity.</p> <p>You can configure EMS using the CLI. For instructions, see the <a href="#">ONTAP 9 EMS Configuration Express Guide</a>.</p>

Task	Description
Optional: Create an SVM management network interface (LIF) for HA systems	<p>A storage virtual machine (SVM) management network interface (LIF) is required if you want to use SnapCenter or SnapDrive for Windows with an HA pair. The SVM management LIF must use a <i>floating</i> IP address when using an HA pair across multiple AWS Availability Zones.</p> <p>Cloud Manager prompts you to specify the floating IP address when you launch the HA pair. If you did not specify the IP address, you can create the SVM Management LIF yourself from System Manager or the CLI. The following example shows how to create the LIF from the CLI:</p> <pre>network interface create -vserver svm_cloud -lif svm_mgmt -role data -data-protocol none -home-node cloud-01 -home -port e0a -address 10.0.2.126 -netmask 255.255.255.0 -status -admin up -firewall-policy mgmt</pre>
Optional: Change the backup location of configuration files	<p>Cloud Volumes ONTAP automatically creates configuration backup files that contain information about the configurable options that it needs to operate properly.</p> <p>By default, Cloud Volumes ONTAP backs up the files to the Cloud Manager host every eight hours. If you want to send the backups to an alternate location, you can change the location to an FTP or HTTP server in your data center or in AWS. For example, you might already have a backup location for your FAS storage systems.</p> <p>You can change the backup location using the CLI. See the <a href="#">ONTAP 9 System Administration Reference</a>.</p>

## Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.