NetApp
ボリューム暗号化によるボリュームの暗号化

Cloud Manager 3.6

Ben Cammett
August 06, 2021

This PDF was generated from https://docs.netapp.com/ja-jp/occm36/task_encrypting_volumes.html on October 27, 2021. Always check docs.netapp.com for the latest.

目次

NetApp ボリューム暗号化によるボリュームの暗号化 1

NetApp ボリューム暗号化によるボリュームの暗号化

NetApp Volume Encryption （ NVE ）は、一度に 1 ボリュームずつ保管データを暗号化するためのソフトウェアベースのテクノロジです。データ、 Snapshot コピー、およびメタデータが暗号化されます。データへのアクセスには、ボリュームごとに 1 つずつ、一意の XTS-AES-256 キーを使用します。

現時点で、 Cloud Volumes ONTAP は外部キー管理サーバを使用した NetApp Volume Encryption をサポートしています。オンボードキーマネージャはサポートされていません。

ONTAP CLI から NetApp Volume Encryption をセットアップする必要があります。その後、 CLI または System Manager を使用して、特定のボリュームで暗号化を有効にできます。Cloud Manager のユーザインターフェイスと API では、 NetApp Volume Encryption がサポートされていません。

"サポートされている暗号化テクノロジの詳細を確認してください"。

手順

1. でサポートされているキー管理ツールのリストを確認します "NetApp Interoperability Matrix Tool で確認できます"。

   Key Managers * ソリューションを検索します。

2. "Cloud Volumes ONTAP CLI に接続します"。
3. Cloud Volumes ONTAP システムに NetApp Volume Encryption ライセンスをインストールします。

   "ONTAP 9 ネットアップ暗号化パワーガイド：ライセンスのインストール"

4. SSL 証明書をインストールして、外部キー管理サーバに接続します。

   "ONTAP 9 ネットアップ暗号化パワーガイド：外部キー管理の設定"

5. CLI または System Manager を使用して、暗号化された新しいボリュームを作成するか、暗号化されていない既存のボリュームを変換します。
   - CLI の使用
     - 新しいボリュームの場合は、 -encrypt パラメータを指定して * volume create * コマンドを使用します。

       "ONTAP 9 ネットアップ暗号化パワーガイド：新しいボリュームでの暗号化の有効化"

     - 既存のボリュームについては、 * volume encryption conversion start * コマンドを使用します。

       "ONTAP 9 ネットアップ暗号化パワーガイド： volume encryption conversion start コマンドを使用した既存のボリュームでの暗号化の有効化"

   - System Manager の略
     - 新しいボリュームの場合は、 * Storage > Volumes > Create > Create FlexVol * の順にクリックし、 * Encrypted * を選択します。

"ONTAP 9 System Manager を使用したクラスタ管理： FlexVol ボリュームの作成"

- 既存のボリュームの場合は、ボリュームを選択し、 * 編集 * をクリックして、 * 暗号化 * を選択します。

  "ONTAP 9 System Manager を使用したクラスタ管理：ボリュームプロパティの編集"

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.