Configuring Cloud Manager to use a proxy server

Cloud Manager 3.7

Ben Cammett
January 03, 2020

This PDF was generated from https://docs.netapp.com/us-en/occm37/task_configuring_proxy.html on October 12, 2020. Always check docs.netapp.com for the latest.

Table of Contents

Configuring Cloud Manager to use a proxy server 1

Configuring Cloud Manager to use a proxy server

When you first deploy Cloud Manager, it prompts you to enter a proxy server if the system does not have internet access. You can also manually enter and modify the proxy from Cloud Manager's settings.

About this task

If your corporate policies dictate that you use a proxy server for all HTTP communication to the internet, then you must configure Cloud Manager to use that proxy server. The proxy server can be in the cloud or in your network.

When you configure Cloud Manager to use a proxy server, Cloud Manager, Cloud Volumes ONTAP, and the HA mediator all use the proxy server.

Steps

1. In the upper right of the Cloud Manager console, click the Settings icon, and select **Cloud Manager Settings**.



2. Under HTTP Proxy, enter the server using the syntax http://*address:port*, specify a user name and password if basic authentication is required for the server, and then click **Save**.

> Cloud Manager does not support passwords that include the @ character.

Result

After you specify the proxy server, new Cloud Volumes ONTAP systems are automatically configured to use the proxy server when sending AutoSupport messages. If you do not specify the proxy server before users create Cloud Volumes ONTAP systems, then they must use System Manager to manually set the proxy server in the AutoSupport options for each system.

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.