# Security group rules for AWS

## Cloud Manager 3.7

Ben Cammett
January 03, 2020

This PDF was generated from https://docs.netapp.com/us-en/occm37/reference_security_groups.html on November 17, 2020. Always check docs.netapp.com for the latest.

# Table of Contents

Security group rules for AWS . . . . . 1
Rules for Cloud Manager . . . . . 1
Rules for Cloud Volumes ONTAP . . . . . 2
Rules for the HA mediator external security group . . . . . 7
Rules for the HA mediator internal security group . . . . . 8

# Security group rules for AWS

Cloud Manager creates AWS security groups that include the inbound and outbound rules that Cloud Manager and Cloud Volumes ONTAP need to operate successfully. You might want to refer to the ports for testing purposes or if you prefer your to use own security groups.

## Rules for Cloud Manager

The security group for Cloud Manager requires both inbound and outbound rules.

### Inbound rules for Cloud Manager

The source for inbound rules in the predefined security group is 0.0.0.0/0.

| Protocol | Port | Purpose |
|---|---|---|
| SSH | 22 | Provides SSH access to the Cloud Manager host |
| HTTP | 80 | Provides HTTP access from client web browsers to the Cloud Manager web console and connections from Cloud Compliance |
| HTTPS | 443 | Provides HTTPS access from client web browsers to the Cloud Manager web console |
| TCP | 3128 | Provides the Cloud Compliance instance with internet access, if your AWS network doesn’t use a NAT or proxy |

### Outbound rules for Cloud Manager

The predefined security group for Cloud Manager opens all outbound traffic. If that is acceptable, follow the basic outbound rules. If you need more rigid rules, use the advanced outbound rules.

#### Basic outbound rules

The predefined security group for Cloud Manager includes the following outbound rules.

| Protocol | Port | Purpose |
|---|---|---|
| All TCP | All | All outbound traffic |
| All UDP | All | All outbound traffic |

#### Advanced outbound rules

If you need rigid rules for outbound traffic, you can use the following information to open only those ports that are required for outbound communication by Cloud Manager.

The source IP address is the Cloud Manager host.

| Service | Protocol | Port | Destination | Purpose |
|---|---|---|---|---|
| Active Directory | TCP | 88 | Active Directory forest | Kerberos V authentication |
| | TCP | 139 | Active Directory forest | NetBIOS service session |
| | TCP | 389 | Active Directory forest | LDAP |
| | TCP | 445 | Active Directory forest | Microsoft SMB/CIFS over TCP with NetBIOS framing |
| | TCP | 464 | Active Directory forest | Kerberos V change & set password (SET_CHANGE) |
| | TCP | 749 | Active Directory forest | Active Directory Kerberos V change & set password (RPCSEC_GSS) |
| | UDP | 137 | Active Directory forest | NetBIOS name service |
| | UDP | 138 | Active Directory forest | NetBIOS datagram service |
| | UDP | 464 | Active Directory forest | Kerberos key administration |
| API calls and AutoSupport | HTTPS | 443 | Outbound internet and ONTAP cluster management LIF | API calls to AWS and ONTAP, and sending AutoSupport messages to NetApp |
| API calls | TCP | 3000 | ONTAP cluster management LIF | API calls to ONTAP |
| | TCP | 8088 | Backup to S3 | API calls to Backup to S3 |
| DNS | UDP | 53 | DNS | Used for DNS resolve by Cloud Manager |
| Cloud Compliance | HTTP | 80 | Cloud Compliance instance | Cloud Compliance for Cloud Volumes ONTAP |

# Rules for Cloud Volumes ONTAP

The security group for Cloud Volumes ONTAP requires both inbound and outbound rules.

## Inbound rules for Cloud Volumes ONTAP

The source for inbound rules in the predefined security group is 0.0.0.0/0.

| Protocol | Port | Purpose |
|---|---|---|
| All ICMP | All | Pinging the instance |

| Protocol | Port | Purpose |
|---|---|---|
| HTTP | 80 | HTTP access to the System Manager web console using the IP address of the cluster management LIF |
| HTTPS | 443 | HTTPS access to the System Manager web console using the IP address of the cluster management LIF |
| SSH | 22 | SSH access to the IP address of the cluster management LIF or a node management LIF |
| TCP | 111 | Remote procedure call for NFS |
| TCP | 139 | NetBIOS service session for CIFS |
| TCP | 161-162 | Simple network management protocol |
| TCP | 445 | Microsoft SMB/CIFS over TCP with NetBIOS framing |
| TCP | 635 | NFS mount |
| TCP | 749 | Kerberos |
| TCP | 2049 | NFS server daemon |
| TCP | 3260 | iSCSI access through the iSCSI data LIF |
| TCP | 4045 | NFS lock daemon |
| TCP | 4046 | Network status monitor for NFS |
| TCP | 10000 | Backup using NDMP |
| TCP | 11104 | Management of intercluster communication sessions for SnapMirror |
| TCP | 11105 | SnapMirror data transfer using intercluster LIFs |
| UDP | 111 | Remote procedure call for NFS |
| UDP | 161-162 | Simple network management protocol |
| UDP | 635 | NFS mount |
| UDP | 2049 | NFS server daemon |
| UDP | 4045 | NFS lock daemon |
| UDP | 4046 | Network status monitor for NFS |
| UDP | 4049 | NFS rquotad protocol |

## Outbound rules for Cloud Volumes ONTAP

The predefined security group for Cloud Volumes ONTAP opens all outbound traffic. If that is acceptable, follow the basic outbound rules. If you need more rigid rules, use the advanced outbound rules.

### Basic outbound rules

The predefined security group for Cloud Volumes ONTAP includes the following outbound rules.

| Protocol | Port | Purpose |
|---|---|---|
| All ICMP | All | All outbound traffic |
| All TCP | All | All outbound traffic |
| All UDP | All | All outbound traffic |

### Advanced outbound rules

If you need rigid rules for outbound traffic, you can use the following information to open only those ports that are required for outbound communication by Cloud Volumes ONTAP.

The source is the interface (IP address) on the Cloud Volumes ONTAP system.

| Service | Protocol | Port | Source | Destination | Purpose |
| --- | --- | --- | --- | --- | --- |
| Active Directory | | | | | |

| | | | | | |
|---|---|---|---|---|---|
| | TCP | 464 | Data LIF (NFS, CIFS) | Active Directory forest | Kerberos V change & set password (SET_CHANGE) |
| **Service** | **Protocol** | **Port** | **Source** | **Destination** | **Purpose** |
| | UDP | 464 | Data LIF (NFS, CIFS) | Active Directory forest | Kerberos key administration |
| | TCP | 749 | Data LIF (NFS, CIFS) | Active Directory forest | Kerberos V change & set password (RPCSEC_GSS) |
| Backup to S3 | TCP | 5010 | Intercluster LIF | Backup endpoint or restore endpoint | Back up and restore operations for the Backup to S3 feature |
| Cluster | All traffic | All traffic | All LIFs on one node | All LIFs on the other node | Intercluster communications (Cloud Volumes ONTAP HA only) |
| | TCP | 3000 | Node management LIF | HA mediator | ZAPI calls (Cloud Volumes ONTAP HA only) |
| | ICMP | 1 | Node management LIF | HA mediator | Keep alive (Cloud Volumes ONTAP HA only) |
| DHCP | UDP | 68 | Node management LIF | DHCP | DHCP client for first-time setup |
| DHCPS | UDP | 67 | Node management LIF | DHCP | DHCP server |
| DNS | UDP | 53 | Node management LIF and data LIF (NFS, CIFS) | DNS | DNS |
| NDMP | TCP | 18600–18699 | Node management LIF | Destination servers | NDMP copy |
| SMTP | TCP | 25 | Node management LIF | Mail server | SMTP alerts, can be used for AutoSupport |
| SNMP | TCP | 161 | Node management LIF | Monitor server | Monitoring by SNMP traps |
| | UDP | 161 | Node management LIF | Monitor server | Monitoring by SNMP traps |
| | TCP | 162 | Node management LIF | Monitor server | Monitoring by SNMP traps |
| | UDP | 162 | Node management LIF | Monitor server | Monitoring by SNMP traps |
| SnapMirror | TCP | 11104 | Intercluster LIF | ONTAP intercluster LIFs | Management of intercluster communication sessions for SnapMirror |
| | TCP | 11105 | Intercluster LIF | ONTAP intercluster LIFs | SnapMirror data transfer |

| Service | Protocol | Port | Source | Destination | Purpose |
|---|---|---|---|---|---|
| Syslog | UDP | 514 | Node management LIF | Syslog server | Syslog forward messages |

# Rules for the HA mediator external security group

The predefined external security group for the Cloud Volumes ONTAP HA mediator includes the following inbound and outbound rules.

## Inbound rules

The source for inbound rules is 0.0.0.0/0.

| Protocol | Port | Purpose |
|---|---|---|
| SSH | 22 | SSH connections to the HA mediator |
| TCP | 3000 | RESTful API access from Cloud Manager |

## Outbound rules

The predefined security group for the HA mediator opens all outbound traffic. If that is acceptable, follow the basic outbound rules. If you need more rigid rules, use the advanced outbound rules.

### Basic outbound rules

The predefined security group for the HA mediator includes the following outbound rules.

| Protocol | Port | Purpose |
|---|---|---|
| All TCP | All | All outbound traffic |
| All UDP | All | All outbound traffic |

### Advanced outbound rules

If you need rigid rules for outbound traffic, you can use the following information to open only those ports that are required for outbound communication by the HA mediator.

| Protocol | Port | Destination | Purpose |
|---|---|---|---|
| HTTP | 80 | Cloud Manager IP address | Download upgrades for the mediator |
| HTTPS | 443 | AWS API services | Assist with storage failover |

| Protocol | Port | Destination | Purpose |
| --- | --- | --- | --- |
| UDP | 53 | AWS API services | Assist with storage failover |

Rather than open ports 443 and 53, you can create an interface VPC endpoint from the target subnet to the AWS EC2 service.

# Rules for the HA mediator internal security group

The predefined internal security group for the Cloud Volumes ONTAP HA mediator includes the following rules. Cloud Manager always creates this security group. You do not have the option to use your own.

## Inbound rules

The predefined security group includes the following inbound rules.

| Protocol | Port | Purpose |
| --- | --- | --- |
| All traffic | All | Communication between the HA mediator and HA nodes |

## Outbound rules

The predefined security group includes the following outbound rules.

| Protocol | Port | Purpose |
| --- | --- | --- |
| All traffic | All | Communication between the HA mediator and HA nodes |

**Copyright Information**

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

**Trademark Information**

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.