云同步 API

Cloud Manager 3.8

Ben Cammett
August 12, 2021

This PDF was generated from https://docs.netapp.com/zh-cn/occm38/api_sync.html on October 27, 2021. Always check docs.netapp.com for the latest.

目□

云同□ API 1
入□ 1
API 参考 2
使用列表 API 2

云同□ API

通□ Web UI 提供的云同□功能也可通□ REST □格的 API □得。

入□

要□始使用 Cloud Sync APIs， □需要□取用□令牌和□的 Cloud Central □□ ID 。在□行 API □用□，□需要将令牌和□□ ID 添加到授□□□中。

□□

1. 从 NetApp Cloud Central □取用□令牌。

```
POST https://netapp-cloud-account.auth0.com/oauth/token
Header: Content-Type: application/json
Body:
{
               "username": "<user_email>",
               "scope": "profile",
               "audience": "https://api.cloud.netapp.com",
               "client_id": "UaVhOIXMWQs5i1WdDxauXe5Mqkb34NJQ",
               "grant_type": "password",
               "password": "<user_password>"
}
```

2. □取 Cloud Central □□ ID 。

```
GET https://cloudsync.netapp.com/api/accounts
Headers: Authorization: Bearer <user_token>
Content-Type: application/json
```

此 API 将返回如下□□：

```
[
  {
    "accountId": "account-JeL97Ry3",
    "name": "Test"
  }
]
```

3. 在□个 API □用的 Authorization □□中添加用□令牌和□□ ID 。

   - 示例 *

以下示例□示了在 Microsoft Azure 中□建数据代理的 API □用。□只需将 <user_token> 和 <AccountID> 替□□□在上述□□中□得的令牌和 ID 即可。

```
POST https://cloudsync.netapp.com/api/data-brokers
Headers: Authorization: Bearer <user_token>
Content-Type: application/json
x-account-id: <accountId>
Body: { "name": "databroker1", "type": "AZURE" }
```

令牌□期□□□行什□操作？

来自 NetApp Cloud Central 的用□令牌具有到期日期。要刷新令牌、□需要再次□用□□ 1 中的 API 。

API □□包括一个 "expires_in" 字段、□字段指出令牌何□□期。

API 参考

有□□个 Cloud Sync API 的文□，□参□ "NetApp Cloud Central"。

使用列表 API

列表 API 是□□ API ，因此不会立即返回□果（例如： `get /data-brokers/ { id } /list-nfs-export-folders` 和 `get /data-brokers/ { id } /list-s3-basses` ）。服□器的唯一□□是 HTTP 状□ 202 。要□得□□□果，□必□使用 `GET /messages/client` API 。

□□

1. □用要使用的列表 API 。
2. 使用 `get /messages/client` API □看操作□果。
3. 使用相同的 API ，方法是将其附加到□□收到的 ID ： `get http://cloudsync.netapp.com/api/messages/client?last=<id_from_step_2>`

   □注意，□次□用 `get /messages/client` API □， ID 都会□生更改。

   - 示例 *

□用 `list-s3-bates` API □，不会立即返回□果：

```
GET http://cloudsync.netapp.com/api/data-brokers/<data-broker-id>/list-s3-buckets
Headers: Authorization: Bearer <user_token>
Content-Type: application/json
x-account-id: <accountId>
```

□果是 HTTP 状□代□ 202 、□意味着□件已被接受、但尚未□理。

要□得操作的□果，□需要使用以下 API ：

```
GET http://cloudsync.netapp.com/api/messages/client
Headers: Authorization: Bearer <user_token>
Content-Type: application/json
x-account-id: <accountId>
```

□果是一个数□，其中一个□象包含 ID 字段。ID 字段表示服□器□送的最后一条消息。例如：

```
[
    {
        "header": {
            "requestId": "init",
            "clientId": "init",
            "agentId": "init"
        },
        "payload": {
            "init": {}
        },
        "id": "5801"
    }
]
```

□在，□可以使用□才收到的 ID □行以下 API □用：

```
GET http://cloudsync.netapp.com/api/messages/client?last=<id_from_step_2>
Headers: Authorization: Bearer <user_token>
Content-Type: application/json
x-account-id: <accountId>
```

□果是一□消息。□个消息内部都是一个有效□□□象，□□象由操作的名称（作□密□）及其□果（作□□）□成。例如：

```
[
    {
        "payload": {
            "list-s3-buckets": [
                {
                    "tags": [
                        {
                            "Value": "100$",
                            "Key": "price"
                        }
                    ],
                    "region": {
                        "displayName": "US West (Oregon)",
                        "name": "us-west-2"
                    },
                    "name": "small"
                }
            ]
        },
        "header": {
            "requestId": "f687ac55-2f0c-40e3-9fa6-57fb8c4094a3",
            "clientId": "5beb032f548e6e35f4ed1ba9",
            "agentId": "5bed61f4489fb04e34a9aac6"
        },
        "id": "5802"
    }
]
```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.