



# **Manage NIS server configurations**

## **ONTAP 9.12.1 REST API reference**

NetApp

February 13, 2024

This PDF was generated from [https://docs.netapp.com/us-en/ontap-restapi-9121/ontap/name-services\\_nis\\_endpoint\\_overview.html](https://docs.netapp.com/us-en/ontap-restapi-9121/ontap/name-services_nis_endpoint_overview.html) on February 13, 2024. Always check docs.netapp.com for the latest.

# Table of Contents

- Manage NIS server configurations . . . . . 1
  - Name-services NIS endpoint overview . . . . . 1
  - Retrieve NIS domain configurations of all SVMs . . . . . 6
  - Create the NIS domain and server configuration for a data SVM . . . . . 12
  - Delete the NIS domain configuration for an SVM . . . . . 20
  - Retrieve the NIS domain and server configurations for an SVM . . . . . 21
  - Update the NIS domain and server configuration for an SVM . . . . . 26

# Manage NIS server configurations

## Name-services NIS endpoint overview

### Overview

NIS servers are used to authenticate user and client computers. NIS domain name and NIS server information is required to configure NIS. It is important to note that this API is used to retrieve and manage NIS server configurations for data SVMs only. NIS configuration for the cluster is managed via </api/security/authentication/cluster/nis> .

### Retrieving NIS Information

The NIS GET endpoint retrieves all of the NIS configurations for data SVMs.

### Examples

#### Retrieving all fields for all NIS configurations

```
# The API:
/api/name-services/nis

# The call:
curl -X GET "https://<mgmt-ip>/api/name-services/nis?fields=*" -H "accept:
application/hal+json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "179d3c85-7053-11e8-b9b8-005056b41bd1",
        "name": "vs1",
        "_links": {
          "self": {
            "href": "/api/svm/svms/179d3c85-7053-11e8-b9b8-005056b41bd1"
          }
        }
      },
      "domain": "domainA.example.com",
      "servers": [
        "10.10.10.10",
        "example.com"
      ],
      "bound-servers": [
```

```

    "10.10.10.10"
  ],
  "_links": {
    "self": {
      "href": "/api/name-services/nis/179d3c85-7053-11e8-b9b8-005056b41bd1"
    }
  }
},
{
  "svm": {
    "uuid": "6a52023b-7066-11e8-b9b8-005056b41bd1",
    "name": "vs2",
    "_links": {
      "self": {
        "href": "/api/svm/svms/6a52023b-7066-11e8-b9b8-005056b41bd1"
      }
    }
  },
  "domain": "domainB.example.com",
  "servers": [
    "2.2.2.2",
    "3.3.3.3",
    "4.4.4.4"
  ],
  "bound-servers": [],
  "_links": {
    "self": {
      "href": "/api/name-services/nis/6a52023b-7066-11e8-b9b8-005056b41bd1"
    }
  }
}
],
"num_records": 2,
"_links": {
  "self": {
    "href": "/api/name-services/nis?fields=*"
  }
}
}

```

## Retrieving all NIS configurations whose bound servers start with 10

```
# The API:
/api/name-services/nis

# The call:
curl -X GET "https://<mgmt-ip>/api/name-services/nis?bound_servers=10*" -H
"accept: application/hal+json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "179d3c85-7053-11e8-b9b8-005056b41bd1",
        "name": "vs1",
        "_links": {
          "self": {
            "href": "/api/svm/svms/179d3c85-7053-11e8-b9b8-005056b41bd1"
          }
        }
      },
      "bound-servers": [
        "10.10.10.10"
      ],
      "_links": {
        "self": {
          "href": "/api/name-services/nis/6a52023b-7066-11e8-b9b8-005056b41bd1"
        }
      }
    }
  ],
  "num_records": 1,
  "_links": {
    "self": {
      "href": "/api/name-services/nis?bound_servers=10*"
    }
  }
}
```

## Retrieving the NIS configuration of a specific SVM

```
# The API:
/api/name-services/nis/{svm.uuid}

# The call:
curl -X GET "https://<mgmt-ip>/api/name-services/nis/179d3c85-7053-11e8-b9b8-005056b41bd1" -H "accept: application/hal+json"

# The response:
{
  "svm": {
    "uuid": "179d3c85-7053-11e8-b9b8-005056b41bd1",
    "name": "vs1"
  },
  "domain": "domainA.example.com",
  "servers": [
    "10.10.10.10",
    "example.com"
  ],
  "bound_servers": [
    "10.10.10.10"
  ]
}
```

## Creating a NIS configuration

The NIS POST endpoint creates a NIS configuration for the specified SVM.

### Example

The following example shows a POST operation:

```
# The API:
/api/name-services/nis

# The call:
curl -X POST "https://<mgmt-ip>/api/name-services/nis" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"svm\": { \"uuid\": \"179d3c85-7053-11e8-b9b8-005056b41bd1\" }, \"domain\": \"domainA.example.com\", \"servers\": [ \"10.10.10.10\", \"example.com\" ] }"
```

---

## Updating the NIS configuration

The NIS PATCH endpoint updates the NIS configuration for the specified NIS server.

### Examples

#### Updating the domain

```
# The API:
/api/name-services/nis/{svm.uuid}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/name-services/nis/179d3c85-7053-11e8-b9b8-005056b41bd1" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"domain\": \"domainC.example.com\", \"servers\": [ \"13.13.13.13\" ] }"
```

---

#### Updating the server

```
# The API:
/api/name-services/nis/{svm.uuid}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/name-services/nis/179d3c85-7053-11e8-b9b8-005056b41bd1" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"servers\": [ \"14.14.14.14\" ] }"
```

---

## Deleting a NIS configuration

The NIS DELETE endpoint deletes the NIS configuration for the specified SVM.

### Example

The following example shows a DELETE operation:

---

```
# The API:
/api/name-services/nis/{svm.uuid}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/name-services/nis/179d3c85-7053-11e8-b9b8-005056b41bd1" -H "accept: application/hal+json"
```

## Retrieve NIS domain configurations of all SVMs

GET /name-services/nis

**Introduced In:** 9.6

Retrieves NIS domain configurations of all the SVMs. The `bound_servers` field indicates the successfully bound NIS servers. Lookups and authentications fail if there are no bound servers.

### Related ONTAP commands

- `vserver services name-service nis-domain show`
- `vserver services name-service nis-domain show-bound`
- `vserver services name-service nis-domain show-bound-debug`

### Learn more

- [DOC /name-services/nis](#)

### Parameters

| Name     | Type   | In    | Required | Description  |
|----------|--------|-------|----------|--|
| domain   | string | query | False    | Filter by domain <ul style="list-style-type: none"><li>• maxLength: 64</li><li>• minLength: 1</li><li>• Introduced in: 9.7</li></ul> |
| svm.uuid | string | query | False    | Filter by svm.uuid <ul style="list-style-type: none"><li>• Introduced in: 9.7</li></ul>  |



| Name                           | Type          | In    | Required | Description  |
|--------------------------------|---------------|-------|----------|--|
| svm.name                       | string        | query | False    | Filter by svm.name <ul style="list-style-type: none"> <li>Introduced in: 9.7</li> </ul>  |
| binding_details.status.code    | string        | query | False    | Filter by binding_details.status.code <ul style="list-style-type: none"> <li>Introduced in: 9.11</li> </ul>  |
| binding_details.status.message | string        | query | False    | Filter by binding_details.status.message <ul style="list-style-type: none"> <li>Introduced in: 9.11</li> </ul>                                       |
| binding_details.server         | string        | query | False    | Filter by binding_details.server <ul style="list-style-type: none"> <li>maxLength: 255</li> <li>minLength: 1</li> <li>Introduced in: 9.11</li> </ul> |
| servers                        | string        | query | False    | Filter by servers <ul style="list-style-type: none"> <li>maxLength: 255</li> <li>minLength: 1</li> <li>Introduced in: 9.7</li> </ul>                 |
| bound_servers                  | string        | query | False    | Filter by bound_servers <ul style="list-style-type: none"> <li>maxLength: 255</li> <li>minLength: 1</li> <li>Introduced in: 9.7</li> </ul>           |
| fields                         | array[string] | query | False    | Specify the fields to return.  |

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| max_records    | integer       | query | False    | Limit the number of records returned.  |
| return_records | boolean       | query | False    | The default is true for GET calls. When set to false, only the number of records is returned.<br><br>• Default value: 1  |
| return_timeout | integer       | query | False    | The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.<br><br>• Default value: 1<br>• Max value: 120<br>• Min value: 0 |
| order_by       | array[string] | query | False    | Order results by specified fields and optional [asc  |

## Response

Status: 200, Ok

| Name        | Type                                 | Description                   |
|-------------|--------------------------------------|-------------------------------|
| _links      | <a href="#">_links</a>               |                               |
| num_records | integer                              | Number of NIS domain records. |
| records     | array[ <a href="#">nis_service</a> ] |                               |

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "num_records": 1,
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "binding_details": {
    },
    "bound_servers": {
    },
    "servers": {
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  }
}
```

## Error

Status: Default, Error

| Name  | Type                  | Description |
|-------|-----------------------|-------------|
| error | <a href="#">error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| next | <a href="#">href</a> |             |
| self | <a href="#">href</a> |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| self | <a href="#">href</a> |             |

binding\_status

| Name    | Type   | Description  |
|---------|--------|--|
| code    | string | Code corresponding to the server's binding status.   |
| message | string | Detailed description of the server's binding status. |

binding\_details

| Name   | Type                           | Description  |
|--------|--------------------------------|--|
| server | string                         | Hostname/IP address of the NIS server in the domain. |
| status | <a href="#">binding_status</a> |  |

svm

| Name   | Type                   | Description                       |
|--------|------------------------|-----------------------------------|
| _links | <a href="#">_links</a> |                                   |
| name   | string                 | The name of the SVM.              |
| uuid   | string                 | The unique identifier of the SVM. |

nis\_service

| Name            | Type                                     | Description  |
|-----------------|--|--|
| _links          | <a href="#">_links</a>                   |  |
| binding_details | array[ <a href="#">binding_details</a> ] | An array of objects where each object represents the NIS server and it's status for a given NIS domain. It is an advanced field. |
| bound_servers   | array[string]                            |  |
| domain          | string                                   | The NIS domain to which this configuration belongs.  |
| servers         | array[string]                            | A list of hostnames or IP addresses of NIS servers used by the NIS domain configuration.   |
| svm             | <a href="#">svm</a>                      |  |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### error

| Name      | Type                                     | Description                                 |
|-----------|--|---|
| arguments | array[ <a href="#">error_arguments</a> ] | Message arguments                           |
| code      | string                                   | Error code                                  |
| message   | string                                   | Error message                               |
| target    | string                                   | The target parameter that caused the error. |

## Create the NIS domain and server configuration for a data SVM

POST /name-services/nis

Introduced In: 9.6

Creates an NIS domain and server configuration for a data SVM. NIS configuration for the cluster is managed via </api/security/authentication/cluster/nis> .

## Important notes

- Each SVM can have one NIS domain configuration.
- Multiple SVMs can be configured with the same NIS domain. Specify the NIS domain and NIS servers as input. Domain name and servers fields cannot be empty.
- Both FQDNs and IP addresses are supported for the servers field.
- IPv6 must be enabled if IPv6 family addresses are specified in the servers field.
- A maximum of ten NIS servers are supported.

## Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the NIS configuration.
- `domain` - NIS domain to which the configuration belongs.
- `servers` - List of NIS server IP addresses.

## Related ONTAP commands

- `vserver services name-service nis-domain create`

## Learn more

- [DOC /name-services/nis](#)

## Parameters

| Name           | Type    | In    | Required | Description   |
|----------------|---------|-------|----------|---|
| return_records | boolean | query | False    | The default is false. If set to true, the records are returned.<br><br>• Default value: |

## Request Body

| Name            | Type                                     | Description  |
|-----------------|--|--|
| _links          | <a href="#">_links</a>                   |  |
| binding_details | array[ <a href="#">binding_details</a> ] | An array of objects where each object represents the NIS server and it's status for a given NIS domain. It is an advanced field. |
| bound_servers   | array[string]                            |  |

| Name    | Type                | Description  |
|---------|---------------------|--|
| domain  | string              | The NIS domain to which this configuration belongs.                                      |
| servers | array[string]       | A list of hostnames or IP addresses of NIS servers used by the NIS domain configuration. |
| svm     | <a href="#">svm</a> |  |

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "binding_details": {
  },
  "bound_servers": {
  },
  "servers": {
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

### Response

Status: 201, Created

| Name                   | Type                   | Description |
|------------------------|------------------------|-------------|
| <a href="#">_links</a> | <a href="#">_links</a> |             |



| Name        | Type               | Description                   |
|-------------|--------------------|-------------------------------|
| num_records | integer            | Number of NIS domain records. |
| records     | array[nis_service] |                               |

### Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "num_records": 1,
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "binding_details": {
    },
    "bound_servers": {
    },
    "servers": {
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  }
}
```

### Headers

| Name     | Description                               | Type   |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

## Error

Status: Default

### ONTAP Error Response Codes

| Error Code | Description  |
|------------|--|
| 1966253    | IPv6 is not enabled in the cluster   |
| 2621488    | Invalid SVM context  |
| 2621706    | The specified SVM UUID is incorrect for the specified SVM name   |
| 3276964    | NIS domain name or NIS server domain is too long. The maximum supported for domain name is 64 characters and the maximum supported for NIS server domain is 255 characters |
| 3276933    | A maximum of 10 NIS servers can be configured per SVM  |
| 13434916   | The SVM is in the process of being created. Wait a few minutes, and then try the command again.  |
| 23724109   | DNS resolution failed for one or more specified servers  |
| 23724112   | DNS resolution failed due to an internal error. Contact technical support if this issue persists   |
| 23724132   | DNS resolution failed for all the specified servers  |
| 23724130   | Cannot use an IPv6 name server address because there are no IPv6 LIFs  |

| Name  | Type                  | Description |
|-------|-----------------------|-------------|
| error | <a href="#">error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| self | <a href="#">href</a> |             |

binding\_status

| Name    | Type   | Description  |
|---------|--------|--|
| code    | string | Code corresponding to the server's binding status.   |
| message | string | Detailed description of the server's binding status. |

binding\_details

| Name   | Type                           | Description  |
|--------|--------------------------------|--|
| server | string                         | Hostname/IP address of the NIS server in the domain. |
| status | <a href="#">binding_status</a> |  |

svm

| Name   | Type                   | Description                       |
|--------|------------------------|-----------------------------------|
| _links | <a href="#">_links</a> |                                   |
| name   | string                 | The name of the SVM.              |
| uuid   | string                 | The unique identifier of the SVM. |

nis\_service

| Name   | Type                   | Description |
|--------|------------------------|-------------|
| _links | <a href="#">_links</a> |             |

| Name            | Type                                     | Description  |
|-----------------|--|--|
| binding_details | array[ <a href="#">binding_details</a> ] | An array of objects where each object represents the NIS server and it's status for a given NIS domain. It is an advanced field. |
| bound_servers   | array[string]                            |  |
| domain          | string                                   | The NIS domain to which this configuration belongs.  |
| servers         | array[string]                            | A list of hostnames or IP addresses of NIS servers used by the NIS domain configuration.   |
| svm             | <a href="#">svm</a>                      |  |

#### \_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| next | <a href="#">href</a> |             |
| self | <a href="#">href</a> |             |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### error

| Name      | Type                                     | Description                                 |
|-----------|--|---|
| arguments | array[ <a href="#">error_arguments</a> ] | Message arguments                           |
| code      | string                                   | Error code                                  |
| message   | string                                   | Error message                               |
| target    | string                                   | The target parameter that caused the error. |

# Delete the NIS domain configuration for an SVM

```
DELETE /name-services/nis/{svm.uuid}
```

**Introduced In:** 9.6

Deletes the NIS domain configuration of an SVM. NIS can be removed as a source from ns-switch if NIS is not used for lookups.

## Related ONTAP commands

- `vserver services name-service nis-domain delete`

## Learn more

- [DOC /name-services/nis](#)

## Parameters

| Name     | Type   | In   | Required | Description                                   |
|----------|--------|------|----------|---|
| svm.uuid | string | path | True     | UUID of the SVM to which this object belongs. |

## Response

Status: 200, Ok

## Error

Status: Default, Error

| Name  | Type                  | Description |
|-------|-----------------------|-------------|
| error | <a href="#">error</a> |             |

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

### See Definitions

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### error

| Name      | Type                                     | Description                                 |
|-----------|--|---|
| arguments | array[ <a href="#">error_arguments</a> ] | Message arguments                           |
| code      | string                                   | Error code                                  |
| message   | string                                   | Error message                               |
| target    | string                                   | The target parameter that caused the error. |

## Retrieve the NIS domain and server configurations for an SVM

GET /name-services/nis/{svm.uuid}

## Introduced In: 9.6

Retrieves NIS domain and server configurations of an SVM. Both NIS domain and servers are displayed by default. The `bound_servers` field indicates the successfully bound NIS servers.

## Related ONTAP commands

- `vserver services name-service nis-domain show`
- `vserver services name-service nis-domain show-bound`
- `vserver services name-service nis-domain show-bound-debug`

## Learn more

- [DOC /name-services/nis](#)

## Parameters

| Name     | Type          | In    | Required | Description                                   |
|----------|---------------|-------|----------|---|
| svm.uuid | string        | path  | True     | UUID of the SVM to which this object belongs. |
| fields   | array[string] | query | False    | Specify the fields to return.                 |

## Response

Status: 200, Ok

| Name                         | Type                                     | Description  |
|------------------------------|--|--|
| <code>_links</code>          | <a href="#">_links</a>                   |  |
| <code>binding_details</code> | array[ <a href="#">binding_details</a> ] | An array of objects where each object represents the NIS server and it's status for a given NIS domain. It is an advanced field. |
| <code>bound_servers</code>   | array[string]                            |  |
| <code>domain</code>          | string                                   | The NIS domain to which this configuration belongs.  |
| <code>servers</code>         | array[string]                            | A list of hostnames or IP addresses of NIS servers used by the NIS domain configuration.   |
| <code>svm</code>             | <a href="#">svm</a>                      |  |



## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "binding_details": {
  },
  "bound_servers": {
  },
  "servers": {
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Error

Status: Default, Error

| Name  | Type  | Description |
|-------|-------|-------------|
| error | error |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| self | <a href="#">href</a> |             |

binding\_status

| Name    | Type   | Description  |
|---------|--------|--|
| code    | string | Code corresponding to the server's binding status.   |
| message | string | Detailed description of the server's binding status. |

binding\_details

| Name   | Type                           | Description  |
|--------|--------------------------------|--|
| server | string                         | Hostname/IP address of the NIS server in the domain. |
| status | <a href="#">binding_status</a> |  |

svm

| Name   | Type                   | Description                       |
|--------|------------------------|-----------------------------------|
| _links | <a href="#">_links</a> |                                   |
| name   | string                 | The name of the SVM.              |
| uuid   | string                 | The unique identifier of the SVM. |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

error

| Name      | Type                                     | Description                                 |
|-----------|--|---|
| arguments | array[ <a href="#">error_arguments</a> ] | Message arguments                           |
| code      | string                                   | Error code                                  |
| message   | string                                   | Error message                               |
| target    | string                                   | The target parameter that caused the error. |

## Update the NIS domain and server configuration for an SVM

PATCH /name-services/nis/{svm.uuid}

**Introduced In:** 9.6

Updates NIS domain and server configuration of an SVM.

### Important notes

- Both NIS domain and servers can be modified.
- Domains and servers cannot be empty.
- Both FQDNs and IP addresses are supported for the servers field.
- If the domain is modified, NIS servers must also be specified.
- IPv6 must be enabled if IPv6 family addresses are specified for the servers field.

### Related ONTAP commands

- `vserver services name-service nis-domain modify`

### Learn more

- [DOC /name-services/nis](#)

### Parameters

| Name     | Type   | In   | Required | Description                                   |
|----------|--------|------|----------|---|
| svm.uuid | string | path | True     | UUID of the SVM to which this object belongs. |

## Request Body

| Name                         | Type  | Description  |
|------------------------------|---|--|
| <code>_links</code>          | <code>_links</code>                                 |  |
| <code>binding_details</code> | <code>array[<a href="#">binding_details</a>]</code> | An array of objects where each object represents the NIS server and it's status for a given NIS domain. It is an advanced field. |
| <code>bound_servers</code>   | <code>array[string]</code>                          |  |
| <code>domain</code>          | <code>string</code>                                 | The NIS domain to which this configuration belongs.  |
| <code>servers</code>         | <code>array[string]</code>                          | A list of hostnames or IP addresses of NIS servers used by the NIS domain configuration.   |
| <code>svm</code>             | <code><a href="#">svm</a></code>                    |  |

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "binding_details": {
  },
  "bound_servers": {
  },
  "servers": {
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Response

Status: 200, Ok

## Error

Status: Default

### ONTAP Error Response Codes

| Error Code | Description  |
|------------|--|
| 1966253    | IPv6 is not enabled in the cluster   |
| 2621488    | Invalid SVM context  |
| 2621706    | The specified SVM UUID is incorrect for the specified SVM name   |
| 3276964    | NIS domain name or NIS server domain is too long. The maximum supported for domain name is 64 characters and the maximum supported for NIS server domain is 255 characters |
| 3276933    | A maximum of 10 NIS servers can be configured per SVM  |
| 23724109   | DNS resolution failed for one or more specified servers  |
| 23724112   | DNS resolution failed due to an internal error. Contact technical support if this issue persists   |
| 23724132   | DNS resolution failed for all the specified servers  |
| 23724130   | Cannot use an IPv6 name server address because there are no IPv6 LIFs  |

| Name  | Type                  | Description |
|-------|-----------------------|-------------|
| error | <a href="#">error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| self | <a href="#">href</a> |             |

binding\_status

| Name    | Type   | Description  |
|---------|--------|--|
| code    | string | Code corresponding to the server's binding status.   |
| message | string | Detailed description of the server's binding status. |

binding\_details

| Name   | Type                           | Description  |
|--------|--------------------------------|--|
| server | string                         | Hostname/IP address of the NIS server in the domain. |
| status | <a href="#">binding_status</a> |  |

svm

| Name   | Type                   | Description                       |
|--------|------------------------|-----------------------------------|
| _links | <a href="#">_links</a> |                                   |
| name   | string                 | The name of the SVM.              |
| uuid   | string                 | The unique identifier of the SVM. |

nis\_service

| Name   | Type                   | Description |
|--------|------------------------|-------------|
| _links | <a href="#">_links</a> |             |



| Name            | Type                                     | Description  |
|-----------------|--|--|
| binding_details | array[ <a href="#">binding_details</a> ] | An array of objects where each object represents the NIS server and it's status for a given NIS domain. It is an advanced field. |
| bound_servers   | array[string]                            |  |
| domain          | string                                   | The NIS domain to which this configuration belongs.  |
| servers         | array[string]                            | A list of hostnames or IP addresses of NIS servers used by the NIS domain configuration.   |
| svm             | <a href="#">svm</a>                      |  |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### error

| Name      | Type                                     | Description                                 |
|-----------|--|---|
| arguments | array[ <a href="#">error_arguments</a> ] | Message arguments                           |
| code      | string                                   | Error code                                  |
| message   | string                                   | Error message                               |
| target    | string                                   | The target parameter that caused the error. |

## Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.