

# Retrieve cluster chassis

ONTAP 9.12.1 REST API reference

NetApp February 13, 2024

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-9121/ontap/cluster\_chassis\_endpoint\_overview.html on February 13, 2024. Always check docs.netapp.com for the latest.

# **Table of Contents**

Retrieve cluster chassis		 	 	 1
Cluster chassis endpoint overv	iew	 	 	 1
Retrieve a collection of chassis		 	 	 3
Retrieve a chassis		 	 	 11

# Retrieve cluster chassis

# **Cluster chassis endpoint overview**

#### Overview

You can use the chassis GET API to retrieve all of the chassis information in the cluster.

## **Examples**

#### Retrieving a list of chassis from the cluster

The following example shows the response with a list of chassis in the cluster:

```
# The API:
/api/cluster/chassis
# The call:
curl -X GET "https://<mgmt-ip>/api/cluster/chassis" -H "accept:
application/hal+json"
# The response:
"records": [
    "id": "021352005981",
    " links": {
      "self": {
        "href": "/api/cluster/chassis/021352005981"
  },
],
"num records": 1,
" links": {
 "self": {
    "href": "/api/cluster/chassis"
  }
}
}
```

#### Retrieving a specific chassis from the cluster

The following example shows the response of the requested chassis. If there is no chassis with the requested

```
# The API:
/api/cluster/chassis/{id}
# The call:
curl -X GET "https://<mgmt-ip>/api/cluster/chassis/021352005981" -H
"accept: application/hal+json"
# The response:
{
"id": "021352005981",
"state": "ok",
"nodes": [
   "name": "node-1",
   "uuid": "6ede364b-c3d0-11e8-a86a-00a098567f31",
   "position": "top",
   "usbs": {
     "supported": true,
     "enabled": true,
     "ports": [
         "connected": false
      }
     1
   },
   "pcis": {
     "cards": [
         "slot": "0",
         "device": "Gigabit Ethernet I210",
         "info": "\t e0M MAC Address: d0:39:ea:3f:06:2b (auto-1000t-
Device Type:
             1533\n\t Firmware Version: 3.25-0.0 0x800005D1\n"
       },
         "slot": "0",
         "device": "Intel Lewisburg series chipset SATA Controller",
         "info": "\t Additional Info: 0 (0xaaf00000) \n\t
SHM2S86Q120GLM22NP FW1146 114473MB 512B/sect (SPG190108HJ) \n"
     1
   },
   " links": {
    "self": {
```

```
"href": "/api/cluster/nodes/6ede364b-c3d0-11e8-a86a-00a098567f31"
      }
   }
 }
],
"frus": [
    "id": "PSU2",
   "type": "psu",
   "state": "ok"
  },
   "id": "PSU1",
   "type": "psu",
   "state": "ok"
  },
   "id": "Fan2",
   "type": "fan",
   "state": "ok"
 },
   "id": "Fan3",
   "type": "fan",
    "state": "ok"
 },
   "id": "Fan1",
   "type": "fan",
   "state": "ok"
 }
],
" links": {
 "self": {
   "href": "/api/cluster/chassis/021352005981"
 }
}
}
```

## Retrieve a collection of chassis

GET /cluster/chassis

Introduced In: 9.6

Retrieves a collection of chassis.

## **Related ONTAP commands**

- system chassis show
- system chassis fru show

## Learn more

• DOC /cluster/chassis

## **Parameters**

Name	Туре	In	Required	Description
nodes.pcis.cards.slot	string	query	False	Filter by nodes.pcis.cards.slo t  • Introduced in: 9.9
nodes.pcis.cards.inf o	string	query	False	Filter by nodes.pcis.cards.inf o  • Introduced in: 9.9
nodes.pcis.cards.de vice	string	query	False	Filter by nodes.pcis.cards.de vice • Introduced in: 9.9
nodes.usbs.supporte d	boolean	query	False	Filter by nodes.usbs.support ed  • Introduced in: 9.9
nodes.usbs.ports.co nnected	boolean	query	False	Filter by nodes.usbs.ports.co nnected  • Introduced in: 9.9

Name	Туре	In	Required	Description
nodes.usbs.enabled	boolean	query	False	Filter by nodes.usbs.enabled  • Introduced in: 9.9
nodes.position	string	query	False	Filter by nodes.position  • Introduced in: 9.8
nodes.name	string	query	False	Filter by nodes.name
nodes.uuid	string	query	False	Filter by nodes.uuid
frus.state	string	query	False	Filter by frus.state
frus.type	string	query	False	Filter by frus.type
frus.id	string	query	False	Filter by frus.id
id	string	query	False	Filter by id
state	string	query	False	Filter by state
shelves.uid	string	query	False	Filter by shelves.uid
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned.  • Default value: 1

Name	Туре	In	Required	Description
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.  • Default value: 1  • Max value: 120  • Min value: 0
order_by	array[string]	query	False	Order results by specified fields and optional [asc

# Response

Status: 200, Ok

Name	Туре	Description
_links	_links	
num_records	integer	Number of records.
records	array[chassis]	

```
" links": {
    "next": {
     "href": "/api/resourcelink"
   },
   "self": {
    "href": "/api/resourcelink"
   }
  },
  "num records": 1,
  "records": {
    "frus": {
     "state": "ok",
    "type": "fan"
    },
    "id": "021352005981",
    "nodes": {
     " links": {
       "self": {
         "href": "/api/resourcelink"
       }
      },
      "name": "node1",
      "pcis": {
        "cards": {
          "device": "Intel Lewisburg series chipset SATA Controller",
         "info": "Additional Info: 0 (0xaaf00000) SHM2S86Q120GLM22NP
FW1146 114473MB 512B/sect (SPG190108GW)",
         "slot": "0"
       }
      },
      "position": "top",
      "usbs": {
       "ports": {
       }
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    "shelves": {
     " links": {
       "self": {
         "href": "/api/resourcelink"
       }
```

```
"uid": "7777841915827391056"

},
    "state": "ok"

}
```

## **Error**

```
Status: Default, Error
```

Name	Туре	Description
error	error	

## Example error

```
{
   "error": {
        "arguments": {
            "code": "string",
            "message": "string"
        },
        "code": "4",
        "message": "entry doesn't exist",
        "target": "uuid"
      }
}
```

## **Definitions**

## See Definitions

href

Name	Туре	Description
href	string	

\_links

Name	Туре	Description
next	href	
self	href	

#### frus

Name	Туре	Description
id	string	
state	string	
type	string	

## \_links

Name	Туре	Description
self	href	

#### cards

Name	Туре	Description
device	string	The description of the PCI card.
info	string	The info string from the device driver of the PCI card.
slot	string	The slot where the PCI card is placed. This can sometimes take the form of "6-1" to indicate slot and subslot.

### pcis

Name	Туре	Description
cards	array[cards]	

## ports

Name	Туре	Description
connected	boolean	Indicates whether or not the USB port has a device connected to it.

#### usbs

The status of the USB ports on the controller.

Name	Туре	Description
enabled	boolean	Indicates whether or not the USB ports are enabled.
ports	array[ports]	
supported	boolean	Indicates whether or not USB ports are supported on the current platform.

### nodes

List of nodes in chassis.

Name	Туре	Description
_links	_links	
name	string	
pcis	pcis	
position	string	The position of the node in the chassis, when viewed from the rear of the system.
usbs	usbs	The status of the USB ports on the controller.
uuid	string	

## shelf\_reference

### Shelf

Name	Туре	Description
_links	_links	
uid	string	

### chassis

Name	Туре	Description
frus	array[frus]	List of FRUs in the chassis.
id	string	
nodes	array[nodes]	List of nodes in the chassis.
shelves	array[shelf_reference]	List of shelves in chassis.
state	string	

### error\_arguments

Name	Туре	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Туре	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

# Retrieve a chassis

GET /cluster/chassis/{id}

Introduced In: 9.6

Retrieves a specific chassis.

### **Related ONTAP commands**

- system chassis show
- system chassis fru show

## Learn more

• DOC /cluster/chassis

## **Parameters**

Name	Туре	In	Required	Description
id	string	path	True	Chassis ID
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Туре	Description
frus	array[frus]	List of FRUs in the chassis.
id	string	
nodes	array[nodes]	List of nodes in the chassis.
shelves	array[shelf_reference]	List of shelves in chassis.
state	string	

```
"frus": {
   "state": "ok",
   "type": "fan"
  "id": "021352005981",
  "nodes": {
   " links": {
     "self": {
       "href": "/api/resourcelink"
     }
    },
    "name": "node1",
    "pcis": {
     "cards": {
       "device": "Intel Lewisburg series chipset SATA Controller",
       "info": "Additional Info: 0 (0xaaf00000) SHM2S86Q120GLM22NP
FW1146 114473MB 512B/sect (SPG190108GW)",
       "slot": "0"
     }
    },
    "position": "top",
    "usbs": {
    "ports": {
    }
   "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "shelves": {
   " links": {
    "self": {
      "href": "/api/resourcelink"
     }
   },
   "uid": "7777841915827391056"
 },
 "state": "ok"
```

#### **Error**

Status: Default, Error

Name	Туре	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
        "code": "string",
        "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
    }
}
```

## **Definitions**

#### **See Definitions**

•			
т	r	11	c
ı		u	J

Name	Туре	Description
id	string	
state	string	
type	string	

### href

Name	Туре	Description
href	string	

## \_links

Name	Туре	Description
self	href	

### cards

Name	Туре	Description
device	string	The description of the PCI card.
info	string	The info string from the device driver of the PCI card.
slot	string	The slot where the PCI card is placed. This can sometimes take the form of "6-1" to indicate slot and subslot.

## pcis

Name	Туре	Description
cards	array[cards]	

### ports

Name	Туре	Description
connected	boolean	Indicates whether or not the USB port has a device connected to it.

usbs

The status of the USB ports on the controller.

Name	Туре	Description
enabled	boolean	Indicates whether or not the USB ports are enabled.
ports	array[ports]	
supported	boolean	Indicates whether or not USB ports are supported on the current platform.

#### nodes

List of nodes in chassis.

Name	Туре	Description
_links	_links	
name	string	
pcis	pcis	
position	string	The position of the node in the chassis, when viewed from the rear of the system.
usbs	usbs	The status of the USB ports on the controller.
uuid	string	

## shelf\_reference

## Shelf

Name	Туре	Description
_links	_links	
uid	string	

## error\_arguments

Name	Туре	Description
code	string	Argument code
message	string	Message argument

error

Name	Туре	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

#### Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

#### **Trademark information**

NETAPP, the NETAPP logo, and the marks listed at <a href="http://www.netapp.com/TM">http://www.netapp.com/TM</a> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.