# Manage Snapshot copy policies and schedules

ONTAP 9.13.1 REST API reference

NetApp
February 13, 2024

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-9131/ontap/storage_snapshot-policies_snapshot_policy.uuid_schedules_endpoint_overview.html on February 13, 2024. Always check docs.netapp.com for the latest.

# Table of Contents

Manage Snapshot copy policies and schedules . . . 1
Storage snapshot-policies snapshot_policy.uuid schedules endpoint overview . . . 1
Retrieve Snapshot copy policy schedules . . . 5
Add a schedule to a Snapshot copy policy . . . 11
Delete a schedule from a Snapshot copy policy . . . 17
Retrieve Snapshot copy policy schedule details . . . 19
Update a Snapshot copy policy schedule . . . 24
Delete a Snapshot copy policy . . . 28
Retrieve Snapshot copy policy details . . . 30
Update a Snapshot copy policy . . . 36

# Manage Snapshot copy policies and schedules

## Storage snapshot-policies snapshot_policy.uuid schedules endpoint overview

### Overview

In ONTAP, scheduled Snapshot copy creation works based on the schedules associated with Snapshot copy policies. ONTAP provides six cluster-wide schedules: "5min", "8hour", "hourly", "daily", "weekly" and "monthly". A Snapshot copy policy is created using at least one of these schedules and up to 5 schedules can be associated with a Snapshot copy policy. A Snapshot copy policy can be linked to a storage object and based on the schedule in the policy, Snapshot copies are created on the object at that interval. Each schedule in a Snapshot copy policy has a Snapshot copy name prefix attached to it. Every Snapshot copy created using this policy has this prefix in its name. There is also a retention count associated with every schedule. This count indicates the maximum number of Snapshot copies that can exist for a given schedule. Once the Snapshot copy count reaches the retention count, on the next create operation, the oldest Snapshot copy is deleted. A retention period can be associated with every schedule. During Snapshot copy creation, this period is set as SnapLock expiry time on Snapshot copy locking enabled volumes.

A schedule can be added, modified or deleted from a Snapshot copy policy.

### Snapshot copy policy schedule APIs

The following APIs are used to perform operations related to Snapshot copy policy schedules:

– POST /api/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/

– GET /api/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/

– GET /api/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}

– PATCH /api/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}

– DELETE /api/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}

### Examples

#### Adding schedule to a Snapshot copy policy

The POST operation is used to create a schedule for a Snapshot copy policy with the specified attributes.

```
# The API:
/api/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/

# The call:
curl -X POST  "https://<mgmt-ip>/api/storage/snapshot-policies/32a0841a-
818e-11e9-b4f4-005056bbab9c/schedules" -H "accept: application/hal+json"
-d '{"schedule.uuid": "7c985d80-818a-11e9-b4f4-005056bbab9c", "count":
"5", "prefix": "new_hourly" }'

# The response:
HTTP/1.1 201 Created
Date: Wed, 29 May 2019 22:41:33 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache,no-store,must-revalidate
Location: /api/storage/snapshot-policies/32a0841a-818e-11e9-b4f4-
005056bbab9c/schedules
Content-Length: 271
Content-Type: application/json
{
"num_records": 1,
"records": [
  {
    "snapshot_policy": {
      "uuid": "32a0841a-818e-11e9-b4f4-005056bbab9c"
    },
    "schedule": {
      "uuid": "7c985d80-818a-11e9-b4f4-005056bbab9c"
    },
    "count": 5,
    "prefix": "new_monthly"
  }
]
}
```

#### Retrieving Snapshot copy policy schedules

The GET operation is used to retrieve Snapshot copy policy schedules.

```
# The API:
/api/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/

# The call:
curl -X GET "https://<mgmt-ip>/api/storage/snapshot-policies/32a0841a-
818e-11e9-b4f4-005056bbab9c/schedules" -H "accept: application/hal+json"
```

```
# The response:
HTTP/1.1 200 OK
Date: Wed, 29 May 2019 22:49:58 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache,no-store,must-revalidate
Content-Length: 898
Content-Type: application/json
{
"records": [
  {
    "snapshot_policy": {
      "uuid": "32a0841a-818e-11e9-b4f4-005056bbab9c"
    },
    "schedule": {
      "uuid": "63d017dc-818a-11e9-b4f4-005056bbab9c",
      "name": "5min"
    }
  },
  {
    "snapshot_policy": {
      "uuid": "32a0841a-818e-11e9-b4f4-005056bbab9c"
    },
    "schedule": {
      "uuid": "64a5c5da-818a-11e9-b4f4-005056bbab9c",
      "name": "8hour"
    }
  },
  {
    "snapshot_policy": {
      "uuid": "32a0841a-818e-11e9-b4f4-005056bbab9c"
    },
    "schedule": {
      "uuid": "63e21a3e-818a-11e9-b4f4-005056bbab9c",
      "name": "daily"
    }
  },
  {
    "snapshot_policy": {
      "uuid": "32a0841a-818e-11e9-b4f4-005056bbab9c"
    },
    "schedule": {
      "uuid": "7c985d80-818a-11e9-b4f4-005056bbab9c",
      "name": "monthly"
    }
```

```
  }
],
"num_records": 4
}
```

#### Retrieving the attributes of a specific Snapshot copy policy schedule

The GET operation is used to retrieve the attributes of a specific Snapshot copy policy schedule.

```
# The API:
/api/storage/snapshot-
policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}

# The call:
curl -X GET "https://<mgmt-ip>/api/storage/snapshot-policies/32a0841a-
818e-11e9-b4f4-005056bbab9c/schedules/7c985d80-818a-11e9-b4f4-
005056bbab9c" -H "accept: application/hal+json"

# The response:
HTTP/1.1 200 OK
Date: Wed, 29 May 2019 22:54:06 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache,no-store,must-revalidate
Content-Length: 238
Content-Type: application/json
{
"snapshot_policy": {
  "uuid": "32a0841a-818e-11e9-b4f4-005056bbab9c"
},
"schedule": {
  "uuid": "7c985d80-818a-11e9-b4f4-005056bbab9c",
  "name": "monthly"
},
"count": 5,
"prefix": "new_monthly",
"snapmirror_label": "-",
"retention_period": "PT20M"
}
```

#### Updating a Snapshot copy policy schedule

The PATCH operation is used to update the specific attributes of a Snapshot copy policy.

```
# The API:
/api/storage/snapshot-
policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}

# The call:
curl -X PATCH  "https://<mgmt-ip>/api/storage/snapshot-policies/32a0841a-
818e-11e9-b4f4-005056bbab9c/schedules/7c985d80-818a-11e9-b4f4-
005056bbab9c" -d '{"count": "10" }' -H "accept: application/hal+json"

# The response:
HTTP/1.1 200 OK
Date: Wed, 29 May 2019 23:08:00 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache,no-store,must-revalidate
Content-Length: 3
Content-Type: application/json
```

#### Deleting a Snapshot copy policy

The DELETE operation is used to delete a Snapshot copy policy.

```
# The API:
/api/storage/snapshot-
policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/storage/snapshot-policies/32a0841a-
818e-11e9-b4f4-005056bbab9c/schedules/7c985d80-818a-11e9-b4f4-
005056bbab9c" -H "accept: application/hal+json"

# The response:
HTTP/1.1 200 OK
Date: Wed, 29 May 2019 23:12:32 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache,no-store,must-revalidate
Content-Length: 3
Content-Type: application/json
```

## Retrieve Snapshot copy policy schedules

GET `/storage/snapshot-policies/{snapshot_policy.uuid}/schedules`

**Introduced In:** 9.8

Retrieves a collection of Snapshot copy policy schedules.

## Related ONTAP commands

- `snapshot policy show`

## Learn more

- DOC /storage/snapshot-policies/{snapshot_policy.uuid}/schedules

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| snapshot_policy.uuid | string | path | True | Snapshot copy policy UUID |
| schedule.name | string | query | False | Filter by schedule.name |
| schedule.uuid | string | query | False | Filter by schedule.uuid |
| retention_period | string | query | False | Filter by retention_period<br>• Introduced in: 9.12 |
| count | integer | query | False | Filter by count |
| prefix | string | query | False | Filter by prefix |
| snapmirror_label | string | query | False | Filter by snapmirror_label |
| snapshot_policy.name | string | query | False | Filter by snapshot_policy.name |
| fields | array[string] | query | False | Specify the fields to return. |
| max_records | integer | query | False | Limit the number of records returned. |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| return_records | boolean | query | False | The default is true for GET calls. When set to false, only the number of records is returned.<br>• Default value: 1 |
| return_timeout | integer | query | False | The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.<br>• Default value: 1<br>• Max value: 120<br>• Min value: 0 |
| order_by | array[string] | query | False | Order results by specified fields and optional [asc |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| num_records | integer | Number of records |
| records | array[snapshot_policy_schedule] | |

**Example response**


```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "num_records": 1,
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "prefix": "string",
    "schedule": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "weekly",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "snapshot_policy": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "default",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
  }
}
```


## Error

```
Status: Default, Error
```

| Name | Type | Description |
| --- | --- | --- |
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| next | href | |
| self | href | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

schedule

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | Job schedule name |
| uuid | string | Job schedule UUID |

snapshot_policy

This is a reference to the Snapshot copy policy.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

snapshot_policy_schedule

The Snapshot copy policy schedule object is associated with a Snapshot copy policy and it defines the interval at which Snapshot copies are created and deleted.

| Name | Type | Description |
|---|---|---|
| _links | _links | |

| Name | Type | Description |
|---|---|---|
| count | integer | The number of Snapshot copies to maintain for this schedule. |
| prefix | string | The prefix to use while creating Snapshot copies at regular intervals. |
| retention_period | string | The retention period of Snapshot copies for this schedule. |
| schedule | schedule | |
| snapmirror_label | string | Label for SnapMirror operations |
| snapshot_policy | snapshot_policy | This is a reference to the Snapshot copy policy. |

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Add a schedule to a Snapshot copy policy

POST `/storage/snapshot-policies/{snapshot_policy.uuid}/schedules`

**Introduced In:** 9.8

Adds a schedule to a Snapshot copy policy.

## Required properties

- `schedule.uuid` or `schedule.name` - Schedule at which Snapshot copies are captured on the volume.
- `count` - Number of Snapshot copies to maintain for this schedule.

## Recommended optional properties

- `prefix` - Prefix to use when creating Snapshot copies at regular intervals.

## Default property values

If not specified in POST, the following default property values are assigned:

- `prefix` - Value of `schedule.name`

## Related ONTAP commands

- `snapshot policy add-schedule`

## Learn more

- DOC /storage/snapshot-policies/{snapshot_policy.uuid}/schedules

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| snapshot_policy.uuid | string | path | True | Snapshot copy policy UUID |
| return_records | boolean | query | False | The default is false. If set to true, the records are returned.<br>• Default value: |

## Request Body

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| count | integer | The number of Snapshot copies to maintain for this schedule. |
| prefix | string | The prefix to use while creating Snapshot copies at regular intervals. |

| Name | Type | Description |
| --- | --- | --- |
| retention_period | string | The retention period of Snapshot copies for this schedule. |
| schedule | schedule | |
| snapmirror_label | string | Label for SnapMirror operations |
| snapshot_policy | snapshot_policy | This is a reference to the Snapshot copy policy. |

**Example request**

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "prefix": "string",
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "weekly",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "snapshot_policy": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  }
}
```

## Response

```
Status: 201, Created
```

#### Headers

| Name | Description | Type |
|---|---|---|
| Location | Useful for tracking the resource location | string |

### Error

```
Status: Default
```

ONTAP Error Response Codes

| Error Code | Description |
|---|---|
| 1638407 | When adding schedule to a Snapshot copy policy, the count for that schedule must be specified. |
| 1638410 | Specified schedule already exists in snapshot policy. |
| 1638413 | Schedule not found. |
| 1638451 | This operation would result in total Snapshot copy count for the policy to exceed maximum supported count. |
| 1638508 | Another schedule has the same prefix within this policy. |
| 1638528 | This operation is not supported in a mixed-version cluster. |
| 1638531 | This operation is not supported because specified policy is owned by the cluster admin. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

schedule

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | Job schedule name |
| uuid | string | Job schedule UUID |

snapshot_policy

This is a reference to the Snapshot copy policy.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

snapshot_policy_schedule

The Snapshot copy policy schedule object is associated with a Snapshot copy policy and it defines the interval at which Snapshot copies are created and deleted.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| count | integer | The number of Snapshot copies to maintain for this schedule. |
| prefix | string | The prefix to use while creating Snapshot copies at regular intervals. |

| Name | Type | Description |
| --- | --- | --- |
| retention_period | string | The retention period of Snapshot copies for this schedule. |
| schedule | schedule | |
| snapmirror_label | string | Label for SnapMirror operations |
| snapshot_policy | snapshot_policy | This is a reference to the Snapshot copy policy. |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
| --- | --- | --- |
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Delete a schedule from a Snapshot copy policy

DELETE `/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}`

**Introduced In:** 9.8

Deletes a schedule from a Snapshot copy policy

## Related ONTAP commands

- `snapshot policy remove-schedule`

## Learn more

- DOC /storage/snapshot-policies/{snapshot_policy.uuid}/schedules

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| snapshot_policy.uuid | string | path | True | Snapshot copy policy UUID |
| schedule.uuid | string | path | True | Snapshot copy policy schedule UUID |

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

ONTAP Error Response Code

| Error Code | Description |
|---|---|
| 1638412 | Schedule does not exist in Snapshot policy. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Retrieve Snapshot copy policy schedule details

GET `/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}`

**Introduced In:** 9.8

Retrieves details of a specific Snapshot copy policy schedule.

## Related ONTAP commands

- `snapshot policy show`

## Learn more

- DOC /storage/snapshot-policies/{snapshot_policy.uuid}/schedules

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| snapshot_policy.uuid | string | path | True | Snapshot copy policy UUID |
| schedule.uuid | string | path | True | Snapshot copy policy schedule ID |
| fields | array[string] | query | False | Specify the fields to return. |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| count | integer | The number of Snapshot copies to maintain for this schedule. |
| prefix | string | The prefix to use while creating Snapshot copies at regular intervals. |
| retention_period | string | The retention period of Snapshot copies for this schedule. |
| schedule | schedule | |
| snapmirror_label | string | Label for SnapMirror operations |
| snapshot_policy | snapshot_policy | This is a reference to the Snapshot copy policy. |

#### Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "prefix": "string",
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "weekly",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "snapshot_policy": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  }
}
```

## Error

```
Status: Default, Error
```

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

schedule

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | Job schedule name |
| uuid | string | Job schedule UUID |

snapshot_policy

This is a reference to the Snapshot copy policy.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |

| Name | Type | Description |
|---|---|---|
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Update a Snapshot copy policy schedule

PATCH `/storage/snapshot-policies/{snapshot_policy.uuid}/schedules/{schedule.uuid}`

**Introduced In:** 9.8

Updates a Snapshot copy policy schedule

## Related ONTAP commands

- `snapshot policy modify-schedule`

## Learn more

- DOC /storage/snapshot-policies/{snapshot_policy.uuid}/schedules

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| snapshot_policy.uuid | string | path | True | Snapshot copy policy UUID |
| schedule.uuid | string | path | True | Snapshot copy policy schedule UUID |

## Request Body

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| count | integer | The number of Snapshot copies to maintain for this schedule. |
| prefix | string | The prefix to use while creating Snapshot copies at regular intervals. |

| Name | Type | Description |
| --- | --- | --- |
| retention_period | string | The retention period of Snapshot copies for this schedule. |
| schedule | schedule | |
| snapmirror_label | string | Label for SnapMirror operations |
| snapshot_policy | snapshot_policy | This is a reference to the Snapshot copy policy. |

**Example request**

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "prefix": "string",
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "weekly",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "snapshot_policy": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  }
}
```

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

ONTAP Error Response Code

| Error Code | Description |
| --- | --- |
| 1638451 | This operation would result in total Snapshot copy count for the policy to exceed maximum supported count. |

| Name | Type | Description |
| --- | --- | --- |
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

schedule

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | Job schedule name |
| uuid | string | Job schedule UUID |

snapshot_policy

This is a reference to the Snapshot copy policy.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

snapshot_policy_schedule

The Snapshot copy policy schedule object is associated with a Snapshot copy policy and it defines the interval at which Snapshot copies are created and deleted.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| count | integer | The number of Snapshot copies to maintain for this schedule. |
| prefix | string | The prefix to use while creating Snapshot copies at regular intervals. |

| Name | Type | Description |
|---|---|---|
| retention_period | string | The retention period of Snapshot copies for this schedule. |
| schedule | schedule | |
| snapmirror_label | string | Label for SnapMirror operations |
| snapshot_policy | snapshot_policy | This is a reference to the Snapshot copy policy. |

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Delete a Snapshot copy policy

DELETE `/storage/snapshot-policies/{uuid}`

**Introduced In:** 9.6

Deletes a Snapshot copy policy

## Related ONTAP commands

- `snapshot policy delete`

## Learn more

- DOC /storage/snapshot-policies

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| uuid | string | path | True | Snapshot copy policy UUID |

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

ONTAP Error Response Code

| Error Code | Description |
|---|---|
| 1638415 | Cannot delete policy. Reason: Policy is in use by at least one volume. |
| 1638416 | Cannot delete policy. Reason: Cannot verify whether policy is in use. |
| 1638430 | Cannot delete policy. Reason: Policy is in use by at least one Vserver. |
| 1638430 | Cannot delete built-in policy. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Retrieve Snapshot copy policy details

GET `/storage/snapshot-policies/{uuid}`

**Introduced In:** 9.6

Retrieves details of a specific Snapshot copy policy.

## Related ONTAP commands

- `snapshot policy show`

## Learn more

- DOC /storage/snapshot-policies

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| uuid | string | path | True | Snapshot copy policy UUID |
| fields | array[string] | query | False | Specify the fields to return. |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| comment | string | A comment associated with the Snapshot copy policy. |
| copies | array[copies] | |
| enabled | boolean | Is the Snapshot copy policy enabled? |
| name | string | Name of the Snapshot copy policy. |
| scope | string | Set to "svm" when the request is on a data SVM, otherwise set to "cluster". |
| svm | svm | |
| uuid | string | |

#### Example response


```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "comment": "string",
  "copies": {
    "prefix": "string",
    "schedule": {
      "name": "hourly"
    }
  },
  "enabled": 1,
  "name": "default",
  "scope": "svm",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
```


## Error

```
Status: Default, Error
```

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

schedule

| Name | Type | Description |
|---|---|---|
| name | string | Schedule at which Snapshot copies are captured on the volume. Some common schedules already defined in the system are hourly, daily, weekly, at 15 minute intervals, and at 5 minute intervals. Snapshot copy policies with custom schedules can be referenced. |

copies

| Name | Type | Description |
|---|---|---|
| count | integer | The number of Snapshot copies to maintain for this schedule. |
| prefix | string | The prefix to use while creating Snapshot copies at regular intervals. |

| Name | Type | Description |
| --- | --- | --- |
| retention_period | string | The retention period of Snapshot copies for this schedule. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours, and minutes. A period specified for years, months, and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively, for example "P10Y" represents a duration of 10 years. A duration in hours and minutes is represented by "PT<num>H" and "PT<num>M" respectively. The period string must contain only a single time element that is, either years, months, days, hours, or minutes. A duration which combines different periods is not supported, for example "P1Y10M" is not supported.</num></num></num></num></num> |
| schedule | schedule | |
| snapmirror_label | string | Label for SnapMirror operations |

svm

| Name | Type | Description |
| --- | --- | --- |
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Update a Snapshot copy policy

PATCH `/storage/snapshot-policies/{uuid}`

**Introduced In:** 9.6

Updates a Snapshot copy policy

## Related ONTAP commands

- `snapshot policy modify`
- `snapshot policy modify-schedule`
- `snapshot policy add-schedule`

## Learn more

- DOC /storage/snapshot-policies

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| uuid | string | path | True | Snapshot copy policy UUID |

## Request Body

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| comment | string | A comment associated with the Snapshot copy policy. |

| Name | Type | Description |
|---|---|---|
| copies | array[copies] | |
| enabled | boolean | Is the Snapshot copy policy enabled? |
| name | string | Name of the Snapshot copy policy. |
| scope | string | Set to "svm" when the request is on a data SVM, otherwise set to "cluster". |
| svm | svm | |
| uuid | string | |

**Example request**

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "comment": "string",
  "copies": {
    "prefix": "string",
    "schedule": {
      "name": "hourly"
    }
  },
  "enabled": 1,
  "name": "default",
  "scope": "svm",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
```

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

ONTAP Error Response Code

| Error Code | Description |
|---|---|
| 1638414 | Cannot enable policy. Reason: Specified schedule not found. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

schedule

| Name | Type | Description |
|---|---|---|
| name | string | Schedule at which Snapshot copies are captured on the volume. Some common schedules already defined in the system are hourly, daily, weekly, at 15 minute intervals, and at 5 minute intervals. Snapshot copy policies with custom schedules can be referenced. |

copies

| Name | Type | Description |
|---|---|---|
| count | integer | The number of Snapshot copies to maintain for this schedule. |
| prefix | string | The prefix to use while creating Snapshot copies at regular intervals. |

| Name | Type | Description |
| --- | --- | --- |
| retention_period | string | The retention period of Snapshot copies for this schedule. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours, and minutes. A period specified for years, months, and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively, for example "P10Y" represents a duration of 10 years. A duration in hours and minutes is represented by "PT<num>H" and "PT<num>M" respectively. The period string must contain only a single time element that is, either years, months, days, hours, or minutes. A duration which combines different periods is not supported, for example "P1Y10M" is not supported.</num></num></num></num></num> |
| schedule | schedule | |
| snapmirror_label | string | Label for SnapMirror operations |

svm

| Name | Type | Description |
| --- | --- | --- |
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

snapshot_policy

The Snapshot copy policy object is associated with a read-write volume used to create and delete Snapshot copies at regular intervals.

| Name | Type | Description |
| --- | --- | --- |
| _links | _links | |

| Name | Type | Description |
| --- | --- | --- |
| comment | string | A comment associated with the Snapshot copy policy. |
| copies | array[copies] | |
| enabled | boolean | Is the Snapshot copy policy enabled? |
| name | string | Name of the Snapshot copy policy. |
| scope | string | Set to "svm" when the request is on a data SVM, otherwise set to "cluster". |
| svm | svm | |
| uuid | string | |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
| --- | --- | --- |
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

**Copyright information**

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

**Trademark information**

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.