# Manage event filter rules

ONTAP 9.13.1 REST API reference

NetApp
February 13, 2024

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-9131/ontap/support_ems_filters_name_rules_index_endpoint_overview.html on February 13, 2024.
Always check docs.netapp.com for the latest.

# Table of Contents

Manage event filter rules . . . . . 1
Support EMS filters name rules index endpoint overview . . . . . 1
Delete an event filter rule . . . . . 3
Retrieve an event filter rule . . . . . 5
Update an event filter rule . . . . . 10

# Manage event filter rules

## Support EMS filters name rules index endpoint overview

### Overview

Manages a specific instance of a rule within a filter. See the documentation for /support/ems/filters for details on the various properties in a rule.

### Examples

#### Retrieving a single instance of a rule

```
# The API:
GET /api/support/ems/filters/{name}/rules/{index}

# The call:
curl -X GET "https://<mgmt-ip>/api/support/ems/filters/no-info-debug-
events/rules/1" -H "accept: application/hal+json"

# The response:
200 OK

# JSON Body
{
"name": "no-info-debug-events",
"index": 1,
"type": "include",
"message_criteria": {
  "name_pattern": "*",
  "severities": "emergency,alert,error,notice",
  "snmp_trap_types": "*",
  "_links": {
    "self": {
      "href":
"/api/support/ems/messages?name=*&severity=emergency,alert,error,notice&sn
mp_trap_type=*"
    }
  }
},
"parameter_criteria": [
  {
    "name_pattern": "*",
    "value_pattern": "*"
  }
],
"_links": {
  "self": {
    "href": "/api/support/ems/filters/no-info-debug-events/rules/1"
  }
}
}
```

**Updating an existing rule to use severity emergency**

```
# The API:
PATCH /api/support/ems/filters/{name}/rules/{index}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/support/ems/filters/test-
filter/rules/1" -H "accept: application/hal+json" -H "Content-Type:
application/json" -d "@test_ems_filter_rules_patch.txt"
test_ems_filter_rules_patch.txt(body):
{
"message_criteria": {
  "severities": "emergency"
}
}

# The response:
200 OK
```

**Deleting a rule from an existing filter**

```
# The API:
DELETE /api/support/ems/filters/{name}/rules/{index}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/support/ems/filters/test-
filter/rules/1" -H "accept: application/hal+json"

# The response:
200 OK
```

# Delete an event filter rule

DELETE `/support/ems/filters/{name}/rules/{index}`

**Introduced In:** 9.6

Deletes an event filter rule.

## Related ONTAP commands

- `event filter rule delete`

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| name | string | path | True | Filter name |
| index | string | path | True | Filter rule index |

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error Code | Description |
|---|---|
| 983091 | A default rule cannot be removed |
| 983092 | The index of the rule provided is outside the allowed range for the filter provided |
| 983095 | The rule index provided is invalid for the filter provided |
| 983110 | There are no user defined rules in the filter provided |
| 983113 | Default filters cannot be modified or removed |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Retrieve an event filter rule

GET `/support/ems/filters/{name}/rules/{index}`

**Introduced In:** 9.6

Retrieves an event filter rule.

## Related ONTAP commands

- `event filter show`

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| name | string | path | True | Filter name |
| index | string | path | True | Filter rule index |
| fields | array[string] | query | False | Specify the fields to return. |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| index | integer | Rule index. Rules are evaluated in ascending order. If a rule's index order is not specified during creation, the rule is appended to the end of the list. |
| message_criteria | message_criteria | Matching message definitions for the filter. A property must be specified. |
| parameter_criteria | array[parameter_criteria] | Parameter criteria used to match against events' parameters. Each parameter consists of a name and a value. When multiple parameter criteria are provided in a rule, all must match for the rule to be considered matched. A pattern can include one or more wildcard '*' characters. |
| type | string | Rule type |

#### Example response


```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "index": 1,
  "message_criteria": {
    "_links": {
      "related": {
        "href": "/api/resourcelink"
      }
    },
    "name_pattern": "callhome.*",
    "severities": "error,informational",
    "snmp_trap_types": "standard|built_in"
  },
  "parameter_criteria": {
    "name_pattern": "vol",
    "value_pattern": "cloud*"
  },
  "type": "include"
}
```


## Error

```
Status: Default, Error
```

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

_links

| Name | Type | Description |
|---|---|---|
| related | href | |

message_criteria

Matching message definitions for the filter. A property must be specified.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name_pattern | string | Message name filter on which to match. Supports wildcards. Defaults to * if not specified. |
| severities | string | A comma-separated list of severities or a wildcard. |
| snmp_trap_types | string | A comma separated list of snmp_trap_types or a wildcard. |

parameter_criteria

Criterion used for parameter based filtering

| Name | Type | Description |
|---|---|---|
| name_pattern | string | Parameter name pattern. Wildcard character '*' is supported. |
| value_pattern | string | Parameter value pattern. Wildcard character '*' is supported. |

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Update an event filter rule

PATCH `/support/ems/filters/{name}/rules/{index}`

**Introduced In:** 9.6

Updates an event filter rule.

## Recommended optional properties

- `message_criteria` - Message criteria used by a rule to match an event.
- `parameter_criteria` - Parameter criteria used by a rule to match an event.

## Related ONTAP commands

- `event filter rule add`
- `event filter rule delete`

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| name | string | path | True | Filter name |
| index | string | path | True | Filter rule index |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| new_index | integer | query | False | New position for the filter rule index |

## Request Body

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| index | integer | Rule index. Rules are evaluated in ascending order. If a rule's index order is not specified during creation, the rule is appended to the end of the list. |
| message_criteria | message_criteria | Matching message definitions for the filter. A property must be specified. |
| parameter_criteria | array[parameter_criteria] | Parameter criteria used to match against events' parameters. Each parameter consists of a name and a value. When multiple parameter criteria are provided in a rule, all must match for the rule to be considered matched. A pattern can include one or more wildcard '*' characters. |
| type | string | Rule type |

**Example request**

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "index": 1,
  "message_criteria": {
    "_links": {
      "related": {
        "href": "/api/resourcelink"
      }
    },
    "name_pattern": "callhome.*",
    "severities": "error,informational",
    "snmp_trap_types": "standard|built_in"
  },
  "parameter_criteria": {
    "name_pattern": "vol",
    "value_pattern": "cloud*"
  },
  "type": "include"
}
```

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error Code | Description |
|---|---|
| 983092 | The index of the rule provided is outside the allowed range for the filter provided |
| 983095 | The rule index provided is invalid for the filter provided |
| 983113 | Default filters cannot be modified or removed |

| Error Code | Description |
| --- | --- |
| 983126 | A rule requires at least one name_pattern, severities, snmp_trap_types, or parameter pattern to be defined |
| 983127 | A property cannot contain a combination of the wildcard characters and other values. |
| 983128 | An invalid value is provided for the property 'snmp_trap_types' |
| 983146 | An invalid value is provided for the property 'severities' |
| 983147 | The severities provided are not supported |
| 983155 | The provided severities property does not match that of the name_pattern |
| 983156 | The provided snmp_trap_types property does not match that of the name_pattern |
| 983157 | The provided severities and snmp_trap_types properties do not match those of the name_pattern |
| 983158 | The name_pattern provided does not exist |
| 983195 | Empty field in parameter_criteria. Both name and value patterns must be specified |
| 983196 | name_pattern and value_pattern fields in parameter_criteria are empty |
| 983211 | Parameter criteria based filtering is not supported in this version of ONTAP |

| Name | Type | Description |
| --- | --- | --- |
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

_links

| Name | Type | Description |
|---|---|---|
| related | href | |

message_criteria

Matching message definitions for the filter. A property must be specified.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name_pattern | string | Message name filter on which to match. Supports wildcards. Defaults to * if not specified. |
| severities | string | A comma-separated list of severities or a wildcard. |
| snmp_trap_types | string | A comma separated list of snmp_trap_types or a wildcard. |

parameter_criteria

Criterion used for parameter based filtering

| Name | Type | Description |
|---|---|---|
| name_pattern | string | Parameter name pattern. Wildcard character '*' is supported. |
| value_pattern | string | Parameter value pattern. Wildcard character '*' is supported. |

ems_filter_rule

Rule for an event filter

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| index | integer | Rule index. Rules are evaluated in ascending order. If a rule's index order is not specified during creation, the rule is appended to the end of the list. |
| message_criteria | message_criteria | Matching message definitions for the filter. A property must be specified. |
| parameter_criteria | array[parameter_criteria] | Parameter criteria used to match against events' parameters. Each parameter consists of a name and a value. When multiple parameter criteria are provided in a rule, all must match for the rule to be considered matched. A pattern can include one or more wildcard '*' characters. |
| type | string | Rule type |

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

**Copyright information**

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

**Trademark information**

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.