# View and update CIFS domain-related information (specific SVM)

ONTAP 9.13.1 REST API reference

NetApp
February 13, 2024

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-9131/ontap/protocols_cifs_domains_svm.uuid_endpoint_overview.html on February 13, 2024. Always check docs.netapp.com for the latest.

# Table of Contents

View and update CIFS domain-related information (specific SVM) . . . . . 1
Protocols CIFS domains svm.uuid endpoint overview . . . . . 1
Retrieve the CIFS domain-related information for an SVM . . . . . 6
Update the CIFS domain-related information for an SVM . . . . . 14

# View and update CIFS domain-related information (specific SVM)

## Protocols CIFS domains svm.uuid endpoint overview

### Overview

Displays CIFS domain-related information of the specified SVM.

### Examples

#### Retrieving all the fields of CIFS domain configurations of a specific SVM

```
# The API:
GET /api/protocols/cifs/domains/{svm.uuid}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/domains/6dd78167-c907-
11eb-b2bf-0050568e7324" -H "accept: application/json"

# The response:
{
"svm": {
  "uuid": "6dd78167-c907-11eb-b2bf-0050568e7324",
  "name": "vs2"
},
"name_mapping": {
  "trusted_domains": [
    "SERVER03.COM",
    "SERVER04.COM"
  ]
},
"server_discovery_mode": "all",
"trust_relationships": [
  {
    "node": {
      "name": "vsNode2",
      "uuid": "4d9400f0-c84b-11eb-90ab-0050568e7324"
    },
    "home_domain": "SERVER02.COM",
    "trusted_domains": [
      "SERVER02.COM"
    ]
```

```
    }
  ],
  "discovered_servers": [
    {
      "node": {
        "name": "vsNode2",
        "uuid": "4d9400f0-c84b-11eb-90ab-0050568e7324"
      },
      "domain": "server02.com",
      "server_type": "kerberos",
      "server_name": "scspb0659002001",
      "server_ip": "192.168.20.1",
      "preference": "preferred",
      "state": "undetermined"
    },
    {
      "node": {
        "name": "vsNode2",
        "uuid": "4d9400f0-c84b-11eb-90ab-0050568e7324"
      },
      "domain": "server02.com",
      "server_type": "ms_ldap",
      "server_name": "scspb0659002001",
      "server_ip": "192.168.20.1",
      "preference": "preferred",
      "state": "undetermined"
    },
    {
      "node": {
        "name": "vsNode2",
        "uuid": "4d9400f0-c84b-11eb-90ab-0050568e7324"
      },
      "domain": "server02.com",
      "server_type": "ms_dc",
      "server_name": "scspb0659002001",
      "server_ip": "192.168.20.1",
      "preference": "preferred",
      "state": "undetermined"
    }
  ],
  "preferred_dcs": [
    {
      "fqdn": "server02.com",
      "server_ip": "192.168.20.1"
    }
  ],
```

```
"password_schedule": {
  "schedule_enabled": false,
  "schedule_weekly_interval": 4,
  "schedule_randomized_minute": 120,
  "schedule_description": "Tue@1:00"
}
}
```

---

**Applying rediscover_trusts query parameter and retrieving all the fields of CIFS domain configurations**

---

```
# The API:
GET /api/protocols/cifs/domains/{svm.uuid}?rediscover_trusts=true

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/domains/6dd78167-c907-
11eb-b2bf-0050568e7324?rediscover_trusts=true" -H "accept:
application/json"

# The response:
{
"svm": {
  "uuid": "6dd78167-c907-11eb-b2bf-0050568e7324",
  "name": "vs2"
},
"name_mapping": {
  "trusted_domains": [
    "SERVER03.COM",
    "SERVER04.COM"
  ]
},
"server_discovery_mode": "all",
"trust_relationships": [
  {
    "node": {
      "name": "vsNode1",
      "uuid": "a64c0906-c7dd-11eb-af15-0050568e403e"
    },
    "home_domain": "SERVER02.COM",
    "trusted_domains": [
      "SERVER02.COM"
    ]
  },
```

---

```
    {
      "node": {
        "name": "vsNode2",
        "uuid": "4d9400f0-c84b-11eb-90ab-0050568e7324"
      },
      "home_domain": "SERVER02.COM",
      "trusted_domains": [
        "SERVER02.COM"
      ]
    }
  ],
  "discovered_servers": [
    {
      "node": {
        "name": "vsNode2",
        "uuid": "4d9400f0-c84b-11eb-90ab-0050568e7324"
      },
      "domain": "server02.com",
      "server_type": "kerberos",
      "server_name": "scspb0659002001",
      "server_ip": "192.168.20.1",
      "preference": "preferred",
      "state": "undetermined"
    },
    {
      "node": {
        "name": "vsNode2",
        "uuid": "4d9400f0-c84b-11eb-90ab-0050568e7324"
      },
      "domain": "server02.com",
      "server_type": "ms_ldap",
      "server_name": "scspb0659002001",
      "server_ip": "192.168.20.1",
      "preference": "preferred",
      "state": "undetermined"
    },
    {
      "node": {
        "name": "vsNode2",
        "uuid": "4d9400f0-c84b-11eb-90ab-0050568e7324"
      },
      "domain": "server02.com",
      "server_type": "ms_dc",
      "server_name": "scspb0659002001",
      "server_ip": "192.168.20.1",
      "preference": "preferred",
```

```
    "state": "undetermined"
  }
],
"preferred_dcs": [
  {
    "fqdn": "server02.com",
    "server_ip": "192.168.20.1"
  }
],
"password_schedule": {
  "schedule_enabled": false,
  "schedule_weekly_interval": 4,
  "schedule_randomized_minute": 120,
  "schedule_description": "Tue@1:00"
}
}
```

#### Modifying the Password Schedule of CIFS domain configurations of a specific SVM

```
# The API:
PATCH /api/protocols/cifs/domains/{svm.uuid}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/domains/a83f816a-c873-
11ed-a3b2-0050568e278e" -H "accept: application/json" -d "{
\"password_schedule\": { \"schedule_enabled\": \"true\" }}"
```

#### Modifying the discovery-mode of CIFS domain configurations of a specific SVM

```
# The API:
PATCH /api/protocols/cifs/domains/{svm.uuid}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/domains/a83f816a-c873-
11ed-a3b2-0050568e278e" -H "accept: application/json" -d "{
\"server_discovery_mode\": \"site\" }"
```

# Retrieve the CIFS domain-related information for an SVM

GET `/protocols/cifs/domains/{svm.uuid}`

**Introduced In:** 9.10

Retrieves the CIFS domain-related information of the specified SVM.

## Important notes

GET operation with query parameter `rediscover_trusts` and `reset_discovered_servers` returns available CIFS domain configurations and also triggers trusts rediscovery and discovered servers reset asynchronously for that SVM.

## Related ONTAP commands

- `vserver cifs domain preferred-dc show`
- `vserver cifs domain trusts show`
- `vserver cifs domain discovered-servers show`
- `vserver cifs domain name-mapping-search show`
- `vserver cifs domain password schedule show`
- `vserver cifs domain discovered-servers discovery-mode show`

## Learn more

- DOC /protocols/cifs/domains/{svm.uuid}

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| rediscover_trusts | boolean | query | False | Force the discovery of trusted domains.<br>• Default value: |
| reset_discovered_servers | boolean | query | False | Force a rediscovery.<br>• Default value: |
| svm.uuid | string | path | True | UUID of the SVM to which this object belongs. |
| fields | array[string] | query | False | Specify the fields to return. |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| discovered_servers | array[discovered_servers] | Specifies the discovered servers records. |
| name_mapping | name_mapping | Specifies the name mapping search records. |
| password_schedule | password_schedule | Specifies the password schedule records. |
| preferred_dcs | array[preferred_dcs] | Specifies the preferred DC records. |
| server_discovery_mode | string | Specifies the mode of server discovery. |
| svm | svm | |
| trust_relationships | array[trust_relationships] | Specifies the trusted domain records. |

**Example response**


```
{
  "discovered_servers": {
    "domain": "test.com",
    "node": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "node1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "preference": "unknown",
    "server_type": "unknown",
    "state": "ok"
  },
  "name_mapping": {
    "trusted_domains": {
    }
  },
  "password_schedule": {
    "schedule_day_of_week": "Sunday",
    "schedule_description": "string",
    "schedule_last_changed_time": "string",
    "schedule_time_of_day": 36900,
    "schedule_warn_message": "string"
  },
  "preferred_dcs": {
    "fqdn": "test.com",
    "server_ip": "4.4.4.4",
    "status": {
      "details": "Response time (msec): 111",
      "reachable": 1
    }
  },
  "server_discovery_mode": "all",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
```

```
    },
    "trust_relationships": {
      "node": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "node1",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
      },
      "trusted_domains": {
      }
    }
  }
```


## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error Code | Description |
|---|---|
| 656463 | SVM UUID must be provided for a query on the field rediscover_trusts and reset_discovered_servers. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

node

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

discovered_servers

| Name | Type | Description |
|---|---|---|
| domain | string | Fully Qualified Domain Name. |
| node | node | |
| preference | string | Server Preference |
| server_ip | string | Server IP address |
| server_name | string | Server Name |
| server_type | string | Server Type |
| state | string | Server status |

name_mapping

Specifies the name mapping search records.

| Name | Type | Description |
|---|---|---|
| trusted_domains | array[string] | |

password_schedule

Specifies the password schedule records.

| Name | Type | Description |
|---|---|---|
| schedule_day_of_week | string | Day of the week for password change schedule. |
| schedule_description | string | Schedule description. |
| schedule_enabled | boolean | Is password schedule enabled. |
| schedule_last_changed_time | string | Last successful password change time. |
| schedule_randomized_minute | integer | Minutes within which schedule start can be randomized. |
| schedule_time_of_day | string | Start time for password change schedule. |
| schedule_warn_message | string | Warning message in case job is deleted. |
| schedule_weekly_interval | integer | Interval in weeks for password change schedule. |

status

Status of CIFS preferred domain controller.

| Name | Type | Description |
|---|---|---|
| details | string | Provides a detailed description of the state if the state is 'down' or the response time of the DNS server if the state is 'up'. |
| reachable | boolean | Indicates whether or not the domain controller is reachable. |

preferred_dcs

| Name | Type | Description |
|---|---|---|
| fqdn | string | Fully Qualified Domain Name. |
| server_ip | string | IP address of the preferred domain controller (DC). The address can be either an IPv4 or an IPv6 address. |

| Name | Type | Description |
| --- | --- | --- |
| status | status | Status of CIFS preferred domain controller. |

svm

| Name | Type | Description |
| --- | --- | --- |
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

trust_relationships

| Name | Type | Description |
| --- | --- | --- |
| home_domain | string | Home Domain Name |
| node | node | |
| trusted_domains | array[string] | Trusted Domain Name |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
| --- | --- | --- |
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Update the CIFS domain-related information for an SVM

PATCH `/protocols/cifs/domains/{svm.uuid}`

**Introduced In:** 9.13

Modifies the CIFS domain-related information of the specified SVM.

## Related ONTAP commands

- `vserver cifs domain password schedule modify`
- `vserver cifs domain discovered-servers discovery-mode modify`

## Learn more

- DOC /protocols/cifs/domains/{svm.uuid}

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| svm.uuid | string | path | True | UUID of the SVM to which this object belongs. |

## Request Body

| Name | Type | Description |
|---|---|---|
| discovered_servers | array[discovered_servers] | Specifies the discovered servers records. |
| name_mapping | name_mapping | Specifies the name mapping search records. |
| password_schedule | password_schedule | Specifies the password schedule records. |
| preferred_dcs | array[preferred_dcs] | Specifies the preferred DC records. |
| server_discovery_mode | string | Specifies the mode of server discovery. |
| svm | svm | |
| trust_relationships | array[trust_relationships] | Specifies the trusted domain records. |

**Example request**


```
{
  "discovered_servers": {
    "domain": "test.com",
    "node": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "node1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "preference": "unknown",
    "server_type": "unknown",
    "state": "ok"
  },
  "name_mapping": {
    "trusted_domains": {
    }
  },
  "password_schedule": {
    "schedule_day_of_week": "Sunday",
    "schedule_description": "string",
    "schedule_last_changed_time": "string",
    "schedule_time_of_day": 36900,
    "schedule_warn_message": "string"
  },
  "preferred_dcs": {
    "fqdn": "test.com",
    "server_ip": "4.4.4.4",
    "status": {
      "details": "Response time (msec): 111",
      "reachable": 1
    }
  },
  "server_discovery_mode": "all",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
```

```
  },
  "trust_relationships": {
    "node": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "node1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "trusted_domains": {
    }
  }
}
```


## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error Code | Description |
|---|---|
| 656392 | Preferred DC's need to be configured if CIFS discovery mode is set to none. |
| 656393 | Default site needs to be configured if CIFS discovery mode is set to site. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

node

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

discovered_servers

| Name | Type | Description |
|---|---|---|
| domain | string | Fully Qualified Domain Name. |
| node | node | |
| preference | string | Server Preference |
| server_ip | string | Server IP address |
| server_name | string | Server Name |
| server_type | string | Server Type |
| state | string | Server status |

name_mapping

Specifies the name mapping search records.

| Name | Type | Description |
|---|---|---|
| trusted_domains | array[string] | |

password_schedule

Specifies the password schedule records.

| Name | Type | Description |
| --- | --- | --- |
| schedule_day_of_week | string | Day of the week for password change schedule. |
| schedule_description | string | Schedule description. |
| schedule_enabled | boolean | Is password schedule enabled. |
| schedule_last_changed_time | string | Last successful password change time. |
| schedule_randomized_minute | integer | Minutes within which schedule start can be randomized. |
| schedule_time_of_day | string | Start time for password change schedule. |
| schedule_warn_message | string | Warning message in case job is deleted. |
| schedule_weekly_interval | integer | Interval in weeks for password change schedule. |

status

Status of CIFS preferred domain controller.

| Name | Type | Description |
| --- | --- | --- |
| details | string | Provides a detailed description of the state if the state is 'down' or the response time of the DNS server if the state is 'up'. |
| reachable | boolean | Indicates whether or not the domain controller is reachable. |

preferred_dcs

| Name | Type | Description |
| --- | --- | --- |
| fqdn | string | Fully Qualified Domain Name. |
| server_ip | string | IP address of the preferred domain controller (DC). The address can be either an IPv4 or an IPv6 address. |

| Name | Type | Description |
| --- | --- | --- |
| status | status | Status of CIFS preferred domain controller. |

svm

| Name | Type | Description |
| --- | --- | --- |
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

trust_relationships

| Name | Type | Description |
| --- | --- | --- |
| home_domain | string | Home Domain Name |
| node | node | |
| trusted_domains | array[string] | Trusted Domain Name |

cifs_domain

| Name | Type | Description |
| --- | --- | --- |
| discovered_servers | array[discovered_servers] | Specifies the discovered servers records. |
| name_mapping | name_mapping | Specifies the name mapping search records. |
| password_schedule | password_schedule | Specifies the password schedule records. |
| preferred_dcs | array[preferred_dcs] | Specifies the preferred DC records. |
| server_discovery_mode | string | Specifies the mode of server discovery. |
| svm | svm | |
| trust_relationships | array[trust_relationships] | Specifies the trusted domain records. |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
| --- | --- | --- |
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

**Copyright information**

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

**Trademark information**

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.