# Manage SVM peer relationships

ONTAP 9.6 REST API reference

NetApp
February 13, 2024

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-96/ontap/svm_peers_endpoint_overview.html on February 13, 2024. Always check docs.netapp.com for the latest.

# Table of Contents

Manage SVM peer relationships . . . 1
SVM peers endpoint overview . . . 1
Retrieve SVM peer relationships . . . 1
Create a new SVM peer relationship . . . 8
Delete an SVM peer relationship . . . 16
Retrieve an SVM peer relationship instance . . . 18
Update an SVM peer relationship . . . 24

# Manage SVM peer relationships

## SVM peers endpoint overview

### Managing SVM peers

The SVM peer commands allow you to create and manage SVM peering relationships.

#### SVM peer APIs

The following APIs are used to manage SVM peers:

- GET /api/svm/peers
- POST /api/svm/peers
- GET /api/svm/peers/{peer.uuid}
- PATCH /api/svm/peers/{peer.uuid}
- DELETE /api/svm/peers/{peer.uuid}

## Retrieve SVM peer relationships

GET `/svm/peers`

Retrieves the list of SVM peer relationships.

### Related ONTAP commands

- `vserver peer show`

### Examples

The following examples show how to retrieve a collection of SVM peer relationships based on a query.

1. Retrieves a list of SVM peers of a specific local SVM

```
GET "/api/svm/peers/?svm.name=VS1"
```

1. Retrieves a list of SVM peers of a specific cluster peer

```
GET "/api/svm/peers/?peer.cluster.name=cluster2"
```

### Learn more

- DOC /svm/peers

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| uuid | string | query | False | Filter by uuid |
| applications | string | query | False | Filter by applications |
| name | string | query | False | Filter by name |
| state | string | query | False | Filter by state |
| peer.cluster.name | string | query | False | Filter by peer.cluster.name |
| peer.cluster.uuid | string | query | False | Filter by peer.cluster.uuid |
| peer.svm.uuid | string | query | False | Filter by peer.svm.uuid |
| peer.svm.name | string | query | False | Filter by peer.svm.name |
| svm.uuid | string | query | False | Filter by svm.uuid |
| svm.name | string | query | False | Filter by svm.name |
| fields | array[string] | query | False | Specify the fields to return. |
| max_records | integer | query | False | Limit the number of records returned. |
| return_records | boolean | query | False | The default is true for GET calls. When set to false, only the number of records is returned. |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| return_timeout | integer | query | False | The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. |
| order_by | array[string] | query | False | Order results by specified fields and optional [asc |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| num_records | integer | Number of records |
| records | array[svm_peer] | |

**Example response**


```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "applications": [
      "snapmirror",
      "lun_copy"
    ],
    "peer": {
      "cluster": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "cluster2",
        "uuid": "ebe27c49-1adf-4496-8335-ab862aebebf2"
      },
      "svm": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      }
    },
    "state": "peered",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
```

```
          }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      },
      "uuid": "string"
    }
  }
```


## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error codes | Description |
|---|---|
| 26345578 | Internal error. Unable to retrieve local or peer SVM name. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**


```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```


## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| next | href | |
| self | href | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

cluster

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

peer

Details for a peer SVM object.

| Name | Type | Description |
|---|---|---|
| cluster | cluster | |
| svm | svm | SVM, applies only to SVM-scoped objects. |

svm

Local SVM details

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

svm_peer

An SVM peer relation object.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| applications | array[string] | A list of applications for an SVM peer relation. |
| name | string | A peer SVM alias name to avoid a name conflict on the local cluster. |
| peer | peer | Details for a peer SVM object. |
| state | string | SVM peering state. To accept a pending SVM peer request, PATCH the state to "peered". To reject a pending SVM peer request, PATCH the state to "rejected". To suspend a peered SVM peer relation, PATCH the state to "suspended". To resume a suspended SVM peer relation, PATCH the state to "peered". The states "initiated", "pending", and "initializing" are system-generated and cannot be used for PATCH. |
| svm | svm | Local SVM details |
| uuid | string | SVM peer relation UUID |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
| --- | --- | --- |
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Create a new SVM peer relationship

POST `/svm/peers`

Creates a new SVM peer relationship.

## Important notes

- The create request accepts peer SVM name as input instead of peer SVM UUID as the local cluster cannot validate peer SVM based on UUID.
- The input parameter `name` refers to the local name of the peer SVM. The `peer cluster name` parameter is optional for creating intracluster SVM peer relationships.

## Required properties

- `svm.name` or `svm.uuid` - SVM name or SVM UUID
- `peer.svm.name` or `peer.svm.uuid` - Peer SVM name or Peer SVM UUID
- `peer.cluster.name` or `peer.cluster.uuid` - Peer cluster name or peer cluster UUID
- `applications` - Peering applications

## Related ONTAP commands

- `vserver peer create`

## Example

Creates a new SVM peer relationship.

```
POST "/api/svm/peers" '{"svm":{"name":"vs1",
"peer.cluster.name":"cluster2", "peer.svm.name":"VS1",
"applications":["snapmirror"]}'
```

## Learn more

- DOC /svm/peers

## Request Body

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| applications | array[string] | A list of applications for an SVM peer relation. |
| name | string | A peer SVM alias name to avoid a name conflict on the local cluster. |
| peer | peer | Details for a peer SVM object. |
| state | string | SVM peering state. To accept a pending SVM peer request, PATCH the state to "peered". To reject a pending SVM peer request, PATCH the state to "rejected". To suspend a peered SVM peer relation, PATCH the state to "suspended". To resume a suspended SVM peer relation, PATCH the state to "peered". The states "initiated", "pending", and "initializing" are system-generated and cannot be used for PATCH. |
| svm | svm | Local SVM details |
| uuid | string | SVM peer relation UUID |

**Example request**


```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "applications": [
    "snapmirror",
    "lun_copy"
  ],
  "peer": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster2",
      "uuid": "ebe27c49-1adf-4496-8335-ab862aebebf2"
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  },
  "state": "peered",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "string"
}
```

## Response

```
Status: 202, Accepted
```

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| applications | array[string] | A list of applications for an SVM peer relation. |
| name | string | A peer SVM alias name to avoid a name conflict on the local cluster. |
| peer | peer | Details for a peer SVM object. |
| state | string | SVM peering state. To accept a pending SVM peer request, PATCH the state to "peered". To reject a pending SVM peer request, PATCH the state to "rejected". To suspend a peered SVM peer relation, PATCH the state to "suspended". To resume a suspended SVM peer relation, PATCH the state to "peered". The states "initiated", "pending", and "initializing" are system-generated and cannot be used for PATCH. |
| svm | svm | Local SVM details |
| uuid | string | SVM peer relation UUID |

**Example response**


```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "applications": [
    "snapmirror",
    "lun_copy"
  ],
  "peer": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster2",
      "uuid": "ebe27c49-1adf-4496-8335-ab862aebebf2"
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  },
  "state": "peered",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "string"
}
```

## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error codes | Description |
|---|---|
| 13434889 | Internal error. Wait and retry. |
| 26345575 | The specified peer cluster name and peer cluster UUID do not match. |
| 26345579 | The specified field is invalid. |
| 26345580 | SVM name or SVM UUID must be provided. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

cluster

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

peer

Details for a peer SVM object.

| Name | Type | Description |
|---|---|---|
| cluster | cluster | |
| svm | svm | SVM, applies only to SVM-scoped objects. |

svm

Local SVM details

| Name | Type | Description |
|---|---|---|
| _links | _links | |

| Name | Type | Description |
| --- | --- | --- |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

svm_peer

An SVM peer relation object.

| Name | Type | Description |
| --- | --- | --- |
| _links | _links | |
| applications | array[string] | A list of applications for an SVM peer relation. |
| name | string | A peer SVM alias name to avoid a name conflict on the local cluster. |
| peer | peer | Details for a peer SVM object. |
| state | string | SVM peering state. To accept a pending SVM peer request, PATCH the state to "peered". To reject a pending SVM peer request, PATCH the state to "rejected". To suspend a peered SVM peer relation, PATCH the state to "suspended". To resume a suspended SVM peer relation, PATCH the state to "peered". The states "initiated", "pending", and "initializing" are system-generated and cannot be used for PATCH. |
| svm | svm | Local SVM details |
| uuid | string | SVM peer relation UUID |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Delete an SVM peer relationship

DELETE `/svm/peers/{peer.uuid}`

Deletes the SVM peer relationship.

## Related ONTAP commands

- `vserver peer delete`

## Example

Deletes an SVM peer relationship.

```
DELETE "/api/svm/peers/d3268a74-ee76-11e8-a9bb-005056ac6dc9"
```

## Learn more

- DOC /svm/peers

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| peer.uuid | string | path | True | |

## Response

```
Status: 202, Accepted
```

## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error codes | Description |
|---|---|
| 26345578 | Internal error. Unable to retrieve local or peer SVM name. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Retrieve an SVM peer relationship instance

GET `/svm/peers/{peer.uuid}`

Retrieves the SVM peer relationship instance.

## Related ONTAP commands

- `vserver peer show`

## Example

Retrieves the parameters of an SVM peer relationship.

```
GET "/api/svm/peers/d3268a74-ee76-11e8-a9bb-005056ac6dc9"
```

## Learn more

- DOC /svm/peers

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| peer.uuid | string | path | True | SVM peer relation UUID |
| fields | array[string] | query | False | Specify the fields to return. |
| return_timeout | integer | query | False | The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| applications | array[string] | A list of applications for an SVM peer relation. |
| name | string | A peer SVM alias name to avoid a name conflict on the local cluster. |
| peer | peer | Details for a peer SVM object. |

| Name | Type | Description |
| --- | --- | --- |
| state | string | SVM peering state. To accept a pending SVM peer request, PATCH the state to "peered". To reject a pending SVM peer request, PATCH the state to "rejected". To suspend a peered SVM peer relation, PATCH the state to "suspended". To resume a suspended SVM peer relation, PATCH the state to "peered". The states "initiated", "pending", and "initializing" are system-generated and cannot be used for PATCH. |
| svm | svm | Local SVM details |
| uuid | string | SVM peer relation UUID |

**Example response**


```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "applications": [
    "snapmirror",
    "lun_copy"
  ],
  "peer": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster2",
      "uuid": "ebe27c49-1adf-4496-8335-ab862aebebf2"
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  },
  "state": "peered",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "string"
}
```

## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error codes | Description |
|---|---|
| 26345578 | Internal error. Unable to retrieve local or peer SVM name. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

cluster

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

peer

Details for a peer SVM object.

| Name | Type | Description |
|---|---|---|
| cluster | cluster | |
| svm | svm | SVM, applies only to SVM-scoped objects. |

svm

Local SVM details

| Name | Type | Description |
|---|---|---|
| _links | _links | |

| Name | Type | Description |
|---|---|---|
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

# Update an SVM peer relationship

PATCH `/svm/peers/{peer.uuid}`

Updates the SVM peer relationship.

## Related ONTAP commands

- `vserver peer modify`

## Examples

The following examples show how to update an SVM peer relationship. The input parameter 'name' refers to the local name of the peer SVM.

1. Accepts an SVM peer relationship

```
 PATCH "/api/svm/peers/d3268a74-ee76-11e8-a9bb-005056ac6dc9"
'{"state":"peered"}'
```

1. Updates the local name of an SVM peer relationship

```
 PATCH "/api/svm/peers/d3268a74-ee76-11e8-a9bb-005056ac6dc9"
'{"name":"vs2"}'
```

## Learn more

- DOC /svm/peers

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| peer.uuid | string | path | True | SVM peer relationship UUID |

## Request Body

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| applications | array[string] | A list of applications for an SVM peer relation. |
| name | string | A peer SVM alias name to avoid a name conflict on the local cluster. |
| peer | peer | Details for a peer SVM object. |
| state | string | SVM peering state. To accept a pending SVM peer request, PATCH the state to "peered". To reject a pending SVM peer request, PATCH the state to "rejected". To suspend a peered SVM peer relation, PATCH the state to "suspended". To resume a suspended SVM peer relation, PATCH the state to "peered". The states "initiated", "pending", and "initializing" are system-generated and cannot be used for PATCH. |

| Name | Type | Description |
|---|---|---|
| svm | svm | Local SVM details |
| uuid | string | SVM peer relation UUID |

**Example request**


```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "applications": [
    "snapmirror",
    "lun_copy"
  ],
  "peer": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster2",
      "uuid": "ebe27c49-1adf-4496-8335-ab862aebebf2"
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  },
  "state": "peered",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "string"
}
```

## Response

```
Status: 202, Accepted
```

## Error

```
Status: Default
```

ONTAP Error Response Codes

| Error codes | Description |
|---|---|
| 13434889 | Internal error. Wait and retry. |
| 26345575 | The specified peer cluster name and peer cluster UUID do not match. |
| 26345576 | Given peer state is invalid. |
| 26345577 | One of the following is required: applications, state, or name. |
| 26345578 | Internal error. Unable to retrieve local or peer SVM name. |
| 26345579 | The specified field is invalid. |
| 26345581 | Peer cluster name could not be retrieved or validated. |

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

cluster

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

peer

Details for a peer SVM object.

| Name | Type | Description |
|---|---|---|
| cluster | cluster | |
| svm | svm | SVM, applies only to SVM-scoped objects. |

svm

Local SVM details

| Name | Type | Description |
|---|---|---|
| _links | _links | |

| Name | Type | Description |
| --- | --- | --- |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

svm_peer

An SVM peer relation object.

| Name | Type | Description |
| --- | --- | --- |
| _links | _links | |
| applications | array[string] | A list of applications for an SVM peer relation. |
| name | string | A peer SVM alias name to avoid a name conflict on the local cluster. |
| peer | peer | Details for a peer SVM object. |
| state | string | SVM peering state. To accept a pending SVM peer request, PATCH the state to "peered". To reject a pending SVM peer request, PATCH the state to "rejected". To suspend a peered SVM peer relation, PATCH the state to "suspended". To resume a suspended SVM peer relation, PATCH the state to "peered". The states "initiated", "pending", and "initializing" are system-generated and cannot be used for PATCH. |
| svm | svm | Local SVM details |
| uuid | string | SVM peer relation UUID |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
| --- | --- | --- |
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

**Copyright information**

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

**Trademark information**

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.